

# Rajalakshmi Engineering College

Name: KEERTHI PRIYA T  
Email: 240701258@rajalakshmi.edu.in  
Roll no: 2116240701258  
Phone: 7397397221  
Branch: REC  
Department: I CSE FC  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_MCQ

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : MCQ

1. Given a pointer to a node X in a singly linked list. If only one point is given and a pointer to the head node is not given, can we delete node X from the given linked list?

**Answer**

Possible if X is not last node.

**Status : Correct**

**Marks : 1/1**

2. Consider an implementation of an unsorted singly linked list. Suppose it has its representation with a head pointer only. Given the representation, which of the following operations can be implemented in  $O(1)$  time?

i) Insertion at the front of the linked list

- ii) Insertion at the end of the linked list
- iii) Deletion of the front node of the linked list
- iv) Deletion of the last node of the linked list

**Answer**

I and III

**Status :** Correct

**Marks :** 1/1

3. The following function takes a singly linked list of integers as a parameter and rearranges the elements of the lists.

The function is called with the list containing the integers 1, 2, 3, 4, 5, 6, 7 in the given order. What will be the contents of the list after the function completes execution?

```
struct node {  
    int value;  
    struct node* next;  
};  
  
void rearrange (struct node* list) {  
    struct node *p,q;  
    int temp;  
    if (! List || ! list->next) return;  
    p=list; q=list->next;  
    while(q) {  
        temp=p->value; p->value=q->value;  
        q->value=temp;p=q->next;  
        q=p?p->next:0;  
    }  
}
```

**Answer**

2, 1, 4, 3, 6, 5, 7

**Status :** Correct

**Marks :** 1/1

4. Which of the following statements is used to create a new node in a singly linked list?

```
struct node {  
    int data;  
    struct node * next;  
}  
typedef struct node NODE;  
NODE *ptr;
```

**Answer**

```
ptr = (NODE*)malloc(sizeof(NODE));
```

**Status :** Correct

**Marks :** 1/1

5. Consider the singly linked list: 15 -> 16 -> 6 -> 7 -> 17. You need to delete all nodes from the list which are prime.

What will be the final linked list after the deletion?

**Answer**

15 -> 16 -> 6

**Status :** Correct

**Marks :** 1/1

6. In a singly linked list, what is the role of the "tail" node?

**Answer**

It stores the last element of the list

**Status :** Correct

**Marks :** 1/1

7. Consider the singly linked list: 13 -> 4 -> 16 -> 9 -> 22 -> 45 -> 5 -> 16 -> 6, and an integer K = 10, you need to delete all nodes from the list that are less than the given integer K.

What will be the final linked list after the deletion?

**Answer**

13 -&gt; 16 -&gt; 22 -&gt; 45 -&gt; 16

**Status :** Correct

**Marks :** 1/1

8. Given the linked list: 5 -> 10 -> 15 -> 20 -> 25 -> NULL. What will be the output of traversing the list and printing each node's data?

**Answer**

5 10 15 20 25

**Status :** Correct

**Marks :** 1/1

9. The following function reverse() is supposed to reverse a singly linked list. There is one line missing at the end of the function.

What should be added in place of "/\*ADD A STATEMENT HERE\*/", so that the function correctly reverses a linked list?

```
struct node {
    int data;
    struct node* next;
};
static void reverse(struct node** head_ref) {
    struct node* prev = NULL;
    struct node* current = *head_ref;
    struct node* next;
    while (current != NULL) {
        next = current->next;
        current->next = prev;
        prev = current;
        current = next;
    }
    /*ADD A STATEMENT HERE*/
}
```

**Answer**

\*head\_ref = prev;

**Status :** Correct

**Marks :** 1/1

10. Linked lists are not suitable for the implementation of?

**Answer**

Binary search

**Status :** Correct

**Marks :** 1/1