

CSA0888.- PYTHON PROGRAMMING

Assignment -3

Name: G.keerthireddy

Reg.no: 192224165

Program 1:

```
def maxProfit(price,n):  
    profit = [0]*n  
  
    max_price = price[n-1]  
  
    for i in range(n-2,0,-1):  
  
        if price[i] > max_price:  
            max_price = price[i]  
  
        profit[i] = max(profit[i+1], max_price-price[i])  
  
    min_price = price[0]  
  
    for i in range(1,n):  
  
        if price[i] < min_price:  
            min_price = price[i]  
  
        profit[i] = max(profit[i-1], profit[i]+(price[i]-min_price))  
  
    result = profit[n-1]  
  
    return result  
  
price = [2,7,9,56,7,4]  
print ("Maximum profit is",maxProfit(price, len(price)))
```

Program 2:

```
from itertools import permutations

comb = permutations([4,5,6], 3)

for i in comb:

    print(i)
```

Program. 3

```
def solve(nums):
    count=0
    n=len(nums)
    for i in range(n):
        for j in range(i+1,n):
            if nums[i] == nums[j]:
                count+=1
    return count

nums=[5,6,7,5,5,7]
print(solve(nums))
```

Program. 4

```
def add_binary_nums(x,y):
    max_len = max(len(x), len(y))

    x = x.zfill(max_len)
    y = y.zfill(max_len)

    result = ""

    carry = 0

    for i in range(max_len-1,-1,-1):
        r = carry
        r += 1 if x[i] == '1' else 0
        r += 1 if y[i] == '1' else 0
        result = ('1' if r % 2 == 1 else '0') + result
        carry = 0 if r < 2 else 1
```

```

        if carry!=0: result = '1' + result

        return result.zfill(max_len)

print(add_binary_nums('1101','100'))

```

Program 5

```

def minJumps(arr,n):

    if (n <= 1):
        return 0

    if (arr[0] == 0):
        return -1

    jump = 1

    subArrEndIndex = arr[0]

    i = 1
    subArrFistHalfMaxSteps = 0
    subArrSecondHalfMaxSteps = 0

    for i in range(1, n):

        subArrEndIndex = i + subArrEndIndex

        if (subArrEndIndex >= n):
            return jump

        firstHalfMaxStepIndex = 0

        j = i
        for j in range(i, subArrEndIndex):
            stepsCanCover = arr[j] + j
            if (subArrFistHalfMaxSteps < stepsCanCover):
                subArrFistHalfMaxSteps = stepsCanCover
                subArrSecondHalfMaxSteps = 0
                firstHalfMaxStepIndex = j
            elif (subArrSecondHalfMaxSteps < stepsCanCover):
                subArrSecondHalfMaxSteps = stepsCanCover

        i = j

    if (i > subArrFistHalfMaxSteps):
        return -1

    jump += 1

```

```

        subArrEndIndex = arr[firstHalfMaxStepIndex]
        subArrFistHalfMaxSteps = subArrSecondHalfMaxSteps
    return -1

```

```

if __name__ == '__main__':

```

```

    arr = [1, 3, 5, 8, 9, 2, 6, 7, 6, 8, 9]
    size = len(arr)

```

```

    print("Minimum number of jumps to reach end is ", minJumps(arr, size))

```

Program 6

```

sentence = input("Enter a sentence: ")

```

```

s = sentence.split()

```

```

s.sort()

```

```

result = []

```

```

n = len(s)

```

```

for i in range(n):
    for j in range(i+1, n):
        two_words = s[i] + " " + s[j]
        result.append(two_words)

```

```

for item in result:
    print(item)

```

Program 7

```

def backtrack():
    global ans, curr, visited, nums

```

```

    if (len(curr) == len(nums)):
        print(*curr)

```

```

    for i in range(len(nums)):

```

```

        if (visited[i]):
            continue

```

```

        if (i > 0 and nums[i] == nums[i - 1] and visited[i - 1] == False):
            continue
        visited[i] = True

```

```

curr.append(nums[i])

backtrack()

visited[i]
visited[i] = False

del curr[-1]

def permuteDuplicates(nums):
    global ans, visited, curr
    nums = sorted(nums)

    backtrack()
    return ans

def getDistinctPermutations(nums):
    global ans, curr, visited

    ans = permuteDuplicates(nums)

if __name__ == '__main__':
    visited = [False]*(5)
    ans, curr = [], []
    nums = [1, 2, 3]
    getDistinctPermutations(nums)

```

Program 8

```

from collections import Counter, defaultdict
user_input = ["cat", "dog", "tac", "edoc", "god", "tacact",
              "act", "code", "deno", "node", "ocde", "done", "catcat"]

def solve(words: list) -> list:

    m = defaultdict(list)

    for word in words:

        frozenset(dict(Counter('cat')).items()):

            hash(frozenset(Counter('cat'))) is equal to
            frozenset({'c', 1}, {'a', 1}, {'t', 1})
            m[frozenset(dict(Counter(word)).items())].append(word)

```

```
return[v for k, v in m.items()]
```

```
print(solve(user_input))
```

Program 9

```
def finding(s,p,n,m):
    #return 1 if n and m are negative
    if n < 0 and m < 0:
        return 1

    #return 0 if m is negative
    if m < 0:
        return 0

    #return n if n is negative
    if n < 0:
        #while m is positive
        while m >= 0:
            if p[m] != '*':
                return 0
            m -= 1
        return 1

    #if dp state is not visited
    if dp[n][m] == -1:
        if p[m] == '*':
            dp[n][m] = finding(s,p,n-1,m) or finding(s,p,n,m-1)
            return dp[n][m]
        else:
            if p[m] != s[n] and p[m] != '?':
                dp[n][m] = 0
                return dp[n][m]
            else:
                dp[n][m] = finding(s,p,n-1,m-1)
                return dp[n][m]

    #return dp[n][m] if dp state is previsited
    return dp[n][m]

def isMatch(s,p):
    global dp
    dp = []

    #resize the dp array
    for i in range(len(s) + 1):
        dp.append([-1] * (len(p) + 1))
    dp[len(s)][len(p)] = finding(s,p,len(s)-1,len(p)-1)
```

```
return dp[len(s)][len(p)]
```

```
def main():  
    s = "baaabab"  
    p = "*****ba*****ab"
```

```
    if isMatch(s,p):  
        print("Yes")  
    else:  
        print("No")
```

```
if __name__ == "__main__":  
    main()
```

Program. 10

```
def editDistance(str1, str2, m, n):  
  
    if m == 0:  
        return n  
  
    if n == 0:  
        return m  
  
    if str1[m-1] == str2[n-1]:  
        return editDistance(str1, str2, m-1, n-1)  
  
    return 1 + min(editDistance(str1, str2, m, n-1),  
                    editDistance(str1, str2, m-1, n),  
                    editDistance(str1, str2, m-1, n-1)  
                )  
  
str1 = "cut"  
str2 = "cat"  
print(editDistance(str1, str2, len(str1), len(str2)))
```