

Air Quality Monitoring

```
#include "MQ135.h"

#include <SoftwareSerial.h>

#define DEBUG true

SoftwareSerial esp8266(9,10); // This makes pin 9 of Arduino as RX pin and pin 10 of Arduino
as the TX pin

const int sensorPin= 0;

int air_quality;

#include <LiquidCrystal.h>

LiquidCrystal lcd(12,11, 5, 4, 3, 2);

void setup() {
  pinMode(8, OUTPUT);
  lcd.begin(16,2);
  lcd.setCursor (0,0);
  lcd.print ("circuitdigest ");
  lcd.setCursor (0,1);
  lcd.print ("Sensor Warming ");
  delay(1000);
  Serial.begin(115200);
  esp8266.begin(115200); // your esp's baud rate might be different
  sendData("AT+RST\r\n",2000,DEBUG); // reset module
  sendData("AT+CWMODE=2\r\n",1000,DEBUG); // configure as access point
  sendData("AT+CIFSR\r\n",1000,DEBUG); // get ip address
  sendData("AT+CIPMUair_quality=1\r\n",1000,DEBUG); // configure for multiple
connections
  sendData("AT+CIPSERVER=1,80\r\n",1000,DEBUG); // turn on server on port 80
  pinMode(sensorPin, INPUT);    //Gas sensor will be an input to the arduino
  lcd.clear();
```


```
}  
  
void loop() {  
  MQ135 gasSensor = MQ135(A0);  
  float air_quality = gasSensor.getPPM();  
  if(esp8266.available()) // check if the esp is sending a message  
  {  
    if(esp8266.find("+IPD,"))  
    {  
      delay(1000);  
  
      int connectionId = esp8266.read()-48; /* We are subtracting 48 from the output because  
the read() function returns the ASCII decimal value and the first decimal number which is 0  
starts at 48*/  
  
      String webpage = "<h1>IOT Air Pollution Monitoring System</h1>";  
  
      webpage += "<p><h2>";  
  
      webpage+= " Air Quality is ";  
  
      webpage+= air_quality;  
  
      webpage+=" PPM";  
  
      webpage += "<p>";  
  
      if (air_quality<=1000)  
      {  
        webpage+= "Fresh Air";  
      }  
    else if(air_quality<=2000 && air_quality>=1000)  
    {  
      webpage+= "Poor Air";  
    }  
    else if (air_quality>=2000 )  
    {  
      webpage+= "Danger! Move to Fresh Air";  
    }  
  }  
}
```

```
webpage += "</h2></p></body>";
String cipSend = "AT+CIPSEND=";
cipSend += connectionId;
cipSend += ",";
cipSend += webpage.length();
cipSend += "\r\n";
sendData(cipSend,1000,DEBUG);
sendData(webpage,1000,DEBUG);
cipSend = "AT+CIPSEND=";
cipSend += connectionId;
cipSend += ",";
cipSend += webpage.length();
cipSend += "\r\n";
String closeCommand = "AT+CIPCLOSE=";
closeCommand+=connectionId; // append connection id
closeCommand+="\r\n";
sendData(closeCommand,3000,DEBUG);
}
}
lcd.setCursor (0, 0);
lcd.print ("Air Quality is ");
lcd.print (air_quality);
lcd.print (" PPM ");
lcd.setCursor (0,1);
if (air_quality<=1000)
{
lcd.print("Fresh Air");
digitalWrite(8, LOW);
}
```

```
else if( air_quality>=1000 && air_quality<=2000 )
{
  lcd.print("Poor Air, Open Windows");
  digitalWrite(8, HIGH );
}
else if (air_quality>=2000 )
{
  lcd.print("Danger! Move to Fresh Air");
  digitalWrite(8, HIGH); // turn the LED on
}
lcd.scrollDisplayLeft();
delay(1000);
}


String sendData(String command, const int timeout, boolean debug)
{
  String response = "";
  esp8266.print(command); // send the read character to the esp8266
  long int time = millis();
  while( (time+timeout) > millis())
  {
    while(esp8266.available())
    {
      // The esp has data so display its output to the serial window
      char c = esp8266.read(); // read the next character.
      response+=c;
    }
  }
  if(debug)
  {
```


```
Serial.print(response);  
}  
return response;  
}
```



The screenshot shows the 'Datastreams' tab in the AQM interface. It features a search bar and a table with columns: Id, Name, Alias, Color, Pin, Data Type, Units, Is Raw, Min, and Max. There are three datastreams listed: Temperature (V0), Humidity (V1), and Gas value (V2).

Id	Name	Alias	Color	Pin	Data Type	Units	Is Raw	Min	Max
1	Temperature	Temperature	Orange	V0	Double		false	0	100
2	Humidity	Humidity	Dark Blue	V1	Double		false	0	600
3	Gas value	Gas value	Purple	V2	Double		false	0	600






The screenshot shows the 'Automations' tab in the AQM dashboard. The page title is 'AQM'. The navigation bar includes 'Home', 'Datastreams', 'Web Dashboard', 'Automations' (selected), 'Metadata', 'Events', and 'Mobile Dashboard'. Below the navigation bar, there is a search bar labeled 'Search datastream'. A message states: 'Define which Datastreams will be available in Automation actions and conditions. Only Virtual Pin, Enumerable and Location Datastreams supported.' Below this, it says '3 Datastreams'. A table lists the datastreams:

Name	Pin	Data Type	Type Of Automation	Condition	Action
Temperature	V0	Double	Sensor	<input type="checkbox"/>	<input type="checkbox"/>
Humidity	V1	Double	Sensor	<input type="checkbox"/>	<input type="checkbox"/>
Gas value	V2	Double	Sensor	<input type="checkbox"/>	<input type="checkbox"/>

The bottom right corner shows a timestamp '2023/10/27 22:55' and a region 'Region: blr1' with a 'Privacy Policy' link.



The screenshot shows the 'Datastreams' tab in the AQM dashboard. The page title is 'AQM'. The navigation bar includes 'Home', 'Datastreams' (selected), 'Web Dashboard', 'Automations', 'Metadata', 'Events', and 'Mobile Dashboard'. Below the navigation bar, there is a search bar labeled 'Search datastream'. A table lists the datastreams:

Id	Name	Alias	Color	Pin	Data Type	Units	Is Raw	Min	Max
1	Temperature	Temperature	Orange	V0	Double		false	0	100
2	Humidity	Humidity	Dark Blue	V1	Double		false	0	600
3	Gas value	Gas value	Purple	V2	Double		false	0	600

The bottom right corner shows a region 'Region: blr1' with a 'Privacy Policy' link.