

ESP32 Temperature and Humidity Monitoring System

Student Name: Keerthi A

Register Number: U03ZW24S0097

Class: B.Sc. 5th Semester MEC

Team Members: Sreethan H D and Jewel Mary Jibi

1. Project Title

ESP32 Based Temperature and Humidity Monitoring System using DHT22 and ThingSpeak

2. Problem Statement

Monitoring temperature and humidity manually can be difficult and time-consuming. This project provides an IoT-based solution to measure temperature and humidity using a DHT22 sensor connected to an ESP32. The collected data is sent through Wi-Fi to the ThingSpeak cloud platform for monitoring and visualization.

3. Objectives

To measure temperature and humidity using the DHT22 sensor.

To interface the DHT22 sensor with ESP32.

To collect sensor readings using MicroPython.

To send the collected data to ThingSpeak through Wi-Fi.

To visualize temperature and humidity readings using graphs.

To understand the basic working of an IoT cloud-based monitoring system.

4. Components and Software Used

Hardware:

ESP32

DHT22 Temperature and Humidity Sensor

Software/Platforms

Wokwi Simulator

MicroPython


ThingSpeak Cloud Platform

GitHub

5. Circuit Diagram Connections

DHT22 Pin	ESP32 Pin	Connection
VCC	3V3	Power
DATA	GPIO 15	Data
GND	GND	Ground

The circuit diagram showing the connections between the ESP32 and DHT22 Sensor is shown below:



6. Block Diagram:

The block diagram of the proposed IoT-based temperature and humidity monitoring system is shown below.



7. Working Principle

The DHT22 sensor measures the surrounding temperature and humidity. The sensor is connected to GPIO 15 of the ESP32.

The ESP32 reads the sensor values using a MicroPython program. It then connects to the Internet through Wi-Fi and sends the temperature and humidity data to the ThingSpeak cloud platform.

ThingSpeak receives the data and displays it in the form of graphs. This allows the sensor readings to be monitored and visualized easily.

8. Program Code

```
import dht
import time
import network
import urequests
from machine import Pin

sensor = dht.DHT22(Pin(15))

wifi = network.WLAN(network.STA_IF)
wifi.active(True)
wifi.connect("Wokwi-GUEST", "")

print("Connecting to Wi-Fi...")

while not wifi.isconnected():
    time.sleep(1)

print("Wi-Fi connected!")

API_KEY = "YOUR_WRITE_API_KEY"

while True:
    sensor.measure()

    temperature = sensor.temperature()
    humidity = sensor.humidity()

    print("Temperature:", temperature, "C")
    print("Humidity:", humidity, "%")
```

```

url = "https://api.thingspeak.com/update?api_key=" + API_KEY
url = url + "&field1=" + str(temperature)
url = url + "&field2=" + str(humidity)
response = urequests.get(url)
print("ThingSpeak response:", response.text)
time.sleep(15)

```

Program Explanation-

The program uses MicroPython to control the ESP32 and DHT22 sensor.

Important parts of the program include:

import dht – imports the DHT sensor library.

from machine import Pin – allows the ESP32 GPIO pin to be used.

dht.DHT22(Pin(15)) – connects the DHT22 data pin to GPIO 15.

sensor.measure() – takes a new measurement.

sensor.temperature() – obtains the temperature value.

sensor.humidity() – obtains the humidity value.


Wi-Fi and HTTP requests are used to send the readings to ThingSpeak.

9. Output

The ESP32 successfully reads temperature and humidity values from the DHT22 sensor.

The readings are displayed in the Wokwi serial monitor and are also sent to ThingSpeak. ThingSpeak displays the received temperature and humidity values using graphs.

Wokwi output screenshot




```

ets Jul 29 2019 12:21:46

rst:0x1 (POWERON_RESET),boot:0x13 (SPI_FAST_FLASH_BOOT)
configsip: 0, SPIWP:0xee
clk_drv:0x00,q_drv:0x00,d_drv:0x00,cs0_drv:0x00,hd_drv:0x00,wp_drv:0x00
mode:DIO, clock div:2
load:0x3fff0030,len:4200
load:0x40078000,len:15236
load:0x40080400,len:3332
entry 0x400805a8
Connecting to Wi-Fi...
Wi-Fi connected!
Temperature: 24.0 C
Humidity: 40.0 %

```

ThingSpeak graph screenshot



10. Applications

Smart home environmental monitoring

Agriculture and greenhouse monitoring

Weather monitoring

Indoor temperature and humidity monitoring

IoT-based environmental monitoring

Educational IoT projects

11. Limitations

The system requires Wi-Fi connectivity for cloud communication.

DHT22 has limitations in measurement range and accuracy.

ThingSpeak requires Internet connectivity to receive and display data.

Sensor readings may vary depending on environmental conditions.

12. Future Scope

The project can be improved by:

Adding more sensors.

Adding mobile notifications and alerts.

Using a mobile application for monitoring.

Adding automatic control based on temperature or humidity.

Storing and analyzing larger amounts of sensor data.

Developing a complete smart-home monitoring system.

13. Team Members' Details

NAMES	REGISTER NUMBER
Keerthi A	U03ZW24S0097
Sreethan H D	U03ZW24S0017
Jewel Mary Jibi	U03ZW24S0014

14. Wokwi Project Link

Wokwi Project:

<https://wokwi.com/projects/475682178620641281>

15. ThingSpeak Channel Link

ThingSpeak Channel ID: 3500612

https://thingspeak.mathworks.com/channels/3500612/private_show

16. Learning Reflection

Through this project, I learned how an IoT system can collect real-time environmental data using sensors and send the data to a cloud platform. I learned how to connect a DHT22 sensor with an ESP32, write a MicroPython program, simulate the circuit using Wokwi, connect the system to Wi-Fi, and send sensor readings to ThingSpeak. I also gained experience in using GitHub to store and present the project files. This project helped me understand the practical working of sensors, microcontrollers, cloud platforms, and IoT communication.

Conclusion

This project successfully demonstrates an IoT-based temperature and humidity monitoring system using ESP32 and DHT22. The sensor data is collected, sent through Wi-Fi to ThingSpeak, and displayed as graphs. Through this project, we gained practical knowledge of IoT, sensors, ESP32, MicroPython, cloud platforms, and Wokwi simulation.