JavaScript - script.js

script.js holds the books array and the application logic. **renderBooks()** builds the table, **toggleIssue()** flips the issued value, **deleteBook()** removes a book, the form handler adds a new book, and **updateStats()** refreshes the dashboard counts.

```
// Library Management Interface - script.js
let books = [
  { id: 1, title: "Python Crash Course", author: "Eric Matthes", category: "Technology", issued: false },
  { id: 2, title: "Wings of Fire", author: "A.P.J. Abdul Kalam", category: "History", issued: true },
  { id: 3, title: "A Brief History of Time", author: "Stephen Hawking", category: "Science", issued: false },
  { id: 4, title: "Artificial Intelligence Basics", author: "Tom Taulli", category: "Technology", issued: false },
  { id: 5, title: "Ponniyin Selvan", author: "Kalki Krishnamurthy", category: "Fiction", issued: true }
];
let nextId = 6;

const bookBody = document.getElementById("bookBody");
const searchBox = document.getElementById("search");
const filterBox = document.getElementById("filter");

function renderBooks() {
  const term = searchBox.value.toLowerCase();
  const filter = filterBox.value;
  bookBody.innerHTML = "";

  books
    .filter(b => b.title.toLowerCase().includes(term) || b.author.toLowerCase().includes(term))
    .filter(b => filter === "all" || (filter === "issued") === b.issued)
    .forEach(b => {
      const row = document.createElement("tr");
      row.innerHTML = `
        <td>${b.id}</td>
        <td>${b.title}</td>
        <td>${b.author}</td>
        <td>${b.category}</td>
        <td><span class="badge ${b.issued ? "issued" : "available"}">${b.issued ? "Issued" :
"Available"}</span></td>
        <td>
          <button class="${b.issued ? "btn-return" : "btn-issue"}"
            onclick="toggleIssue(${b.id})">${b.issued ? "Return" : "Issue"}</button>
          <button class="btn-delete" onclick="deleteBook(${b.id})">Delete</button>
        </td>`;
      bookBody.appendChild(row);
    });

  updateStats();
}

function updateStats() {
  const issued = books.filter(b => b.issued).length;
  document.getElementById("totalCount").textContent = books.length;
  document.getElementById("issuedCount").textContent = issued;
  document.getElementById("availCount").textContent = books.length - issued;
}

function toggleIssue(id) {
  const book = books.find(b => b.id === id);
  book.issued = !book.issued;
  renderBooks();
}

function deleteBook(id) {
  books = books.filter(b => b.id !== id);
  renderBooks();
}

document.getElementById("bookForm").addEventListener("submit", function (e) {
  e.preventDefault();
  books.push({
    id: nextId++,
    title: document.getElementById("title").value.trim(),
    author: document.getElementById("author").value.trim(),
```

```
    category: document.getElementById("category").value,
    issued: false
  });
  this.reset();
  renderBooks();
});

searchBox.addEventListener("input", renderBooks);
filterBox.addEventListener("change", renderBooks);

renderBooks();
```