

SKILL WEEK – 4

Session-7

TASK 1: Process Synchronization and Child Process Monitoring Using waitpid()

```
GNU nano 8.7.1
#include <stdio.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    pid_t child1, child2;
    int status;

    printf("Session 7 - Process Synchronization\n");
    printf("Parent PID: %d\n\n", getpid());

    child1 = fork();

    if (child1 < 0) {
        perror("fork failed");
        return 1;
    }

    if (child1 == 0) {
        printf("Child 1 started. PID: %d\n", getpid());
        sleep(2);
        printf("Child 1 completed.\n");
        exit(10);
    }

    child2 = fork();

    if (child2 < 0) {
        perror("fork failed");
        return 1;
    }

    if (child2 == 0) {
        printf("Child 2 started. PID: %d\n", getpid());
        sleep(4);
        printf("Child 2 completed.\n");
        exit(20);
    }

    printf("Parent is monitoring both child processes...\n");

    waitpid(child1, &status, 0);

    if (WIFEXITED(status)) {
        printf("Parent: Child 1 (PID %d) exited with status %d.\n",
            child1, WEXITSTATUS(status));
    }

    waitpid(child2, &status, 0);

    if (WIFEXITED(status)) {
        printf("Parent: Child 2 (PID %d) exited with status %d.\n",
            child2, WEXITSTATUS(status));
    }

    printf("Parent: All child processes completed.\n");

    return 0;
}
```

```

keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ nano session7_task1.c
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ gcc session7_task1.c -o session7_task1
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ ./session7_task1
Session 7 - Process Synchronization
Parent PID: 1615

Parent is monitoring both child processes...
Child 1 started. PID: 1616
Child 2 started. PID: 1617
Child 1 completed.
Parent: Child 1 (PID 1616) exited with status 10.
Child 2 completed.
Parent: Child 2 (PID 1617) exited with status 20.
Parent: All child processes completed.
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ |

```

TASK 2: To Retrieve PATH Variable, Parse Search Directories, Locate Executables, Verify Permissions, Handle Missing Commands, Test Command Resolution

```

GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/stat.h>

#define MAX_PATHS 100
#define MAX_LENGTH 4096

int main() {
    char *path_env;
    char *path_copy;
    char *directory;
    char full_path[MAX_LENGTH];
    char command[100];

    printf("Session 7 - PATH Command Resolution\n");

    path_env = getenv("PATH");

    if (path_env == NULL) {
        printf("PATH variable not found.\n");
        return 1;
    }

    path_copy = malloc(strlen(path_env) + 1);

    if (path_copy == NULL) {
        perror("malloc failed");
        return 1;
    }

    strcpy(path_copy, path_env);

    printf("\nEnter command to locate: ");
    scanf("%99s", command);

    directory = strtok(path_copy, ":");

    while (directory != NULL) {
        snprintf(full_path, sizeof(full_path),
            "%s/%s", directory, command);

        if (access(full_path, X_OK) == 0) {
            struct stat file_info;

            if (stat(full_path, &file_info) == 0) {
                printf("\nExecutable found!\n");
                printf("Command      : %s\n", command);
                printf("Full path   : %s\n", full_path);
                printf("Executable permission: Yes\n");
            }
        }

        directory = strtok(NULL, ":");
    }
}

```

```
keerthi_priya@LAPTOP-OSGV × + v
GNU nano 8.7.1

path_env = getenv("PATH");

if (path_env == NULL) {
    printf("PATH variable not found.\n");
    return 1;
}

path_copy = malloc(strlen(path_env) + 1);

if (path_copy == NULL) {
    perror("malloc failed");
    return 1;
}

strcpy(path_copy, path_env);

printf("\nEnter command to locate: ");
scanf("%99s", command);

directory = strtok(path_copy, ":");

while (directory != NULL) {

    snprintf(full_path, sizeof(full_path),
             "%s/%s", directory, command);

    if (access(full_path, X_OK) == 0) {
        struct stat file_info;

        if (stat(full_path, &file_info) == 0) {
            printf("\nExecutable found!\n");
            printf("Command      : %s\n", command);
            printf("Full path   : %s\n", full_path);
            printf("Executable permission: Yes\n");

            free(path_copy);
            return 0;
        }
    }

    directory = strtok(NULL, ":");
}

printf("\nCommand not found in PATH.\n");
printf("Command: %s\n", command);

free(path_copy);

return 0;
}
```

```
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ nano session7_task2.c
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ gcc session7_task2.c -o session7_task2
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ ./session7_task2
Session 7 - PATH Command Resolution

Enter command to locate: ls

Executable found!
Command      : ls
Full path    : /usr/bin/ls
Executable permission: Yes
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ ./session7_task2
Session 7 - PATH Command Resolution

Enter command to locate: hello

Command not found in PATH.
Command: hello
keerthi_priya@LAPTOP-OSGVCE7A:/mnt/c/JavaPrograms$ |
```

Session – 8

TASK 1: To Detect Variable References, Expand Values, Handle Undefined Variables, Update Tokens, Support Nested Variables, Test Expansion Logic

```
keerthi_priya@LAPTOP-OSGV  ×  +  ▾
GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

#define MAX_INPUT 500
#define MAX_OUTPUT 1000

void expand_variables(const char *input, char *output) {
    int i = 0;
    int j = 0;

    while (input[i] != '\0' && j < MAX_OUTPUT - 1) {
        if (input[i] == '$') {
            i++;

            /* Support ${VARIABLE} */
            if (input[i] == '{') {
                i++;

                char variable[100];
                int k = 0;

                while (input[i] != '\0' &&
                    input[i] != '}' &&
                    k < 99) {
                    variable[k++] = input[i++];
                }

                variable[k] = '\0';

                if (input[i] == '}')
                    i++;

                char *value = getenv(variable);

                if (value != NULL) {
                    for (int v = 0;
                        value[v] != '\0' && j < MAX_OUTPUT - 1;
                        v++) {
                        output[j++] = value[v];
                    }
                } else {
                    printf("Undefined variable: %s\n", variable);
                }
            }

            /* Support $VARIABLE */
            else if (isalnum((unsigned char)input[i]) ||
                input[i] == '_' ) {

```

```
keerthi_priya@LAPTOP-OSGV  ×  +  ▾
GNU nano 8.7.1

                while ((isalnum((unsigned char)input[i]) ||
                    input[i] == '_') &&
                    k < 99) {
                    variable[k++] = input[i++];
                }

                variable[k] = '\0';

                char *value = getenv(variable);

                if (value != NULL) {
                    for (int v = 0;
                        value[v] != '\0' && j < MAX_OUTPUT - 1;
                        v++) {
                        output[j++] = value[v];
                    }
                } else {
                    printf("Undefined variable: %s\n", variable);
                }
            }

            /* Just '$' */
            else {
                output[j++] = '$';
            }
        }

        else {
            output[j++] = input[i++];
        }
    }

    output[j] = '\0';
}

int main() {
    char input[MAX_INPUT];
    char output[MAX_OUTPUT];

    printf("Session 8 - Variable Expansion\n");
    printf("Enter text containing variables:\n");
    printf("myshell> ");

    fgets(input, sizeof(input), stdin);
    input[strcspn(input, "\n")] = '\0';

    if (strlen(input) == 0) {
        printf("Empty input.\n");
        return 0;
    }
}
```

```
keerthi_priya@LAPTOP-OSGV × + v
GNU nano 8.7.1
        v++) {
            output[j++] = value[v];
        }
    } else {
        printf("Undefined variable: %s\n", variable);
    }
}

/* Just '$' */
else {
    output[j++] = '$';
}

else {
    output[j++] = input[i++];
}

output[j] = '\0';
}

int main() {
    char input[MAX_INPUT];
    char output[MAX_OUTPUT];

    printf("Session 8 - Variable Expansion\n");
    printf("Enter text containing variables:\n");
    printf("myshell> ");

    fgets(input, sizeof(input), stdin);
    input[strcspn(input, "\n")] = '\0';

    if (strlen(input) == 0) {
        printf("Empty input.\n");
        return 0;
    }

    printf("\nOriginal input:\n");
    printf("%s\n", input);

    expand_variables(input, output);

    printf("\nExpanded output:\n");
    printf("%s\n", output);

    printf("\nExpansion validation:\n");
    printf("Variable expansion completed successfully.\n");

    return 0;
}
```

```
keerthi_priya@LAPTOP-OSGV × + v
keerthi_priya@LAPTOP-OSGVCE7A:~$ nano session8_task1.c

keerthi_priya@LAPTOP-OSGVCE7A:~$ gcc session8_task1.c -o session8_task1
keerthi_priya@LAPTOP-OSGVCE7A:~$ ./session8_task1
Session 8 - Variable Expansion
Enter text containing variables:
myshell> echo $USER

Original input:
echo $USER

Expanded output:
echo keerthi_priya

Expansion validation:
Variable expansion completed successfully.
keerthi_priya@LAPTOP-OSGVCE7A:~$ ./session8_task1
Session 8 - Variable Expansion
Enter text containing variables:
myshell> Home directory: $HOME

Original input:
Home directory: $HOME

Expanded output:
Home directory: /home/keerthi_priya

Expansion validation:
Variable expansion completed successfully.
keerthi_priya@LAPTOP-OSGVCE7A:~$ ./session8_task1
Session 8 - Variable Expansion
Enter text containing variables:
myshell> Value: $NOTDEFINED

Original input:
Value: $NOTDEFINED
Undefined variable: NOTDEFINED

Expanded output:
Value:

Expansion validation:
Variable expansion completed successfully.
keerthi_priya@LAPTOP-OSGVCE7A:~$ |
```

TASK 2: To Identify Built-ins, Create Dispatch Table, Execute In- Process Commands, Handle Invalid Commands, Maintain State, Test Dispatch Logic

```
keerthi_priya@LAPTOP-OSGV × + v
GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>

#define MAX_INPUT 100

void cmd_help() {
    printf("Dispatching built-in: help\n\n");
    printf("Available built-in commands:\n");
    printf("  help - Display available commands\n");
    printf("  pwd  - Display current directory\n");
    printf("  cd   - Change directory\n");
    printf("  exit - Exit the shell\n");
}

void cmd_pwd() {
    printf("Dispatching built-in: pwd\n");

    char cwd[MAX_INPUT];

    if (getcwd(cwd, sizeof(cwd)) != NULL) {
        printf("%s\n", cwd);
    } else {
        perror("getcwd failed");
    }
}

void cmd_cd(char *path) {
    printf("Dispatching built-in: cd\n");

    if (path == NULL) {
        fprintf(stderr, "cd: missing argument\n");
        return;
    }

    if (chdir(path) != 0) {
        perror("cd failed");
    }
}

void cmd_exit() {
    printf("Dispatching built-in: exit\n");
    printf("Exiting shell...\n");
    exit(0);
}

int main() {
    char input[MAX_INPUT];
    char *command;
    char *argument;
```

```
keerthi_priya@LAPTOP-OSGV  ×  +  ▾
GNU nano 8.7.1
void cmd_exit() {
    printf("Dispatching built-in: exit\n");
    printf("Exiting shell...\n");
    exit(0);
}

int main() {
    char input[MAX_INPUT];
    char *command;
    char *argument;

    printf("Session 8 - Built-in Command Dispatcher\n");
    printf("Type 'help' to see available commands.\n\n");

    while (1) {
        printf("myshell> ");
        fflush(stdout);

        if (fgets(input, sizeof(input), stdin) == NULL) {
            break;
        }

        input[strcspn(input, "\n")] = '\0';

        command = strtok(input, " ");
        argument = strtok(NULL, " ");

        if (command == NULL) {
            continue;
        }

        if (strcmp(command, "help") == 0) {
            cmd_help();
        }
        else if (strcmp(command, "pwd") == 0) {
            cmd_pwd();
        }
        else if (strcmp(command, "cd") == 0) {
            cmd_cd(argument);
        }
        else if (strcmp(command, "exit") == 0) {
            cmd_exit();
        }
        else {
            printf("Invalid command: %s\n", command);
            printf("Type 'help' to see available built-ins.\n");
        }
    }

    return 0;
}
```

```
keerthi_priya@LAPTOP-OSGVCE7A:~$ cd ~
keerthi_priya@LAPTOP-OSGVCE7A:~$ nano session8_task2.c
keerthi_priya@LAPTOP-OSGVCE7A:~$ gcc session8_task2.c -o session8_task2
keerthi_priya@LAPTOP-OSGVCE7A:~$ ./session8_task2
Session 8 - Built-in Command Dispatcher
Type 'help' to see available commands.

myshell> help
Dispatching built-in: help

Available built-in commands:
  help - Display available commands
  pwd  - Display current directory
  cd   - Change directory
  exit - Exit the shell
myshell> pwd
Dispatching built-in: pwd
/home/keerthi_priya
myshell> cd/tmp
Invalid command: cd/tmp
Type 'help' to see available built-ins.
myshell> cd /tmp
Dispatching built-in: cd
myshell> pwd
Dispatching built-in: pwd
/tmp
myshell> hello
Invalid command: hello
Type 'help' to see available built-ins.
myshell> exit
Dispatching built-in: exit
Exiting shell...
keerthi_priya@LAPTOP-OSGVCE7A:~$ |
```

