RAJALAKSHMI ENGINEERING COLLEGE

Keerthivasan A 251001114-2025-IT

S2

Started on	Sunday, 30 August 2026, 7:17 PM
State	Finished
Completed on	Sunday, 30 August 2026, 7:21 PM
Time taken	4 mins 24 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
#include<stdlib.h>
int sumarr(const void *a,const void *b){
    return *(int *)a - *(int *)b;
}
int main()
{
    int n,i;
    long sum=0;
    scanf("%d", &n);
    int a[n];

    for (i = 0; i < n; i++)
        scanf("%d", &a[i]);
    qsort(a, n, sizeof(int), sumarr);

    for (i = 0; i < n; i++)
        sum += (long long)a[i] * i;

    printf("%ld", sum);

    return 0;

}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course