



CONTINENTAL THERMAL ENGINEERS PVT LTD
BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
UNITS	MMWC	MMWC	CFM	M ³ /Hr				
CLP-2-2-2500	50	36	2500	4290	2	4	1450	1450
CLP-2-3-4000	50	30	4000	6860	3	4	1450	1450
CLP-2-5-8500	50	34	8500	14575	5	4	1450	1450
CLP-2-7.5-14000	50	23	14000	24000	7.5	4	1450	1450
CLP-2-10-18000	50	32	18000	30860	10	6	960	960
CLP-2-15-25000	50	27	25000	42860	15	6	965	965
CLP-2-20-37000	50	30	37000	63430	20	8	720	720
CLP-2-25-47000	50	35	47000	80575	25	8	725	725
CLP-2-30-55000	50	33	55000	94290	30	8	725	725
CLP-2-40-75000	50	27	75000	128575	40	8	730	730
CLP-3-2-2300	75	62	2300	3945	2	4	1450	1450
CLP-3-3-3200	75	59	3200	5490	3	4	1450	1450
CLP-3-5-6000	75	63	6000	10290	5	4	1450	1450
CLP-3-7.5-10000	75	62	10000	17145	7.5	4	1450	1450
CLP-3-10-12000	75	60	12000	20575	10	4	1450	1450
CLP-3-15-18000	75	55	18000	30860	15	4	1450	1450
CLP-3-20-25000	75	50	25000	42860	20	4	1450	1450
CLP-3-25-33000	75	45	33000	56575	25	4	1450	1450
CLP-3-30-40000	75	40	40000	68575	30	4	1450	1450
CLP-3-40-53000	75	51	53000	90860	40	6	960	960
CLP-3-50-68000	75	47	68000	116575	50	6	960	960



CONTINENTAL THERMAL ENGINEERS PVT LTD

BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
CLP-4-2-1600	100	95	1600	2745	2	4	1450	1450
CLP-4-3-2200	100	95	2200	3775	3	4	1450	1450
CLP-4-5-3700	100	93	3700	6345	5	4	1450	1450
CLP-4-7.5-6500	100	91	6500	11145	7.5	4	1450	1450
CLP-4-10-9000	100	89	9000	15430	10	4	1450	1450
CLP-4-15-14500	100	84	14500	24860	15	4	1450	1450
CLP-4-20-19500	100	80	19500	33430	20	4	1450	1450
CLP-4-25-25000	100	76	25000	42860	25	4	1450	1450
CLP-4-30-30500	100	72	30500	52290	30	4	1450	1450
CLP-4-40-41000	100	65	41000	70290	40	4	1450	1450
CLP-4-50-51000	100	60	51000	87430	50	4	1450	1450
CLP-4-60-61000	100	54	61000	104575	60	4	1450	1450
CLP-5-2-1200	125	124	1200	2060	2	4	1450	1450
CLP-5-3-1900	125	120	1900	3260	3	4	1450	1450
CLP-5-5-3600	125	116	3600	6175	5	4	1450	1450
CLP-5-7.5-6000	125	117	6000	10290	7.5	4	1450	1450
CLP-5-10-7200	125	116	7200	12345	10	4	1450	1450
CLP-5-15-12000	125	112	12000	20575	15	4	1450	1450
CLP-5-20-16000	125	108	16000	27430	20	4	1450	1450
CLP-5-25-20000	125	105	20000	34290	25	4	1450	1450
CLP-5-30-24500	125	101	24500	42000	30	4	1450	1450
CLP-5-40-32500	125	96	32500	55715	40	4	1450	1450
CLP-5-50-41000	125	90	41000	70290	50	4	1450	1450
CLP-5-60-49500	125	86	49500	84860	60	4	1450	1450



CONTINENTAL THERMAL ENGINEERS PVT LTD BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
CLP-6-2-1000	150	148	1000	1715	2	4	1450	1450
CLP-6-3-1600	150	146	1600	2745	3	4	1450	1450
CLP-6-5-2900	150	143	2900	4975	5	4	1450	1450
CLP-6-7.5-4500	150	140	4500	7715	7.5	4	1450	1450
CLP-6-10-6000	150	137	6000	10290	10	4	1450	1450
CLP-6-15-10000	150	132	10000	17145	15	4	1450	1450
CLP-6-20-13000	150	135	13000	22290	20	4	1450	1450
CLP-6-25-16000	150	133	16000	27430	25	4	1450	1450
CLP-6-30-20000	150	130	20000	34290	30	4	1450	1450
CLP-6-40-27000	150	125	27000	46290	40	4	1450	1450
CLP-6-50-34000	150	120	34000	58290	50	4	1450	1450
CLP-6-60-41000	150	116	41000	70290	60	4	1450	1450
CHB-8-2-700	200	194	700	1200	2	2	2900	2900
CHB-8-3-1100	200	190	1100	1890	3	2	2900	2900
CHB-8-5-2200	200	183	2200	3775	5	2	2900	2900
CHB-8-7.5-3300	200	176	3300	5660	7.5	2	2900	2900
CHB-8-10-4400	200	182	4400	7545	10	2	2900	2900
CHB-8-15-6600	200	178	6600	11315	15	2	2900	2900
CHB-8-20-9000	200	190	9000	15430	20	4	1450	1450
CHB-8-25-11500	200	188	11500	19715	25	4	1450	1450
CHB-8-30-14700	200	185	14700	25200	30	4	1450	1450
CHB-8-40-20000	200	180	20000	34290	40	4	1450	1450
CHB-8-50-25000	200	178	25000	42860	50	4	1450	1450
CHB-8-60-30500	200	173	30500	52290	60	4	1450	1450



CONTINENTAL THERMAL ENGINEERS PVT LTD
BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
CHB-10-2-600	250	249	600	1030	2	2	2900	2900
CHB-10-3-1000	250	246	1000	1715	3	2	2900	2900
CHB-10-5-1500	250	244	1500	2575	5	2	2900	2900
CHB-10-7.5-2500	250	240	2500	4285	7.5	2	2900	2900
CHB-10-10-3500	250	247	3500	6000	10	2	2900	2900
CHB-10-15-5000	250	245	5000	8575	15	4	1450	1450
CHB-10-20-6700	250	243	6700	11490	20	4	1450	1450
CHB-10-25-9500	250	240	9500	16290	25	4	1450	1450
CHB-10-30-12000	250	238	12000	20575	30	4	1450	1450
CHB-10-40-15500	250	235	15500	26575	40	4	1450	1450
CHB-10-50-20500	250	231	20500	35145	50	4	1450	1450
CHB-10-60-24000	250	228	24000	41145	60	4	1450	1450
CHB-12-2-500	300	300	500	860	2	2	2900	2900
CHB-12-3-800	300	298	800	1375	3	2	2900	2900
CHB-12-5-1300	300	296	1300	2230	5	2	2900	2900
CHB-12-7.5-2200	300	292	2200	3775	7.5	2	2900	2900
CHB-12-10-2900	300	289	2900	4975	10	2	2900	2900
CHB-12-15-4200	300	297	4200	7200	15	4	1450	1450
CHB-12-20-6000	300	295	6000	10290	20	4	1450	1450
CHB-12-25-8000	300	293	8000	13715	25	4	1450	1450
CHB-12-30-9500	300	291	9500	16290	30	4	1450	1450
CHB-12-40-13000	300	288	13000	22290	40	4	1450	1450
CHB-12-50-17000	300	285	17000	29145	50	4	1450	1450
CHB-12-60-20000	300	282	20000	34290	60	4	1450	1450



CONTINENTAL THERMAL ENGINEERS PVT LTD
BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
CCB-16-2-400	400	400	400	690	2	2	2900	2900
CCB-16-3-600	400	398	600	1030	3	2	2900	2900
CCB-16-5-1000	400	394	1000	1715	5	2	2900	2900
CCB-16-7.5-1600	400	390	1600	2745	7.5	2	2900	2900
CCB-16-10-2100	400	387	2100	3600	10	2	2900	2900
CCB-16-15-3200	400	390	3200	5490	15	2	2900	2900
CCB-16-20-4200	400	383	4200	7200	20	2	2900	2900
CCB-16-25-6000	400	385	6000	10290	25	2	2900	2900
CCB-16-30-7500	400	386	7500	12860	30	2	2900	2900
CCB-16-40-10000	400	386	10000	17145	40	2	2900	2900
CCB-16-50-12500	400	383	12500	21430	50	2	2900	2900
CCB-16-60-15000	400	386	15000	25715	60	2	2900	2900
CCB-18-2-350	450	450	350	600	2	2	2900	2900
CCB-18-3-550	450	449	550	945	3	2	2900	2900
CCB-18-5-900	450	446	900	1545	5	2	2900	2900
CCB-18-7.5-1450	450	442	1450	2490	7.5	2	2900	2900
CCB-18-10-1900	450	439	1900	3260	10	2	2900	2900
CCB-18-15-3000	450	435	3000	5145	15	2	2900	2900
CCB-18-20-4000	450	434	4000	6860	20	2	2900	2900
CCB-18-25-5000	450	435	5000	8575	25	2	2900	2900
CCB-18-30-6500	450	435	6500	11145	30	2	2900	2900
CCB-18-40-9000	450	434	9000	15430	40	2	2900	2900
CCB-18-50-11000	450	436	11000	18860	50	2	2900	2900
CCB-18-60-13500	450	438	13500	23145	60	2	2900	2900



CONTINENTAL THERMAL ENGINEERS PVT LTD BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
UNITS	MMWC	MMWC	CFM	M ³ /Hr				
CCB-20-2-300	500	500	300	515	2	2	2900	2900
CCB-20-3-500	500	499	500	860	3	2	2900	2900
CCB-20-5-800	500	498	800	1375	5	2	2900	2900
CCB-20-7.5-1300	500	497	1300	2230	7.5	2	2900	2900
CCB-20-10-1800	500	495	1800	3090	10	2	2900	2900
CCB-20-15-2700	500	490	2700	4630	15	2	2900	2900
CCB-20-20-3800	500	486	3800	6515	20	2	2900	2900
CCB-20-25-4700	500	486	4700	8060	25	2	2900	2900
CCB-20-30-5800	500	487	5800	9945	30	2	2900	2900
CCB-20-40-7800	500	487	7800	13375	40	2	2900	2900
CCB-20-50-10000	500	488	10000	17145	50	2	2900	2900
CCB-20-60-12000	500	485	12000	20575	60	2	2900	2900
CCB-24-3-400	600	600	400	690	3	2	2900	2900
CCB-24-5-700	600	599	700	1200	5	2	2900	2900
CCB-24-7.5-1000	600	598	1000	1715	7.5	2	2900	2900
CCB-24-10-1500	600	594	1500	2575	10	2	2900	2900
CCB-24-15-2400	600	591	2400	4115	15	2	2900	2900
CCB-24-20-3200	600	590	3200	5490	20	2	2900	2900
CCB-24-25-4000	600	590	4000	6860	25	2	2900	2900
CCB-24-30-4200	600	589	4200	7200	30	2	2900	2900
CCB-24-40-6700	600	587	6700	11485	40	2	2900	2900
CCB-24-50-8500	600	587	8500	14575	50	2	2900	2900
CCB-24-60-10200	600	584	10200	17490	60	2	2900	2900



CONTINENTAL THERMAL ENGINEERS PVT LTD BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
CSP-28-3-350	700	680	350	600	3	2	2900	2900
CSP-28-5-600	700	680	600	1030	5	2	2900	2900
CSP-28-7.5-900	700	680	900	1545	7.5	2	2900	2900
CSP-28-10-1250	700	680	1250	2145	10	2	2900	2900
CSP-28-15-1850	700	680	1850	3175	15	2	2900	2900
CSP-28-20-2500	700	665	2500	4290	20	2	2900	2900
CSP-28-25-3100	700	665	3100	5315	25	2	2900	2900
CSP-28-30-3700	700	665	3700	6345	30	2	2900	2900
CSP-28-40-5000	700	665	5000	8575	40	2	2900	2900
CSP-28-50-6200	700	655	6200	10630	50	2	2900	2900
CSP-28-60-7500	700	655	7500	12860	60	2	2900	2900
CSP-32-3-275	800	785	275	475	3	2	2900	2900
CSP-32-5-500	800	785	500	860	5	2	2900	2900
CSP-32-7.5-750	800	785	750	1290	7.5	2	2900	2900
CSP-32-10-1050	800	785	1050	1800	10	2	2900	2900
CSP-32-15-1550	800	780	1550	2660	15	2	2900	2900
CSP-32-20-2100	800	780	2100	3600	20	2	2900	2900
CSP-32-25-2600	800	775	2600	4460	25	2	2900	2900
CSP-32-30-3100	800	775	3100	5315	30	2	2900	2900
CSP-32-40-4200	800	760	4200	7200	40	2	2900	2900
CSP-32-50-5200	800	760	5200	8915	50	2	2900	2900
CSP-32-60-6200	800	760	6200	10630	60	2	2900	2900



CONTINENTAL THERMAL ENGINEERS PVT LTD

BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
CSP-36-3-250	900	885	250	430	3	2	2900	2900
CSP-36-5-450	900	885	450	775	5	2	2900	2900
CSP-36-7.5-700	900	885	700	1200	7.5	2	2900	2900
CSP-36-10-900	900	885	900	1545	10	2	2900	2900
CSP-36-15-1400	900	885	1400	2400	15	2	2900	2900
CSP-36-20-1850	900	885	1850	3175	20	2	2900	2900
CSP-36-25-2300	900	875	2300	3950	25	2	2900	2900
CSP-36-30-2750	900	875	2750	4715	30	2	2900	2900
CSP-36-40-3700	900	860	3700	6345	40	2	2900	2900
CSP-36-50-4600	900	860	4600	7890	50	2	2900	2900
CSP-36-60-5500	900	860	5500	9430	60	2	2900	2900
UNITS	MMWC	MMWC	CFM	M ³ /Hr				
CHP-40-5-350	1000	995	350	600	5	2	2900	2900
CHP-40-7.5-600	1000	990	600	1030	7.5	2	2900	2900
CHP-40-10-800	1000	985	800	1375	10	2	2900	2900
CHP-40-15-1300	1000	982	1300	2230	15	2	2900	2900
CHP-40-20-1900	1000	980	1900	3260	20	2	2900	2900
CHP-40-25-2400	1000	978	2400	4115	25	2	2900	2900
CHP-40-30-2900	1000	975	2900	4975	30	2	2900	2900
CHP-40-40-4000	1000	973	4000	6860	40	2	2900	2900
CHP-40-50-5000	1000	970	5000	8575	50	2	2900	2900
CHP-40-60-6000	1000	965	6000	10290	60	2	2900	2900



CONTINENTAL THERMAL ENGINEERS PVT LTD BLOWER SPECIFICATION CHART

DIRECT DRIVE BLOWERS

BLOWER MODEL	TOTAL PRESSURE	STATIC PRESSURE	AIR VOLUME		MOTOR HP	No.OF POLES	MOTOR RPM	FAN RPM
CHPT-44-5-250	1100	1095	250	690	5	2	2900	2900
CHPT-44-7.5-500	1100	1090	500	1030	7.5	2	2900	2900
CHPT-44-10-700	1100	1085	700	1715	10	2	2900	2900
CHPT-44-15-1200	1100	1080	1200	2400	15	2	2900	2900
CHPT-44-20-1600	1100	1075	1600	3090	20	2	2900	2900
CHPT-44-25-2100	1100	1070	2100	3945	25	2	2900	2900
CHPT-44-30-2600	1100	1060	2600	5490	30	2	2900	2900
CHPT-44-40-3600	1100	1045	3600	7030	40	2	2900	2900
CHPT-44-50-4600	1100	1035	4600	8400	50	2	2900	2900
CHPT-44-60-5500	1100	1030	5500		60	2	2900	2900
CHPT-48-5-250	1200	1180	250	430	5	2	2900	2900
CHPT-48-7.5-400	1200	1178	400	690	7.5	2	2900	2900
CHPT-48-10-600	1200	1170	600	1030	10	2	2900	2900
CHPT-48-15-1000	1200	1165	1000	1715	15	2	2900	2900
CHPT-48-20-1400	1200	1160	1400	2400	20	2	2900	2900
CHPT-48-25-1800	1200	1155	1800	3090	25	2	2900	2900
CHPT-48-30-2300	1200	1150	2300	3945	30	2	2900	2900
CHPT-48-40-3200	1200	1145	3200	5490	40	2	2900	2900
CHPT-48-50-4100	1200	1140	4100	7030	50	2	2900	2900
CHPT-48-60-4900	1200	1135	4900	8400	60	2	2900	2900