

**CPU09CMI - 4K ROM - GAL Selection Table.**

Type	I/O	G1 - 16MHz card 12 MHz & 16MHz	G1 - Standard card 8MHz & 12MHz	G2 - All cards	Programmer
GAL16V8A-15LP	2	x	x	CMI_2	1, 2
GAL16V8B-15LP	1	x	x	CMI_2	1, 2
GAL16V8D-15LP	1	x	x	CMI_2	1, 2
GAL16V8D-25LP	1	x	x	CMI_2	1, 2
GAL22V10B-15LP	3	CMI-4X_1	CMI-1X_1	x	1, 2
GAL22V10D-15LP	3	CMI-4X_1	CMI-1X_1	x	1, 2
ATF16V8B-15PC	1	x	x	ATF-CMI_2	2, 3, 1
ATF16V8B-25PC	1	x	x	ATF-CMI_2	2, 3, 1
ATF22V10B-15PC	1	ATF-CMI-4X_1	ATF-CMI_1X_1	x	2, 3, 1
ATF22V10C-15PC	5	ATF-CMI-4X_1	ATF-CMI_1X_1	x	2, 3, 1
PALCE16V8-15PC	1	x	x	CMI_2	2
PALCE16V8-25PC	1	x	x	CMI_2	2
PALCE16V8H-15PC/4	4	x	x	CMI_2	2, 3
PALCE16V8H-25PC	4	x	x	CMI_2	2, 3
PALCE22V10H-15PC/4	4	CMI-4X_1	CMI-1X_1	x	2
PALCE22V10H-25PC/4	4			x	x
PALCE22V10Q-25PC	4	CMI-4X_1	CMI-1X_1	x	2

Tested

Any open field means not used/tested

First nr preferred

Also tested a mix ATF / GAL / PALCE and -15 / -25

<b>I/O:</b> 1 = I/O 50K pull up 2 = I/O No pull up 3 = I/O Active pull up 4 = 100K 50K No pull up 5 = I/O Pin keeper	<b>Programmer:</b> 1 = Xgpro TL866II Plus, Sw 12.90 Fw 04.2.132 2 = GALEP-4, Galep32 Version 1.20.4 3 = TOP2013, Sw Topall 8.92 - Fw 6.30 x = No programmer available
--	---

Remarks: I/O type 4 depending on device suffix, /4 = 100K, /5 = 50K, otherwise NO pull-up.

I/O type 2, 4 and 5 may need a pull-up on floating input pins.

Some ATF16V8B had errors on the TL866II Plus but not on the GALEP-4.

Do select the full name in the programmer A, B, C, D, H or Q version !

Otherwise you will get programming errors !

TOP2013 also select the correct speed -10, -15 or -25 !