- DO -

The DO command is used to process a text file as a list of commands. The DO command allows up to 10 parameters or a total of 128 characters to be passed to the command file.

DESCRIPTION

The general syntax of the DO command is:

DO <file spec>[param1,param2,param3...]

where <file spec> is the name of the DO command file. The default extension of a command file is DO.
In a command file some special characters are used:

! All characters on a line following the exclamation mark are treated as comment. During echoing of the comment line parameters are substituted when they are used.

& This character is the lead-in character for a parameter to be substituted in this place. The '&' must be followed by a letter 'A' to 'J'. 'A' is the first parameter from the command line and 'J' is the tenth parameter. Parameters on the command line must be separated by a comma. Empty parameters can be passed by two comma's.

+ If the plus sign is used on the first position on a line then the line is passed to FLEX, after parameter substitution as a command. If there is no plus sign on a line then the characters of the line may be used as input for the executing command. Else unused lines are ignored by DO.

This character can be placed immediately following a plus sign on a command line to enable continuation of the DO command if an error should occur during execution of the specified command line. Otherwise the DO command is aborted by an error. The '' mark may be followed by a digit 1 to 9. This digit gives the number of lines of the DO command file to be skipped if an error occurs executing the specified command.

% When the percent sign is placed in an input parameter field then one character is expected from the console input.

_ The underscore character may be placed before any of the above mentioned characters (including the underscore itself) to make them lose their special meaning.

EXAMPLES

A DO command file can be created with BUILD or EDI (extension = .DO).

```
! This file formats the disk in drive  1.
! &A is the disk name. The volume number is &B.
+NEWDISK 1
%YNYN&A
&B
+CAT 1
! Finished...
```

Name this file ND.DO and place it on drive 0.
Now put the scratch disk in drive 1 and give the command:

```
+++DO 0.ND MYDISK.NEW,12
```

You will see the following:

```
! This file formats the disk in drive 1.
! MYDISK.NEW is the disk name. The volume number is 12.
++NEWDISK 1
ARE YOU SURE  ? Y  this answer is expected from you)
Scratch disk in drive 1 ? Y
Double sided disk ? N
Double density disk  ?  Y
System disk ? N
Volume name : MYDISK.NEW
Volume number : 12
```

At this moment the disk will be formatted.
When NEWDISK is ready, the empty CAT of drive 1 is shown.
If no or not sufficient input parameters are given after the command line of the executing command and before the next command line then normal input from the console is expected.
Console input for one character can also be forced using the '%' in an input parameter field.
In a DO command file DO itself may be called again. Execution of the new DO command terminates the previous DO command, so in fact it is just a restart of the DO command with a new command parameter file and/or parameters.
The DO command occupies about 1k of memory below FLEX MEMEND.