


基础 Foundation



Stationary Crane
固定式起重机

塔身 Tower	高度 (米) TH(m)	臂长 (米) Jib reach(m)	基础载荷 Foundation loadings			地脚反力 Corner forces	
			Mc(kN.m)	Nc(kN)	H(kN)	F1(kN)	F2(kN)
L69B	48,0	75	4834	1122	188,7	-1429	1990

运输 Shipping

塔身 Tower	高度 (米) TH(m)	集装箱数量 Container QTY			
		FR	40' OP	40' HQ	20' GP
L69B	48,0			11	

机构性能 Mechanisms

机构特性 Mechanisms specification											kW
起升 Hoisting		75LVF40	m/min	82,0	69,0	46,0	41,0	34,5	23,0	500m	75
			t	3,5	5,0	8,0	7,0	10,0	16,0		
变幅 Trolleying		6T3V7	m/min	65							185Nm
		8DVF7		74							7,5
回转 Slewing		RZV95×3	r/min	0,67							95Nm×3
行走 Travelling		5RTVF4	m/min	25							5,5×4
电源 Power Supply						380V 50Hz / 440V 60Hz					
KVA 供电容量 Necessary Electric Power						103 kVA					

沈阳宝泉商贸有限公司

地址: 辽宁省沈阳市大东区东北大马路264号, 509-511室

电话: 0086-24-26210512

邮箱: bqswgs@163.com

网址: http://www.bq-sy.com


SHENYANG BAOQUAN BUSINESS CO., LTD

ADD: ROOM NO.509-511, NO.264 DONGBEI DAMALU ROAD, DADONG DISTRICT, SHENYANG CHINA


Tel: 0086-24-26210512

E-mail: bqswgs@163.com


Url: http://www.bq-sy.com




起重臂 Jib



载荷特性 Load Diagrams




塔身 Tower



Tower configuration
塔身组成

序号 No.	塔身 Tower	标节 Mast	高度 (米) HH(m)	臂长 (米) Jib reach(m)
1	L69B	16	48,0	30-75

附着 Anchorages



塔身 Tower	L69B		
	m	工作状态 Working	非工作状态 Off Working
H1	37,5	—	—
H2	27,0	—	—
H3	37,5	—	—
H4	37,5	—	—
H5	12,0	—	—
H6	36,0	—	—
P1	—	24,2	27,3
P2	—	23,2	26,3
V	—	105,0	94,5
A	2,6		
B	2,6		