Assignment 8: Embeddings, Recurrent Networks, and Sequences (Part 3)

New Attempt

Due Jun 1 by 5:59pm **Points** 6 **Submitting** a text entry box or a file upload

Question 8 (1 point)

For this week's homework, we're using a Hugging Face Trainer wrapper to finetune and evaluate a PyTorch model (because pytorch supports gradient_accumulation_steps to accumulate gradients across training batches). [Perhaps someday Keras' model.fit() will also support a gradient_accumulation_steps argument.]

The console output for this week's Kaggle task includes print(model) output for the PyTorch model.

For my model, the console output can be found here: https://www.cross-entropy.net/ML530/imdb-console.txt

When I look at the "RobertaEmbeddings", I see the following entry for "word_embeddings":
(word_embeddings): Embedding(50265, 1024, padding_idx=1)

This means our vocabulary consists of 50,265 tokens, and each embedding consists of 1,024 features per token.

So the total number of parameters for "word_embeddings" is 51,471,360 (50,265 tokens * 1,024 features per token); and these parameters occupy 205,885,440 (51,471,360 parameters * 4 per bytes per float32 parameters) bytes of memory.

For the model you choose ...
a) Which model did you choose?
b) What is the size of the vocabulary?
c) How many features are used for each token?
d) How many parameters are there for the word embeddings?
e) How much memory is consumed to store these parameters? [Assume float32 representation for the parameters.]

Model 8 (5 points)

Please navigate to the following URL to accept the invitation for this Kaggle task:

https://www.kaggle.com/t/4ff5f2bdd33e455a9ee9b1d85149850a

Activate the pytorch conda environment on your VM
conda activate py37_pytorch

Install the Kaggle API and the Hugging Face transformers library into your pytorch environment:
pip install kaggle
pip install transformers

Download the data and the finetuning script:
kaggle competitions download ml530-2021-sp-imdb
wget --timeout=2 https://www.cross-entropy.net/ML530/imdb-train.py.txt

Pick one of the following models to build a model for sentiment classification, then use that name as an argument when running the imdb-train.py.txt script:
bert-base-cased
bert-base-uncased
bert-large-cased
bert-large-uncased
roberta-base
roberta-large
distilbert-base-uncased
distilbert-base-cased
distilroberta-base
microsoft/deberta-base
microsoft/deberta-large
squeezebert/squeezebert-uncased

You can find descriptions for these models here: https://huggingface.co/transformers/pretrained_models.html

The size of the "roberta-large" model is stated as "24-layer, 1024-hidden, 16-heads, 355M parameters". The "1024-hidden" means each embedding has 1024 features (so d_model = 1024). The larger the number of layers, the longer it will take to train. The large the number of features per embedding, the longer it will take to train. The "roberta-large" model takes around 6 hours for training and evaluation on a K80 GPU on a lab machine.

For example, to run roberta-large, use:
python imdb-train.py.txt roberta-large

Upload your predictions:
kaggle competitions submit ml530-2021-sp-imdb -f predictions.csv -m "imdb submission"

Previous Next

Submission

✓ Submitted!
Jun 7 at 8:53pm (late)
Submission Details
Download HW08.txt

Grade: 6 (6 pts possible)
Graded Anonymously: no

Comments:
No Comments