Memory and Spatial Constraints on Eventual Translation in Langton's Ant

Hao Ke

Abstract

How much memory and space does a Langton ant need to sustain motion that never becomes periodically translating? We first give an exact prediction algorithm. A black read is old at memory length D when its cell was absent from the preceding D visits. From any complete finite initial state, the next old-black read is computable, with polynomial bit complexity for fixed D. Finite arithmetic segments retain every skipped write and allow exact continuation. Geometric bounds give quadratic deadlines for finite event prefixes and total queries outside any fixed finite region. They imply that a non-eventually- translating orbit must repeatedly consume black marks that are simultaneously remote, created late and left unread for a long time. A twenty-cell construction shows why spatial scale remains necessary in lifetime bounds even when the intervening event count is fixed. Independently, exact crossing-record counts and a local visit inequality force whole-prefix oblique width at least $(1-o(1))\log_2 \log T$ by time T on every non-eventually-translating orbit. Width uses non-axis normals normalized by $\min(|\alpha|, |\beta|) = 1$. Together these results provide effective event queries and necessary temporal and spatial resources for persistent nontranslation.

1 Introduction

A short record of the ant's turns determines the geometry of its recent visits. If the current cell occurs in that record, its colour follows from the last visit and the intervening flip. If it does not, a predictor can provisionally treat it as white. This prediction fails exactly when the ant reads a black cell absent from its recent visits. Such a cell may be an unvisited obstacle in the initial colouring or a mark left long ago by the ant itself.

We study this failure for a memory of D turns. The first question is algorithmic: given the entire finite colouring now, can one find the next failure without simulating a potentially distant collision? The second is physical: after skipping a long predicted flight, can one retain every black cell needed to continue the calculation? We answer both questions. A finite suffix predictor gives a repeating candidate motion, exact arithmetic finds its first disagreement with the colouring, and finite arithmetic segments record all writes made during the skipped flight.

These algorithms also constrain how old marks can influence later motion. We prove that a flight ending at a prediction failure lies in a bounded tube around the segment joining its endpoints. This yields quadratic bounds on the time to a given number of failures and makes queries outside a fixed finite region decidable. Applied repeatedly,

the bounds imply that an orbit which never becomes periodically translating must consume black marks that are simultaneously newly created, arbitrarily old when read, and arbitrarily far away. Here a mark's lifetime begins with a white-to-black update and ends at the next read of that cell, which turns it white.

A twenty-cell construction explains the spatial parameter in these bounds. With only twenty initially black cells and exactly 31 intervening failures for $D = 128$, a family of inputs produces lifetimes of unbounded duration. The inputs spread farther apart as the duration grows. Thus fixed black mass and a fixed number of failures do not by themselves control a lifetime.

Crossing records then quantify how much transverse space persistent nontranslation requires. Equal guarded records force a permanently translating future. Incoming heights determine the entire crossing history and its retained inside field. Counting these requests gives a minimum amount of crossing work, while a local corner inequality bounds repeated visits in a narrow band. Combining the two yields a double-logarithmic lower bound on whole-prefix oblique width, uniformly over normalized non-axis normals. This argument uses crossings rather than old-black events, and supplies an independent geometric constraint on the same class of orbits. The method adapts Hennie's crossing sequences [7] to spatial cuts with retained colour histories. The space threshold discussed in [8] is measured against input length; our geometric width is instead measured against elapsed orbit time.

Gajardo's symbolic treatment relates long return paths to infinite memory effects [1]. Gajardo, Moreira and Goles establish P-hardness of arbitrary cell visitation through finite circuit configurations [6]; their infinite computation construction uses an infinite background. Our target is the specific failure of a finite-recency predictor on complete finite input. For fixed D, the event algorithm is polynomial in sparse binary input size. The periodic read test uses full-drift chronology [3], and the finite-region argument uses the square escape theorem [4]. Highway multiplicity for generalized rules is studied in [2]; we use the classical two-colour rule.

Section 3 constructs the predictor. Sections 4–5 prove the geometric bounds, which then control the cost of exact continuation in Section 6. Sections 7–8 derive remote feedback. Section 9 presents the twenty-cell construction and explains the role of spatial scale in the event estimates. Section 10 derives the independent crossing-information width bound.

2 Model and results

A complete state $X = (B, p, h)$ has finite $B \subset \mathbb{Z}^2$. White turns right, black turns left; flip then move. Cartesian headings N,E,S,W have vectors $(0,1), (1,0), (0,-1), (-1,0)$ and are numbered $0, 1, 2, 3$. Write $\mathrm{pos}(X) = p$, and let $\mathrm{dir}(h)$ be the unit vector of heading h. The turn $\mathrm{turn}(X)$ is R when $p \notin B$ and L when $p \in B$. The standard highway, abbreviated P104 below, repeats the classical 104-turn word with displacement $(2, 2)$ up to quarter-turn rotation and cyclic phase. Let F be the invertible update. A state at time t precedes update t, which maps $F^t X$ to $F^{t+1} X$. For $D \geq 1$, write

$Q = 2^D$, the number of length-D turn words, and define the intrinsic event

$$S_D(X) \iff p \in B \quad \text{and} \quad \mathrm{pos}(F^{-j}X) \neq p \quad (1 \le j \le D).$$

Its inverse-history definition applies at the input time as well as later. It records an old black read. For forward times at least D, the definition uses the actual preceding D visits. At the input time, inverse dynamics supply the same history convention. An initially black cell can trigger this event even if the ant has never read it during the forward run.

A *black lifetime* is a pair of update times $b < e$: update b changes a cell from white to black, and update e is its next read. Its age at consumption is $e - b$. Initially black inventory has no post-input birth. An orbit is *eventually translating* if, after some time, its turns repeat with a heading-restoring period and nonzero displacement; its full black field still records the accumulated trail. A *complete endpoint* below includes that entire field, the head position and the heading.

Write $m = |B|$, let b denote the input coordinate bit length when discussing complexity, and put $R = \max(\{\|q - p\|_\infty : q \in B\} \cup \{0\})$. The algorithms return either the first requested event with its exact post-event state, or a certificate that the requested event never occurs.

Prediction and continuation. The next S_D, if present, occurs before $Q(R + 2Q + 10)$, where R is the initial head-relative radius. Existence is decidable in polynomial bit time for fixed D on sparse explicit input. Finite XOR segments allow the exact full endpoint to be returned without expanding every skipped write. The first n events and their full encoded endpoint are computable in $f(D)\,\mathrm{poly}(m + n + b)$, where m is the initial mass, b the coordinate bit length, and n is measured numerically.

Geometry. With $W = \mathrm{diam}_\infty(B \cup \{p\})$, the time just after event n, whenever it exists, is at most

$$T_D(n, W) = Qn(W + 2Q + 10) + 5Q^2 n(n - 1). \tag{1}$$

Between a starting head p and its next event cell e, the entire finite trajectory stays within $3Q + 1$ of $[p, e]$. After joining successive event locations the corresponding tube radius is $3Q + 2$.

Remote feedback. For every fixed finite region K, existence of an S_D outside K is decidable. If a trajectory is not eventually a nonzero translator, then for every D, K, T there are infinitely many black lifetimes born after T, lasting more than D, and consumed outside K. The properties hold simultaneously for the same lifetimes.

Newly generated feedback. The first exterior old lifetime born since the input checkpoint is totally computable, including its exact birth, consumption and complete post-state. On a non-eventually-translating orbit, for every sufficiently large time horizon H, Section 8 gives $\Omega(\sqrt{H}/\log H)$ lifetimes with birth after $H^{1/4}$ up to integer rounding, radius of order $\log H$, and age of order $\log\log H$.

Spatial-scale obstruction. For every even $n \ge 20$, a complete 20-black initial state writes a cell at time 60 and next reads it at $624n - 1516$, with exactly 31 intervening S_{128} events. Its first permanent P104 time is $624n - 742$. Thus no lifetime bound depending only on D, intervening event count and initial mass can hold uniformly.

Crossing information and oblique width. Independently of prediction failures, crossing-record counts and a local visit inequality force every finite-support orbit that is not eventually translating to satisfy

$$\liminf_{T\to\infty} \frac{w_{\alpha,\beta}(T)}{\log\log T} \geq \frac{1}{\log 2}$$

for every non-axis normal normalized by $\min(|\alpha|, |\beta|) = 1$. Here $w_{\alpha,\beta}(T)$ is the range of $\alpha x_t + \beta y_t$ over the whole prefix $0 \leq t \leq T$. Section 10 gives the uniform finite profile deadline behind this bound.

3 Predicting the next old-black read

3.1 Definitions and an intrinsic finite-local target

Write X=(B,p,h), headings N,E,S,W. Let F be the literal update. Define

$$R(X) = \max(\{\|q - p\|_\infty : q \in B\} \cup \{0\}).$$

For integer $D \geq 1$, define the stale-black predicate

$$S_D(X) \iff p \in B \text{ and } \operatorname{pos}(F^{-k}X) \neq p \quad (1 \leq k \leq D). \tag{2}$$

The inverse is literal and unique: set $q = p - \operatorname{dir}(h)$, flip q, and undo a right turn when q is black in the supplied post-state, otherwise undo a left turn. Only cells at distance at most D from p are read during D inverse steps. Consequently (2) is a translation-invariant finite local predicate on the present colouring and heading. It is determined by this finite neighbourhood.

Using the intrinsic backward orbit makes (2) defined even at input time zero. At forward times $t \geq D$, it says exactly: the current read is black and the same cell has not been read in the previous D updates. A very old white reread is not an S_D event. A never-yet-read initial black cell can be an S_D event too. This convention is distinguished from an age defined only after time zero.

Let $\tau_D(X) = \min\{t \geq 0 : S_D(F^t X)\}$, when it exists. This target comprises infinitely many full states; the result below is not just specified-full-state reachability.

3.2 Prediction identity: no event means one unique next turn

For a D-letter word $w = w_0 \cdots w_{D-1}$ over $\{\mathrm{R}, \mathrm{L}\}$, order the letters chronologically from oldest to newest and execute its geometric turns from a fixed pose. Compare the final position to the preceding D pre-update positions, indexed by $j = 0, \ldots, D-1$. If the last matching position has index j, set $f_D(w) = \operatorname{opposite}(w_j)$; if there is no match, set $f_D(w) = \mathrm{R}$. This depends only on w: translation and quarter turns preserve position equality.

Recover the actual previous D turns of X using F^{-1}, and write $w(X)$ for the turns at $F^{-D}X, \dots, F^{-1}X$, in that order. Pre-update position j corresponds to $F^{-(D-j)}X$, and $\mathrm{suffix}_{D-1}(w) = w_1 \cdots w_{D-1}$ (the empty word when $D = 1$). The following equality is exact for every finite state:

$$\mathrm{turn}(X) \neq f_D(w(X)) \iff S_D(X). \tag{3}$$

Moreover the only possible mismatch is predicted R versus actual L.

Proof: a recent previous read fixes the current colour to its flipped value. With no recent previous read, f_D predicts R. This is wrong precisely when the current cell is black. Old white cells and virgin white cells both give R. The backward suffix is part of the actual orbit and is recovered uniquely by inverse updates.

While S_D is absent, suffixes evolve autonomously as

$$w \longmapsto \mathrm{suffix}_{D-1}(w)\, f_D(w).$$

This is a deterministic map on $Q = 2^D$ states. Its generated infinite turn word has a transient shorter than Q and period at most Q. This alone does not prove that the physical ant follows the word forever: distant black cells may cause a first mismatch. The next section bounds when any such mismatch can occur.

3.3 First mismatch against an ultimately periodic motion plan

Consider a complete finite state Y of radius r and a proposed periodic turn word u of length P, with matching start/end heading and displacement $d \neq 0$. Let q_i, $0 \leq i < P$, be its relative pre-update positions in the head-centred frame $p_Y = 0$, so B_Y is translated into that frame and $q_0 = 0$. Its proposed future reads are

$$q_i + kd, \qquad k \geq 0.$$

Earlier periodic reads of the same cell correspond exactly to

$$q_j - q_i = \ell d, \quad \ell \geq 0, \quad (\ell > 0 \text{ or } j < i), \quad k \geq \ell. \tag{4}$$

Each such ℓ is at most P: the finite footprint's pairwise infinity-distance is at most P, and $\|d\|_\infty \geq 1$. Earlier-read parity can change only at these finitely many thresholds ℓ.

The initial colour contribution is $\mathbf{1}_{B_Y}(q_i + kd)$. If this is nonzero then

$$k\|d\|_\infty \leq r + \|q_i\|_\infty \leq r + P,$$

so $k \leq r + P$. For fixed phase i, each cell of B_Y can match $q_i + kd$ at only one epoch, since $d \neq 0$. Its initial-colour indicator is therefore supported at that single

epoch; earlier writes contribute separately through their parity. Thus the cell colour produced by literal dynamics at each phase i, which must match the turn u_i, is

$$\mathbf{1}_{B_Y}(q_i + kd) \ \oplus \ \big(\#\{\text{eligible pairs in (4)}\} \bmod 2\big). \tag{5}$$

All changes occur by epoch r+P+1. Testing every breakpoint, including the last infinite constant interval, is necessary and sufficient for infinite execution. If there is a mismatch, its first time is strictly below

$$P(r + P + 2). \tag{6}$$

This statement concerns the first mismatch, not a hypothetical trajectory after an earlier mismatch. Induction in time ensures that the proposed path agrees with the real path up to that first point.

If u does not restore heading, repeat it two or four times to restore heading. The resulting displacement is zero, since the quarter-rotated displacement vectors sum to zero. If heading is restored but $d = 0$ already, use u itself. In either case let v be the closed-pose block, of length at most $4P$. If two consecutive copies of v were both physically valid, all flips would occur twice and the complete state would recur. Such an orbit would remain in finitely many cells forever, impossible for the classical ant. Hence a first mismatch occurs before $2|v| \le 8P$ updates.

The classical unboundedness theorem is due to Bunimovich and Troubetzkoy; we use the accessible corner proof in [2, Section 2]. Its argument is as follows. If the set I of infinitely read cells were nonempty and finite, choose a cell maximizing x+y. After the north and east neighbours have ceased being read, the checkerboard/heading-axis invariant fixes the only possible entering and leaving directions at that cell. This requires the same read colour on every sufficiently late visit, contradicting colour alternation. This proves that the orbit cannot remain in a bounded region.

3.4 Uniform waiting theorem

Theorem (first-event waiting bound). For every finite state X and $D \ge 1$, with $Q = 2^D$, put

$$\mathcal{H}_D(X) = Q(R(X) + 2Q + 10). \tag{7}$$

Exactly one of the following occurs:

- $\tau_D(X)$ exists and $0 \le \tau_D(X) < \mathcal{H}_D(X)$;
- S_D never occurs at any nonnegative time; the ant has a nonzero translating periodic trace with period at most Q, beginning at a time at most Q.

Thus observing no S_D event at times 0,...,$\mathcal{H}_D(X) - 1$ proves that none ever occurs.

Proof: construct the autonomous suffix trajectory. If a physical mismatch occurs before the first repeated suffix, (3) gives the event within Q updates. Otherwise at a repetition time $j \le Q$, the physical trajectory has followed the plan and a periodic

suffix cycle of length $P \le Q$ begins from its current phase. The current complete radius is at most $R(X)+j$: initial black cells move relative to the ant by at most j; any newly black cell is also within j steps of it.

For nonzero translational drift, (6) bounds a first future mismatch by

$$j + P(R(X) + j + P + 2) \le Q(R(X) + 2Q + 3).$$

For a closed geometric plan, the other bound is $j+8P \le 9Q$. Both are strictly covered by (7). If no mismatch exists, the planned periodic trace is the exact infinite future. A closed or rotating periodic plan was excluded above, so its drift is nonzero. By (3), no mismatch also means no S_D event. This proves both the waiting bound and the dichotomy.

3.4.1 What is the corresponding decision problem?

The family

$$\mathcal{L}_D = \{X : \exists t \ge 0,\ S_D(F^t X)\}. \tag{8}$$

is recursive, uniformly in D.

A simple decision algorithm simulates the explicit finite bound (7). The implementation uses the stronger symbolic version: only the first suffix cycle is produced, then all-future ray/flip arithmetic finds the first event, or verifies a permanent event-free trace. No simulation to a late arithmetic collision is necessary.

3.4.2 Bit complexity of the implemented first-event decision

With an explicit sparse list of m black coordinates of bit length at most b, the symbolic first-event algorithm uses time $2^{O(D)}$ times a polynomial in the input length. In particular, for every fixed D, language (8) is decidable in polynomial time in the sparse binary-coordinate input size.

Indeed inverse-history recovery uses D steps; the suffix search uses at most $Q = 2^D$ states; its explicit black field has at most $m+Q+D$ cells. The candidate word has length at most Q, and the ray verifier checks $O(Qm+Q^2)$ phase/cell and phase/phase relations. All coordinate, epoch and offset arithmetic has bit length polynomial in b+D. Closed-pose control replay costs at most $8Q$ updates. Ordinary polynomial-time set/dictionary implementations suffice. The parameter factor grows exponentially in D.

For fixed D the upper bound is linear in R. This order cannot in general be replaced by a radius-independent constant: take a certified event-free P104 state with D=128 and insert one remote black cell at a virgin frontier site k highway periods ahead. Until its first read the original periodic trajectory is unchanged. The first event is at $104k + O(1)$, while $R = 2k + O(1)$. The phase-ray calculation gives the constants exactly. The full input coordinates supply the growing scale.

4 Geometry between prediction failures

A finite event segment starts from a complete state and ends just after its first S_D update. Its endpoints constrain every intervening read, even when the segment contains a very long predicted flight. Throughout this section $Q = 2^D$ and $\|\cdot\|$ denotes the maximum norm.

4.1 Two-endpoint tube for a finite event macro

Start at X with head p. Suppose its first S_D event is at offset τ, at cell e. The macro includes that read and its actual outgoing move, so its duration is $L = \tau + 1$. Let $[p, e]$ denote the real line segment between its endpoints.

Theorem (endpoint tube and distance-sensitive time). Every head position from time 0 through time $\tau + 1$ is in

$$[p, e] + [-(3Q + 1), 3Q + 1]^2. \tag{9}$$

Every changed cell is in the same tube, and

$$L \le Q\|e - p\|_\infty + 5Q^2. \tag{10}$$

The tube does not depend on the radius or cardinality of B. Unchanged black cells outside it remain physically present; (9) does not enclose the full input black field. The next-event premise is essential.

4.1.1 Proof

Until the first event, the actual turns agree with the autonomous suffix predictor. Its word has a prefix of length $j \le Q$ and a cycle u of length $P \le Q$. If the event occurs in that prefix, its whole path and actual outgoing move are within Q+1 of p, sufficient for (9)–(10).

Otherwise let a be the head after the j-step prefix, and v_i the relative pre-update phase positions of u. Then $\|a - p\|_\infty \le j$ and $\|v_i\|_\infty \le P$.

First suppose u restores heading and has nonzero displacement d. Write the event as phase i, epoch k, so

$$e = a + v_i + kd.$$

When $k \ge 1$, any earlier phase position in epoch $\ell \le k$ has

$$\begin{gathered} a + v_s + \ell d = (1 - \lambda)a + \lambda e + v_s - \lambda v_i, \\ \lambda = \ell/k \in [0, 1]. \end{gathered} \tag{11}$$

The error has ℓ_∞ norm at most $2P$. Moving a to p costs at most j; the prefix is within j of p as well. For k=0 all cycle-prefix positions are within j+P of p directly. Thus

all positions through the event read lie in $[p, e] + [-3Q, 3Q]^2$. The true mismatched outgoing move costs at most one more.

Also, since d is a nonzero integer vector,

$$k \le k\|d\| \le \|e - p\| + j + P.$$

Hence

$$\begin{aligned} \tau + 1 &= j + kP + i + 1 \\ &\le Q\|e - p\| + 2Q^2 + 2Q \\ &\le Q\|e - p\| + 5Q^2. \end{aligned} \tag{12}$$

If the cycle rotates heading, repeat it twice or four times to restore heading. The resulting geometric block is closed, since its successively rotated drift vectors sum to zero. If heading is already restored with $d = 0$, use one copy. The closed block has length at most $4P$; its footprint is within $2P$ of a, because a point on a closed unit-step walk is reached by either side of the loop. Thus (9) again holds. Two physically valid copies of a closed block would repeat the complete state (every cell is toggled an even number of times), impossible by the no-bounded-orbit argument of Subsection 3.3. Consequently $\tau + 1 \le j + 8P \le 9Q$, which is at most $5Q^2$ because $Q \ge 2$. This proves (10) also in the closed cases. Every changed cell was a read position, proving the final assertion. □

This argument needs only a finite macro to its first event, not a presumption that any candidate predictor cycle is physically realizable forever.

4.2 The event skeleton carries the large-scale geometry

List the actual S_D event times $t_1 < t_2 < \cdots$ and cells e_i. Put

$$H_D = 3Q + 2, \qquad s_m = t_m + 1,$$
$$J_m = \|e_1 - p_0\| + \sum_{i=1}^{m-1} \|e_{i+1} - e_i\|.$$

Corollary (event-chain tube). Up to the complete post-mth-event state, the entire head path is contained in the H_D-neighbourhood of the polygonal chain

$$p_0 \longrightarrow e_1 \longrightarrow \cdots \longrightarrow e_m. \tag{13}$$

and

$$J_m + 1 \le s_m \le QJ_m + 6Q^2 m. \tag{14}$$

In particular, all changed cells are in that tube; the complete state still contains every unaltered initial black cell outside it.

Proof: each later macro starts one unit from e_i. Replacing that start by e_i in (9) adds at most one to the tube radius. Sum (10), bounding each later source-to-event distance by $\|e_{i+1} - e_i\|_\infty + 1$. The lower bound follows from unit-speed motion between the actual event cells. □

For every real linear functional a, the maximum of $a \cdot p_s$ over this prefix lies between $\max(a \cdot p_0, a \cdot e_1, \dots, a \cdot e_m)$ and that value plus $H_D\|a\|_1$. Thus, on an infinite event chain, any direction in which the head is unbounded above is also a direction in which these event locations are unbounded above. This controls the directional ranges of the event locations.

This is stronger than using the convex hull of the whole black field: far, untouched black debris does not enlarge the event-to-event tube. The bound follows from the geometry between consecutive events.

A lifetime with no intervening event. Let $N_D(b, e)$ count S_D events strictly between the birth and consumption of a black lifetime. If this count is zero, its age is bounded independently of the initial diameter. At a white birth b there is no S_D event. If $e - b > D$ and there is none in (b,e), the death is the first S_D from X_b and its source/event positions are equal. The endpoint-tube time estimate gives $e - b + 1 \le 5 \cdot 4^D$. If $e - b \le D$ the weaker bound $e - b \le 5 \cdot 4^D$ is immediate. Thus

$$N_D(b, e) = 0 \quad \Longrightarrow \quad e - b \le 5 \cdot 4^D. \tag{15}$$

5 Quadratic event budgets

Put $C(X) = \mathrm{conv}(B \cup \{p\})$, and let X_n be the complete state just after event n.

Theorem (convex-hull and quadratic event bounds). A finite event segment, including every intermediate head position, satisfies the enclosure

$$C(X_{\mathrm{next}}) \subset C(X) + [-5Q, 5Q]^2.$$

Iterating gives $C(X_n) \subset C(X_0) + [-5Qn, 5Qn]^2$ and the stated $T_D(n, W)$, together with the radius bound $R(X_n) \le W + 10Qn$. The first-event waiting estimate is the predictor bound proved above, given in (7).

5.1 A geometric lemma for a translating motion plan

Start at $Y = (B, p, h)$. Let a nonempty word u of length P restore heading and have nonzero drift d. Write its pre-update phase positions as $q_0, \dots, q_{P-1}$, with $q_0 = p$. The prescribed infinite positions are $q_i + kd$ for $k \ge 0$. These are at first just a motion plan: executability is not assumed.

Until its first read mismatch with literal LR dynamics, the plan is the actual orbit, by induction on updates. All earlier plan writes then legitimately contribute to its current read colour.

5.1.1 Only finitely many old-field and self-read changes matter

A previous phase j visits the position $q_i + kd$ precisely when

$$q_j - q_i = sd, \quad s \geq 0, \quad (s > 0 \text{ or } j < i), \quad k \geq s.$$

For each phase pair this toggles parity at one threshold s. Let K_{self} be the maximum of all these s and zero. Since the two phase points are connected by at most P unit moves within the block,

$$K_{\text{self}} \|d\|_\infty \leq P. \tag{16}$$

Let K_B be the greatest epoch $k \geq 0$ for which some $q_i + kd$ is in the actual finite set B. If there is no such pair, put K_B=-1. This maximum is finite. If $K_B \geq 0$, retain one corresponding black point

$$z = q_j + K_B d \in B. \tag{17}$$

Put

$$K_* = \max(0, K_{\text{self}}, K_B + 1). \tag{18}$$

At every epoch $k \geq K_*$ the old field contributes zero at every phase and every self-read threshold has stabilized. The prescribed read-colour vector is thus constant in k there. If a mismatch exists at all, a first mismatch must occur within epochs $0, \dots, K_*$, hence at an offset strictly below $(K_* + 1)P$.

This remains true if early old-black cells temporarily mask a self-inconsistent motion plan. Such masking ends by K_B+1 and has not been silently discarded. The argument works for either direction of colour mismatch; its later suffix instantiation has the special R-to-L mismatch property.

5.1.2 The same cutoff bounds space by a constant halo, not by travel time

We prove that every prescribed read in epochs $0, \dots, K_*$ is in

$$\text{conv}(B \cup \{p\}) + [-3P, 3P]^2. \tag{19}$$

If $K_* = K_{\text{self}}$, (16) gives $\|kd\|_\infty \leq P$ for all $k \leq K_*$, while $\|q_i - p\|_\infty \leq P$. These points are within $2P$ of p, already sufficient for (19). If $K_* = 0$ the statement is immediate.

Otherwise take $K_* = K_B + 1$ and the old black point z from (17). For $0 \leq k \leq K_B$ and $K_B > 0$, put $\lambda = k/K_B$. Then

$$q_i + kd = (1 - \lambda)p + \lambda z + (q_i - p) - \lambda(q_j - p).$$

The first two terms lie on the segment $[p, z]$; the remainder has ℓ_∞ norm at most $2P$. For k=K_B+1, add d to the k=K_B expression; $\|d\|_\infty \le P$, giving $3P$. When K_B=0, the two epochs k=0,1 are within $2P$ of p directly. Thus (19) holds in every case, including ties between maxima in (18).

In particular, if the plan has a first physical mismatch, all positions before and at that read satisfy (19). Executing the actual mismatched move instead of the planned one adds at most one unit of halo. The old field and every new black cell at the resulting complete endpoint also lie inside (19) enlarged by one, since each new black cell is a previously updated location.

There is no claim that an arbitrarily long valid event-free translating tail stays in (19). The finite mismatch is an essential hypothesis.

5.2 The one-event convex-hull bound

Run the order-D predictor from X until an immediate S_D event or a repeated suffix. Before the repetition $j \le Q$, all written cells and the head are within Q of the original head, so

$$C(X_j) \subset C(X) + [-Q, Q]^2. \tag{20}$$

An immediate event and its outgoing move have the claimed bound trivially. At a repeated suffix the plan cycle has length $P \le Q$.

If the heading is restored and drift is nonzero, apply Subsection 5.1 from the full state X_j. A finite next event is exactly its first mismatch. By (19),(20) and the real final update, the entire macro stays within halo

$$Q + 3P + 1 \le 4Q + 1 \le 5Q. \tag{21}$$

If the cycle rotates heading, repeat it at most four times to get a closed-pose plan; if its displacement is already zero use one copy. This closed plan has length $L \le 4P$. Each point of a closed unit-step walk is reachable from its origin in either time direction, so its distance from the origin is at most $L/2 \le 2P$. If two copies of that plan were fully executable, they would flip each cell an even total number of times and restore the pose, repeating the complete state. Consequently a mismatch occurs before $2L \le 8P$. All positions up to its read are in the same closed footprint, and the true mismatched move adds one unit. The resulting source-relative halo is at most $Q + 2P + 1 \le 5Q$.

Every unchanged black cell was already in C(X), and every newly black cell was on the bounded read footprint. This proves both the path and complete-support parts of the one-event enclosure.

5.3 Iteration and coordinate bit lengths

Minkowski sums of ℓ_∞ balls add their radii. Applying the one-event enclosure successively proves the iterated enclosure, and also covers the complete trajectory between

checkpoints. The ℓ_∞ diameter of $C(X_0) + [-5Qn, 5Qn]^2$ is $W + 10Qn$. Both the current head and each current black cell lie in that set, proving the stated radius bound.

The nth macro starts after n-1 events. Because the event offset is strictly less than (7), and the post-event duration is offset+1, its duration is at most

$$Q(W + 10Q(n-1) + 2Q + 10).$$

Summing from 1 through n proves the quadratic time bound. These are integer non-strict bounds for post-event time; the event itself occurred one update earlier.

For each fixed D, the event deadline is quadratic in the event count. Its constants retain the initial diameter and depend exponentially on D.

5.3.1 Complete XOR histories still have a growing number of terms

In the symbolic representation of Section 6, a skipped periodic phase adds a finite arithmetic segment of actual read positions, and ordinary updates add singletons. Starting from an explicit m-black input, every generated term endpoint up to n events is an actual read location covered by the iterated enclosure; original singleton terms also lie in that hull. This is true before syntactic cancellations, since every term records actual read positions along the finite trajectory. Each nontrivial segment has nonzero integer stride, so its length is at most W+10Qn+1 (distance between its two endpoints is length-1 times a norm at least one). If initial absolute coordinate bit length is b, endpoints and lengths thus have bit length

$$O(b + D + \log(n+1)). \tag{22}$$

per coordinate and length. The number of segment terms can grow as $m + n(9Q+1)$, as proved in the continuation construction below. Temporary inverse-history reconstruction adds at most D additional local moves; it changes neither the returned state nor this asymptotic bit bound.

6 Exact continuation with complete history

6.1 Finite arithmetic segments and symmetric difference

For integer a,v and $n \geq 1$ put

$$\mathrm{Seg}(a, v, n) = \{a + jv : 0 \leq j < n\}.$$

If $n > 1$ require $v \neq 0$. An encoded colouring consists of a finite list of segments and means their symmetric difference. A singleton is a segment of length one. Thus an explicit finite black set embeds exactly as singleton terms. Every encoded state still has finite support, including after a huge skipped prefix. Overlaps cancel modulo two; they are never silently interpreted as union.

Membership of a point is the parity of the segments containing it. For a nontrivial segment, containment is one integer-collinearity test followed by a finite-index interval test. A literal update and its inverse therefore remain exactly computable without expanding any segment. Identical singleton terms may be cancelled syntactically; no cell is removed because it is presumed irrelevant. The list is not canonical: distinct expressions may encode the same finite set.

6.2 Exact first mismatch against a periodic motion plan

Let a supplied word u have length P, restore heading, and have nonzero drift d. Its pre-update phase positions are q_i. The proposed future reads are

$$q_i + kd, \qquad 0 \le i < P, \quad k \ge 0.$$

As in the earlier finite-field verifier, an earlier periodic read at this same position exists for each pair (j,r) satisfying

$$q_j - q_i = rd, \quad r \ge 0, \quad (r > 0 \text{ or } j < i), \quad k \ge r.$$

Each pair toggles read parity at the one threshold r. These are finite in number.

Now intersect a phase ray with one old finite segment:

$$q_i + kd = a + jv, \qquad k \ge 0, \quad 0 \le j < n. \tag{23}$$

If d and v are not parallel, determinants give at most one integer pair (k,j), which is tested against the bounds. If they are parallel but a-q_i is not, there is no intersection. Otherwise reduce a nonzero coordinate of d to

$$\alpha k - \beta j = \gamma, \qquad \alpha > 0.$$

Writing $g = \gcd(\alpha, |\beta|)$, there is no solution unless g divides γ. When it does, solutions for k form one residue class modulo $|\beta|/g$. The finite bounds on j supply an interval $[\mathrm{lo}, \mathrm{hi}]$, intersected with $k \ge 0$. Thus (23) is either empty, a singleton, or a finite arithmetic progression of epochs. The singleton case also handles length-one terms independently of the unused stride.

For a phase i, its initial-black contribution is the XOR of membership in these finitely many epoch progressions. Partition $k \ge 0$ at all progression starts, ends+1, and earlier-read thresholds. Within each partition interval, the active progressions are fixed; their combined parity is periodic in k, with period dividing the least common multiple of their moduli. The earlier- read parity is constant on that interval. Test a whole residue period, or the shorter finite interval. The final unbounded interval has no active finite segment and needs one parity test.

This is an exhaustive finite algorithm, not sampling a few epochs. It decides whether u^ω is the exact future; otherwise it finds the first mismatch. Until the first mismatch

the proposed and literal paths agree by induction, so its position and time are real. The running time can depend on a large lcm. No polynomial-time claim is made for arbitrary segment-encoded input strides.

6.3 Exact algebra of the skipped writes

Suppose the first n proposed updates have been verified (including n=0). For each phase i put

$$n_i = \max\left(0, \left\lfloor \frac{n-1-i}{P} \right\rfloor + 1\right).$$

Its updated cells are exactly $\mathrm{Seg}(q_i, d, n_i)$, omitting phases with $n_i = 0$. Therefore the complete endpoint is

$$B_n = B_0 \triangle \bigtriangleup_{\substack{0 \le i < P \\ n_i > 0}} \mathrm{Seg}(q_i, d, n_i). \tag{24}$$

If n=kP+i, the endpoint position is $q_i + kd$ and its heading is the recorded heading before phase i. Equation (24) accounts for every flip, including self-overlap, overlap between phases, and overlap with every old segment. It adds at most P terms regardless of n. The helper applying (24) does not assert that an arbitrary geometric word is physically executable; its caller must first establish validity through the chosen prefix.

At the first mismatch of the recency-D predictor, the planned turn is R and the actual turn is L. Toggle that point in (24), turn left and move once. This is the exact full input for the next macro, with no separate history oracle: the needed preceding D positions are recovered by the literal inverse.

6.4 Total single-event macro and finite iteration

For $D \ge 1$ put $Q = 2^D$. The previous suffix identity says that no S_D event means one deterministic next turn from the latest D-turn word. There are Q words. Execute at most Q matching turns until an event or a repeated suffix occurs. In the latter case the prediction has a period $P \le Q$.

If its geometric period is nontranslating or rotates the heading, two copies of a closed-pose block of length at most $4P$ expose a mismatch: otherwise the complete state would recur and the ant would be permanently confined. Literal no-bounded-orbit excludes that. Replaying at most $8P$ steps handles this case.

For nonzero translation apply Subsection 6.2. A valid infinite word gives a certified permanent event-free tail. Otherwise (24) and one real black update give the next full post-event state. Every input is finite and every arithmetic search here is finite, so this single macro is total without caller resource caps.

If the input expression has M terms, an event output has at most

$$M + 9Q + 1 \quad \text{terms.} \tag{25}$$

The loose uniform value covers Q preliminary writes, at most $8Q$ closed-plan writes, or at most Q new periodic segment terms, and the final event. Inverse history recovery is temporary and does not alter the returned physical field. Nontrivial new segment strides are period drifts; both coordinate magnitudes are at most Q. The same statement applies to a terminating tail's entry state.

After n successive event outputs from an explicit m-black input, the expression has at most $m + n(9Q + 1)$ terms. The finite iteration computes the first n events, or stops earlier with a certified event-free tail. The returned field includes every initial cell and every subsequent flip.

6.5 Complexity of a finite event prefix

For an explicit sparse input with m black cells, coordinate bit length b, fixed D, and an event count n measured numerically (or in unary), the first n events and their complete compressed endpoint are computable in

$$f(D)\,\mathrm{poly}(m + n + b). \tag{26}$$

All initial terms are singletons, and every nontrivial generated stride has components of magnitude at most Q by (25). A parallel intersection modulus is $|\beta|/g \le Q$, where β is the chosen signed coordinate of the segment stride after the same sign normalization as α in Section 6.2. Hence all residue periods divide $\Lambda_Q = \mathrm{lcm}(1, \dots, Q)$, a function only of D. The numbers of old terms, phase pairs and interval endpoints are polynomial in m+n for fixed Q. One whole residue enumeration therefore costs a factor at most Λ_Q, not a factor equal to the huge skipped physical time.

The convex-hull bound in Section 5 gives $O(b+D+\log(n+1))$ bits for every generated endpoint and segment length. Membership, determinant, gcd and residue computations therefore have polynomial bit cost. Together with the polynomial number of terms and the fixed-D residue enumeration, this proves (26).

The generated-stride premise supplies the fixed residue bound used in (26); arbitrary symbolic strides are discussed in Section 12.

7 Spatially filtered events and remote feedback

The tube bounds turn a spatial event restriction into a finite stopping criterion. We use the following escape theorem from [4]: for any axis-aligned square with ℓ lattice sites on each side, any colouring and any starting pose inside it, the first exit occurs within

$$E_*(\ell) = \frac{13 \cdot 3^{\ell-1} - 2\ell^2 - 4\ell - 5}{2}$$

updates. Exterior colours remain unread until the exit. For uniformity with the supplied event certificates, all bounds below use the valid, looser choice $E(\ell) = 8\ell 3^{\ell} + 1 \geq E_*(\ell)$, for $\ell \geq 1$.

7.1 A finite-region burst bound, independent of the outside field

Let K be a nonempty fixed finite set of lattice cells, w its ℓ_∞ diameter, and choose an axis-aligned square enclosing $K + [-H_D, H_D]^2$. A sufficient side is

$$\ell(K, D) = w + 2H_D + 1, \qquad b(K, D) = E(\ell(K, D)). \tag{27}$$

Theorem (bounded internal bursts). A consecutive run in the event list whose event cells all belong to K has length at most b(K,D). The bound is independent of the rest of the complete black field and of the starting time.

Proof: start immediately before the first event of that run. The event-chain tube corollary keeps the whole actual path, through every completed internal event in the run, inside the square in (27). Its first exit is no later than $E(\ell)$. Thus the elapsed time through any such consecutive completed run is strictly less than $E(\ell)$, and the number of distinct event reads is at most that elapsed time. The slightly weaker integer bound $b(K, D)$ is sufficient. Exterior colours can be arbitrary because they stay unchanged before first exit. □

The word 'consecutive' refers to events, not ordinary updates. The ant may execute many non-event updates between them. Neither infinite local oscillation nor arbitrarily much exterior storage invalidates this uniform bound.

Corollary (unbounded event locations). For each fixed D, an orbit has infinitely many S_D events if and only if their positions form an unbounded set. If the events are infinite, infinitely many lie outside every fixed finite K.

An infinite tail confined to K would contradict the bounded-burst theorem after its last external event. A finite event list has a finite position set, giving the reverse direction. This is not a claim that e_i tends to infinity: returns to K can occur infinitely often, interleaved with external events.

7.2 A total spatially filtered event algorithm

Theorem (spatially filtered event query). Uniformly in a complete finite X, integer $D \geq 1$ and explicitly supplied finite K, the following predicate is decidable:

$$\exists t \geq 0 : \quad S_D(F^t X) \text{ and } \operatorname{pos}(F^t X) \notin K. \tag{28}$$

The algorithm returns the first such event, when one exists. A negative answer also certifies eventual nonzero translating periodicity, but need not certify standard P104.

Algorithm: call the already-total next-event procedure. If it certifies no future S_D, return a negative answer and its periodic certificate. If its event cell is outside K,

return that event and accumulated time. Otherwise execute the finite prefix through that event with the complete field retained and repeat.

Every individual query and finite replay terminates. Were the outer loop infinite, there would be infinitely many S_D events all in K, contradicting the unbounded-event-location corollary. This proves termination. More quantitatively, use K union $\{p_0\}$ in (27): every completed inside-only prefix has its whole path inside that square, so fewer than its $E(\ell)$ literal updates, hence at most $E(\ell)$ internal events, can precede the final query. The final external event itself may be arbitrarily distant in time. For K empty, the original next-event procedure suffices directly.

The implementation leaves $E(\ell)$ symbolic, instead of attempting to construct an integer such as $3^{6\cdot 2^{128}}$. It uses literal replay of inside-event intervals; no efficient full symbolic continuation is claimed for huge inside intervals. The symbolic escape bound is used to prove that the number of iterations is finite.

7.2.1 An explicit first-external-event deadline

Let $R_0 = \max_{q\in B_0} \|q - p_0\|_\infty$ (zero for empty B), and use $\ell_0 = \ell(K \cup \{p_0\}, D)$. If an external event exists, its first time is strictly less than

$$(Q+1)E(\ell_0) + Q(R_0 + 2Q + 10). \tag{29}$$

Indeed, the head first exits the guard square at some $\tau \le E(\ell_0)$. Either an external event has already occurred, or all preceding event cells are in K. In the latter case the next S_D after τ, if present, cannot be in K: otherwise (13) would enclose the whole prefix through it inside that square, contradicting the exit at τ. Apply the existing first-event waiting bound at X_τ, using $R(X_\tau) \le R_0 + \tau$. If there is no next event, there is no external event at all. This is also a direct two-stage decision proof, independent of the loop argument.

For fixed D and fixed K in the normalized p_0=0 frame, the filtered predicate is polynomial-time in the sparse binary-coordinate input encoding, using the existing fixed-D polynomial-time next-event procedure. There are only constantly many internal events, and the total literal inside-prefix replay is bounded by $E(\ell_0)$, a constant in this fixed-parameter assertion.

The spatially filtered query goes beyond the unfiltered first-event test of Section 3: the first many S_D events can occur inside K and must be ignored. The earlier fixed-n event theorem alone does not say when that filtering loop stops. The endpoint tube plus finite-domain escape now proves that it always does.

7.3 Quantitative exterior feedback on every infinite event chain

Let $N_D(t)$ count all S_D reads at offsets $0 \le s < t$, and let $M_{D,K}(t)$ count those outside fixed K. Put $b_K = b(K, D)$, as defined in the bounded-burst theorem. Internal events occur in at most $M_{D,K}(t) + 1$ runs, so that theorem gives

$$
\begin{aligned}
N_D(t) &\le b_K + (b_K+1)M_{D,K}(t),\\
M_{D,K}(t) &\ge \left\lfloor \frac{N_D(t)}{b_K+1} \right\rfloor .
\end{aligned}
\tag{30}
$$

For an infinite S_D chain, define the computable integer

$$
n_D(t,W) = \max\{n \ge 0 : T_D(n,W) \le t\}. \tag{31}
$$

with the deadline (1). It follows that

$$
M_{D,K}(t) \ge \left\lfloor \frac{n_D(t,W)}{b_K+1} \right\rfloor . \tag{32}
$$

For fixed X, D, K, this gives an $\Omega(\sqrt{t})$ lower bound on the number of exterior events along an infinite event chain. The constant depends on the fixed region through b_K+1. For empty K, use $M_{D,K} = N_D$ and $b_K = 0$.

7.3.1 A stronger exterior-only quadratic deadline

The factor b_K+1 in (32) can be avoided in the leading quadratic coefficient. Augment the state hull by the observation region:

$$
C_K(X) = \operatorname{conv}(B \cup \{p\} \cup K), \qquad W_K = \operatorname{diam}_\infty C_K(X_0).
$$

A finite macro ending just after the first external S_D event satisfies

$$
\begin{aligned}
C_K(X_{\text{new}}) &\subset C_K(X) + [-9Q, 9Q]^2,\\
\text{duration} &\le 2Q \operatorname{diam}_\infty C_K(X) + 20Q^2 + b_K.
\end{aligned}
\tag{33}
$$

To prove (33), if there are internal events, their entire prefix is in $\operatorname{conv}(\{p\} \cup K) + [-H_D, H_D]^2$ by (13). The full field at the last internal post-event state is therefore in $C_K(X) + [-H_D, H_D]^2$, without dropping the initial field. Apply the $5Q$ one-event convex-hull theorem of Section 5 to the final ordinary event macro. Since $H_D + 5Q = 8Q + 2 \le 9Q$, (33) follows. With no internal event, the original $5Q$ bound is already sufficient.

For the duration calculation, put $W := \operatorname{diam}_\infty C_K(X)$. Then (10) bounds the first internal event duration by

$$
QW + 5Q^2.
$$

From its pre-read state through the last internal post-event state there are fewer than b_K further updates, by the burst proof. At that boundary the complete head-relative

radius is at most $W + 2H_D = W + 6Q + 4$. The first-event estimate makes the last macro at most $Q(W + 8Q + 14)$ updates. Adding these conservative bounds gives

$$2QW + 13Q^2 + 14Q + b_K \le 2QW + 20Q^2 + b_K,$$

since $Q \ge 2$. With no internal event, the original $Q(W + 2Q + 10)$ estimate is smaller. Overcounting the first internal read only weakens the bound. For empty K, use $b_K = 0$.

After n external events, (33) gives augmented width at most $W_K + 18Qn$. Consequently the post-nth-external-event time, if present, satisfies

$$U_{D,K}(n, W_K) = n(2QW_K + 20Q^2 + b_K) + 18Q^2 n(n-1). \tag{34}$$

On an infinite chain,

$$M_{D,K}(t) \ge \max\{n \ge 0 : U_{D,K}(n, W_K) \le t\}. \tag{35}$$

For every fixed K, the leading asymptotic coefficient is $\sqrt{t}/(\sqrt{18}Q)$, independent of K. The spatial expansion is measured directly in exterior-event count.

7.4 Simultaneously remote, late-born, arbitrarily long black lifetimes

An orbit that is not eventually a nonzero translating periodic trace has infinitely many S_D events for each D, by the first-event waiting theorem.

Theorem (remote long feedback necessity). On every such orbit, for every $D \ge 1$, finite K, and time T, there are infinitely many cells/lifetimes described by times b,e with

$$\begin{gathered} T < b < e, \qquad e - b > D, \qquad x \notin K, \\ \text{update } b \text{ reads } x \text{ white and makes it black,} \\ \text{update } e \text{ is its next read, black.} \end{gathered} \tag{36}$$

These lifetimes can be chosen at infinitely many distinct, unbounded cells. This does not assert that the whole event sequence eventually avoids each cell.

Proof: restart at the complete state at time $T + 1$. The unbounded-event-location corollary supplies infinitely many later S_D events outside K. At most $|B_{T+1}|$ can consume black lifetimes already present at the restart. Every other such read consumes a lifetime born at a real forward white update $b \ge T + 1$, at the same exterior cell. The intrinsic S_D condition then forces $e - b > D$. There was no intermediate read because black lifetimes end at their next read. Removing the finitely many initial-lifetime events from an unbounded event-position set leaves an unbounded set, so the surviving lifetimes can be chosen at infinitely many distinct cells. Equations (32) and (35) also give count bounds after subtracting the finite stock. □

The same lifetimes satisfy all three requirements: late birth, large age and remote consumption. The endpoint-tube argument forces this feedback to recur outside every finite region.

8 Exact detection of newly generated remote feedback

Spatial filtering can be refined to distinguish newly generated memory from black lifetimes already present in the input. This refinement returns the first qualifying lifetime, its provenance, and a complete state from which the query can be repeated. It also makes the dependence of remote feedback on the observation scale quantitative.

8.1 The first birth-filtered query

Fix a complete source state $X = (B, p, h)$, $D \geq 1$, and a finite set K. A qualifying lifetime consists of consecutive reads of a cell $q \notin K$ at times b, e, with

$$0 \leq b < e, \qquad e - b > D,$$

where update b turns right and update e turns left. The question asks for the least consumption time e, its birth b, the cell q, and the complete state $F^{e+1}X$. An initially black coordinate can qualify after its initial lifetime has been consumed and the site has been written black again.

Put $M = |B|$, $Q = 2^D$, and $W = \operatorname{diam}_\infty(B \cup \{p\} \cup K)$. To keep one explicit bound throughout this section, use the conservative square escape estimate

$$\ell = \operatorname{diam}_\infty K + 2(3Q + 2) + 1, \qquad b_K = 8\ell 3^\ell + 1$$

for nonempty K, and $b_K = 0$ for empty K. The stronger escape bound used earlier can decrease this budget. The exterior-event estimate is

$$U(n, W) = n(2QW + 20Q^2 + b_K) + 18Q^2 n(n-1).$$

Theorem (first newly generated exterior lifetime). The birth-filtered query is total on every finite input. It uses at most $(M+1)(b_K+1)$ ordinary next-S_D calls. A positive answer satisfies $e + 1 \leq U(M+1, W)$. A negative answer certifies eventual nonzero translating periodicity.

Proof. Process the exact successive S_D events in chronological order. Ignore those in K. For an exterior black read, find the last read of the same cell at a nonnegative time strictly before the event. If one exists, it is a white read and hence the birth of the consumed lifetime; return it. If none exists, the event consumes one of the M source lifetimes. Each source lifetime can be skipped only once. In particular, consuming a source lifetime does not permanently exclude its coordinate.

There are at most M skipped exterior events. Each intervening run of internal events has length at most b_K, by the fixed-region burst bound. Either a qualifying exterior event or a permanently event-free suffix is therefore reached within the stated number of calls. The successful event is no later than exterior event $M + 1$, which proves

the deadline. In the negative case only finitely many S_D occur, so the finite-suffix theorem gives eventual translating periodicity. The ordered search returns the first qualifying consumption. □

The negative certificate concerns translating periodicity; its translating word is not presumed standard. Optional implementation limits return an inconclusive status. The unlimited algorithm terminates by the proof above, without expanding the possibly enormous integer 3^{ℓ}.

8.2 Complete endpoints and exact birth provenance

Alongside the XOR field, store each actual read sequence as a finite arithmetic segment with its time progression:

$$(a, v, L, t_0, \delta_t, \chi), \qquad \text{read } a + jv \text{ at } t_0 + j\delta_t, \quad 0 \le j < L.$$

Here $\chi \in \{\mathrm{L}, \mathrm{R}\}$ records the turn at each read in this phase stream: L reads black and R reads white. A repeated heading-restoring word contributes one such segment per phase; literal updates contribute singleton records. These records partition all executed updates, including those skipped by arithmetic acceleration. Intersecting a queried cell with every segment and selecting the largest recorded time below e recovers its exact last writer. The same records retain every field toggle, giving the complete reusable post-state.

The arithmetic applies to nonprimitive strides as well. Recall the phase-ray intersection $q_i + kd = a + jv$ in (23), with d the period drift, q_i the phase position, $k \ge 0$, and $0 \le j < L$. For nontrivial parallel segments write $d = gu$, $v = hu$, $a - q_i = \eta u$, with u primitive and $g > 0$. The intersection equation is $gk = \eta + hj$; its congruence and finite index bounds give a finite arithmetic progression of epochs k. Singleton records use the direct ray-membership test. Nonparallel segments use an exact determinant solve. Splitting epochs modulo the least common multiple of progression steps reduces the colour parity to finite interval sweeps, including the final infinite interval. Thus neither a remote initial marker nor a remote write is lost during acceleration.

For fixed D and fixed K in the translated source-pose frame, the query has polynomial bit complexity on explicitly listed sparse input. There are $O_{D,K}(M + 1)$ calls, each adding $O_D(1)$ segments. Generated strides and the required residue modulus are bounded in terms of D; the existing finite-macro bounds control coordinate and time bit lengths. For arbitrary compressed initial fields, totality still holds, while the call bound uses actual black cardinality rather than the number of XOR terms.

8.3 Adaptive checkpoints

On a trajectory that is never eventually translating periodic, the query is positive from every actual checkpoint s. One may choose D and a finite K using the known history, then obtain a lifetime born at or after s, consumed outside K, with age greater than D. Restarting after its consumption produces temporally nonoverlapping lifetimes. Including previously selected cells in the next K makes their sites distinct. The region is fixed during each call and may change between calls. Each round has its own complete-source mass and deadline.

8.4 A simultaneous growing-scale lower bound

Normalize $p_0 = 0$, and put $M_0 = |B_0|$ and $W_0 = \operatorname{diam}_\infty(B_0 \cup \{0\})$. For a large integer horizon H, define

$$L = \lfloor \log_3 H \rfloor \geq 64, \qquad D_H = \lfloor \log_2 L \rfloor - 5, \quad Q_H = 2^{D_H},$$
$$R_H = \lfloor L/16 \rfloor, \quad K_H = [-R_H, R_H]^2 \cap \mathbb{Z}^2, \quad s_H = \lfloor H^{1/4} \rfloor.$$

Use $\ell_H = 2R_H + 6Q_H + 5$ and the preceding definition of b_K. Let n_H be the largest nonnegative integer satisfying

$$U_{D_H, K_H}(n_H, W_0 + 2R_H) \leq H.$$

Theorem (growing-scale feedback). On every non-eventually-translating finite-support orbit, the number $F(H)$ of black lifetimes satisfying simultaneously

$$s_H \leq b < e < H, \qquad e - b > D_H, \qquad \|q\|_\infty > R_H$$

is at least $\max(0, n_H - M_0 - 2s_H)$. Moreover,

$$\liminf_{H \to \infty} \frac{F(H) \lfloor \log_3 H \rfloor}{\sqrt{H}} \geq \frac{32}{\sqrt{18}}.$$

Proof. For each horizon the orbit has infinitely many S_{D_H}, so the uniform exterior deadline supplies at least n_H exterior consumptions before H. At most s_H precede the cutoff s_H. At that cutoff there are at most $M_0 + s_H$ black lifetimes, so at most that many later consumptions can have earlier births. Subtracting these supplies proves the finite bound. The counted objects are distinct lifetimes, and may occur at the same coordinate at different times.

For the asymptotic estimate,

$$L/64 < Q_H \leq L/32, \quad \ell_H \leq 5L/16 + 5, \quad b_{K_H} = O(LH^{5/16}).$$

The linear coefficient of U is $O_X(L^2 + LH^{5/16})$, negligible at its positive quadratic root. Hence $n_H = (1 + o(1))\sqrt{H}/(\sqrt{18}Q_H)$. Finally, $M_0 + 2s_H = o(\sqrt{H}/L)$, giving the displayed lower limit. □

Thus one uniform estimate forces late births, a growing excluded radius, and a growing memory age on the same collection of lifetimes. The conclusion is a necessary condition on non-eventually-translating motion. It supplies $\Omega_X(\sqrt{H}/\log H)$ lifetimes, while radius, age and birth cutoff scale respectively as $\log H$, $\log\log H$ and $H^{1/4}$.

The dedicated controls compare complete endpoints and exact birth times against literal dynamics on 120 inputs, include source-coordinate rebirth, and exercise arithmetic at epoch 10^{60}. On the blank orbit, repeated queries with $D = 128$, $K = \emptyset$ return 31 positive rounds before a periodic negative answer at checkpoint 9990. This illustrates how exact renewal detection fits an orbit that eventually reaches the standard highway.

9 A twenty-black construction and the role of distance

The following construction realizes the spatial-scale obstruction with a fixed number of input cells and a fixed number of intervening events. Its lifetime has birth $b = 60$, consumption $e = 624n-1516$, and age $e-b = 624n-1576$. The exact first permanent standard time is $e + 774$. All twenty cells are specified at input time. We give the full affine construction and the guard argument for every even $n \geq 20$. The outgoing port from the four-cell theorem [5] supplies the five building blocks used to control this lifetime and its event count. The local tail certificates in Subsection 9.1.1 also recheck this imported reference on its complete field.

9.1 Exact seed and the inherited reference

The literal rule is white/right, black/left, toggle then move, on $\mathbb{Z}^2$. A state at time t precedes update t. Headings are $\mathrm{N}, \mathrm{E}, \mathrm{S}, \mathrm{W} = 0, 1, 2, 3$. All unspecified input cells are white.

Use the already certified outgoing four-cell port

$$G = \{(0, -1), (1, 1), (1, 3), (2, 2)\}.$$

at the origin facing E. Let $\rho(x, y) = (y, -x)$ be clockwise quarter rotation. At a pose (p, h), write $G[p, h] = p + \rho^{h-1}G$. For even $n \geq 20$ the complete input black set is

$$B_n = \bigcup_{i=0}^{4} G[p_i, h_i].$$

with the following five poses:

i	p_i	h_i
0	$(0, 0)$	E
1	$(n-1, n)$	N
2	$(-n, 3n-4)$	W
3	$(-5n+5, -n)$	S
4	$(-3n, -3n+8)$	E

Start the one physical ant at $(0, 0), \mathrm{E}$. Subsection 9.2 proves that these five four-cell sets are pairwise disjoint, so the input has exactly twenty black sites.

9.1.1 Reference trajectory and tail certificates

Define A as the first 182 turns of the literal orbit from $(G, (0, 0), \mathrm{E})$, and U as its next 104 turns. The prefix A reaches $(5, 1), \mathrm{E}$ with 36 black sites; Theorem 2 and Section 3 of [5] certify that the subsequent word is U^ω, with drift $(2, 2)$. Define q_i and θ_i as the absolute reference pose at time $182 + i$. The finite phase data used below are

$$q_{14} = (8, 2), \quad \theta_{14} = \mathrm{E}, \quad U_{14} = \mathrm{R};$$
$$q_{61} = (7, 8), \quad \theta_{61} = \mathrm{N};$$
$$q_{71} = (6, 9), \quad \theta_{71} = \mathrm{N}.$$

The reference reads $(0, 2)$ white at update 60, does not read it again in the 182-step prelude, and never reads it on the tail (all tail x-coordinates are at least four). It is therefore a newly born, permanent black lifetime on the unperturbed reference. The constructed circuit will read it again.

The four initial G sites are first read at offsets 1,22,32,58. The only later S_{128} reads of this reference are at offsets 157,280,281, with respective previous reads 9,144,145. The no-later-events claim is checked for all future: for each L phase of U, there is a same-cell preceding phase at distance at most 128 already available by tail epoch one. The finite prelude/first epoch is checked literally. The stationary maximum black reread gap on U^ω is 116.

The reference's complete 36-cell state passes both the all-epoch breakpoint parity verifier and the independent stable-class/clean-seed-and-ray verifier. The latter criterion uses Jillhewar's supplied-word realization criterion [3]. The four-cell port is the construction of [5].

9.2 Universal autonomous execution of the five stages

Put $n = 2k$, $k \geq 10$. The five claimed stage words, in their respective rotated poses, are

$$\begin{aligned} &AU^{k-4}U[0:61], \\ &AU^{2k-5}U[0:71], \\ &AU^{4k-6}U[0:61], \\ &AU^{2k-7}U[0:71], \\ &AU^{3k-4}U[0:14]. \end{aligned} \tag{37}$$

The endpoint identities from the phase data give the start times

$$\begin{gathered} t_0 = 0, \quad t_1 = 52n - 173, \quad t_2 = 156n - 440, \\ t_3 = 364n - 821, \quad t_4 = 468n - 1296, \quad e = 624n - 1516. \end{gathered} \tag{38}$$

Stages 0 through 3 end at the next table pose. Stage 4 ends at $(0, 2), \mathrm{E}$, before its next update. This final update is not included in (37).

Endpoint algebra alone would not prove these words executable: previous wakes and future initial ports could cause an earlier divergence. The next certificate is the missing physical guard.

9.2.1 Pairwise separation of all stage read sets

Let $V_i(k)$ be the full set of pre-update read positions in stage i of (37), not its black set and not just its net flips. The following ten strict separations cover every pair. A row states $\max \ell(V_A) < \beta \le \min \ell(V_B)$.

A	B	$\ell(x,y)$	$\beta(k)$
0	1	y	$2k$
2	0	x	0
3	0	y	-2
4	0	x	0
2	1	x	$-2k+1$
3	1	y	$2k$
4	1	y	$2k$
3	2	y	$-2k+1$
2	4	$x-y$	-11
3	4	x	$-6k$

Here is the all-parameter checking argument. Each read set is exactly a union of 182 affine points, 104 affine arithmetic segments, and the stated 14/61/71 partial-epoch points. For stage i, put $r_i \equiv h_i - 1 \pmod 4$ and $d_i = \rho^{r_i}(2,2)$. Here h_i is the heading of the stage pose in the five-port table. Define the full-period exponents in (37) by

$$(R_0(k), \dots, R_4(k)) = (k-4, 2k-5, 4k-6, 2k-7, 3k-4).$$

A repeated-phase segment has the form

$$p_i(k) + \rho^{r_i} q_j + a d_i, \qquad 0 \le a < R_i(k),$$

Its extrema under ℓ are at $a = 0$ or $a = R_i(k) - 1$, according to the sign of $\ell(d_i)$. They are affine integer functions of k. Partial-epoch positions use $a = R_i(k)$. Thus each table row reduces to finitely many inequalities $\alpha k + \gamma \ge 0$. Such an inequality holds for all integers $k \ge 10$ iff $\alpha \ge 0$ and $10\alpha + \gamma \ge 0$. These two conditions are checked exactly, for every point and segment; no sampling or floating-point optimization is involved.

The certificate mapped in Subsection 9.5 contains 6,832 such inequalities and has minimum integer slack zero. Every $R_i(k)$ is also checked to be positive throughout the domain. In particular the table establishes $V_i(k) \cap V_j(k) = \emptyset$. Every initial port cell belongs to the corresponding reference's first 59 reads, hence to its V_i. The twenty input cells are consequently distinct, and a port belonging to another stage is outside the whole current read set.

9.2.2 Why the disjoint read sets suffice

At the start of stage i, previous stages have changed only cells in their V_j. Every other initial port is also outside V_i. On V_i the complete true field therefore agrees

with a fresh rotated G, with white everywhere else on that read set. First-difference induction makes the entire stage word in (37) literal. Induction over the five stages proves (37)–(38) for the one complete input B_n. All previous black residue is still present outside the current stage reads.

Formula B_n places all gates at time zero. The read-set separation therefore proves that each distant gate leaves all earlier stages unchanged.

9.2.3 The actual long-memory return and the count 31

The target $x = (0, 2)$ is not initially black. Stage 0 writes it black at $b = 60$. It is not read again in that stage, and the read-set separations exclude it from stages 1–4 up to time e. At time e the ant reaches x, E and reads it black; its next turn is L, while the fresh stage-4 reference would require R. This is an exact first returned lifetime, not a geometric near-return.

In $(60, e)$, stage 0 contributes its three offsets 157,280,281. Each of stages 1–4 contributes all seven reference offsets 1,22,32,58,157,280,281. No other stage has read any of its cells. Its four initial black first reads occur at absolute times greater than 128, and so are genuine intrinsic S_{128} events. All other gaps are those of the reference. Therefore the count is exactly

$$3 + 4 \cdot 7 = 31. \tag{39}$$

The consumption at time e itself is not included. This convention matters.

9.3 Full-history P104 recovery certificate

For the future after the return, retain the complete endpoint $B_e(n)$. It has all five old wakes. We do not replace the physical input by a cleaned configuration.

Use the fixed unbounded region

$$\Omega = \{(x, y) : x \geq -16,\ -14 \leq x + y \leq 12\}. \tag{40}$$

We prove that the restriction of $B_e(n)$ to Ω is the same 90-cell set C for every $k \geq 10$. This is an equality of restrictions for every parameter in this constructed family.

9.3.1 All-parameter equality of the protected field

The complete endpoint is the XOR of all twenty initial sites and every actual read position in (37), counted with its visit parity. The stage-1 read set has $x + y > 12$. Stage 3 has $x + y < -14$. Stage 2 has $x - y < -44$, whereas Ω entails $x - y = 2x - (x + y) \geq -44$. Those three stages and their initial ports miss Ω.

Stage 0 has a fixed prefix and NE period streams. Every epoch $j \geq 6$ has $x + y > 12$; all $k \geq 10$ include the first six epochs. Its terminal partial epoch is outside Ω. Thus its restriction is constant.

For stage 4, let $r = 3k - 4$ and change epoch variable from j to $v = j - r$. Every tail point becomes

$$p_4(k) + q_i + j(2,2) = q_i + (-8,0) + v(2,2). \tag{41}$$

independent of k. Complete epochs have $-r \le v \le -1$; the partial epoch has $v = 0$ and $i < 14$. At $k = 10$, $r = 26$. Every additional epoch $v \le -27$ lies below $x + y = -14$. The stage-4 initial port and 182-step prefix also lie below that line for all $k \ge 10$.

Consequently C is the following finite XOR, restricted to Ω:

$$\begin{gathered} G; \quad \text{all 182 stage-zero prefix reads;} \\ q_i + j(2,2), \quad 0 \le i < 104,\ 0 \le j < 6; \\ q_i + (-8,0) + v(2,2), \quad 0 \le i < 104,\ -26 \le v < 0; \\ q_i + (-8,0), \quad 0 \le i < 14. \end{gathered} \tag{42}$$

The checker identified in Subsection 9.5 evaluates the finite XOR expression (42) directly. It obtains 90 cells. It additionally verifies all 1,247 affine and 208 constant inequalities used above. The genuine full endpoints for eight parameters are checked against an independent literal replay as a control, not as the universal argument.

9.3.2 Protected scattering and exact first standard time

From the reference state $(C, (0,2), \mathrm{E})$, execute 774 literal updates. All positions remain in Ω. The complete reference endpoint has 162 black cells and pose $(5,-3), \mathrm{E}$. Its next 104-word is the cyclic phase-103 shift of U, with drift $(2,-2)$. Both independent infinite checks certify its entire future. Every tail phase lies in Ω, and adding $(2,-2)$ preserves $x + y$ and increases x. Thus the whole infinite reference future stays in Ω.

The true state at time e agrees with this reference on all of Ω. By first-difference coupling its whole future read trace is the same, for every n, irrespective of the physically retained exterior wakes. This proves standardness from $e + 774$.

The reference turn at offset 773 is R; the preceding letter in the backwards 104-periodic extension of the certified tail is L. Therefore a standard future cannot start at or before $e+773$: any such 104-periodic word would agree with the known tail over a whole period and hence at the preceding offset as well. The mismatch contradicts that. Together with the positive certificate, this proves the exact first time claimed above, including the exclusion of starts before e. It does not rely on a finite observed repetition as an infinite certificate.

Every member of the constructed family therefore reaches the standard highway at the exact time $624n - 742$.

9.4 Why a lifetime bound needs spatial information

Let $N_D(b, e)$ count S_D reads strictly between a black lifetime's birth and its consumption. On all complete finite-support classical inputs there is no finite-valued function $F(D, m, M)$, computable or otherwise, satisfying

$$e - b \le F(D, N_D(b, e), |B_0|). \tag{43}$$

for every post-input-created consumed black lifetime. In this family the three arguments are fixed at $(128, 31, 20)$, while $e - b = 624n - 1576$ is unbounded. The same examples refute a bound in terms of an upper budget $m = 31$ and $M = 20$. Their excursion radius is unbounded as well.

The no-intervening-event bound (15) shows that zero events do give a diameter-independent lifetime bound. The twenty-cell family shows why this cannot be extended to an arbitrary fixed positive event count.

The quadratic event deadline retains the input diameter and therefore allows these delays: in this family $|B_0| = 20$ while $\mathrm{diam}(B_0) = \Theta(n)$. The construction varies the input with n and every member eventually reaches the standard highway.

9.4.1 A corresponding count of ten-turn violations

Let $\mathcal{L}_{10}$ contain the cyclic ten-turn factors of the standard word U, and let J_{10} test whether the true ten-turn window ending now is outside this set. There are 84 allowed factors. On every X_n the number of J_{10} events strictly in $(60, e)$ is exactly 264.

To check this uniformly, replace each U^r in (37) by one U. All r are positive. Every removed complete standard cycle contains only allowed factors; both length-nine boundary contexts are unchanged and one retained cycle is longer than their combined lengths. Therefore no forbidden-factor occurrence is lost or created at a splice. Direct counting on the fixed compressed word gives 264. The same calculation through the protected recovery and nine following standard turns gives 532 J10 events from absolute update 9 onwards, with the last at $e+782$. Later factors are standard. Eight uncompressed physical runs corroborate the interior count.

Thus initial black mass and the number of intervening ten-turn violations also leave these lifetime durations unbounded.

9.5 Exact finite premises and immutable supplement

The finite premises in this section are regenerated by the twenty-cell checker memo ry_feedback/verification/scalable_feedback_circuit/check.py. Its source, helper circ uit.py, and retained report.json are fixed in the public `langtons-ant-core` scientific supplement at commit e932522, scalable-feedback package on GitHub. Paths below are relative to that directory. The checker uses Python 3.10+ with assertions enabled and only the standard library. Copy that directory to a disposable location and run python3check.py; compare the resulting JSON with the immutable retained report. The dependency map is as follows.

1. circuit.reference() defines A, U, q_i, θ_i by literal replay from G. check.reference_controls() checks the 36-cell endpoint, offsets $14, 61, 71$, birth at update 60, seven event offsets, and the all-future predecessor bound with maximum stationary gap 116. Its two infinite-tail checks appear in the report under reference.period_parity and reference.ordered_classes; the gap and offsets are recorded in the same reference object. The previous reads $9, 144, 145$ are obtained by replaying the first 390 updates, as in that function's literal control.

2. check.affine_endpoint_controls() checks the 20 affine pose/time equalities in (38), recorded under endpoints. circuit.separation_certificate() checks all ten rows of the separation table, all 6,832 affine inequalities, their minimum slack zero and positivity of every repeat count; its output is separation. These are universal affine checks on $k \geq 10$, not a sampled-parameter inference.

3. circuit.protected_core() evaluates exactly the XOR in (42). circuit.protected_region_certificate() checks the 1,247 affine and 208 constant inequalities that justify this restriction for all $k \geq 10$. The protected_region object records these counts and the 90-cell result; recovery.core_sha256 identifies the sorted coordinate list evaluated by the checker.

4. check.recovery_controls() checks all 774 protected updates, the 162-cell endpoint $((5, -3), \mathrm{E})$, the phase-103 shift, drift $(2, -2)$, containment of every prefix/tail phase in Ω, and the incompatible turn at offset 773. The recovery object records these results. Its all-future checks are circuit.verify_period() (parity breakpoints) and check.ordered_class_check() (full-drift chronology and clean-seed/ray equality). Region invariance then protects the whole tail, as proved above.

5. check.finite_family_controls() independently replays the eight listed parameters, checks full endpoint fields and the exact 31-event count, and records them under finite_family. The universal count follows from the reference offsets and stage separation, rather than from those eight controls. check.factor_controls() records the exact ten-factor counts $84, 264, 532$ and final offset 782 under factor_counts.

The report also records SHA256 digests of both verifier sources. The trusted finite basis is this explicit integer replay and the two implemented infinite-tail criteria, together with the analytic coverage and coupling arguments above; it has not been formalized in a proof assistant.

10 Crossing information and spatial growth

Remote feedback is a temporal requirement on persistent nontranslation. Crossing records give an additional spatial requirement. They describe the information carried by the head through a cut, a method introduced for Turing machines by Hennie [7]. The following argument proves the needed half-plane coupling directly. Its local incoming-axis invariant is standard ant geometry [2]. The log-log work-space threshold reviewed in [8] concerns input length; here the independent variable is the elapsed time of one complete ant orbit.

Write ETC for eventual translation of position, heading and turn with a nonzero drift and a fixed period. The complete black field may retain a growing wake. This is the same translating alternative used in the feedback theorems.

For real $\alpha, \beta \neq 0$, normalize $\min(|\alpha|, |\beta|) = 1$ and define

$$w_{\alpha,\beta}(T) = \max_{0 \le t \le T} (\alpha p_t.x + \beta p_t.y) - \min_{0 \le t \le T} (\alpha p_t.x + \beta p_t.y).$$

Here $p_t.x$ and $p_t.y$ denote the horizontal and vertical coordinates of p_t. This is normal-coordinate width, not Euclidean width when the normal has a large norm. Both components must be nonzero.

Theorem 10.1 (Width gap)**.** *Every classical finite-support orbit that is not* ETC *satisfies, for every such normal,*

$$\liminf_{T \to \infty} \frac{w_{\alpha,\beta}(T)}{\log \log T} \ge \frac{1}{\log 2}.$$

The finite bound from which this follows is uniform in the normalized normal. Consequently the conclusion also holds for time-dependent normal choices, and for the infimum of these widths over all admissible normals at each time.

10.1 A finite certificate with its own future protection

For an integer a write $R_a = \{(x, y) : x > a\}$. Suppose two times $s < t$ and cuts $a < b$ satisfy

$$p_t = p_s + d, \quad h_t = h_s, \quad d = (b - a, \delta), \tag{44}$$

$$(B_s \cap R_a) + d = B_t \cap R_b, \tag{45}$$

$$p_u \in R_a \quad (s \le u \le t). \tag{46}$$

The comparison in (45) is the complete inside field.

Lemma 10.2 (Nested-domain pumping)**.** *Conditions* (44)–(46) *imply that the trace from s is permanently translating with period $t - s$ and drift d.*

Proof. Until its first exit, the trajectory in a half-plane depends only on its inside field and starting pose. Thus the two inside states have the same first-exit duration $\tau \in \mathbb{N} \cup \{\infty\}$. Put $P = t - s$. If $\tau \le P$, the finite guard fails. If $P < \tau < \infty$, the orbit must exit the smaller R_b between t and its exit from R_a at $s + \tau$. But the second inside state predicts its first exit at $t + \tau > s + \tau$. Therefore $\tau = \infty$. Determinism now identifies the entire two futures up to translation. Since $b > a$, the drift is nonzero. No exterior cell has been removed from the physical state. □

Set

$$a_0 = \max(\{p_0.x\} \cup \{q.x : q \in B_0\}).$$

For a finite actual prefix through T, the crossing record of the cut $x = c + \frac{1}{2}$ lists every crossing in chronological order, with its direction and height. Normalize heights by subtracting their minimum. If $c \ge a_0$ and $p_T.x > c$, the directions are necessarily $E, W, \dots, E$: the head starts to the left of the cut and ends to its right, so eastward and westward crossings alternate, beginning and ending eastward.

Lemma 10.3 (Complete crossing records)**.** *Two equal nonempty normalized records at cuts $a_0 \le a < b < p_T.x$ produce a certificate satisfying Lemma 10.2 at times no later than T.*

Proof. Both right half-planes are initially white. Their first complete right-side excursions have translated entry poses and therefore translated read/write histories until the first exit. Between excursions, left-side updates do not change the right-side field. Induction over the equal records gives translated complete inside fields at their last eastward entries, at times s and t. The translation in height is the difference of record minima. The last entry at b must follow the last entry at a, since otherwise ending beyond b would require a later b-entry. There is no exit from R_a between s and t, because s is its last entry before T. All three conditions follow. □

The records are finite histories, not a query to the infinite future. A far initial black cell to the right invalidates the hypothesis even when it has not yet altered the observed finite path.

10.2 Exact record capacity and crossing work

Number headings N, E, S, W by $0, 1, 2, 3$. The value $h - x - y \pmod 2$ is invariant. An east crossing of cut $c+\frac{1}{2}$ arrives in column $c+1$; a west crossing arrives in column c. Both arrivals have horizontal heading, so their height parities differ. Consecutive heights in a crossing record therefore alternate parity, also after normalization.

For $H \ge 0$ put

$$E = \lfloor H/2 \rfloor + 1, \qquad O = \lceil H/2 \rceil, \qquad U = EO, \qquad V = (E-1)O.$$

Proposition 10.4 (Parity capacity)**.** *The number of normalized height words of length $2j+1$, with span at most H and alternating parity, is*

$$c_H(j) = (H+1)U^j - HV^j, \qquad j \ge 0,$$

where $0^0 = 1$.

Proof. Over $\{0, \dots, H\}$ the count before requiring minimum zero is $E^{j+1}O^j + O^{j+1}E^j = (H+1)U^j$. Words omitting zero use $E-1$ even symbols and O odd symbols, giving HV^j. Subtract them. □

Not every word counted by this proposition is necessarily physically realizable. It is an exact count of a necessary combinatorial class.

Incoming requests reconstruct the record. For an eligible cut the genuine record has the form

$$E(y_0), W(z_0), E(y_1), W(z_1), \dots, E(y_j).$$

The exit heights z_i are determined responses to the incoming heights y_i. This causal constraint gives a smaller capacity than the parity count.

Lemma 10.5 (Request injectivity)**.** *The incoming heights $(y_0, \dots, y_j)$ determine every completed right-side excursion: its exit height, duration and complete inside field after return. They also determine the complete inside field immediately before the final entry. Vertically translated request lists give translated full records.*

Proof. The first entry sees an entirely white half-plane. Literal dynamics uniquely determine its first exit and all writes up to that exit, when it exists. During an outside excursion no inside cell changes. The next entry therefore sees exactly the retained field produced by the preceding calls. Induction proves the assertion for all completed excursions. Translation invariance also identifies histories at horizontally shifted cuts. The final request records its entry; it need not return. □

All entry heights have the same parity. Put $m = \min_i y_i$ and encode the record by the integer word

$$\rho_c = ((y_0 - m)/2, \dots, (y_j - m)/2).$$

Two genuine records agree up to translation if and only if these request codes agree: restriction to the entries gives one direction, and Lemma 10.5 gives the other. Thus equal request codes at two eligible cuts yield the certificate of Lemma 10.3.

Proposition 10.6 (Request capacity)**.** *For $H \geq 1$, put $q = \lfloor H/2 \rfloor + 1$. The number of genuine normalized records of length $2j+1$ and span at most H is at most*

$$b_H(j) = q^{j+1} - (q-1)^{j+1}. \tag{47}$$

For $H = 0$, only the one-letter signature exists.

Proof. A request code has $j+1$ letters in $\{0, \dots, q-1\}$ and contains zero. Subtracting the words omitting zero gives (47). Request injectivity makes this an upper bound for genuine signatures. At height zero a completed return would violate the opposite parities of entry and exit heights. □

For example, at $H = 10$ and $j = 5$ the parity capacity is $169{,}643{,}750$, whereas the request capacity is $31{,}031$. These count combinatorial classes; a request code contributes an available object even when it has no returning, span-admissible physical response.

Write $A^*_H(r) = \sum_{j=0}^{r} b_H(j)$, with $A^*_H(-1) = 0$ and $b_0(j) = \mathbf{1}_{j=0}$. Let $\mathcal{P}^*_H(N)$ be the minimum total length of N distinct objects, with $b_H(j)$ objects of length $2j+1$. If r is the first index with $A^*_H(r) \geq N$, shortest-layer filling gives

$$\mathcal{P}^*_H(N) = \sum_{j<r} (2j+1) b_H(j) + (2r+1)(N - A^*_H(r-1)). \tag{48}$$

Set $\mathcal{P}^*_H(0) = 0$ and $\mathcal{P}^*_0(N) = \infty$ for $N > 1$. At height one, $b_1(j) = 1$, so $\mathcal{P}^*_1(N) = N^2$. For $q \geq 2$, the cumulative capacity is the integer geometric sum

$$A^*_H(r) = \frac{q(q^{r+1} - 1)}{q - 1} - (q-1) \sum_{j=0}^{r} (q-1)^j.$$

Theorem 10.7 (Request-work dichotomy)**.** *Let $N = (p_T.x - a_0)_+$. For $N > 0$ let H be the maximum span of the crossing records at the N cuts $a_0, \dots, p_T.x - 1$. Either a permanent translation certificate occurs in this finite prefix or*

$$\mathcal{P}^*_H(N) \le \lceil T/2 \rceil.$$

Proof. Without a certificate, the N request codes are distinct. Request capacity therefore bounds their summed full-record lengths below by (48). Each listed crossing is a different horizontal update, and horizontal and vertical updates alternate. □

Corollary 10.8 (Entropy form)**.** *In the second alternative, when $H \ge 2$ and $N > 0$, let $\overline{J} = \lfloor (\lceil T/2 \rceil - N)/2 \rfloor$. Then*

$$\log(N!) \le \overline{J} \log q + N \log\bigl(2(1 + \overline{J}/N)\bigr). \tag{49}$$

Proof. The difference-of-powers identity gives $b_H(j) \le (j+1)q^j$, and hence $A^*_H(r) \le 2(r+1)q^r$ for $q \ge 2$. Order the pair counts of the N actual records as $j_1 \le \cdots \le j_N$ and put $J = \sum_i j_i$. Since $i \le A^*_H(j_i)$, summing logarithms and applying concavity gives

$$\log(N!) \le J \log q + N \log\bigl(2(1 + J/N)\bigr).$$

Their total length is $2J + N \le \lceil T/2 \rceil$, so $J \le \overline{J}$. The right-hand side increases with J. □

Corollary 10.9 (Speed–spread tradeoff)**.** *For an orbit which is not* ETC*, suppose $T_i \to \infty$ and $N(T_i)/T_i \to v > 0$. Then $v < 1/2$ and its record spans satisfy*

$$\liminf_i \frac{\log(H(T_i) + 2)}{\log T_i} \ge \frac{4v}{1 - 2v}.$$

Proof. The cases $H \le 1$ give at least quadratic work or exclude $N > 1$, and are therefore eventually absent. Also $H \le \lceil T/2 \rceil$, since height variation cannot exceed the number of vertical moves. The work inequality already gives $v \le 1/2$. If $v = 1/2$, then $\overline{J} = o(T)$, and the right-hand side of (49) is $o(T \log T)$, contradicting $\log(N!) \sim vT \log T$. For $v < 1/2$, divide by $T \log T$ and use $\overline{J}/T \to (1 - 2v)/4$ and $\log N / \log T \to 1$. □

Half-turns and quarter-turns give the other directions. For example, speed $v = 1/52$ requires exponent at least $2/25$ on a nontranslating orbit. Subpolynomial crossing-height spread is consequently incompatible with positive horizontal upper speed. Together with $H = O(T)$ the bound also gives $v \le 1/6$. No bound on repeated visits is assumed.

10.3 A numerical finite-profile deadline

For $H \geq 0$, $C \geq 1$, and a complete source, define

$$\begin{aligned} R &= \max(\{0\} \cup \{|q.x - p_0.x| : q \in B_0\}), \\ L &= H + 1, \qquad M(H, C) = A^*_H(LC - 1), \\ D(R, H, C) &= \big[2(R + M(H, C)) + 1\big]LC. \end{aligned}$$

Theorem 10.10 (Profile deadline)**.** *Suppose a finite prefix through T has vertical span at most H in every visited column and at most C updates of every site. Either it contains a permanent translation certificate or $T \leq D(R, H, C)$.*

Proof. In an eligible record, east crossings update their departure sites in its left column. There are at most LC such updates. Since the record starts and ends east, its odd length is at most $2LC - 1$. Every such record therefore lies in a class of size $M(H, C)$. Reaching a point with $x > p_0.x + R + M(H, C)$ would give more than $M(H, C)$ cuts beyond the complete initial support at that subprefix endpoint, forcing a duplicate record. A half-turn gives the analogous left bound. If no certificate occurs, every head position has $|x - p_0.x| \leq R + M(H, C)$. There are at most $2(R + M) + 1$ visited columns, each with at most L updated sites and at most C updates per site. □

The final unupdated head is not charged as an update. At a final east crossing, its departure is still in the counted left column; all west crossings of an eligible record are earlier. Black cells outside the corridor remain present. Their coordinates matter through the initial frontier, not through an assumed future-active quotient. The bound is linear in numerical R at fixed H, C, but is not a polynomial bit-complexity claim.

10.4 Local visit bounds and slowly widening trajectories

Let $n(v)$ count updates in a finite segment, excluding the terminal position. For either adjacent pair $u = v + (\pm 1, 0)$ and $z = v + (0, \pm 1)$,

$$n(v) \leq 2n(u) + 2n(z) + 5. \tag{50}$$

For completeness, the incoming axis at v is fixed. A visit is exceptional if it is the initial update, arrives from the selected incoming neighbour, or leaves to the selected outgoing neighbour. On every other visit both directions are fixed, hence the turn and read color are fixed. Alternation of colors forces at least $\lfloor n(v)/2 \rfloor$ exceptions. There are at most $n(u) + n(z) + 2$, including the initial and terminal allowances, proving (50).

If all head positions of a prefix lie in $a \leq \alpha x + \beta y \leq b$ with $\min(|\alpha|, |\beta|) = 1$, choose the adjacent pair increasing the linear form. Both children increase it by at least one. The analogous pair decreases it. Iterating toward the nearer boundary, with $F(-1) = 0$ and $F(d) = 4F(d - 1) + 5$, gives

$$n(v) \leq C_h := \frac{5(4^{\lfloor h/2 \rfloor + 1} - 1)}{3}, \qquad h = \lfloor b - a \rfloor.$$

Each column contains at most $\lfloor (b-a)/|\beta| \rfloor + 1 \le h+1$ lattice sites. Therefore Theorem 10.10 proves the explicit alternative

$$\text{a certificate occurs, or} \qquad T \le D_{\mathrm{obl}}(R,h) := D(R,h,C_h). \tag{51}$$

No infinite confinement is assumed in (51).

Proof of Theorem 10.1. For $h \ge 2$, $C_h \le (20/3)2^h$ and $q \le h+1$. Bounding A_h^* by $2(r+1)q^r$ at $r = (h+1)C_h - 1$ yields

$$\log D_{\mathrm{obl}}(R,h) = O_R\big((h+1)2^h \log(h+2)\big).$$

On an orbit which is not ETC, no finite certificate can occur. Thus for every T, with $h = \lfloor w_{\alpha,\beta}(T) \rfloor$,

$$\log\log T \le h\log 2 + \log(h+1) + \log\log(h+2) + O_R(1).$$

This first forces $h \to \infty$ and then gives the claimed liminf. All constants are independent of the normalized normal. For an infimum choose a normal with width less than one above the infimum; the bounded difference does not change the asymptotic conclusion. □

For example, an eventual tube

$$|y - \theta x| \le g(|x|), \qquad \theta \ne 0, \qquad g(r) = o\big(\log\log(r+e^e)\big)$$

forces ETC: unit speed makes its prefix normal span $o(\log\log T)$; a finite initial part contributes only a constant. For irrational θ this is impossible, because a nonzero integer translating drift has a nonzero linear deviation from that slope. The width g is allowed to tend to infinity.

There is a corresponding nonstraight extension. Let $f : \mathbb{Z} \to \mathbb{Z}$ be nondecreasing with $f(x+L) \ge f(x)+1$ for some fixed $L \ge 1$. A north/west path of length $L(H+1)$ leaves the corridor $f(x) \le y \le f(x)+H$ above its top. Expanding (50) along this binary tree gives

$$C_{L,H} = \frac{5(4^{L(H+1)} - 1)}{3}.$$

The profile deadline then implies, for any nontranslating orbit whose prefix fits that corridor with a possibly increasing $H(T)$,

$$\liminf_{T\to\infty} \frac{H(T)}{\log\log T} \ge \frac{1}{L\log 4}.$$

The bound $H(T)$ covers the entire prefix, not a window from which old deviations have been deleted.

10.5 Nonconstant cyclic turning rules

The geometric information argument also applies to generalized cyclic ants. Let a rule $\omega \in \{R, L\}^m$ contain both letters, let a read increment its cell state modulo m, and let only finitely many initial states differ from zero. Put

$$a = \min(\#R(\omega), \#L(\omega)), \qquad \kappa = m/a.$$

For a cyclic prefix at phase s, let $n_c(s, r)$ count turn c. Define

$$b_\omega = \max_{s,c,\,0\le r<m} \{r - \kappa n_c(s, r)\}.$$

Every full m-block has at least a copies of either turn, so $n \le \kappa n_c(s, n) + b_\omega$ for every prefix length. In the corner argument, all nonexceptional visits require one fixed turn. Visits with the opposite turn are exceptional, giving

$$n(v) \le \kappa(n(u) + n(z)) + 2\kappa + b_\omega.$$

The rest of the proof is unchanged, replacing C_h by

$$C_\omega(h) = \left\lceil (2\kappa + b_\omega) \frac{(2\kappa)^{\lfloor h/2 \rfloor + 1} - 1}{2\kappa - 1} \right\rceil.$$

Theorem 10.11 (Frequency-dependent width gap)**.** *Every non-eventually-translating finite-support orbit for the fixed rule ω satisfies*

$$\liminf_{T\to\infty} \frac{w_{\alpha,\beta}(T)}{\log\log T} \ge \frac{2}{\log(2\kappa)}.$$

Proof. Heading-axis parity and crossing parity still alternate. Complete half-plane coupling and request reconstruction remain deterministic with m colors. The local visit bound grows as $O_\omega((2\kappa)^{h/2})$. Substitution into the same finite profile deadline and taking two logarithms proves the claim. □

For classical RL, $\kappa = 2$, $b_\omega = 1$, recovering the exact earlier local-time constant. Every balanced cyclic rule has the same asymptotic coefficient $1/\log 2$, though its finite constants may differ.

10.6 Effectivity and reproducibility

For a supplied rational non-axis normal and integer width bound, an implemented algorithm follows complete states, checks the running width, and compares all crossing records at new left/right horizontal records beyond the full initial support. It returns a first observed width violation or a permanent translating certificate. Without a user cap, (51) proves termination. It need not construct the large deadline integer during execution. A capped run returns `UNKNOWN`, never a negative dynamical conclusion.

The certificate checker independently replays the finite source, compares the full half-plane fields, and checks the finite no-exit guard. A separate phase-ray parity check

tests all initial black hits, all self-write breakpoints, and the final infinite interval. An unseen forward defect is therefore not ignored. A translating answer does not assert permanent satisfaction of the supplied width bound; a non-tangent translator may later leave it.

The Python simulator and an independently written C++ vector simulator agree on every path position and complete endpoint field of 100 supplied inputs, totalling 113,152 updates per implementation. Further checks exhaust the stated small parity-word classes, verify integer packing and entropy inequalities, check finite corner bounds, and reject malformed or unguarded certificates. Four actual standard-tail inputs in different rotations return 104-step certificates. These are implementation checks, not proofs that all tails are standard. The finite cyclic-rule balance calculation is checked for every nonconstant rule word of lengths two through eight. The general-rule classifier is not implemented; its extension is analytic.

The request-capacity module separately checks 78 complete inputs and 86,647 updates per literal implementation. A persistent half-plane replay compares 186 complete residual fields; the controls also compare request-code and full-signature equality, exact integer packing, and damaged histories. It uses the same hash-pinned baseline simulator and C++ oracle as the preceding module, together with a separate right-excursion implementation.

The reproduction entry point is

```
python3 memory_feedback/reproduce.py --crossing-only
```

using Python's standard library and a C++17 compiler. The default replay works in a temporary directory and compares an immutable report. The universal claims are the displayed analytic arguments, not extrapolations of the tests.

11 Reproduction

Run `python3 memory_feedback/reproduce.py` to replay the eight scoped modules: first-event prediction, exact XOR continuation, event geometry, remote filtering, birth-filtered feedback, the twenty-cell circuit, crossing information, and request reconstruction. The checks compare full finite fields, reconstruct integer and rational inequalities, and verify permanent periodic tails at all parity breakpoints. Parameter families are covered by the affine and geometric proofs above; finite controls test their numerical premises.

12 Limitations

Request capacity counts possible incoming codes; it is an upper bound on genuine crossing histories, not a physical realization count or a stock fixed by the initial state. Request injectivity proves uniqueness of completed excursions; it does not decide whether an arbitrary proposed excursion returns. The work bound concerns distinct records, without assuming statistically independent input information. The width estimate uses whole-prefix normal-coordinate width with both normal components nonzero. The exact combinatorial capacity does not establish physical sharpness of

the asymptotic width coefficient. A translating certificate allows general periods and drifts. The extension to nonconstant cyclic turning rules is analytic; a generalized-rule classifier is not implemented.

The polynomial bounds fix D, and the spatially filtered query also fixes K in the normalized input frame. The factor $f(D)$ may be doubly exponential, and the finite-region escape constant can be enormous. The event count n is measured numerically, not by $\log n$; the bounds do not give a polynomial ordinary-step simulation. Arbitrary compressed input strides retain totality but need not obey the bounded residue periods of histories generated from explicit sparse inputs. For fixed K, the exterior deadline has a leading coefficient independent of K; its linear coefficient and asymptotic onset depend on b_K. This gives no uniform estimate for regions growing with time.

The total queries decide a next event or a finite event prefix. They do not decide whether an infinite event chain occurs, nor whether every finite seed eventually reaches a standard highway. The directional tube bounds control ranges rather than limiting speeds or angular convergence. Remote feedback is necessary on the stated non-eventually-translating orbits; the construction supplies a family of increasingly long lifetimes with different finite inputs. Each member reaches the standard highway, so autonomous infinite renewal from one fixed seed remains open.

13 Perspective

The predictor supplies a total query, while the XOR representation supplies its reusable physical output. The tube and escape arguments make fixed-region filtering total and force nonperiodic behaviour to renew memory remotely. The construction shows that mass and event count alone cannot replace spatial information. The crossing argument supplies a complementary requirement: persistent nontranslation forces every normalized oblique width to grow at least double-logarithmically with elapsed time. Complete-field coupling connects both parts: it makes event continuation exact and turns repeated guarded crossing records into permanent translation.

14 References

1. Anahí Gajardo. *A symbolic projection of Langton's Ant (Extended Abstract)*. DMTCS Proceedings AB, 57–68 (2003). doi:10.46298/dmtcs.2312.
2. Anahí Gajardo, Victor H. Lutfalla and Michaël Rao. *Ants on the highway*. Natural Computing 24, 497–509 (2025). doi:10.1007/s11047-025-10018-9. Author version: arXiv:2409.10124v1.
3. Atharva Jillhewar. *Finite-Support Periodic Highways of Langton's Ant: Necessary Conditions, Transverse Exclusions, and Exact Search* (2026). doi:10.21203/rs.3.rs-10516269/v1. Theorem 3.1 and Remark 3.2 supply full-drift visit chronology and seed reconstruction.
4. Hao Ke. *An Ant on the Clock: Exponential Escape Bounds for Langton's Ant*, version 0.4.0 (2026). doi:10.5281/zenodo.23402379.
5. Hao Ke. *Four Black Cells Force an Outgoing Highway: A Sharp Half-Plane Threshold for Langton's Ant*, version 0.1.0 (2026). doi:10.5281/zenodo.23402414.
6. Anahí Gajardo, Andrés Moreira and Eric Goles. *Complexity of Langton's ant*. Discrete Applied Mathematics 117, 41–50 (2002). doi:10.1016/S0166-218X(00)00334-6.
7. F. C. Hennie. One-Tape, Off-Line Turing Machine Computations. *Information and Control* 8 (1965), 553–578. doi:10.1016/S0019-9958(65)90399-2.
8. D. Ranjan, R. Chang and J. Hartmanis. *Space Bounded Computations: Review and New Separation Results*. Cornell University report, 20 December 1989, Section 2. https://userpages.cs.umbc.edu/chang/papers/loglog/loglog.pdf.