Protected Highway Formation and Scattering in Langton's Ant

Hao Ke
Independent researcher
i@kehao.me

Abstract

Which parts of an initial colouring can determine a Langton ant's permanent motion while shielding other cells from every future read? We give three constructions based on equality of complete colourings in protected regions. First, four black cells launch the standard period-104 highway into a half-plane; three cells force exit within the sharp bound of 918 updates. This port also completes any finite observation to a highway by four exterior additions. Second, a four-layer rectangular black frame shields every interior colouring: all fillings produce the same entire trace, with exact entrance times determined by the dimensions and their parity. Solid rectangles from the southwest corner facing north satisfy the sharp bound $242(n+m)+29325$ on first highway entrance. Third, certified highway scattering rules compose along arbitrary finite compatible sequences, including excursions that read back old wake. All obstacles are present initially and all written history is retained. First-difference coupling isolates the protected regions; exact read-colour identities, affine separation inequalities and infinite-tail certificates establish the required interfaces.

1 A sharp outgoing interface

A colouring is a set $B \subseteq \mathbb{Z}^2$ of black cells; p and h denote the ant's position and cardinal heading. On an update, the ant turns left on black and right on white, toggles the current cell, and moves one unit in the new heading. Cartesian headings N,E,S,W have vectors $(0,1),(1,0),(0,-1),(-1,0)$; a right turn maps (u,v) to $(v,-u)$. Let (B_t,p_t,h_t) be the state before update t, and define its observation as

$$O_t = (p_t, h_t, \mathbf{1}_{B_t}(p_t)).$$

The half-plane result permits arbitrary exterior colouring. Finite support is required for the exterior-completion theorem.

Put $\mathcal{H}_+ = \{(x,y) : x \geq 0\}$. A *one-sided port* is a finite black seed in $\mathcal{H}_+$ whose trajectory, from $(0,0)$ facing east, remains in $\mathcal{H}_+$ forever. The *standard P104 trace* is the fixed blank-orbit 104-turn word at update 9977, repeated forever, with a lattice translation, quarter-turn rotation and cyclic phase allowed. Positions, headings and read colours are part of this trace; black cells away from its future path remain in the state.

A local pattern can determine the ant's eventual motion while leaving an arbitrarily long initial observation unchanged. We construct such a pattern using four black

cells in a half-plane. The supporting line separates its entire future from any configuration on the other side, making the pattern an outgoing interface for arbitrary finite histories. A matching lower bound shows that four cells are necessary for this one-sided interface.

Rectangular frames provide a second geometry for protection. With a white exterior and the southwest/north pose, four black layers keep every future read outside an arbitrary deep interior. We determine the first permanent highway entrance for all such frames and all solid rectangles, and give a separate classification for centre-started solid squares. Four layers minimize this common-trace shielding contract; the port theorem minimizes black-cell count.

The scattering part starts from an explicit thirteen-cell standard-highway seed and composes protected scattering rules. The central closure condition is equality of the entire field in the next protected region. Increasing guards establish this condition for arbitrarily many encounters. A further return packet deliberately revisits old wake, then recovers a closed outgoing interface using a second exact comparison region. These two constructions give complementary finite-train theorems.

Gajardo, Moreira and Goles already compose finite logical gates, crossings and paths, ending a circuit in a highway seed [1, Section 2]. Our contribution specifies a sharp four-cell one-sided interface and proves closure of protected highway scattering under arbitrary finite composition, including return to old wake with the full field retained. The four-cell exterior completion theorem applies after any prescribed finite observation. Etse's finite-rectangle escape problem [2] instead bounds time in a finite domain; our half-plane threshold bounds the initial black inventory in an infinite domain.

Theorem 1 (Sharp half-plane escape)**.** *Start at $(0,0)$ facing east. For every initial colouring with at most three black sites in $\mathcal{H}_+$, regardless of the colours in $x<0$, the first-exit time*

$$\tau = \min\{t \ge 0 : (p_t)_x < 0\}$$

satisfies $\tau \le 918$. Equality holds for $B_* = \{(0,-1),(2,1),(3,3)\}$ with all other cells white.


Theorem 2 (A four-cell outgoing port)**.** *For the complete initial black set $G = \{(0,-1),(1,1),(1,3),(2,2)\}$, all other cells white, and initial pose $(0,0),E$, every p_t lies in $\mathcal{H}_+$. At update 182 the position is $(5,1)$, the heading is E, and there are 36 black cells. The entire future from this state is the standard P104 trace, with drift $(2,2)$ per 104 updates. Consequently four is the minimum black-cell cardinality of a one-sided port.*

The port gives a completion theorem for any finite initial state. The preserved object is the observed trajectory: the four extra black cells are present in the modified colouring from time zero.

Theorem 3 (Four-cell exterior completion)**.** *Let $X=(B,p,h)$ have finite black support. Given a finite protected set P, an integer $T \ge 0$, and any axis-aligned square Q containing B, P and the ℓ^∞ ball of radius T about p, one can compute a four-element set $A \subset \mathbb{Z}^2 \setminus Q$ such that the evolution of $X^+=(B\cup A,p,h)$ satisfies*

$$O_t(X^+) = O_t(X) \quad (0 \le t < T), \qquad (B\cup A)\cap P = B \cap P$$

and eventually has the standard P104 trace. If Q has n cells per side, that trace starts by update $E(n)+182$, where $E(n) = (13\cdot 3^{n-1} - 2n^2 - 4n - 5)/2$.



Three cells
first exit at 918

Four cells
standard tail from 182

Figure 1: The sharp three-cell witness B_* and the four-cell port G. Cell coordinates refer to square centres. The ant starts at $(0, 0)$ facing east; the blue line separates columns -1 and 0.

The proof has three parts. First-contact branching reduces the unrestricted three-cell problem to a finite family. Exact parity then certifies the four-cell infinite trajectory. Finally, the port is placed beyond the first exit from Q, so its future avoids every earlier black cell.

2 First-contact coverage and the sharp bound

For a finite seed $S \subset \mathcal{H}_+$, start at $(0, 0)$ facing east, with all other cells white. Let $t(S)$ be the first-exit time from $\mathcal{H}_+$, when finite. Let $V(S)$ contain each cell visited before $t(S)$ whose first read is white. Define

$$\mathcal{F}_0 = \{\varnothing\}, \qquad \mathcal{F}_{j+1} = \{S \cup \{q\} : S \in \mathcal{F}_j,\ q \in V(S)\}.$$

This construction uses the cells reached by exact trajectories, so the input coordinates require no bounding box.

Lemma 4 (First-contact coverage)**.** *If every member of $\mathcal{F}_0, \dots, \mathcal{F}_k$ exits in finite time, every colouring with at most k black sites in $\mathcal{H}_+$ exits by $M = \max\{t(S) : S \in \mathcal{F}_j,\ 0 \le j \le k\}$.*

Proof. Suppose an actual trajectory stays in $\mathcal{H}_+$ through time M. Start with $S = \varnothing$, a subset of its initially black sites in $\mathcal{H}_+$. If the actual trajectory agrees with the trajectory from S until its exit, it exits by M, contrary to the supposition. Otherwise take the first differing read. All earlier reads and writes agree; hence their colour difference at this cell is its initial colour difference. The cell belongs to the actual initial black set but not to S. It was never read earlier, since an earlier read would already have revealed that difference. Thus it belongs to $V(S)$, and adjoining it gives a member of the next family, still a subset of the actual black set. Each repetition adds a distinct black cell. At most k repetitions exhaust that set, after which a further differing read is impossible. Cells in $x < 0$ are not read before the first exit. □

Exact enumeration gives the complete families:

j	$\lvert\mathcal{F}_j\rvert$	$\max t(S)$
0	1	2
1	2	38
2	20	106
3	261	918

The 284 records specify each seed, exit time and exit position. A verifier reconstructs all first-visit sets, checks equality with the next family, and replays every exit. A separate implementation branches on the initial colour at each first visit, with a three-black budget, and obtains the same maximum. The two enumerations have different counts because the online tree identifies redundant or unread black choices.

For B_*, the ant is at $(0, 7)$ facing south before update 917, reading white. The resulting right turn moves it to $(-1, 7)$ at time 918. The finite certificates and Lemma 4 prove Theorem 1. A check that reaches its safety cap fails; it never treats an unfinished trajectory as evidence of escape or eternal residence.

3 Certifying the outgoing infinite trace

Exact replay of G for 182 updates gives the endpoint in Theorem 2, with every prefix position in $\mathcal{H}_+$. Let B' be its complete 36-cell black set. Fix the standard word w, obtained by replaying the blank ant from $(0, 0), N$ to time 9977 and reading its next 104 turns. The same word, started from $(5, 1), E$, restores its heading and has drift $d = (2, 2)$.

Write q_i for the *absolute* pre-update position in phase $i \in \{0, \dots, 103\}$ of this proposed block. Its infinite motion plan reads $q_i + kd$ at time $104k+i$, and the x-coordinates of the q_i range from 4 through 9. It therefore suffices to verify the read colour at every such position and time. An earlier visit at phase j in epoch ℓ reaches the same cell precisely when $q_j - q_i = (k - \ell)d$. The integer $s = k - \ell$ below records this epoch difference; each earlier visit contributes one flip.

Lemma 5 (Finite parity test for an infinite trace)**.** *Let a finite word w restore its heading with nonzero drift d, and let q_i be its phase positions. From a finite initial black set B', the proposed repeated trace is an actual ant trajectory if and only if, for every phase i and integer $k \geq 0$,*

$$\mathbf{1}_{B'}(q_i + kd) \;\oplus\; \left|\{(j, s) : q_j - q_i = sd,\ 0 \leq s \leq k,\ s > 0 \text{ or } (s = 0 \text{ and } j < i)\}\right| \bmod 2 = \mathbf{1}_{\{w_i = L\}}. \tag{1}$$

It is sufficient to check $k = 0$, every nonnegative overlap threshold s, and every nonnegative initial-black hit epoch and its successor.

Proof. A previous read at $q_j + \ell d$ affects the proposed read at $q_i + kd$ exactly when $q_j - q_i = (k - \ell)d$. Setting $s = k - \ell$, its time is earlier exactly when $s > 0$, or $s = 0$ and $j < i$; nonnegative ℓ gives $s \leq k$. Each preceding read toggles the cell once, giving the left side of (1). Necessity follows from the rule, and sufficiency follows by induction on chronological time.

For fixed i, j, nonzero d gives at most one integer s, whose parity contribution starts at that threshold. Each initial black cell lies on the phase ray at at most one epoch k; its contribution is present only there, so both k and $k + 1$ are breakpoints.

Between consecutive breakpoints every term is constant. The last breakpoint also represents the final unbounded interval. These finitely many tests therefore cover every $k \geq 0$. □

For the port endpoint, the test uses 170 phase/epoch evaluations and accepts w^ω. Applied independently to the actual blank endpoint, it certifies that w is the standard infinite word. The prefix guard, the phase-position range and the positive x-drift now prove the port stays in $\mathcal{H}_+$ forever. Together with Theorem 1, this proves four-cell optimality.

An additional check uses chronological visits to each physical cell, as in the periodic-realisability criterion of Jillhewar [3]. Partition phases modulo the full group $\mathbb{Z}d$, and write $q_i = a + \ell_i d$ in each class. The cell $a + nd$ is visited at times $104(n - \ell_i) + i$ for all $\ell_i \leq n$. At these times the prescribed colours must alternate, beginning with its initial colour. The visit list changes only when n passes a phase level ℓ_i; initial black cells add singleton changes. Checking the resulting finite intervals, including the last, is another exact all-future verification. The independent audit checks 40 cell intervals in 22 translation classes, both for the port and the blank reference.

The smallest black set required on the port's future read set consists of 13 cells:

$$K_0 = \{(4,3),(4,4),(5,1),(5,5),(5,6),(5,7),\\ (6,1),(6,2),(6,3),(6,6),(7,1),(7,4),(7,5)\}.$$

It is contained in B'. The remaining 23 black cells miss every phase ray $q_i + \mathbb{N}d$, and remain as stationary physical history.

4 Completing an arbitrary finite history

Proof of Theorem 3. Simulate the original state to its first exit from Q, at time τ, exterior position $e = p_\tau \notin Q$ and heading $g = h_\tau$. Finite-domain escape ensures termination; the integer-clock bound [5] gives $\tau \leq E(n)$. Since Q contains the radius-T ball and each step has unit length, $\tau > T$.

The exiting move crosses one side of Q, so g is its outward normal. Let R be the quarter-turn rotation mapping east to g, and set

$$A = e + RG.$$

The outward closed half-plane through e is disjoint from Q. Every cell of A lies in it, so A has four distinct, initially white cells outside Q. None is read before time τ.

Compare the original and augmented runs. Induction gives equal positions, headings and read colours before the exit, together with the exact complete-field relation

$$B_t^+ = B_t \triangle A = B_t \cup A \qquad (0 \leq t \leq \tau).$$

All of B_τ is inside Q, because the original support and every earlier write lie there. At the exit the augmented state thus consists of the placed port, with pose (e, g), and physical debris B_τ strictly behind its supporting line.

The placed port's entire future remains in the outward half-plane by Theorem 2. Induction on updates couples its trajectory to the augmented run: every read avoids B_τ, so both runs read the same colour and make the same turn, write and move. The

inside debris remains present and unchanged. The standard trace begins by time $\tau + 182$, hence by $E(n) + 182$. The earlier observation equality includes the first T updates, and adding A preserves every initial colour in P. □

The construction has the quantifier form $\forall X\, \forall P\, \forall T\, \exists A$ with $|A| = 4$: its conclusion concerns the augmented input X^+. The matching lower bound characterizes one-sided ports from a boundary pose.

5 Protected rectangular interiors

The same first-difference principle protects a finite interior when the reference trajectory never enters it. Here the protected set lies inside a black frame. We first give the exact shielding and entrance statements, then prove them with complete-field affine-word certificates. All cells outside the displayed finite input are white. For this section define

$$\tau_{\mathrm{hw}}(X) = \min\{t \geq 0 : \text{the complete future trace from } X_t \text{ is standard P104}\}.$$

Write $\tau(n, m) = \tau_{\mathrm{hw}}(R_{n,m}, (0, 0), N)$ for a solid rectangle; this is an entrance time, distinct from the earlier half-plane exit time.

5.1 Four-layer rectangular shielding

For positive integers n, m, put

$$R_{n,m} = [0, n-1] \times [0, m-1] \cap \mathbb{Z}^2.$$

When $n, m \geq 10$, define the deep interior and the four-layer frame by

$$I_{n,m} = [4, n-5] \times [4, m-5] \cap \mathbb{Z}^2, \qquad G_{n,m} = R_{n,m} \setminus I_{n,m}.$$

Start the ant at $(0, 0)$ facing north.

Theorem 6 (Shielding and exact entrance)**.** *For every $n, m \geq 10$ and every $A \subseteq I_{n,m}$, the complete input $B_A = G_{n,m} \cup A$ has the same infinite head and turn trace as the solid rectangle $R_{n,m}$. No cell of $I_{n,m}$ is ever read. Its first permanent standard entrance time and drift per 104 updates are given by Table 1.*

n	m	First permanent entrance $\tau(n, m)$	Drift
even	even	$78n + 44m + 555$	$(2, 2)$
even	odd	$30n + 44m + 438$	$(2, -2)$
odd	even	$38n + 62m + 1538$	$(-2, 2)$
odd	odd	$28n + 28m + 287$	$(-2, -2)$

Table 1: All four formulas include the full transient. The input pose is fixed at the southwest corner facing north.




Figure 2: The four-layer initial frame. The ant evolves on the full lattice from this initial colouring.

For a fixed pair of dimensions, Theorem 6 covers exactly $2^{(n-8)(m-8)}$ choices of the interior. More precisely, the complete physical fields satisfy

$$B_t^A \triangle B_t^{A'} = A \triangle A' \qquad (t \geq 0). \tag{2}$$

The internal information stays present and unchanged; it is not erased in a reduced simulation.

Proposition 7 (Sharpness of the common-trace thickness)**.** *Four is the minimum integer frame thickness that guarantees the common-trace shielding assertion uniformly over the domain* $n, m \geq 10$*.*

Proof. Theorem 6 gives sufficiency. In the solid 10-by-10 input, the first read of $(3, 3)$ occurs at update 1242 and requests L. Removing that one initially black cell preserves the first 1242 turns and changes the turn at that update to R. Both inputs have a black frame of thickness three. The first-read witness is checked by literal vector dynamics in `controls.py`. It also defeats every smaller thickness, since the same modified cell is then unconstrained. □

5.2 All solid rectangles and a sharp uniform bound

Write $\tau(n, m) = \tau_{\mathrm{hw}}((R_{n,m}, (0, 0), \mathrm{N}))$, including dimensions below ten.

Theorem 8 (Complete solid-rectangle classification)**.** *Every positive pair* n, m *has a finite* $\tau(n, m)$*. Its exact value is specified by four two-parameter affine branches, thirty-six one-parameter affine branches, and a table of* 3501 *finite pairs. For all positive* n, m*,*

$$\tau(n, m) \leq 242(n + m) + 29325. \tag{3}$$

The coefficient 242 *is minimal among bounds* $\alpha(n + m) + C$ *with a fixed finite* C*. At coefficient* 242*, the additive constant* 29325 *is minimal.*

Here is the precise partition, including its finite boundary. Table 1 covers $n, m \geq 10$. If $n = i \in \{1, \ldots, 9\}$ and $m \geq 200$, use the first two formula columns of Appendix B. If

$m = i \in \{1, \dots, 9\}$ and $n \geq 200$, use its last two columns. Every remaining pair belongs to

$$E = \{(n, m) : 1 \leq n, m < 200,\ \min(n, m) \leq 9\}. \tag{4}$$

These domains are disjoint and exhaustive. The cardinality is $199^2 - 190^2 = 3501$. The complete finite table is supplied as the corner rows of `finite_report.json`; its check does not infer any untested dimension from a nearby one.

Proof of the uniform bound and sharpness, given the certificate leaves. Each affine branch is verified as an actual infinite trajectory by Section 5.4. On a thin branch, write the long side as $L = 200 + p + 2a$, where $p \in \{0, 1\}$ and $a \geq 0$. The exact entrance is $\alpha L + \beta$, with every $\alpha \leq 242$. Thus its difference from $242(n + m)$ is nonincreasing in a and is bounded by its value at $a = 0$. The same coefficient comparison applies separately to both parameters in the four large-rectangle branches. Every such base value is at most 29325. The exact maximum of the residual $\tau(n, m) - 242(n + m)$ over (4) is 29325, attained at $(30, 4)$ with $\tau(30, 4) = 37553$. These rational-free integer comparisons are recomputed in `coverage.py`.

For every odd $n \geq 201$, the certified height-five branch has

$$\tau(n, 5) = 242n + 8703.$$

Consequently any $\alpha < 242$ leaves an unbounded residual $(242 - \alpha)n + 8703 - 5\alpha$, so no fixed C works. At $\alpha = 242$, the input $(30, 4)$ forces $C \geq 37553 - 242(34) = 29325$. This proves both optimality claims. □

5.3 Centre-started solid squares

Let $C_r = [-r, r]^2 \cap \mathbb{Z}^2$ be completely black initially, with the ant at the origin facing north and a white exterior. This is a different pose contract from the corner-started classification.

Theorem 9 (Centred odd-side squares)**.** *Every integer $r \geq 0$ has a permanent standard future, and*

$$\tau_c(r) = \begin{cases} 248r + 9475, & r \geq 32 \text{ even}, \\ 820r + 24110, & r \geq 43 \text{ odd}. \end{cases}$$

The remaining 37 radii are listed in Appendix C. Quarter-turn rotation gives the same entrance time for each of the other three cardinal initial headings.

The domains are $r = 32 + 2a$ and $r = 43 + 2a$ with $a \geq 0$. Their complements among nonnegative integers are precisely $0, \dots, 31$ and $33, 35, 37, 39, 41$. The square and its central position are invariant under quarter turns. The analogous arbitrary-heading claim is not asserted at the fixed southwest corner of a general rectangle.

5.4 Complete-field verification of affine words

We now give the finite-to-infinite bridge used in all three theorems. Each universal certificate is readable JSON containing its full parameter domain, rectangle, initial pose, a list of fixed words with affine repetition counts, and one final standard word. It asserts no precomputed endpoint field. The verifier reconstructs every intermediate complete field from the initial rectangle and all writes.

5.4.1 Fixed words and first reads

The consecutive-read condition is the symbolic consistency criterion of Gajardo [6, Section 3]. We use its complete-field form below.

Lemma 10 (Exact finite execution)**.** *A finite geometrical turn word executes on a supplied complete field B if and only if its first request at every read cell matches B, and all consecutive requests at that cell alternate. Its complete output field is B symmetric-differenced with the cells visited an odd number of times.*

Proof. Only an update at the cell changes its colour. Necessity follows immediately. For sufficiency, induct on time: a first read has the supplied initial bit, and a later read sees the bit left by its immediate preceding read. The requested turn and next pose therefore agree with literal dynamics. Each toggle contributes once to the symmetric difference; unread input cells remain unchanged. □

This is the elementary read-order formulation underlying the symbolic method [6]. It is applied independently to each fixed block on that block's actual complete source, not on a freshly chosen seed.

5.4.2 Unbounded repeated blocks

A certificate has the form

$$u_1^{c_1(\lambda)} u_2^{c_2(\lambda)} \cdots u_M^{c_M(\lambda)} v^{\omega}, \qquad \lambda \in D \subseteq \mathbb{Z}^d. \tag{5}$$

The words are explicitly spelled. The counts c_i are integer affine functions and are proved nonnegative on D. A count-one block may change heading arbitrarily. Every other powered block restores its starting heading and has a fixed nonzero displacement. Hence all subsequent block anchors and elapsed times are affine in λ; there is no product of two unbounded variables.

Consider one heading-restoring word u of length P and drift $d \neq 0$. Let q_i be its pre-update offsets from its block origin $p(\lambda)$, and let $B(\lambda)$ be the complete field at the start of this block. Phase i of copy k reads $p(\lambda) + q_i + kd$. Define the finite set

$$H_i = \{(j, s) : q_j - q_i = sd,\ s > 0 \text{ or } (s = 0 \text{ and } j < i)\}.$$

An earlier occurrence of phase j at the same cell must be in copy $k-s$. It exists exactly when $k \geq s$. Thus the required read equation is

$$\mathbf{1}_{B(\lambda)}(p(\lambda) + q_i + kd) \ \oplus \bigoplus_{(j,s)\in H_i} \mathbf{1}_{k\geq s} = \mathbf{1}_{u_i = L}. \tag{6}$$

Here $\oplus$ denotes parity addition. This includes previous copies, earlier phases in the current copy, and every original or generated black cell.

Lemma 11 (All-parameter repeated-block certificate)**.** *If (6) holds for every $\lambda \in D$ and every integer $0 \leq k < c(\lambda)$, then the entire repeated block is the literal execution on the supplied complete source. Its full output is*

$$B'(\lambda) = B(\lambda) \ \triangle \bigtriangleup_{0\leq i<P} \{p(\lambda) + q_i + kd : 0 \leq k < c(\lambda)\}. \tag{7}$$

The analogous equation for every $k \geq 0$ verifies the entire infinite periodic tail.

Proof. Induct through chronological update order. Before each requested read, all preceding updates have agreed with the prescribed motion, so their complete contribution is exactly the second term of (6). This proves the next turn and move. Equation (7) counts every flip modulo two. A single phase stream is injective because $d \neq 0$; overlaps between different streams cancel only by symmetric difference. For an infinite tail, the same induction proves each finite prefix, and therefore every update of the infinite future. □

5.4.3 Why each universal check is finite

The initial rectangle is an integer set with affine parameter bounds. Fixed block writes are finite unions of affine points. Each phase stream in (7) is defined by an existential integer k with affine bounds. These descriptions are closed under union, intersection, projection and difference. They are Presburger sets throughout, with finite black fibres at every finite block boundary.

For one phase, the verifier constructs the integer set of pairs (λ, k) where (6) fails, and requires that set to be empty. The finitely many self-overlap thresholds in H_i are reconstructed from the literal word, not accepted from a certificate table. The final tail uses $k \geq 0$ without an upper cutoff. Likewise the shielding test constructs all phase reads that intersect $I_{n,m}$ and requires emptiness. It checks fixed blocks as well as repeated blocks and the infinite tail.

These are exact integer-set operations implemented with ISL/GMP [7]. Arithmetic failure is an exception, not an empty-set answer. Neither real-valued relaxation nor observation of a few large parameters is an acceptance condition. Discovery by comparing several traces only proposes (5); it is outside the trusted acceptance path.

5.4.4 Certifying the first entrance

Suppose the accepted standard tail begins at time T. Scan backward through the final fixed block to find the maximal suffix of length s agreeing with the phase-aligned backward extension of that tail. The preceding letter must exist and disagree. It follows that standardness starts at $T - s$. If it began earlier, its 104-periodic word would agree with the known tail over a full period, hence with its entire aligned backward extension, contradicting that preceding letter. Every universal certificate in this package ends at its first entrance itself, so $s = 0$; the general check retains the suffix calculation. Finite cases apply the same argument to their full recorded prefix.

5.5 Finite certificate leaves and coverage

The universal data comprise 42 certificates and 1922 spelled blocks. All acceptance reports are reconstructed by the verifier. Table 2 describes the certificate obligations; its counts are computational obligations, not distinct trajectories.

For the four frame branches the parameterisation is

$$n = 10 + p + 2a, \qquad m = 10 + q + 2b, \qquad a, b \geq 0, \quad p, q \in \{0, 1\}.$$

There are respectively $47, 34, 50, 23$ blocks in parity order $00, 01, 10, 11$. Applying Lemmas 10 and 11 yields the four solid-rectangle trajectories, their exact first times and the infinite avoidance of the deep interior.

Family	Schemas	Read obligations	Interior-avoidance obligations
Large corner rectangles	4	2838	2838
Thin corner rectangles	36	51863	0
Centred squares	2	16783	0
Total	42	71484	2838

Table 2: A fixed block checks its distinct first-read cells after checking internal alternation; a powered block checks each word phase over its entire integer parameter domain.

To transfer these trajectories to arbitrary A, compare two complete sources differing only in $I_{n,m}$. Before any first differing read, their poses and read letters agree, and each shared update preserves their field difference. The certified solid reference never reads that region, so a first differing read is impossible. This proves Theorem 6 and (2); it does not assume the desired future invisibility.

For thin rectangles, the fixed side $i = 1, \ldots, 9$, its axis, and the long-side parity select exactly one of 36 certificates. The all-parameter proof covers every long side at least 200. The finite complement (4) is then exhausted. For centred squares the two universal certificates have 95 and 307 blocks and cover precisely the two domains in Theorem 9; its finite complement has 37 members.

Every one of the 3538 finite cases is executed both in C++ integer-vector dynamics and in a separate Python vector implementation. Each implementation performs $32\,681\,376$ updates. The comparisons include the entire turn prefix, pose and sorted complete endpoint field, not just cardinalities or hashes. The native code certifies the suffix by all-epoch parity breakpoints; the Python check independently uses ordered full translation classes and the minimal seed criterion [3]. The persistent report stores a digest only after the complete sets have been compared. The reported first time is independently recomputed from the preceding-letter test.

Additional controls replay one finite instance of all 42 schemas; check 736 frame interiors, including every interior assignment at sizes 10×10, 10×11, 11×10, and 11×11; retain an unread distant marker; and reject a blocker placed 10^{60} periods down a proposed future ray. Six malformed or corrupted certificates are rejected without repair. The 10^{60} check uses exact arithmetic, not a simulation of that many periods. These controls supplement the all-parameter identities; they are not their proof.

6 Guarded composition of highway scattering

A black marker placed on a future white read of a standard highway changes that turn and triggers a finite recovery. We construct a library whose outputs are again standard highways, directed northeast or southeast. Both directions advance eastward, allowing a vertical boundary to move beyond each completed collision while leaving its historical field behind it.

The result proved in this section is an arbitrary finite composition theorem: start from the explicit standard seed below, choose a compatible sequence from the thirty-rule table, and separate consecutive collisions by at least one hundred full periods.

Installing all markers initially produces exactly that sequence and then a permanent standard highway. The precise placement formula and time bound appear in Theorem 12. Compatibility means that the output orientation of one rule is the input orientation of the next.

A *guard* is a half-plane containing every read in the current recovery and its outgoing tail. We compare the complete colouring on that half-plane. Nested guards make this comparison valid at the next marker despite all past writes elsewhere. The following proof develops the rule table, the guarded field identity, and finally the induction over encounters.

6.1 Literal convention and finite certificate data

A state is the complete finite black set B, position p, and heading h in $\mathrm{N}, \mathrm{E}, \mathrm{S}, \mathrm{W} = 0, 1, 2, 3$. White turns right, black turns left, then flip and move. Time t is before update t. All markers are installed at time zero. There is no intervention between encounters and no physical deletion of old cells.

Use the following complete thirteen-cell standard-highway seed:

$$K = \{(0,6), (1,5), (0,5), (2,4), (0,4), (2,3), (-1,3),\\ (1,2), (-1,2), (1,1), (2,0), (1,0), (0,0)\}.$$

The start pose is $(0,0)$ facing east, and every cell outside K is initially white. Its standard word w, length 104, and displacement $d = (2,2)$ are reproduced and infinitely checked in the `check.py` identified below. Let P_i, H_i be its pre-update phase positions and headings, $0 \le i < 104$, with $P_0 = (0,0)$. Let R_0 be identity and $R_1(x,y) = (y,-x)$, a clockwise rotation. The two incoming orientations have displacement $d_k = R_k d,\ k = 0, 1$.

We place markers at sites whose first highway visit is the intended collision. These sites are identified by fresh phases. A phase j is fresh when its cell has no earlier visit in the two-sided planned standard geometry. For $P_j - P_i = ad$, an earlier visit exists exactly when

$$a < 0 \quad \text{or} \quad (a = 0 \text{ and } i < j).$$

The finite test yields 22 fresh phases:

```
13,14,15,27,28,29,32,38,45,46,47,
55,56,57,60,61,62,70,71,72,75,89.
```

This is geometry of a certified periodic plan; it does not assume an infinite physical seed or replace the intrinsic history of an arbitrary input.

6.1.1 The 30 checked rules

The defining supplement is the literal `TABLE` in `four_cell_port/verification/guarded_scattering/check.py` at the immutable source revision specified in Reproducibility below. Its SHA256 is

```
7b199ee5d2f291eb5450c3f232d2bbf91e469de2bd9eb416a753393886d3da14
```

The 30 rows have schema (k, j, g, t, a, x, y, h): incoming rotation, collision phase, guard, recovery updates including the marker update, outgoing standard phase, endpoint coordinates, and heading ($0, 1, 2, 3$ mean N,E,S,W). Thus each row defines $g_r = g$, $t_r = t$, $a_r = a$ and $v_r = (x, y)$; its outgoing rotation is the unique k' satisfying $h \equiv H_a + k' \pmod 4$. The same file defines the literal 104-letter `WORD` and thirteen-cell `BASE` used here. These finite data, together with the displayed mature-field formula, completely determine all thirty kernels and their endpoints. The graph is:

Incoming	Outgoing	Allowed collision phases
NE	NE	13,14,27,28,60,61,70,75,89
NE	SE	29,32,38,55,56,62,71
SE	SE	13,14,27,28,60,61,70,75,89
SE	NE	15,45,46,47,57

There are 16 NE-input rules and 14 SE-input rules. Recovery lengths range from 312 to 32656 updates. These are supplied sufficient recovery boundaries, not necessarily first permanent-P104 times. The finite incoming kernels contain 24 to 252 black cells; some recovered kernels contain 1797 black cells. The termination rank in Appendix A does not require that this black mass decrease.

6.2 Exact mature-wake restriction and guarded recovery

For a rule (k,j,g), put $A_i = R_k(P_i - P_j)$ and $d_k = R_k d$. Put $u_i = 0$ if $i < j$ and $u_i = -1$ otherwise. Define the finite set by XOR:

$$M_{k,j,g} = \bigtriangleup_{i=0}^{103} \bigtriangleup_{\lceil (g - A_{i,x})/2 \rceil \le a \le u_i} \{A_i + a d_k\}.$$

It is the restriction to $x \ge g$ of all writes before the collision in the mature incoming standard plan. The positive x drift makes the displayed ranges finite. Freshness implies 0 is not in M. The certificate kernel is

$$X_r = (M \cup \{0\}, (0, 0), (H_j + k) \bmod 4).$$

For each of the 30 rules the checker proves the following finite obligations:

1. The literal t-update execution ends at the declared complete kernel field and pose; a separately written integer-vector simulator agrees on every turn and on the complete endpoint.
2. Every recovery read has $x \ge g$.
3. Both exact infinite-tail verifiers accept the declared standard phase from that endpoint. Its drift has positive x component 2, and every phase read in the first tail period has $x \ge g$.

The two infinite tests are not finite repetition heuristics. One evaluates, for each phase ray, all onset thresholds for previous writes and all exceptions from the finite initial black field. Parity is constant between those finitely many breakpoints, including the last infinite interval. The other orders all visits to a fixed translation-class cell: write its coordinate as $b + m d_k$ and the phase position as $b + z_i d_k$, for a fixed class

representative b. That phase visits at time $104m + (i - 104z_i)$, when $m \geq z_i$. Those visits must alternate colours beginning with the actual initial colour. It checks every change of the active list and every finite-field exception. The two tests share the integer geometry primitives; they are two independently formulated all-future checks, not two independently maintained software stacks.

Guard lemma. Add any finite black field G contained in $x < g$ to X_r. The entire future read/turn sequence remains that of X_r, and G is never touched.

Proof. Until a first $x < g$ read, first-difference induction gives the certified recovery and then its certified tail. Both stay in $x \geq g$, so no first such read exists. This proves invisibility instead of assuming it. G remains physically present. The same reasoning holds until a later, explicitly planned marker interrupts the tail. Permanent protection across such interruptions requires the nesting argument in the next section. □

6.3 Finite arithmetic certificate for every compatible pair

Suppose rule r has outgoing rotation k, matching the incoming rotation of the next rule s, displacement d_k, outgoing phase a and endpoint v_r relative to its marker. To place a later phase-j marker after n full periods plus the phase adjustment, its position relative to the previous marker is

$$\begin{aligned} q' &= v_r + (n + \mathbf{1}_{\{j<a\}})d_k + R_k(P_j - P_a), \\ \text{flight duration} &= 104n + ((j - a) \bmod 104). \end{aligned} \tag{8}$$

Use $n \geq 100$. This deliberately loose threshold is not asserted optimal. For the next rule s with guard g_s, its absolute half-plane starts at $q'_x + g_s$. The certificate checks that this boundary is strictly to the right of:

- every previous recovery read and every black cell of its complete kernel endpoint;
- the previous guard;
- the entire synthetic standard past before that endpoint.

The last maximum is finite and, relative to v_r, equals

$$\max_{0 \leq i < 104} \left[(R_k P_i)_x - (R_k P_a)_x + \begin{cases} 0 & i < a, \\ -2 & i \geq a. \end{cases} \right]. \tag{9}$$

Earlier epochs only decrease x by further multiples of 2. Formula (9), rather than a simulation horizon, proves that all omitted pre-output planned writes are outside the next half-plane.

There are exactly 448 compatible ordered rule pairs. At $n = 100$ all pass, with minimum strict-boundary slack **122** and minimum marker x displacement **184**. For larger n, the left-hand boundary increases by $2(n - 100)$ and the earlier objects do not change. Thus the same inequalities hold for every $n \geq 100$. The 16 initial NE choices also pass; the minimum initial boundary slack is 160.

Future markers cannot interrupt an earlier recovery because they lie strictly beyond its full read footprint. Nor can they interrupt an earlier free flight: the x overshoot of a periodic flight before its target is bounded by twice the maximum of the two finite canonical x spans plus 2, which is less than 184. The checker tests this

bound against every pair. Consequently chronological order of the planned encounters is proved; it is not an extra all-future assumption hidden in the definition of an admissible train.

6.3.1 Why the output really re-enters the same input family

At the next collision half-plane, all previous endpoint black cells and all previous retired debris are outside. Inside, only the newly generated standard writes and the remaining preinstalled markers occur. By (9), adding back the synthetic pre-output past changes nothing there. Therefore those newly generated writes restrict to exactly M_{k,j,g_s}. The current marker adds its single black cell; more distant markers remain untouched. This is equality of the complete inside field, not equality on a fixed-radius sample or merely on reference rays. It proves closure of the interface needed by the next rule.

All later guards strictly increase. Between guards, the certified tail stays to the right of the previous one; each later recovery stays to the right of its newer guard. Hence every retired western region is permanently protected under the whole composed run, even though later deflections occur.

6.4 All-length, multi-encounter convergence theorem

Choose any finite directed word $r_1, \dots, r_m$ in the displayed two-state graph, starting NE, and any integers $n_1, \dots, n_m \geq 100$. Let rule r_i have incoming rotation k_i, collision phase j_i, recovery time t_{r_i}, endpoint v_{r_i} and outgoing phase a_i. Set $p_0 = (0,0)$ and $a_0 = 0$. Starting NE gives $k_1 = 0$; compatibility makes each subsequent k_i the preceding rule's outgoing rotation. For $i = 1, \dots, m$, define

$$q_i = p_{i-1} + (n_i + \mathbf{1}_{\{j_i < a_{i-1}\}}) d_{k_i} + R_{k_i}(P_{j_i} - P_{a_{i-1}}),$$
$$p_i = q_i + v_{r_i}.$$

This is (8) written from the preceding recovery endpoint, including the initial canonical endpoint when $i = 1$. This is a finite, effective prescription using integer arithmetic and the fixed rule table. Define the literal initial state

$$B_0 = K \cup \{q_1, \dots, q_m\} \cup G, \qquad p_0 = (0,0), \quad h_0 = \mathrm{E},$$

where G is any finite set in $x < -1$. The markers, K and G are disjoint, so $|B_0| = 13 + m + |G|$. No marker is installed later during the run.

Theorem 12 (Guarded scattering trains)**.** *Every such state encounters the markers in the prescribed order, executes all prescribed recoveries with its complete history retained, and reaches permanent standard P104 by time*

$$T = \sum_{i=1}^{m} \big[104 n_i + ((j_i - a_{i-1}) \bmod 104) + t_{r_i}\big]. \tag{10}$$

For $m = 0$ take $T = 0$ and final orientation NE. For $m > 0$, the final direction is the graph's final NE or SE orientation.

Proof. The canonical tail has minimum read x=-1, so G cannot affect its first flight. The initial-boundary inequalities remove K and every synthetic pre-start write from the first collision half-plane. Freshness and the flight overshoot bound give the first encounter and its complete restricted kernel. Apply the guard lemma up to the next encounter. Subsection 6.3 proves both that this next encounter is not premature and that it again has exactly the required restricted kernel. Induct on the finite rule word. Nested guards keep every retired part invisible throughout all remaining recoveries. After the last marker there is no further perturbation ahead and the final infinite-tail certificate applies with the entire western history still present. Summing the actual flight and recovery lengths gives (10). □

This is not just checking more finite seeds: m, all gap parameters, and the finite western history are unbounded. The proof is the closed-interface induction, not extrapolation from the replay tests.

6.4.1 A concrete repeated-turn instance

Repeat the pair (NE phase 29, SE phase 15) twelve times, with every $n_i = 100$. The initial field has **37 black cells**, including the thirteen-cell base. The first six markers are

```
(204,201), (422,-20), (653,194),
(871,-27), (1102,187), (1320,-34).
```

The 24 prescribed encounters complete at time **451214**, with head at (5387,-81), NE output and standard phase 94. The retained complete field then has **43669** black cells. Both infinite-tail tests accept it. This illustrates why a decreasing black-cell count is unnecessary.

7 Composable excursions with genuine old-wake readback

The preceding rules keep the highway advancing east. Here we construct an excursion that turns northwest, reverses southeast, and reads a black cell written during its earlier approach. A final marker restores a northeast highway. Three markers specify one such excursion; any finite number of these three-marker patterns can be installed in the initial field.

Theorem 14 proves arbitrary finite composition, with an independent excursion parameter $n_i \geq 100$ and incoming gap $m_i \geq 100$ for each pattern. The five stages of one pattern are shown below. Their purpose is to establish a complete field identity at the old-cell read, independent of how far the middle flight travels.




Figure 3: Stages of a return pattern. The flights between finite recoveries have arbitrarily large prescribed length. This is a stage diagram, not a scale drawing of the trace.

The coordinates $s = x+y$, $\ell = y-x$ and $r = x-y$ describe the three guards. Northeast motion increases s by four per period. Northwest motion holds s fixed and increases ℓ; southeast motion holds s fixed and increases r. These directions isolate the distant reversal and then the return region from the fields left by earlier stages.

7.1 Convention, standard word, and finite mature restrictions

Use the state and clockwise-rotation conventions of Section 1 and the integer heading convention $\mathrm{N}, \mathrm{E}, \mathrm{S}, \mathrm{W} = 0, 1, 2, 3$ of Section 6.1. All fields in this section are complete finite black sets.

Use exactly the standard word w and thirteen-cell NE seed K from `four_cell_port/verification/guarded_scattering/check.py`. Let P_i, H_i be its 104 pre-update positions and headings, with $P_0 = 0$, $H_0 = \mathrm{E}$ and $d = (2, 2)$. Its minimum future value of x+y is zero. Write w_a for its cyclic word beginning at phase a, and R_k for clockwise rotation through k quarter-turns, with $k = 0, 1, 2, 3$ giving NE, SE, SW, NW drift respectively. Step i of w_a has canonical phase $(a + i)$ mod 104; the subscripts of $Q_{B,i}$ and $Q_{D,i}(0)$ below index these relative steps. These phase coordinates specify the reference trajectories used in each stage of the construction.

Put

$$s(x, y) = x + y, \quad r(x, y) = x - y, \quad \ell(x, y) = y - x, \quad G = -160.$$

For a phase j, orientation k, and a linear form f with $f(R_k d) > 0$, define

$$\begin{aligned} M(j, k, f, G) &= \bigtriangleup_{i=0}^{103} \bigtriangleup_{L_i \le a \le u_i} \{R_k(P_i - P_j) + aR_k d\}, \\ L_i &= \left\lceil \frac{G - f(R_k(P_i - P_j))}{f(R_k d)} \right\rceil, \\ u_i &= \begin{cases} 0 & i < j, \\ -1 & i \ge j. \end{cases} \end{aligned} \tag{11}$$

This is finite. It is the exact parity of all planned standard writes before a phase-j collision, restricted to $f \ge G$. It is a description of a finite restriction, not an infinite physical input. A finite approach realizes it once the old physical endpoint and the synthetic past omitted before that approach lie outside the comparison half-plane. Those obligations are proved below, not assumed from observed repetition.

Define the marker coordinates

$$q_2(n) = (-2n - 15, 2n + 11), \qquad q_3 = (177, -260).$$

Our first collision interface has head 0, heading $H_{57} = \mathrm{S}$ and field

$$\begin{aligned} &M_1 \cup \{0, q_2(n), q_3\} \cup H, \\ &M_1 = M(57, 0, s, G), \qquad H \subset \{s < G\}. \end{aligned} \tag{12}$$

where H is any finite complete historical black field. The two-marker version omits q_3. Future packets add further markers above the current packet's entire read extent; their noninterference is proved in Subsection 7.7.

7.2 Finite A and C blocks, and the first long flight

7.2.1 First turn A

The exact 832-update orbit from $(M_1 \cup \{0\}, 0, H_{57})$ ends at

$$v_A = (-12, 12), \qquad h_A = \mathrm{S},$$

with 580 black cells and a certified standard NW tail w_{58}. Every A read has $-10 \le s \le 9$ and every tail read has $s \ge G$. Both infinite checkers accept this complete reference endpoint. Its initial field has 484 cells.

Let $Q_{B,i}$ be the pre-update positions in the primary collision frame of the flight w_{58} launched from v_A at $n = 0$. Thus $Q_{B,0} = v_A = (-12, 12)$ and $Q_{B,14} = (-15, 11)$, so

$$q_2(n) = Q_{B,14} + n(-2, 2) = (-2n - 15, 2n + 11),$$

and the first reference read there is exactly $104n + 14$ updates later. The finite ray calculation enumerates every i and integer z with $q_2(0) - Q_{B,i} = z(-2, 2)$. All n+z are nonnegative for $n \ge 100$, and $\min(104z + i) = 14$. The expected letter is R. This checks first contact, not just that the proposed marker eventually lies on the reference route.

The marker $q_2(n)$ is strictly left of all A reads, for every $n \ge 100$. The fixed q_3 is absent from A and from every future NW phase ray. The old field H is outside $s \ge G$; the A prefix and its NW reference remain inside. First-difference coupling proves the actual A block and the subsequent $104n + 14$-update flight B, ending at the black marker q_2. Its absolute packet time is $104n + 846$.

7.2.2 Distant reversal C

The collision has canonical phase $58 + 14 = 72$ and rotation $k = 3$. Let $M_2 = M(72, 3, \ell, G)$. The exact 51272-update orbit from

$$(M_2 \cup \{0\}, 0, (H_{72} + 3) \bmod 4)$$

ends at $v_C = (-24, -44)$, heading N, with 2569 black cells and a certified SE reference tail w_{18}. Its initial field has 485 black cells. All its finite reads have $\ell \ge G$ and, after translation by $q_2(n)$, $s \ge G$. Its bounds are $-75 \le s \le 63$ and $-76 \le r \le 54$ in local coordinates.

The true field before this C block agrees with this kernel on

$$\Omega_C(n) = \{v : s(v) \ge G,\ \ell(v - q_2(n)) \ge G\}. \tag{13}$$

Indeed every black cell of the A endpoint and q_3 lies strictly below the ell boundary. So does every point of the synthetic standard past preceding the A endpoint. Their maxima are finite; subtracting $\ell(q_2(n)) = 4n + 26$ makes each required strict inequality an integer affine inequality in n. They hold at n=100 with nonnegative slope thereafter. Hence inside (13), the actual B writes equal exactly the mature M_2 writes from (11). The marker adds $\{0\}$. The arbitrary H contributes nothing because of the s boundary.

Thus C is an actual literal block on the complete input. No all-future conclusion for the true orbit is inferred from its isolated-kernel tail: the older field outside Ω_C will matter during the reverse flight.

7.3 The first return to a previously written black cell

At C's end the head is

$$q_2(n) + v_C = (-2n - 39, 2n - 33), \qquad h = \mathrm{N}. \tag{14}$$

at packet time $104n + 52118$. Its isolated reference follows w_{18} southeast. Let $Q_{D,i}(0)$ be the 104 phase positions from (-39,-33), heading N. For general n the phase positions are $Q_{D,i}(0) - n(2, -2)$.

The true field and this reference differ by the following exact XOR:

$$B_{A,\mathrm{out}} \triangle B_{\mathrm{writes}} \triangle (q_2(n) + M_2) \triangle \{q_3\} \triangle H. \tag{15}$$

Here $B_{A,\mathrm{out}}$ is the complete field after block A, and B_{writes} is the symmetric difference of all read sites during flight B, counting each visit once.

The finite C writes cancel because both trajectories execute them identically. The two copies of the marker q_2 also cancel. This identity retains every older write; it does not identify the true state with a cleaned reference.

All reverse reference phase rays have s values strictly below both the NW B write stream and $q_2(n) + M_2$, while still having $s \geq G$. Therefore they cannot read those two terms or H. The remaining first-difference query is against the fixed finite A endpoint and q_3.

For each phase i and black point $b \in B_{A,\mathrm{out}} \cup \{q_3\}$, enumerate integers z satisfying

$$b - Q_{D,i}(0) = z(2, -2).$$

There are 158 phase/cell candidates. Every n+z is nonnegative for $n \geq 100$. The minimum of 104z+i is -170, attained at phase index 38 and $b = q^* = (-38, -32)$. No candidate belongs to q_3. The reference letter there is R and the actual cell is black. Hence the actual reverse flight has exact length

$$104n - 170 = 104(n - 2) + 38. \tag{16}$$

and ends in the old black read at packet time $208n + 51948$. Before it, all turns agree with the SE reference. At it, the real turn is L rather than R.

7.3.1 The black cell was created by the same actual trajectory

In the incoming NE plan relative to phase 57, solve

$$q^* = P_i - P_{57} + ad, \qquad 104a + i - 57 < 0.$$

The last such read is $i = 89,\ a = -17$, at time -1736, and $w_{89} = R$. The A block never reads q^*; B is disjoint by its s range; C misses the return region below; and (16) proves that D does not read q^* earlier. Thus its black lifetime is exactly

$$(208n + 51948) - (-1736) = 208n + 53684. \tag{17}$$

In every train realization below, the incoming flight has more than 1736 updates, so this birth occurs after the finite input time, even in the first packet. It is not an initially supplied marker, an intrinsic pre-input lifetime, or a cell that is simply presumed eventually relevant.

7.4 A constant full comparison field after an arbitrarily long excursion

Use the fixed region

$$\Omega = \{s \geq G,\ r \geq G\}. \tag{18}$$

At the old read q^*, the true field restricted to Ω is independent of n. This is the closure-enabling fact. The arbitrary H is absent by its s guard. The distant q_2 marker and all C reads are outside Ω for every $n \geq 100$: their r values are -4n-26 plus a bounded local value, strictly below G. This does not say they were erased; they remain in the complete true endpoint.

For completeness, here is an explicit finite XOR formula for the field in Ω. Start with $B_{A,\text{out}} \cup \{q_3\}$. For each $Q_{B,i}$ put

$$h_i = \left\lfloor \frac{r(Q_{B,i}) - G}{4} \right\rfloor.$$

Add by XOR all $Q_{B,i} + j(-2, 2)$ with $0 \leq j \leq h_i$ and $s(Q_{B,i}) \geq G$. All $h_i < 100$ (in fact $32 \leq h_i \leq 35$ and $\sum_i (h_i + 1) = 3618$), so all epochs $0 \leq j \leq h_i$ are present for every $n \geq 100$. The terminal 14 B reads at epoch n are outside Ω. Thus these are exactly the B writes inside Ω, not a truncation by simulation time.

For the reverse flight write its complete epochs as v=j-n, so $-n \leq v \leq -3$. For each $Q_{D,i}(0)$ put

$$l_i = \left\lceil \frac{G - r(Q_{D,i}(0))}{4} \right\rceil.$$

Add by XOR $Q_{D,i}(0) + v(2, -2)$ for $l_i \leq v \leq -3$ when $s(Q_{D,i}(0)) \geq G$. All $l_i \geq -n$ for $n \geq 100$. Finally add the first 38 phase positions at v=-2, if they lie in Ω. Restrict the resulting finite field to Ω.

The resulting field C_{old} has 1446 cells. Its exact hash and the 3618 B terms and 3893 D terms are recorded in `four_cell_port/verification/return_scattering/report.json`, reconstructed by the adjacent `check.py` in the pinned verification snapshot. This is equality of the entire inside field, including the old A scar and both relevant write streams. It is not equality on the next few read positions or a bounded mask inferred from matching poses. Every lower/upper epoch omission is justified by the linear forms above.

7.4.1 Two-marker output

From $(C_{\text{old}} \setminus \{q_3\}, q^*, \text{S})$, an exact 9308-update block ends at (-22,-60),S, with a certified SE w_{14} tail. All these finite reads and the infinite tail stay in Ω. First-difference induction with (18) proves that the complete two-marker state is permanently standard by packet time $208n + 61256$.

This is already an all-n positive family with a real unbounded-age readback. Its whole-input realizations from K have fifteen initial black cells when there is no extra debris. The coordinate parameter n controls the excursion length.

7.4.2 Reset to the original NE interface

The marker q_3 is not read in that 9308-update recovery. It is the phase-15 first-visit cell exactly 10401 updates along that w_{14} SE tail, measured from the end of the 9308-update block (thus at update $9308+10401 = 19709$ from q^*), and is read white/R there by the unmarked reference. The third initial black cell changes that turn. The complete finite block from $(C_{\text{old}}, q^*, \text{S})$ has 23661 updates and ends at

$$v_{\text{out}} = (203, -244), \qquad h = \text{E}, \qquad \text{NE phase } 94. \tag{19}$$

All its reads and its infinite NE tail stay in Ω. Two infinite criteria accept its complete 3453-black comparison endpoint. The same coupling proves the actual three-marker packet permanently standard by $208n + 75609$ when no later packet interrupts it.

The initial q_3 has not been manufactured by this process: omitting it gives the different, permanent SE future just proved.

7.5 Single-packet theorem and protection under later interruptions

Theorem 13 (One return pattern)**.** *Every state with initial field* (12)*, initial pose* $(0, 0), \text{S}$*,* $n \geq 100$ *and arbitrary finite* $H \subset \{s < G\}$*, has the three-marker behavior just described and reaches NE standard phase 94 by time* $208n + 75609$*. The two-marker state has the SE output from Subsection 7.4.1. All supplied black history remains physically present.*

Proof. Subsections 7.2 and 7.3 give the exact A, B, C, D execution and first old read. Subsection 7.4 gives the exact whole-field restriction and protected finite E continuation and tail. The comparison paths remain within the regions on which field agreement was established, so a first divergent read is impossible. This is a finite-stage induction plus an infinite-tail certificate, not extrapolation from the sampled n values. □

For the three-marker packet, every read before (19) satisfies

$$-109 \leq s \leq 59. \tag{20}$$

The upper bound also covers all initial M_1 cells and the three markers. The NW and SE flights have constant s on each phase ray; their arbitrarily long lengths do not enlarge (20). The finite A, C, E blocks supply the other extrema. At the C boundary, (14) gives x=-2n-39, so no n-independent backward x-displacement or bounded-diameter packet footprint can replace this argument.

A later marker may interrupt the final NE tail. The single-packet theorem alone would not guarantee old-history protection after that interruption. The next section supplies the necessary nested-guard induction for the full composition.

7.6 Finite arithmetic connector and marker ordering

A packet outputs pose v_{out}, orientation NE, phase 94. After $m \geq 100$ full periods and phase adjustment to 57, its next primary marker is displaced by

$$\Delta(m) = v_{\text{out}} + (m+1)d + P_{57} - P_{94} = (2m + 208, 2m - 242). \tag{21}$$

Thus $s(\Delta(m)) = 4m - 34 \geq 366$. The next diagonal guard starts at $s(\Delta(m)) + G \geq 206$, while all previous packet black cells and reads not in inherited history have $s \leq 59$. The minimum guard slack is 147, strictly positive. Every synthetic pre-output standard write is also below the next boundary; this is checked for each phase at its latest possible pre-output epoch, with all earlier epochs decreasing s further.

It follows that, at the next primary, the full inside field consists exactly of its M_1, its three still-unread markers, and still later preinstalled markers. The actual NE flight writes and the mature synthetic writes agree there because the omitted pre-flight past is entirely outside. Inherited earlier history is below an even older guard and hence below the new one.

The companion markers of this next packet cannot interrupt that NE approach: $q_2(n)$ and q_3 have r respectively -4n-26 and 437 relative to the primary, outside all two-sided incoming NE phase lines. This is a geometric disjointness test, not merely checking a finite flight. Nor can markers from a still later packet cause a premature contact. Their minimum relative s is -83; (21) places them strictly above both the current packet's entire read maximum and the maximum s of an incoming flight before its primary. The latter is at most primary s+1, as checked from the 104 phases with their latest pre-collision epochs.

These inequalities prove the chronological order of all planned contacts, not just compatibility of consecutive endpoint poses. For $m > 100$ their left sides increase by $4(m - 100)$; no further trajectory simulation is required.

7.7 Arbitrarily many genuine returns from one complete finite input

Choose any integer $k \geq 0$ and any integer lists

$$m_1, \ldots, m_k \geq 100, \qquad n_1, \ldots, n_k \geq 100.$$

Start with pose $p_0 = 0$, phase $a_0 = 0$, orientation NE. For i=1,...,k set

$$\begin{aligned} Q_i &= p_{i-1} + (m_i + \mathbf{1}_{\{57 < a_{i-1}\}})d + P_{57} - P_{a_{i-1}}, \\ p_i &= Q_i + v_{\text{out}}, \qquad a_i = 94. \end{aligned} \tag{22}$$

Install at input time all three cells

$$Q_i, \qquad Q_i + q_2(n_i), \qquad Q_i + q_3.$$

The complete input is K plus these cells plus any finite black $G_0 \subset \{s < 0\}$; its ant starts at 0,E. All these sets are disjoint, and the input has exactly $13 + 3k + |G_0|$ black cells. Markers are never installed during execution. For k=0 the initial state is already on the certified NE future.

Theorem 14 (Arbitrary finite return trains)**.** *Every such finite input follows the prescribed packets with all past writes retained and reaches permanent standard P104 by*

$$T = \sum_{i=1}^{k} \big[104m_i + ((57 - a_{i-1}) \bmod 104) + 208n_i + 75609\big]. \tag{23}$$

The output after $k > 0$ packets is p_k, heading E, NE phase 94. Each packet contains the genuine post-input-created black lifetime (17)*.*

Proof. The canonical initial ray has $s \geq 0$, so it cannot read G_0. The first primary guard is beyond every K cell and the entire synthetic pre-start past; at $m_1 = 100$ its slack is at least 243. Its companion markers miss the incoming NE rail, and later markers are beyond the finite read envelope. Therefore the first collision has the correct complete restricted field (12).

Apply Theorem 13 up to its output, but keep all later markers in the physical state. Subsection 7.6 proves that they have not altered this prefix, that the next collision has exactly the required restricted field, and that its guard is strictly above all preceding history. Induct on i. The guards strictly increase in the same absolute linear form s. Between collisions the previous certified tail remains above its previous guard; within each new packet all reads stay above the new guard. Consequently no later reset reactivates a retired region. After the last packet there is no remaining forward perturbation and the certified NE tail persists. Summing the exact block lengths proves (23). □

The assertion about arbitrary finite G_0 is a proved initial guard, not a deletion of an unknown future-active set. Complete-state train replays retain G_0 and every black point from every earlier excursion.

7.7.1 Small input and repeated-return examples

With $m_1 = n_1 = 100$ and no G_0, the three markers are

`(204,205), (-11,416), (381,-55).`

Together with K this is a sixteen-black finite seed. It writes (166,173) at time 8721 and next reads it black at time 83205, an exact lifetime of 74484 updates. It has a certified NE output at time 106866, at (407,-39), with 7796 black cells.

The retained six-packet example has $m_i = 100$ and $n_i = (100, 101, 150, 103, 211, 100)$. Its thirty-one-black input executes six such returns and has a certified NE output at time 675566, at (2447,-249), with 50671 black cells. These are examples of the all-k proof, not a claim about all sixteen- or thirty-one-black initial states.

8 Verification and relation to earlier work

The verification package separates the finite data from the coverage proof. The original integer checker reconstructs the 284-seed table, the complete 182-step endpoint, and two all-future certificates. A complex-coordinate implementation independently checks the online colour tree and the blank and port prefixes. A third integer-vector implementation reads the immutable certificates, reconstructs family coverage, and checks per-cell chronological intervals. Corrupted exit data and missing branches are rejected, as are changes to the 13 active black cells and a blocker 10^{100} periods ahead. An off-trace marker is correctly accepted as dormant history.

The exterior constructor is also tested on 96 finite states, covering all four exit sides and including 16 cases translated by coordinates of magnitude 10^{30}. The tests verify the exact complete-field difference before exit, retention of the inside debris, and the all-future certificate after the placed port. These cases test the implementation; the universal statement is the geometric coupling proof above.

Our clock paper supplies the square bound used for the explicit completion time [5]. The one-black theorem establishes eventual standard-highway behaviour for unchanged singleton inputs [4]. The present contribution is the sharp initial cardinality threshold for a one-sided port, the exact three-cell exit bound, and a four-cell completion for arbitrary finite histories, followed by the protected composition and return theorems. The general periodic-realisability criterion [3] is used as a verification method; the new threshold is established by first-contact coverage.

The rectangle module supplies 42 all-parameter certificates and a finite complement of 3,538 complete inputs. Its ISL/GMP checks [7] decide emptiness of bad-read sets and avoidance of the protected interior; independent Python/C++ trajectories cover the finite leaves. Run `python3 four_cell_port/reproduce.py --frames-only --jobs 3` for this full chain. The source manifest binds the word data, checkers and retained reports. The integrated entrypoint also checks ports and scattering.

9 Limitations

Rectangle statements retain the specified pose and white exterior. Three layers can change the trace, which proves sharpness for shielding rather than a claim about convergence. A frame becomes a scattering input only if the separate scattering interface conditions are verified.

The constructions prescribe a finite initial field and finitely many preinstalled instructions. Their train lengths, gaps and excursion parameters are arbitrary within the stated domains, including $n_i, m_i \geq 100$ where required, but their proofs apply to these specified seed families and guard hypotheses. They do not construct autonomous infinite instruction renewal or establish convergence for every finite-support input.

The reported recovery boundaries are sufficient onset times and need not be the first permanent-P104 times. Fixed black-cell cardinality does not bound the coordinates or the excursion length in these families. The sharp three/four-cell threshold concerns inward boundary ports; it does not assert minimality among all exterior modifications of an individual input.

10 Conclusion

Protected interiors give a second application of the same coupling principle. The rectangle classification covers every interior filling behind four black layers and determines exact permanent entrance times, while the solid-rectangle family gives sharp global constants within its specified input contract.

The sharp four-cell port connects a local resource threshold with effective completion of finite histories. The scattering constructions give explicit standard-highway seeds with composable collision interfaces. Its proof requires agreement on a complete protected region and a strictly advancing guard; matching endpoint poses alone would not suffice. The return construction extends that interface to unbounded excursions and actual readback of old self-written memory, while retaining the full field at every stage.

Each finite train has its markers fixed at input time. The number of packets is supplied by that finite input, while every gap and excursion parameter may be arbitrarily large. Each theorem specifies its complete initial field and proves the entire sequence of encounters from those pre-placed markers.

Reproducibility. The accompanying source package contains the complete article, finite certificates and checkers. Its `sources.json` manifest binds every input by SHA-256. The public project is https://github.com/kehao95/langtons-ant-core/tree/main/four_cell_port. Run from the repository or extracted source package:

```
python3 four_cell_port/reproduce.py
make -C four_cell_port/paper
```

The checks use Python 3.10+, a C++17 compiler and ISL/GMP for the rectangle integer-set obligations. The proofs combine analytic arguments and exact finite computation. Input hashes and the scope of each check are recorded with the verification evidence.

AI assistance. Generative AI assisted with developing and checking arguments, implementing verification programs, and revising the exposition.

A Termination ranks for certified scattering descriptions

The following rank is defined on the certified scattering train, whose checkpoints are its finite recovery boundaries.

During a recovery choose its finite read rectangle Q, including its endpoint. Exterior colours remain unchanged. Let $s = x + y - c$, with integer c centering the rectangle's diagonal range, and $M = \max_{p\in Q} |s(p)|$. Write $\chi(x, y) = (-1)^{x+y}$ and let $\sigma = \chi(p)$ when the head is vertical and $\sigma = -\chi(p)$ when it is horizontal. This sign is invariant under an update. With this convention, use the scaled integer clock

$$C_Q(X) = -5\sigma \sum_{q\in B\cap Q} \chi(q)\big(4^{M+s(q)} + 4^{M-s(q)}\big) + G(p, h),$$

where $G(p, h) = 2(4^{M+s(p)} - 4^{M+1-s(p)})$ for $h = \mathrm{N}, \mathrm{E}$ and $G(p, h) = 2(4^{M-s(p)} - 4^{M+1+s(p)})$ for $h = \mathrm{S}, \mathrm{W}$. It is $5 \cdot 4^M$ times the $r = 4$ clock, with the unchanged outside contribution subtracted. Writing F for the single-step update map, every internal literal update satisfies

$$C_Q(FX) - C_Q(X) \geq 2 \cdot 4^M. \tag{24}$$

A computable upper bound U_Q for all internal colourings and poses is

$$5 \sum_{q\in Q} \big(4^{M+s(q)} + 4^{M-s(q)}\big) + \max_{p\in Q,h} |G(p, h)|.$$

Thus

$$\rho_Q(X) = \left\lceil \frac{U_Q - C_Q(X)}{2 \cdot 4^M} \right\rceil. \tag{25}$$

is a nonnegative integer which strictly decreases on every internal recovery update. Each stored finite recovery checks (24), (25), and the complete endpoint clock again. The universal identity is imported from the clock theorem [5]; these finite checks validate the particular representation and convention.

The whole certified computation has a lexicographic rank in $\mathbb{N} \times \{0,1\} \times \mathbb{N}$:

$$(\text{unread input markers},\ \text{mode},\ \text{local fuel}),$$

with recovery mode 1 and flight mode 0. During flight, local fuel is the exact number of updates to the next marked read, computed by (8). Reading that marker decreases the first coordinate, permitting a reset to recovery mode. During recovery, use ρ_Q; returning to flight decreases mode, permitting the next flight fuel to be reset. After the last recovery the certificate program halts. This is a rank on the state with its finite checked train description, not a claimed all-input physical-state rank. It stops at certification; the actual ant then continues forever along its highway.

The logical role of closure is crucial: generated historical black cells do not create further unaccounted marker obligations because their possible interactions have been absorbed in the verified recovery and then isolated by the guard. The rank is defined for a state together with its certified finite train description.

A.1 A finite-stage rank for return packets

The return pattern gives a finite sequence of certified stages. Use a finite-stage lexicographic rank

$$(\text{unfinished patterns},\ \text{remaining stage index},\ \text{local fuel}),$$

The stage order is incoming NE flight, A, B, C, D, E. Each flight has the exact remaining update count from the formulas above. In each finite A, C or E block, choose its finite read rectangle, including the last endpoint, and use the scaled integer $r = 4$ clock already proved in the clock construction above. The unchanged exterior contribution cancels. Its computable upper bound over all internal fields and poses yields the nonnegative integer fuel

$$\left\lceil \frac{U_Q - C_Q(X)}{\epsilon_Q} \right\rceil, \qquad \epsilon_Q = 2 \cdot 4^M,$$

which decreases at every internal literal update. This remains valid for the true complete field: unread differences inside that rectangle merely contribute constant terms, and the universal clock inequality holds for every colouring. Transitions to the next stage decrease the middle coordinate, allowing fuel to reset. Completing a packet decreases the first coordinate and starts the next incoming flight; completing the last packet halts the certificate program. The actual ant continues forever along its highway.

Unbounded excursion n makes the two flight counters large but does not create new unbudgeted stages: the exact XOR return query and full return-region equality proved that there is exactly the certified old collision and recovery. That is the closure fact on which the rank relies. The clock did not prove the guard, the return-field equality, or all-input coverage.

This rank carries the finite description of the prescribed return train.

B Thin-rectangle formulas

In Table 3, $L \geq 200$ is the long side with the indicated parity. The columns give the exact first entrance for $(n, m) = (i, L)$ and (L, i), always with the southwest/north pose. No symmetry between these two ordered dimension pairs is assumed.

	$\tau(i, L)$		$\tau(L, i)$	
i	L even	L odd	L even	L odd
1	$64L + 6928$	$84L + 15501$	$14L + 669$	$32L + 452$
2	$40L + 1227$	$32L + 603$	$8L + 1183$	$36L + 648$
3	$30L + 191$	$22L + 974$	$30L + 550$	$110L + 3592$
4	$104L + 6173$	$60L + 1864$	$72L + 28524$	$64L + 3814$
5	$78L + 1639$	$28L + 427$	$30L + 630$	$242L + 8703$
6	$60L + 4768$	$48L + 606$	$68L + 1030$	$38L + 1910$
7	$62L + 1751$	$28L + 483$	$30L + 746$	$40L + 999$
8	$150L + 9506$	$44L + 678$	$78L + 907$	$38L + 2034$
9	$62L + 1872$	$28L + 539$	$30L + 834$	$28L + 539$

Table 3: All thirty-six thin branches, with $L \geq 200$.

C Finite centred-square values

The following table completes Theorem 9. The side length is $2r + 1$.

r	$\tau_c(r)$	r	$\tau_c(r)$	r	$\tau_c(r)$
0	9978	13	11998	26	27840
1	1714	14	4498	27	30466
2	3457	15	4595	28	26617
3	5818	16	8489	29	45703
4	709	17	8307	30	27392
5	5850	18	20313	31	82416
6	23647	19	20929	33	70370
7	7032	20	42934	35	62256
8	6701	21	11507	37	59370
9	3491	22	14689	39	46873
10	8655	23	44445	41	72616
11	13318	24	31139		
12	10852	25	26487		

D Fixed standard word

The following two lines concatenate to the chosen 104-letter reference:

```
RRLLLLRLRRRRLRRRRLLLLRLRRRRLRLLRRLLLLRRLLRRRRLLRRLRL
LRLLRLRLLRRRRLLRLLRRRRLLRRRRLLRLRRRRLRLLLLRRRRLRRLRR
```

The companion control reproduces the complete blank-plane state after 9977 updates, with 715 black cells and pose $(-15, 10), W$. Its next 104 letters are a cyclic phase of this word; both all-future checks certify that phase on the complete state. Thus "standard" is fixed by the classical blank reference, not by the number 104 alone. The word is primitive by a direct finite shift test.

References

[1] A. Gajardo, A. Moreira and E. Goles, "Complexity of Langton's ant," *Discrete Applied Mathematics* 117 (2002), 41–50. doi:10.1016/S0166-218X(00)00334-6.

[2] K. R. Etse, "How Long Can The Escaping Ant Be Confined?," *MFCS 2026*, LIPIcs 386, 49:1–49:17. doi:10.4230/LIPIcs.MFCS.2026.49.

[3] A. Jillhewar, "Finite-Support Periodic Highways of Langton's Ant: Necessary Conditions, Transverse Exclusions, and Exact Search," Paper bundled with the software/source archive, version 1.3 (31 July 2026), Section 3, "A constructive periodic-realisability criterion," theorem "Periodic-realisability criterion." doi:10.5281/zenodo.21716510.

[4] H. Ke, "Every One-Black-Cell Langton Ant Reaches the Period-104 Highway: A Lean-Checked Proof," Zenodo, version 0.2.0 (2026). doi:10.5281/zenodo.23341609.

[5] H. Ke, "An Ant on the Clock: Exponential Escape Bounds for Langton's Ant," Zenodo, version 0.4.0 (2026). doi:10.5281/zenodo.23402379.

[6] A. Gajardo, "A symbolic projection of Langton's Ant (Extended Abstract)," DMTCS Proceedings AB (2003), 57–68. doi:10.46298/dmtcs.2312.

[7] Integer Set Library, *Manual*, Sets and Relations. https://libisl.sourceforge.io/user.html.