



HikCentral Professional Video jsDecoder SDK

Developer Guide

Legal Information

About this Document

- This Document includes instructions for using and managing the Product. Pictures, charts, images and all other information hereinafter are for description and explanation only. Unless otherwise agreed, our company makes no warranties, express or implied.
- Please use this Document with the guidance and assistance of professionals trained in supporting the Product.

Trademarks Acknowledgment

All trademarks and logos mentioned are the properties of their respective owners.

LEGAL DISCLAIMER

- TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THIS DOCUMENT AND THE PRODUCT DESCRIBED, WITH ITS HARDWARE, SOFTWARE AND FIRMWARE, ARE PROVIDED "AS IS" AND "WITH ALL FAULTS AND ERRORS". OUR COMPANY MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY, SATISFACTORY QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. THE USE OF THE PRODUCT BY YOU IS AT YOUR OWN RISK. IN NO EVENT WILL OUR COMPANY BE LIABLE TO YOU FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR INDIRECT DAMAGES, INCLUDING, AMONG OTHERS, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, OR LOSS OF DATA, CORRUPTION OF SYSTEMS, OR LOSS OF DOCUMENTATION, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), PRODUCT LIABILITY, OR OTHERWISE, IN CONNECTION WITH THE USE OF THE PRODUCT, EVEN IF OUR COMPANY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR LOSS.
- YOU ACKNOWLEDGE THAT THE NATURE OF THE INTERNET PROVIDES FOR INHERENT SECURITY RISKS, AND OUR COMPANY SHALL NOT TAKE ANY RESPONSIBILITIES FOR ABNORMAL OPERATION, PRIVACY LEAKAGE OR OTHER DAMAGES RESULTING FROM CYBER-ATTACK, HACKER ATTACK, VIRUS INFECTION, OR OTHER INTERNET SECURITY RISKS; HOWEVER, OUR COMPANY WILL PROVIDE TIMELY TECHNICAL SUPPORT IF REQUIRED.
- YOU AGREE TO USE THIS PRODUCT IN COMPLIANCE WITH ALL APPLICABLE LAWS, AND YOU ARE SOLELY RESPONSIBLE FOR ENSURING THAT YOUR USE CONFORMS TO THE APPLICABLE LAW. ESPECIALLY, YOU ARE RESPONSIBLE, FOR USING THIS PRODUCT IN A MANNER THAT DOES NOT INFRINGE ON THE RIGHTS OF THIRD PARTIES, INCLUDING WITHOUT LIMITATION, RIGHTS OF PUBLICITY, INTELLECTUAL PROPERTY RIGHTS, OR DATA PROTECTION AND OTHER PRIVACY RIGHTS. YOU SHALL NOT USE THIS PRODUCT FOR ANY PROHIBITED END-USES, INCLUDING THE DEVELOPMENT OR PRODUCTION OF WEAPONS OF MASS DESTRUCTION, THE DEVELOPMENT OR PRODUCTION OF CHEMICAL OR BIOLOGICAL WEAPONS, ANY ACTIVITIES IN THE CONTEXT

RELATED TO ANY NUCLEAR EXPLOSIVE OR UNSAFE NUCLEAR FUEL-CYCLE, OR IN SUPPORT OF HUMAN RIGHTS ABUSES.

- IN THE EVENT OF ANY CONFLICTS BETWEEN THIS DOCUMENT AND THE APPLICABLE LAW, THE LATTER PREVAILS.

Contents

Chapter 1 Overview	1
1.1 Introduction	1
1.2 Runtime Environment	1
1.3 Terms and Definitions	1
1.4 Components and Constraints	1
1.5 Update History	4
Chapter 2 API Reference	5
2.1 JSPlugin	5
2.2 JS_ArrangeWindow	6
2.3 JS_CapturePicture	6
2.4 JS_CloseSound	7
2.5 JS_Disable3DZoom	8
2.6 JS_DisableZoom	8
2.7 JS_Enable3DZoom	9
2.8 JS_EnableZoom	10
2.9 JS_Fast	10
2.10 JS_FrameForward	11
2.11 JS_FullScreenDisplay	12
2.12 JS_FullScreenSingle	12
2.13 JS_GetOSDTime	13
2.14 JS_GetVolume	14
2.15 JS_OpenSound	14
2.16 JS_Pause	15
2.17 JS_Play	16
2.18 JS_Resize	17
2.19 JS_Resume	18

2.20 JS_Seek	18
2.21 JS_SelectWnd	19
2.22 JS_SetSecretKey	20
2.23 JS_SetVolume	20
2.24 JS_Slow	21
2.25 JS_StartSave	22
2.26 JS_StartTalk	22
2.27 JS_Stop	23
2.28 JS_StopRealPlayAll	24
2.29 JS_StopSave	24
2.30 JS_StopTalk	25
2.31 JS_TalkSetVolume	25
Appendix A. Appendixes	27
A.1 Sample Code of Starting Live View via jsDecoder SDK	27
A.2 Dependencies between OpenAPI and jsDecoder SDK	28

Chapter 1 Overview

1.1 Introduction

The jsDecoder SDK is a software development kit that provides APIs and a no plug-in solution to start live view and playback of device via the web browser.

1.2 Runtime Environment

Operating System

* Windows 7/8/10 (32-bit or 64-bit)

Web Browser

- Mozilla * with Version 52 or Above
- Google * with Version 45 or Above

1.3 Terms and Definitions

DIV Window

The window without popping up on the browser page , which is marked with "DIV".

Display Window

Sub window of DIV window, whose size varies with that of DIV window.

1.4 Components and Constraints

Components

Component	File Name
jsDecoder Folder	AudioRenderer.js
	Decoder.js
	Decoder.wasm
	DecodeWorker.js
	SuperRender_10.js
	SuperRender_20.js
	systemTransform-worker.min.js

Component	File Name
	SystemTransform.js
	SystemTransform.js.mem
	cryptio.min.js
	jquery-1.12.1.min.js
	jquery.cookie.js
	jsPlugin-1.2.0.min.js
	uuid.js
	polyfill2.js
demo.html	\

Constraints

Functions	jsDecoder 1.X	jsDecoder 2.X
Protocol	Supports HTTP and HTTPS.	Supports HTTPS.
Live View	- The maximum resolution of videos that can be decoded is 1080P. - When the video resolution is 1080P, only one channel's decoding is Supported. The decoding time duration of 1080P video is 22 ms, and the rendering time duration is 9 ms. - When the video resolution is CIF, it Supportss four channels' decoding.	Supports video encoding format (H. 264 and H.256) and audio encoding format (AAC, AACLD, ADPCM, G711, G722_1, G726, MP2, and Opus). Refer to <i>Table 1-1</i> for details.
Capture	Supports	Supports
Digital Zoom	Supports	Supports
Window Division	Supports	Supports
Full Screen	Supports	Supports
Two-Way Audio	Not Supports	Supports

Functions	jsDecoder 1.X	jsDecoder 2.X
Playback	- The maximum resolution of videos that can be decoded is 1080P. - When the video resolution is 1080P, only one channel's decoding is Supported. The decoding time duration of 1080P video is 22 ms, and the rendering time duration is 9 ms. - When the video resolution is CIF, it Supports four channels' decoding.	Supports video encoding format (H. 264 and H.256) and audio encoding format (AAC, AACLD, ADPCM, G711, G722_1, G726, MP2, and Opus). Refer to <i>Table 1-1</i> for details.
Fast/Slow Forward	Supports 4× and ¼× speed	Supports 4× and ¼× speed
Reverse Playback	Not Supports	Not Supports
Transcoding Playback	Supports	Supports
Single Frame	Supports	Supports
Recording	Only Supported by Google Chrome (with virtual file system).	Supports
Draw on Video	Supports	Supports
Counting Statistics, Dynamic Health Monitoring, and Other Private Information Processing	Not Supports	Not Supports
Synchronous Playback	Not Supports	Not Supports

Table 1-1 Video Encoding Format

Video Encoding Format	Resolution	Video Parameter (Bps*Fps)	Decoding Channel (Operating System: Windows 7)	Decoding Channel (Operating System: Windows 7)	Decoding Channel (Operating System: Windows 7)
/	/	/	CPU: I7_8700K Graphic Card: RTX2080	CPU: I5-9400/F Graphic Card: GTX1050TI	CPU: I3-8100 Graphic Card: GT1030D5
H265	1080P	4M*25	6	4	3
H265	720P	2M*25	14	10	6
H264	1080P	4M*25	6	4	3
H264	720P	2M*25	14	10	6

1.5 Update History

Summary of Changes in Version 2.3_Jun., 2022

1. Supports more video encoding format (H.264 and H.256) and audio encoding format (AAC, AACLD, ADPCM, G711, G722_1, G726, MP2, and Opus).
Supports more channels (6 channels for 1080P and 14 channels for 720P) and smoother picture ((Bps*Fps)=4M*25).
2. Supports two-way audio.

Summary of Changes in Version 1.0_Sept., 2019

New document.

Chapter 2 API Reference

2.1 JSPlugin

Create the plug-in.

Prerequisite

The jsPlugin-1.0.0.min.js has been loaded in the web page.

API Definition

None.

Parameters

Parameter Name	Required or Optional	Description
[IN] szId	Required	A container to create the plug-in. For example, <div id=" playWind"> , that is, creating plug-in in the .
[IN] iType	Required	Plug-in type: 0-no video display window; 1-with video display window.
[IN] iWidth	Required	Width of the created plug-in.
[IN] iHeight	Required	Height of the created plug-in.
[IN] iMaxSplit	Required	Maximum number of window divisions supported by the created plug-in.
[IN] iCurrentSplit	Required	Default number of window divisions after creating the plug-in.
[IN] szBasePath	Required	Basic path for saving the file jsPlugin-1.0.0.min.js, which is relative to the root directory of web server.

Return Value

None.

Example

Sample Code of Creating Plug-in

```
var oJSPlugin = new JSPlugin({
  szId: "playWind",
  iType: 1,
  iWidth: 600,
```

```
iHeight: 400,  
iMaxSplit: 4,  
iCurrentSplit: 1,  
szBasePath: "../dist"  
});
```

2.2 JS_ArrangeWindow

Set the number of sub windows for the display window, that is, set the window division mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_ArrangeWindow(  
    iWndType  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndType	Required	Window division modes: 1 (1-window division); 2 (4-window division); 3 (9-window division), 4 (16-window division).

Return Value

None.

Example

Sample Code of Setting Window Division Mode

```
oJSPlugin.JS_ArrangeWindow(4);
```

2.3 JS_CapturePicture

Start capturing picture.

Prerequisite

The plug-in has been created.

API Definition

```
JS_CapturePicture (  
    iWndNum,  
    szPictureName,  
    szType  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szPictureName	Required	Capture file name.
[IN] szType	Optional	Picture formats: BMP, JPG, JPEG. The default format is JPG.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Stating Capturing Picture

```
oJSPlugin.JS_CapturePicture (0,'img','jpg');
```

2.4 JS_CloseSound

Turn off audio.

Prerequisite

The plug-in has been created.

API Definition

```
JS_CloseSound (  
)
```

Parameters

None.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Turning Off Audio

```
oJSPlugin.JS_CloseSound ();
```

2.5 JS_Disable3DZoom

Disable 3D positioning.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Disable3DZoom (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Disabling 3D Positioning

```
oJSPlugin.JS_Disable3DZoom (0);
```

2.6 JS_DisableZoom

Disable digital zoom.

Prerequisite

The plug-in has been created.

API Definition

```
JS_DisableZoom (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

None.

Example

Sample Code of Enabling Digital Zoom

```
oJSPlugin.JS_DisableZoom (0);
```

2.7 JS_Enable3DZoom

Enable 3D positioning.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Enable3DZoom (  
    iWndNum,  
    fCallback  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] fCallback	Required	Drawing callback. After calling this callback function, you can start drawing rectangle frame on the video image and get the frame information via this callback function when the frame is drawn.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Enabling 3D Positioning

```
oJSPlugin.JS_Enable3DZoom (0, function(){})
```

2.8 JS_EnableZoom

Enable digital zoom.

Prerequisite

The plug-in has been created.

API Definition

```
JS_EnableZoom (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Enabling Digital Zoom

```
oJSPlugin.JS_EnableZoom (0);
```

2.9 JS_Fast

Enable fast forward during playback.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_Fast (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Remarks

The playing speed will be doubled for each time calling this API.

Example

Sample Code of Enabling Fast Forward

```
oJSPlugin.JS_Fast (0);
```

2.10 JS_FrameForward

Start single frame playback.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_FrameForward (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Starting Single Frame Playback

```
oJSPlugin.JS_FrameForward (0);
```

2.11 JS_FullScreenDisplay

Display the plug-in in full screen mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_FullScreenDisplay (  
    bFullScreen  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] bFullScreen	Required	Whether to display in full screen mode: "true"-yes. You can press ESC on the keyboard to exit the full screen mode.

Return Value

None.

Example

Sample Code of Displaying Plug-in in Full Screen Mode

```
oJSPlugin.JS_FullScreenDisplay (true);
```

2.12 JS_FullScreenSingle

Display a single window in full screen mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_FullScreenSingle (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

None.

Example

Sample Code of Displaying a Window in Full Screen Mode

```
oJSPlugin.JS_FullScreenSingle (0);
```

2.13 JS_GetOSDTime

Get the OSD time of video to refresh the time bar during playback.

Prerequisite

The plug-in has been created.

API Definition

```
JS_GetOSDTime (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object. You can get the OSD time (number of seconds from 1970-01-01 00:00:00 to the current time) from the Promise callback.

Example

Sample Code of Getting OSD Time

```
JS_GetOSDTime(0).then(function (iTime) {  
    console.log(iTime); //print the OSD time  
});
```

2.14 JS_GetVolume

Get the volume.

Prerequisite

The plug-in has been created.

API Definition

```
JS_GetVolume (  
    iWndNum,  
    cbCallback  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] cbCallback	Required	Callback parameters, in which the volume value is returned.

Return Value

None.

Example

Sample Code of Getting Volume

```
oJSPlugin. JS_GetVolume(0, function (iVolume){  
    console.log(iVolume); //print the volume value  
});
```

2.15 JS_OpenSound

Turn on audio in exclusive mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_OpenSound (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Turning On Audio

```
oJSPlugin.JS_OpenSound (0);
```

2.16 JS_Pause

Pause playing.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_Pause (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Pausing Playing

```
oJSPlugin.JS_Pause (0);
```

2.17 JS_Play

Start playing.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Play(  
  szURL,  
  oParams,  
  iWndNum,  
  szStartTime,  
  szStopTime  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] szURL	Required	Stream URL. For example, ws://ip:port/101, the 101 refers to the main stream of channel No.1 (the first "1" is the channel No., "01" represents the stream type of main stream, and "02" represents the stream type of sub-stream).
[IN] oParams	Required	Parameter object for authentication when connecting different domains. For example, {session: sessionId}.
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szStartTime	Optional	Start time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.
[IN] szStopTime	Optional	Stop time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.

Return Value

Promise object.

Example

Sample Code of Starting Playing

```
oJSPlugin.JS_Play(
    "ws://10.41.7.235:559/101;",
    {
        playURL: 'file/vag://10.41.7.138:6300/sessions/e7c228b7b360424b86955c734c7772d8?
https=1&range=20190410T010021-20190410T013648', //live view URL
        auth: "admin:wacspzz1", //authentication information
        token: "EAAAAAAQAADV4gVBxl8hE/ZK9jrXVnCGLON+eIJu5YmbmWYLz8sWXJXhnFTxEfex4a+yzAGDdc4=" //token
information
        proxy: "10.5.6.8" //target address of the proxy, which should be configured according to the actual situation
    }, //parameter objects of stream media server
    0,
    "20170620T000000Z",
    "20170620T235900Z"
).then(
    function() {}, //callback when succeeded
    function() {} //callback when failed
);
```

2.18 JS_Resize

Set the width and height of the video plug-in.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Resize (
    iWidth,
    iHeight
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWidth	Required	Width, unit: pixel.
[IN] iHeight	Required	Height, unit: pixel.

Return Value

None.

Example

Sample Code of Setting Plug-in Width and Height

```
oJSPlugin.JS_Resize (400, 600);
```

2.19 JS_Resume

Resume playing.

Prerequisite

- The plug-in has been created.
- The playback has paused or the single frame playback has started.

API Definition

```
JS_Resume (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Resuming Playing

```
oJSPlugin.JS_Resume (0);
```

2.20 JS_Seek

Locate the position in the video to start playback.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Seek(  
    iWndNum,  
    szStartTime,  
    szStopTime  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szStartTime	Optional	Start time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.
[IN] szStopTime	Optional	Stop time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.

Return Value

Promise object.

Example

Sample Code of Positing to Start Playback

```
oJSPlugin.JS_Seek (0, "20170620T000000Z", "20170620T235900Z");
```

2.21 JS_SelectWnd

Select the display window.

Prerequisite

The plug-in has been created.

API Definition

```
JS_SelectWnd (
    iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return 0 for success and -1 for failure.

Example

Sample Code of Selecting Display Window

```
oJSPlugin.JS_SelectWnd (0);
```

2.22 JS_SetSecretKey

Set stream key.

Prerequisite

The plug-in has been created.

API Definition

```
JS_SetSecretKey (  
    iKeyType  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iKeyType	Required	Encryption types: 0-not encrypt; 1-encrypt by AES algorithm.

Return Value

None.

Example

Sample Code of Setting Stream Key

```
oJSPlugin.JS_SetSecretKey(4);
```

2.23 JS_SetVolume

Set the volume.

Prerequisite

The plug-in has been created.

API Definition

```
JS_SetVolume (  
    iWndNum,
```

```
iVolume  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] iVolume	Required	Volume value, which ranges from 0 to 100.

Return Value

None.

Example

Sample Code of Setting Volume

```
oJSPlugin.JS_SetVolume (0, 60);
```

2.24 JS_Slow

Enable slow forward during playback.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_Slow (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Remarks

The playing speed will be halved for each time calling this API.

Example

Sample Code of Enabling Slow Forward

```
oJSPlugin.JS_Slow (0);
```

2.25 JS_StartSave

Start recording.

Prerequisite

The plug-in has been created.

API Definition

```
JS_StartSave (  
    iWndNum,  
    szFileName  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szFileName	Required	Video file name, the default file suffix is .mp4.

Return Value

Promise object.

Example

Sample Code of Starting Recording

```
oJSPlugin.JS_StartSave (0, "10.17.137.229_01_20170101000000.mp4");
```

2.26 JS_StartTalk

Start two-way audio.

Prerequisite

The plug-in has been created.

API Definition

```
JS_StartTalk (  
  talkUrl  
)
```

Parameters

Parameter Name	Required or Optional	Description
talkUrl	Required	URL for two-way audio.

Return Value

Promise object.

Example

Sample Code of Starting Two-Way Audio

```
oJSPlugin.JS_StartTalk (wss://10.2.145.66:655/EUrl/CLJ52BW);
```

2.27 JS_Stop

Stop playing.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Stop (  
  iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Stopping Playing

```
oJSPlugin.JS_Stop (0);
```

2.28 JS_StopRealPlayAll

Stop the live view of all windows.

Prerequisite

The plug-in has been created.

API Definition

None.

Parameters

None.

Return Value

None.

Example

Sample Code of Stopping Live View of All Windows

```
oJSPlugin.JS_StopRealPlayAll ();
```

2.29 JS_StopSave

Stop recording.

Prerequisite

The plug-in has been created.

API Definition

```
JS_StopSave (  
    iWndNum  
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Stopping Recording

```
oJSPlugin.JS_StopSave (0);
```

2.30 JS_StopTalk

Stop two-way audio.

Prerequisite

The plug-in has been created.

Return Value

Promise object.

Example

Sample Code of Stopping Two-Way Audio

```
oJSPlugin.JS_StopTalk ();
```

2.31 JS_TalkSetVolume

Set volume of two-way audio.

Prerequisite

The plug-in has been created.

API Definition

```
JS_TalkSetVolume (  
    volume  
)
```

Parameters

Parameter Name	Required or Optional	Description
volume	Required	The volume of two-way audio, which ranges from 0 to 100.

Return Value

Promise object.

Example

Sample Code of Setting Volume of Two-Way Audio

```
oJSPlugin.JS_TalkSetVolume (50);
```

Appendix A. Appendixes

A.1 Sample Code of Starting Live View via jsDecoder SDK

The following contents show the sample code of starting live view via jsDecoder SDK. For more details, refer to `demo_window_simple_preview.html`.

For high performance, the following 3 request headers should be added when the web resource is returned by server:

`add_header Cross-Origin-Embedder-Policy require-corp;`

`add_header Cross-Origin-Opener-Policy same-origin;`

`add_header Cross-Origin-Resource-Policy cross-origin;`

Reference JS File

```
<script src="jsDecoder/polyfill2.js"></script>
<script src="jsDecoder/jsPlugin-1.2.0.min.js"></script>
<script src="jsDecoder/jquery-1.12.1.min.js"></script>
<script src="jsDecoder/jquery.cookie.js"></script>
<script src="jsDecoder/cryptico.min.js"></script>
<script src="jsDecoder/uuid.js"></script>
```

Create jsDecoder Instance

```
//Initialize the plug-in
var jsDecoder = new JSPlugin({
  szId: "playWind",
  iType: 2,
  iWidth: 600,
  iHeight: 400,
  iMaxSplit: 4,
  iCurrentSplit: 2,
  szBasePath: "./dist",
  oStyle: {
    border: "#343434",
    borderSelect: "red",
    background: "#4C4B4B"
  }
});
```

Start Live View

```
jsDecoder.JS_Play(url, {
  playURL: playUrl, //Stream URL for live view
  auth: deviceUser + ":" + devicePassword, //Authentication information, i.e., user name and password of device
  token: token
}, iWind).then(function() {
  console.log("realplay success");
```

```
},function () {  
  console.log("realplay failed");  
});
```

A.2 Dependencies between OpenAPI and jsDecoder SDK

OpenAPI Name	Function of Video jsDecoder SDK
Get camera information by No.: /api/resource/v1/cameras/indexCode	Live view and playback
Get information of a decoding device: /api/resource/v1/encodeDevice/indexCode/encodeDeviceInfo	Live view and playback (search for device information to get access protocol type)
Get live view stream URL of camera: /api/video/v1/cameras/previewURLs	Live view
Get playback stream URL of camera: /api/video/v1/cameras/playbackURLs	Playback

