SIM-01 conventional-band definitions (derived)

Derived by `tools/sim01_band_definitions.py` from `results/sim01/20261107T203522Z_d64d297c_8043684/tables/thresholds_summary.csv`. No experimental result was recomputed or altered. Frequencies in Hz; ambiguity level -3 dB.

- **Median band**: from the median f_SL to the median f_amb over the steering set (a typical direction).
- **As reported (Rev 0)**: median f_SL to the earliest f_amb. This mixed convention was used in the SIM-01 Rev 0 report and is neither typical nor guaranteed.
- **Guaranteed band**: from the latest f_SL to the earliest f_amb, so that every steering direction in the set has a closed mainlobe and no -3 dB ambiguity lobe. Empty when latest f_SL >= earliest f_amb.

ID	Steering set	Median band	Ratio	As reported (Rev 0)	Ratio	Guaranteed band	Ratio
A0	horizon	none (no pattern)	n/a	none	n/a	none	n/a
A1	horizon	1,465 to 5,192	3.54	1,465 to 4,432	3.03	2,501 to 4,432	1.77
A2	horizon	733 to 2,596	3.54	733 to 2,216	3.03	1,251 to 2,216	1.77
A3	horizon	1,306 to 2,010	1.54	1,306 to 1,877	1.44	1,465 to 1,877	1.28
A4	horizon	527 to 717	1.36	527 to 623	1.18	586 to 623	1.06
A0	depressed30	none (no pattern)	n/a	none	n/a	none	n/a
A1	depressed30	1,551 to 5,500	3.55	1,551 to 4,751	3.06	2,501 to 4,751	1.90
A2	depressed30	776 to 2,750	3.55	776 to 2,376	3.06	1,251 to 2,376	1.90
A3	depressed30	1,395 to 2,138	1.53	1,395 to 2,011	1.44	1,551 to 2,011	1.30
A4	depressed30	526 to 731	1.39	526 to 608	1.16	empty	n/a

Steering sets: horizon ring (el = 0 deg) and depressed ring (el = -30 deg), 24 azimuths each at 15 deg spacing. 'Guaranteed' applies only to these sampled directions and to the idealized model.