

Keith R. Bennett's Technical Blog

About

Mailing Files Programmatically with GMail

By [keithrbennett](#) on July 25th, 2012

Recently I had the need to send someone multiple 1-2 MB files. Email was the best option, for reasons that are not very interesting, and outside the scope of this article.

I naturally turned to my favorite language, Ruby. I did a little research into the various gems and their configuration, and offer this simple example (source code below) in the hope that it will save you a little time if you have the same need.

I've tried to trim out anything not relating to the actual sending of the mail so that you can more easily understand it and adapt it for your use.

– Keith

```
1  #!/usr/bin/env ruby
2  # Mails a file using GMail's SMTP Server.
3  # For illustrative purposes; error checking and testing
4  #
5  # Requirements:
6  #   1) the 'mail' gem must be installed
7  #   2) a file named 'pw.txt' containing the Google passw
8  #       in the current directory.
9  #
10 # Ruby versions: tested on 1.9.3, 1.8.7, JRuby
11 #
12 # Keith Bennett
13
14 require 'rubygems' # Need this for Ruby 1.8
15 require 'mail'
16
```

```
17
18 ATTACHMENT_FILESPEC = 'attachment.txt'
19 File.open(ATTACHMENT_FILESPEC, 'w') do |file|
20   file << "Sample attachment text file, sent #{Time.now}"
21 end
22
23
24 # Used for GMail authentication and the 'from' header field
25 def my_gmail_address
26   # Return your gmail address, e.g.:
27   'me@gmail.com'
28 end
29
30
31 # Used for 'to' header field
32 def recipients
33   # a single address or a comma separated list of email
34   'mom@aol.com,fred@people.com'
35 end
36
37
38 # GMail password for SMTP authentication.
39 # Create a file named 'pw.txt' and put your password there
40 # Not the best way to do this!
41 def password
42   File.read('pw.txt')
43 end
44
45
46 def body_text
47   "This message contains the following attachment: #{ATTACHMENT_FILESPEC}"
48 end
49
50
51 def subject_text
52   "Gmail-It Attached File: #{ATTACHMENT_FILESPEC}"
53 end
54
55
56 # This information could probably be put in the Mail.defaults
57 # but it's here in case multiple mail calls are made.
58 Mail.defaults do
59   delivery_method :smtp, {
60     :address      => "smtp.gmail.com",
61     :port         => 587,
62     :domain       => 'gmail.com',
63     :user_name    => my_gmail_address,
64     :password     => password,
65     :enable_starttls_auto => true }
```

```
66 end
67
68 puts "Delivering file: #{ATTACHMENT_FILESPEC} to #{recip
69
70 Mail.deliver do
71   from      my_gmail_address
72   to        recipients
73   subject   subject_text
74   body      body_text
75   add_file  ATTACHMENT_FILESPEC
76 end
77
78 puts "File #{ATTACHMENT_FILESPEC} sent."
79 puts "Check recipient email account(s) (#{recipients}) t
```

mail-using-gmail.rb hosted with ❤ by GitHub

[view raw](#)Categorized under: [Uncategorized](#).

Tagged with: no tags.

Leave a Response

You must be [logged in](#) to post a comment.[← class_eval, instance_eval, eval](#)[JRuby Presentation, Northern Virginia Ruby User Group](#)[→](#)

META

- [Register](#)
- [Log in](#)
- [Entries RSS](#)
- [Comments RSS](#)
- [WordPress.org](#)

ARCHIVES

- November 2015
- November 2013
- August 2013
- January 2013
- December 2012
- November 2012
- September 2012
- July 2012
- January 2012
- June 2011
- May 2011
- March 2010
- July 2009
- March 2009
- February 2009
- November 2008

RECENT ACTIVITY

Posts

Comments

- The Case for Nested Methods in Ruby
- Ruby's inject/reduce and each_with_object
- 🍏 in Your System Prompt
- Using Oracle in JRuby with Rails and Sequel
- Copying (RVM) Data Between Hosts Using ssh, scp, and netcat
- Building A Great Ruby Development Environment and Desktop with Linux Mint 13 "Maya" Mate
- Intro to Functional Programming in Ruby
- WordPress Administration with Ruby
- Stealth Conditionals in Ruby
- Hello, Nailgun; Goodbye, JVM Startup Delays

ARCHIVES

Categories

Tags

Dates

