failed to send CA Event for app launch measurements for ca_event_type. 1
event_name: com.apple.app_launch_measurement.ExtendedLaunchMetrics

My name is Keith Wood and I attend FAU.
I am currently in my First year and I own 9 dogs.
It is true that I want more pets.

Lab0
main

Running Lab0 on iPhone 16

Main (Base)   ViewCont

Lab0 ⟩ Lab0 ⟩ Main ⟩ Main (Base) ⟩ No Se

Lab0
  Lab0
    AppDelegate
    Assets   M
    Info
    Main   M
    SceneDelegate
    ViewController M

View Controller Sc...

iPhone 16
iOS 18.6

10:39

First   Keith

Last   Wood

School   FAU

First   Second   Third   Fourth

Fourth

Pets   9   —   +

—   +

More Pets   ⬤

⬤

Introduce Self

Filter

Auto

to send CA Event for app launch measurements for ca_event_type: 1
name: com.apple.app_launch_measurement.ExtendedLaunchMetrics
e is Keith Wood and I attend FAU.
urrently in my First year and I own 9 dogs.
true that I want more pets.

```swift
class ViewController: UIViewController {

    @IBOutlet weak var numberOfPets: UILabel!

    @IBOutlet weak var morePetsStepper: UIStepper!

    @IBOutlet weak var morePetsSwitch: UISwitch!


    @IBAction func stepperDidChange(_ sender: UIStepper) {

        numberOfPets.text = "\(Int(sender.value))"    Show Issues
    }



    @IBAction func introduceSelfDidTapped(_ sender: UIButton) {

            // Lets us choose the title we have selected from the segmented control
            // In our example that is whether it is first, second, third or forth
            let year = yearSegmentedControl.titleForSegment(at: yearSegmentedControl.selectedSegmentIndex)

            // Creating a constant of type string that holds an introduction. The introduction receives the values from the outlet
                connections.
            let introduction = """
            My name is \(firstNameTextField.text!) \(lastNameTextField.text!) and I attend \(schoolNameTextField.text!).
            I am currently in my \(year!) year and I own \(numberOfPets.text!) dogs.
            It is \(morePetsSwitch.isOn) that I want more pets.
            """

            print(introduction)
    }



    override func viewDidLoad() {
        super.viewDidLoad()
        // Do any additional setup after loading the view.
    }

}
```

Lab0
main

Lab0) iPhone 16   Running Lab0 on iPhone 16   ⚠ 8

Main (Base)   ViewController

Lab0) Lab0) ViewController) M introduceSelfDidTapped(_:)

- Lab0
  - Lab0
    - AppDelegate
    - Assets   M
    - Info
    - Main   M
    - SceneDelegate
    - ViewController M

```swift
//
//  ViewController.swift
//  Lab0
//
//  Created by Keith Wood on 8/18/25.
//

import UIKit

class ViewController: UIViewController {

    @IBOutlet weak var firstNameTextField: UITextField!

    @IBOutlet weak var lastNameTextField: UITextField!

    @IBOutlet weak var schoolNameTextField: UITextField!

    @IBOutlet weak var yearSegmentedControl: UISegmentedControl!

    @IBOutlet weak var numberOfPets: UILabel!

    @IBOutlet weak var morePetsStepper: UIStepper!

    @IBOutlet weak var morePetsSwitch: UISwitch!


    @IBAction func stepperDidChange(_ sender: UIStepper) {

        numberOfPets.text = "\(Int(sender.value))"
    }


    @IBAction func introduceSelfDidTapped(_ sender: UIButton) {

            // Lets us choose the title we have selected from the segmented control
            // In our example that is whether it is first, second, third or forth
            let year = yearSegmentedControl.titleForSegment(at: yearSegmentedControl.selectedSegmentIndex)

            // Creating a constant of type string that holds an introduction. The introduction receives the values from the outlet
                connections.
            let introduction = """
```

Filter

Lab0

Line: 42 Col: 72