Table of Contents

Introduction	1.1
Show help message and version	1.2
Redirect strace's output to file	1.3
Attach to running processes	1.4
Trace child processes	1.5
Detach process on execve syscall	1.6
Detach strace and tracee processes	1.7
Show statistics of system calls	1.8
Customize tracing event behavior	1.9
Change environment variables' values	1.10
Run command as other user	1.11
Set output format of naming constant	1.12
Customize string output	1.13
Print instruction pointer	1.14
Handle signals	1.15
Show file descriptor related information	1.16
Show timestamp of system call	1.17
Show time spent in each system call	1.18
Print stack trace of every system call	1.19
Trace only system calls accessing path	1.20
Suppress attach/detach/exit status messages	1.21
Display strace's debug information	1.22
Set the overhead for tracing system calls	1.23
Align return value column	1.24
The end	1.25

Strace little book

I like researching debugging techniques, so I decide to write this booklet to introduce strace. The following is the official definition of strace:

strace is a diagnostic, debugging and instructional userspace utility for Linux. It is used to monitor and tamper with interactions between processes and the Linux kernel, which include system calls, signal deliveries, and changes of process state.

System administrators, diagnosticians and trouble-shooters will find it invaluable for solving problems with programs for which the source is not readily available since they do not need to be recompiled in order to trace them.

The operation of strace is made possible by the kernel feature known as ptrace.

In one word, strace helps you know a process's activities between user-space and kernel-space. Let's check a simple example to get first impression of strace:

strace outputs all the syscalls' names, arguments, and return values. Very cool, isn't it? OK, let's begin our journey now.

Show help message

As other *NIX commands, -h option shows a concise help message of strace :

```
# strace -h
usage: strace [-CdffhiqrtttTvVwxxy] [-I n] [-e expr]...
              [-a column] [-o file] [-s strsize] [-P path]...
              -p pid... / [-D] [-E var=val]... [-u username] PRO
G [ARGS]
  or: strace -c[dfw] [-I n] [-e expr]... [-0 overhead] [-S sort
by]
              -p pid... / [-D] [-E var=val]... [-u username] PRO
G [ARGS]
Output format:
  -a column
                 alignment COLUMN for printing syscall results (
default 40)
  -i
                 print instruction pointer at time of syscall
                 obtain stack trace between each syscall
  -k
```

-v shows version:

```
# strace -V
strace -- version 4.26
Copyright (c) 1991-2018 The strace developers <https://strace.io
>.
This is free software; see the source for copying conditions. T
here is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICUL
AR PURPOSE.

Optional features enabled: stack-trace=libunwind stack-demangle
m32-mpers mx32-mpers
```

Show help message and version		

Redirect strace's output to file

You can use -o option to specify a file which saves strace 's output:

Additionally, -A option can be used to append log to an existing file instead of truncate it:

```
# ls -lth log.txt
-rw-r--r-- 1 root root 3.6K Feb 28 10:07 log.txt
# strace -o log.txt ls
log.txt
# ls -lth log.txt
-rw-r--r-- 1 root root 3.6K Feb 28 10:08 log.txt
# strace -A -o log.txt ls
log.txt
# ls -lth log.txt
-rw-r--r-- 1 root root 7.2K Feb 28 10:08 log.txt
```

Attach to running processes

strace can attach and trace running processes. Check following simple example:

Build and launch two processes:

```
# gcc dead_loop.c -o dead_loop
# ./dead_loop &
[1] 2194
# ./dead_loop &
[2] 2195
```

Use -p option to trace one process:

```
# strace -p 2194
strace: Process 2194 attached
restart_syscall(<... resuming interrupted nanosleep ...>) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7ffc037bf730) = 0
.....
```

Use -p option to trace multiple processes:

```
# strace -p 2194,2195
strace: Process 2194 attached
strace: Process 2195 attached
[pid 2194] restart_syscall(<... resuming interrupted nanosleep
...> <unfinished ...>
[pid 2195] restart_syscall(<... resuming interrupted nanosleep
...> <unfinished ...>
[pid 2194] <... restart_syscall resumed> ) = 0
[pid 2194] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
[pid 2195] <... restart_syscall resumed> ) = 0
.....
```

strace can also utilize pidof command to trace processes:

```
# strace -p "`pidof dead_loop`"
strace: Process 2195 attached
strace: Process 2194 attached
[pid 2194] restart_syscall(<... resuming interrupted nanosleep
...> <unfinished ...>
[pid 2195] restart_syscall(<... resuming interrupted nanosleep
...>) = 0
[pid 2195] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
[pid 2194] <... restart_syscall resumed> ) = 0
.....
```

Or use pgrep:

```
# strace -p "`pgrep dead_loop`"
strace: Process 2194 attached
strace: Process 2195 attached
[pid 2195] restart_syscall(<... resuming interrupted nanosleep
...> <unfinished ...>
[pid 2194] restart_syscall(<... resuming interrupted nanosleep
...>) = 0
[pid 2194] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
[pid 2195] <... restart_syscall resumed> ) = 0
[pid 2195] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
.....
```

Trace child processes

Check following code:

```
# cat fork.c
#include <sys/types.h>
#include <unistd.h>
int main(void)
{
        int pid = fork();
        if (pid < 0)
        {
                 return 1;
        }
        else
        {
                 while (1)
                         sleep(1);
                 }
        return 0;
}
```

By default, strace won't trace child processes spawned by fork , vfork and clone :

```
fstat(3, {st mode=S IFREG|0644, st size=98317, ...}) = 0
mmap(NULL, 98317, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7f045e508000
close(3)
openat(AT_FDCWD, "/usr/lib/libc.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\3\0>\0\1\0\0\0000C\2\0\
0 \setminus 0 \setminus 0 \setminus 0"..., 832) = 832
lseek(3, 792, SEEK_SET)
                                         = 792
read(3, "\4\0\0\0\24\0\0\0\3\0\0GNU\0\201\336\t\36\251c\324\23
3E\371SoK\5H\334"..., 68) = 68
fstat(3, {st_mode=S_IFREG|0755, st_size=2136840, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS
(-1, 0) = 0x7f045e506000
lseek(3, 792, SEEK_SET)
                                         = 792
read(3, "\4\0\0\0\24\0\0\0\3\0\0GNU\0\201\336\t\36\251c\324\23
3E\371SoK\5H\334"..., 68) = 68
lseek(3, 864, SEEK_SET)
                                         = 864
read(3, "\4\0\0\0\20\0\0\5\0\0\0GNU\0\2\0\0\300\4\0\0\0\3\0\0\
0\0\0\0\0, 32) = 32
mmap(NULL, 1848896, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0)
= 0x7f045e342000
mprotect(0x7f045e364000, 1671168, PROT_NONE) = 0
mmap(0x7f045e364000, 1355776, PROT_READ|PROT_EXEC, MAP_PRIVATE|M
AP_{FIXED}|MAP_{DENYWRITE}, 3, 0x22000) = 0x7f045e364000
mmap(0x7f045e4af000, 311296, PROT_READ, MAP_PRIVATE|MAP_FIXED|MA
P_DENYWRITE, 3, 0x16d000) = 0x7f045e4af000
mmap(0x7f045e4fc000, 24576, PROT_READ|PROT_WRITE, MAP_PRIVATE|MA
P_FIXED|MAP_DENYWRITE, 3, 0x1b9000) = 0x7f045e4fc000
mmap(0x7f045e502000, 13888, PROT_READ|PROT_WRITE, MAP_PRIVATE|MA
P_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7f045e502000
close(3)
                                         = 0
arch_prctl(ARCH_SET_FS, 0x7f045e507500) = 0
mprotect(0x7f045e4fc000, 16384, PROT_READ) = 0
mprotect(0x556c0647d000, 4096, PROT_READ) = 0
mprotect(0x7f045e54a000, 4096, PROT_READ) = 0
munmap(0x7f045e508000, 98317)
                                         = 0
clone(child_stack=NULL, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_S
ETTID|SIGCHLD, child_tidptr=0x7f045e5077d0) = 5082
nanosleep(\{tv\_sec=1, tv\_nsec=0\}, 0x7ffd59b050d0) = 0
nanosleep(\{tv\_sec=1, tv\_nsec=0\}, 0x7ffd59b050d0) = 0
nanosleep(\{tv\_sec=1, tv\_nsec=0\}, 0x7ffd59b050d0) = 0
```

To trace child processes, -f option need to be specified:

```
# strace -f ./fork
execve("./fork", ["./fork"], 0x7ffcebee9288 /* 21 vars */) = 0
                                         = 0x55d21e20b000
brk(NULL)
arch_prctl(0x3001 /* ARCH_??? */, 0x7ffd52e9e610) = -1 EINVAL (I
nvalid argument)
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such fil
e or directory)
openat(AT_FDCWD, "/etc/ld.so.cache", 0_RDONLY|0_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=98317, ...}) = 0
mmap(NULL, 98317, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7fd7e2fd8000
close(3)
                                         = 0
openat(AT_FDCWD, "/usr/lib/libc.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0000C\2\0\
0 \setminus 0 \setminus 0 \setminus 0"..., 832) = 832
lseek(3, 792, SEEK_SET)
                                         = 792
read(3, "\4\0\0\0\24\0\0\0\3\0\0GNU\0\201\336\t\36\251c\324\23
3E\371SoK\5H\334"..., 68) = 68
fstat(3, {st_mode=S_IFREG|0755, st_size=2136840, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS
, -1, 0) = 0x7fd7e2fd6000
lseek(3, 792, SEEK_SET)
                                         = 792
read(3, "\4\0\0\0\24\0\0\0\3\0\0GNU\0\201\336\t\36\251c\324\23
3E\371SoK\5H\334"..., 68) = 68
lseek(3, 864, SEEK_SET)
                                         = 864
read(3, "\4\0\0\0\20\0\0\5\0\0\0GNU\0\2\0\0\300\4\0\0\0\3\0\0\
0\0\0\0\0, 32) = 32
mmap(NULL, 1848896, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0)
= 0x7fd7e2e12000
mprotect(0x7fd7e2e34000, 1671168, PROT_NONE) = 0
mmap(0x7fd7e2e34000, 1355776, PROT_READ|PROT_EXEC, MAP_PRIVATE|M
AP_FIXED|MAP_DENYWRITE, 3, 0x22000) = 0x7fd7e2e34000
mmap(0x7fd7e2f7f000, 311296, PROT_READ, MAP_PRIVATE|MAP_FIXED|MA
P_DENYWRITE, 3, 0x16d000) = 0x7fd7e2f7f000
```

```
mmap(0x7fd7e2fcc000, 24576, PROT_READ|PROT_WRITE, MAP_PRIVATE|MA
P_FIXED|MAP_DENYWRITE, 3, 0x1b9000) = 0x7fd7e2fcc000
mmap(0x7fd7e2fd2000, 13888, PROT_READ|PROT_WRITE, MAP_PRIVATE|MA
P FIXED|MAP_ANONYMOUS, -1, 0) = 0x7fd7e2fd2000
close(3)
                                        = 0
arch_prctl(ARCH_SET_FS, 0x7fd7e2fd7500) = 0
mprotect(0x7fd7e2fcc000, 16384, PROT_READ) = 0
mprotect(0x55d21d27e000, 4096, PROT_READ) = 0
mprotect(0x7fd7e301a000, 4096, PROT_READ) = 0
munmap(0x7fd7e2fd8000, 98317)
                                        = 0
clone(child_stack=NULL, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_S
ETTID|SIGCHLD, child_tidptr=0x7fd7e2fd77d0) = 5087
strace: Process 5087 attached
     5086] nanosleep({tv_sec=1, tv_nsec=0},
[pid
                                              <unfinished ...>
     5087] nanosleep({tv_sec=1, tv_nsec=0},
                                              <unfinished ...>
[pid
      5086] <... nanosleep resumed> 0x7ffd52e9e5b0) = 0
[pid
     5087] <... nanosleep resumed> 0x7ffd52e9e5b0) = 0
[pid
[pid 5087] nanosleep({tv_sec=1, tv_nsec=0},
                                              <unfinished ...>
[pid 5086] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
. . . . . .
```

Let's see a more complicated case:

```
#include <sys/types.h>
#include <unistd.h>
#include <omp.h>
int main(void)
{
    #pragma omp parallel num_threads(2)
    {
        sleep(30);
        int pid = fork();
        while (1)
        {
            sleep(1);
        }
    }
    return 0;
}
```

Above code will spawn 2 threads, and every thread will fork another child process after waiting 30 seconds:

```
# ./fork &
[1] 5239
# ps -T 5239
PID SPID TTY STAT TIME COMMAND
5239 5239 pts/1 Sl 0:00 ./fork
5239 5240 pts/1 Sl 0:00 ./fork
```

Use any SPID (5239 or 5240 in this case), strace will trace all child processes of threads belong to current process:

```
# strace -p 5239 -f
strace: Process 5239 attached with 2 threads
[pid 5240] restart_syscall(<... resuming interrupted nanosleep</pre>
...> <unfinished ...>
[pid 5239] restart_syscall(<... resuming interrupted nanosleep</pre>
...> <unfinished ...>
[pid 5240] <... restart_syscall resumed> ) = 0
[pid 5239] <... restart_syscall resumed> ) = 0
[pid 5239] clone(child_stack=NULL, flags=CLONE_CHILD_CLEARTID|C
LONE CHILD SETTID|SIGCHLD, child tidptr=0x7f6dd132ced0) = 5245
[pid 5240] futex(0x7f6dd14f47a0, FUTEX_WAIT_PRIVATE, 2, NULL) =
 -1 EAGAIN (Resource temporarily unavailable)
[pid 5240] clone(strace: Process 5245 attached
child_stack=NULL, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_SETTID|
SIGCHLD, child_tidptr=0x7f6dd132b9d0) = 5246
[pid 5240] futex(0x7f6dd14f47a0, FUTEX_WAKE_PRIVATE, 1) = 0
[pid 5240] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
[pid 5239] futex(0x7f6dd14f47a0, FUTEX_WAKE_PRIVATE, 1) = 0
[pid 5239] nanosleep({tv_sec=1, tv_nsec=0}, strace: Process 524
6 attached
 <unfinished ...>
     5246] set_robust_list(0x7f6dd132b9e0, 24) = 0
[pid
[pid 5246] futex(0x7f6dd14f47a0, FUTEX_WAKE_PRIVATE, 1) = 0
[pid 5246] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
[pid 5245] set_robust_list(0x7f6dd132cee0, 24) = 0
[pid 5245] nanosleep({tv_sec=1, tv_nsec=0}, <unfinished ...>
```

Detach process on execve syscall

-b syscall option can be used to instruct strace to detach process when specified syscall is executed. However, currently only execve is supported.

Check following program code (the code is from here):

```
# cat myecho.c
#include <stdio.h>
#include <stdlib.h>
int main(int argc, char *argv[])
{
    int j;
    for (j = 0; j < argc; j++)
       printf("argv[%d]: %s\n", j, argv[j]);
   exit(EXIT_SUCCESS);
}
# cat execve.c
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
int main(int argc, char *argv[])
{
    char *newargv[] = { NULL, "hello", "world", NULL };
    char *newenviron[] = { NULL };
    if (argc != 2) {
        fprintf(stderr, "Usage: %s <file-to-exec>\n", argv[0]);
        exit(EXIT_FAILURE);
    }
    newargv[0] = argv[1];
    execve(argv[1], newargv, newenviron);
    perror("execve"); /* execve() returns only on error */
    exit(EXIT_FAILURE);
}
```

Compile them:

```
# gcc myecho.c -o myecho
# gcc execve.c -o execve
```

Observer the output of using -b:

The log shows that strace detached the process once execve is executed.

-b can be combined use with -f to ignore some insignificant child processes during debugging (please refer Trace child processes section).

Detach strace and tracee processes

-D option is used to detach strace and tracee processes. E.g.:

```
# strace -D ./dead_loop
strace: Process 19816 attached
.....
```

Open another terminal to check the process relationship:

You can see now dead_loop is not child process of strace.

Show statistics of system calls

-c option can be used to summarize the statistics of every system call:

time	seconds	usecs/call	calls	errors	syscall
20.92	0.000050	50	1		munmap
19.25	0.000046	23	2		getdents64
14.64	0.000035	5	6		close
10.46	0.000025	25	1		write
10.46	0.000025	12	2		ioctl
9.21	0.000022	4	5		fstat
9.21	0.000022	7	3		brk
5.86	0.000014	3	4		openat
0.00	0.000000	0	5		read
0.00	0.000000	0	3		lseek
0.00	0.000000	0	12		mmap
0.00	0.000000	0	5		mprotect
0.00	0.000000	0	1	1	access
0.00	0.000000	0	1		execve
0.00	0.000000	0	2	1	arch_prctl

strace shows the time and error count of every system call. Similarly, -c option can print both regular output and statistics:

```
# strace -C ls
execve("/usr/bin/ls", ["ls"], 0x7ffe91857fa8 /* 21 vars */) = 0
brk(NULL)
                                         = 0x555bd69bc000
arch_prctl(0x3001 /* ARCH_??? */, 0x7ffc6ea19940) = -1 EINVAL (I
nvalid argument)
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such fil
e or directory)
openat(AT_FDCWD, "/etc/ld.so.cache", 0_RDONLY|0_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=98317, ...}) = 0
mmap(NULL, 98317, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7fdf81c6f000
. . . . . .
                                         = 0
close(1)
close(2)
                                        = 0
exit_group(0)
                                         = ?
+++ exited with 0 +++
% time
           seconds usecs/call calls
                                            errors syscall
          0.000256
 26.89
                            21
                                      12
                                                    mmap
 13.97
          0.000133
                            33
                                       4
                                                    openat
 11.45
          0.000109
                            21
                                       5
                                                    fstat
          0.000091
 9.56
                            15
                                       6
                                                    close
          0.000076
 7.98
                            15
                                       5
                                                    mprotect
. . . . . .
```

Notice that -c and -c options are mutually exclusive. Please notice the time here measured is system time of every system call. If wall time is required, it is -w option :

```
# strace -w -c ls
project
% time seconds usecs/call calls errors syscall
----
19.85 0.000297 24 12 mmap
17.98 0.000270 269 1 execve
9.32 0.000140 23 6 close
.....
```

There is another -S sortby option to customize histogram output sorted by calls, name and nothing (default is sorted by time). E.g.:

time	seconds	usecs/call	calls	errors	svscall
27.66	0.000164	13	12		mmap
8.26	0.000049	8	6		close
7.76	0.000046	9	5		read
5.40	0.000032	6	5		fstat
13.15	0.000078	15	5		mprotect
5.23	0.000031	7	4		openat
5.23	0.000031	10	3		lseek
4.05	0.000024	8	3		brk
4.05	0.000024	12	2		ioctl
1.69	0.000010	5	2	1	arch_prctl
7.93	0.000047	23	2		getdents64
4.55	0.000027	27	1		write
5.06	0.000030	30	1		munmap
0.00	0.000000	Θ	1	1	access
0.00	0.000000	0	1		execve

Customize tracing event behavior

-e expression is the most complicated option which you use a qualifying expression to denote which events to trace or how to trace them. The format of expression is:

```
[qualifier=][!][?]value1[,[?]value2]...
```

Qualifier can be trace (or t), abbrev (or a), verbose (or v), raw (or x), signal / signals (or s), read / reads (or r), write / writes (or w), fault , inject , or kvm . If no qualifier is specified, trace is the used. E.g., -e open is equal to -e trace=open or -e t=open .

The value part can contain one or more values, and it depends on the qualifier.

E.g., -e t=open,write means only output open and write system calls.

! is used to filter out the specified system call. E.g.:

```
# strace -e trace=\!write ls
```

This won't trace write system call (The ! need to be escaped in bash shell). ? is used to suppress the error. Compare the following outputs:

```
# strace -e trace=op ls
strace: invalid system call 'op'
# strace -e trace=?op ls
project
+++ exited with 0 +++
```

" @64 ", " @32 ", or " @x32 " suffixes can be used to specify system calls only for the 64-bit , 32-bit , or 32-on-64-bit respectively.

The value can also be all or none which mean following all system calls or nothing:

Values for trace qualifier

Below table describes the valid values for trace qualifier (Most are just copied from strace manual):

Value	Meaning
set	Trace the system calls in set. E.g., "strace -e write Is".
/regex	Trace all the system calls which match regular expression. E.g., "strace -e /wr* ls".
%file	Trace all the system calls which take a file name as an argument. It incules open, stat, etc.
%process	Trace all the system calls which involve process management. Such as fork, wait, etc.
%network(or %net)	Trace all the network related system calls.
%signal	Trace all signal related system calls.
%ipc	Trace all IPC related system calls.
%desc	Trace all file descriptor related system calls.
%memory	Trace all memory mapping related system calls.
%stat	Trace stat syscall variants.
%lstat	Trace Istat syscall variants.
%fstat	Trace fstat and fstatat syscall variants.
%%stat	Trace syscalls used for requesting file status (stat, Istat, fstat, fstatat, statx, and their variants).
%statfs	Trace statfs, statfs64, statvfs, osf_statfs, and osf_statfs64 system calls. The same effect can be achieved with -e trace=/^(.*_)?statv?fs regular expression.
%fstatfs	Trace fstatfs, fstatfs64, fstatvfs, osf_fstatfs, and osf_fstatfs64 system calls. The same effect can be achieved with -e trace=/fstatv?fs regular expression.
%%statfs	Trace syscalls related to file system statistics (statfs-like, fstatfs-like, and ustat). The same effect can be achieved with - e trace=/statv?fs fsstat ustat regular expression.
%pure	Trace syscalls that always succeed and have no arguments. Currently, this list includes arc_gettls, getdtablesize, getegid, getegid32, geteuid, geteuid32, getgid, getgid32, getpagesize, getpgrp, getpid, getppid, get_thread_area (on architectures other than x86), gettid, get_tls, getuid, getuid32, getxgid, getxpid, getxuid, kern_features, and metag_get_tls.

To know detailed information about which category a specific system call belongs to, you can refer sysent.h, sysent_shorthand_defs.h, and syscallent.h for your machine (E.g., X86_64 file is here).

abbrev qualifier

abbrev qualifier is used to omit printing each member of large structures. The default value is all . The following example shows how to check environment variables when executing execve system call:

```
# strace -e trace=execve -e abbrev=none ls
execve("/usr/bin/ls", ["ls"], ["SHELL=/bin/bash", "PWD=/root", "
LOGNAME=root", "XDG_SESSION_TYPE=tty", "HOME=/root", "LANG=C", "
SSH_CONNECTION=10.218.195.134 65"..., "XDG_SESSION_CLASS=user",
"TERM=xterm", "USER=root", "SHLVL=1", "XDG_SESSION_ID=19", "XDG_
RUNTIME_DIR=/run/user/0", "SSH_CLIENT=10.218.195.134 65285 "...,
"PATH=/root/.cargo/bin:/usr/local"..., "DBUS_SESSION_BUS_ADDRES
S=unix:pa"..., "HG=/usr/bin/hg", "MAIL=/var/spool/mail/root", "S
SH_TTY=/dev/pts/0", "_=/usr/bin/strace"]) = 0
+++ exited with 0 +++
```

Actually, strace has -v option which just leverages abbrev qualifier (code is here):

```
case 'v':
    qualify("abbrev=none");
    break;
```

verbose qualifier

verbose qualifier is used to instruct whether deference structures of system calls or not. The default value is all . E.g., if you don't want to deference structures of execve , you can do this:

```
# strace -e trace=execve -e verbose=execve ls
execve("/usr/bin/ls", ["ls"], 0x7fffc8641bd0 /* 20 vars */) = 0
+++ exited with 0 +++
```

raw qualifier

raw qualifier is used to print undecoded arguments in hexadecimal format. You can compare the output of access without and with raw qualifier:

```
# strace -e access ls
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such fil
e or directory)
+++ exited with 0 +++
# strace -e access -e raw=access ls
access(0x7f11091183a0, 0x4) = -1 ENOENT (No such fil
e or directory)
+++ exited with 0 +++
```

signal qualifier

By default, strace will capture all signals. signal qualifier can be used to customize which signals should be traced. Check the following code:

Build and run it in one terminal:

```
# gcc dead_loop.c -o dead_loop
# ./dead_loop
```

Use strace to track it in another terminal:

```
# strace -p `pidof dead_loop`
strace: Process 18085 attached
restart_syscall(<... resuming interrupted nanosleep ...>) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7ffd8492c6f0) = 0
.....
```

Press Ctrl+C in first terminal to kill dead_loop process, you will find SIGINT related information is printed out in second terminal:

```
# strace -p `pidof dead_loop`
strace: Process 18085 attached
restart_syscall(<... resuming interrupted nanosleep ...>) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7ffd8492c6f0) = 0
.....
nanosleep({tv_sec=1, tv_nsec=0}, {tv_sec=0, tv_nsec=825212664})
= ? ERESTART_RESTARTBLOCK (Interrupted by signal)
--- SIGINT {si_signo=SIGINT, si_code=SI_KERNEL} ---
+++ killed by SIGINT +++
```

If you ignore SIGINT , the SIGINT won't be showed:

```
# strace -p `pidof dead_loop` -e signal=\!int
strace: Process 18091 attached
restart_syscall(<... resuming interrupted nanosleep ...>) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7ffc92b62710) = 0
nanosleep({tv_sec=1, tv_nsec=0}, {tv_sec=0, tv_nsec=361293365})
= ? ERESTART_RESTARTBLOCK (Interrupted by signal)
```

read and write qualifiers

read / write qualifiers are used to perform a full hexadecimal and ASCII dump of all the data read/write from file descriptors. Check following example:

```
# strace -e read=3 ls
execve("/usr/bin/ls", ["ls"], 0x7ffd0fd7d750 /* 21 vars */) = 0
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\
0 \setminus 0 \setminus 0'' \dots, 832) = 832
 | 00000 7f 45 4c 46 02 01 01 00
                                   00 00 00 00 00 00 00 00
                                                             .ELF
. . . . . . . . . . . . |
 20 20 00 00 00 00 00 00
                                                             ..>.
      . . . . . . |
 00020 40 00 00 00 00 00 00 00
                                   38 52 00 00 00 00 00 00
                                                            @...
....8R..... |
 00030 00 00 00 00 40 00 38 00
                                   09 00 40 00 16 00 15 00
@.8...@.....
 00040 01 00 00 00 04 00 00 00
                                   00 00 00 00 00 00 00 00
. . . . . . . . . . . . |
 00050 00 00 00 00 00 00 00 00
                                   00 00 00 00 00 00 00 00
| 00060 b0 14 00 00 00 00 00 b0 14 00 00 00 00 00
. . . . . . . . . . . . |
. . . . . .
```

inject qualifier

The definition of inject qualifier is like this:

```
-e inject=set[:error=errno|:retval=value][:signal=sig][:syscall=
syscall][:delay_enter=usecs][:delay_exit=usecs][:when=expr]
```

It is used to tamper a specific set of system calls.

:error=errno can set the wrong return value of a system call. E.g.:

```
# strace -e inject=read:error=1 ls
.....
read(3, 0x7ffca47eb418, 832) = -1 EPERM (Operation no
t permitted) (INJECTED)
close(3) = 0
.....
```

:retval=value does the reverse thing: set the correct return value:

Please notice :error=errno and :retval=value are mutually exclusive.

:signal=sig sets which signal will be delivered when entering a system call:

:delay_enter=usecs / :delay_exit=usecs are used to set how many microseconds are delayed before entering/exiting system calls:

```
# strace -e inject=read:delay_enter=10:delay_exit=10 ls
```

:syscall=syscall is used to inject the specified system call, only "pure" system call is allowed now (please refer Values for trace qualifier section).

:when=expr is used to control the frequency of injection. By default every invocation will be injected. The format of the expression is one of the following:

Frequency	Meaning
first	For every syscall from the set, perform an injection for the syscall invocation number first only.
first+	For every syscall from the set, perform injections for the syscall invocation number first and all subsequent invocations.
first+step	For every syscall from the set, perform injections for syscall invocations number first, first+step, first+step+step, and so on.

For example:

The inject takes effect when calling read in the second time.

There are two more tracing events: fault=set[:error=errno][:when=expr] is similar as inject, and kvm=vcpu is used to print exit reason of kvm vcpu (requires kernel version 4.16 or later).

Change environment variables' values

-E option is used to change environment variables' values. Actually, strace just calls putenv() function (code is here). Check following code:

```
# cat env_test.c
#include <stdio.h>
#include <stdlib.h>

int main(void)
{
    char *p = NULL;
    if (p = getenv("HG"))
    {
        printf("HG enviromental variable value is %s\n", p);
    }
    else
    {
            printf("HG enviromental variable value is not set\n");
      }
    return 0;
}
```

Build and run it:

```
# gcc env_test.c -o env_test
# ./env_test
HG enviromental variable value is /usr/bin/hg
```

Set HG to other value:

```
# strace -E "HG=git" ./env_test
.....
write(1, "HG enviromental variable value i"..., 38HG enviromenta
l variable value is git
) = 38
.....
```

Remove HG:

```
# strace -E "HG" ./env_test
.....
write(1, "HG enviromental variable value i"..., 42HG enviromenta
l variable value is not set
) = 42
.....
```

Run command as other user

-u username option can run command as other user, and this option only take effect when executing as root. Check following example:

```
# cat getuid.c
#include <unistd.h>
#include <sys/types.h>
#include <stdio.h>

int main(void)
{
    printf("uid is %d\n", getuid());
    return 0;
}
```

Build and run it as root:

```
# gcc getuid.c -o getuid
# strace ./getuid
execve("./getuid", ["./getuid"], 0x7ffce778f8a0 /* 12 vars */) =
0
brk(NULL) = 0x563fe210a000
.....
write(1, "uid is 0\n", 9uid is 0
) = 9
exit_group(0) = ?
+++ exited with 0 +++
```

It shows uid is 0. Run the program as another user:

This time, uid is 1000.

Set output format of naming constant

By default, strace will decode naming constant (equals to use -X abbrev option):

```
# strace ls
.....
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such fil
e or directory)
.....
```

If raw value is wanted, using -x raw option:

```
# strace -X raw ls
.....
access("/etc/ld.so.preload", 0x4) = -1 ENOENT (No such fil
e or directory)
.....
```

-X verbose outputs both:

```
# strace -X verbose ls
.....
access("/etc/ld.so.preload", 0x4 /* R_OK */) = -1 ENOENT (No suc
h file or directory)
```

Customize string output

-x option makes non-ASCII strings outputted in hexadecimal format (default is octal):

-xx makes all strings outputted in hexadecimal format:

Furthermore, -s strsize changes the maximum print size of string (default value is 32). Compare the following outputs:

(1) Using default value:

```
# strace ls
.....
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\0\0\0\0\0\0\0\..., 832) = 832
......
```

(2) Double the size:

Please note that filenames are not considered strings and are always printed in full.

Print instruction pointer

-i option is used to print instruction pointer of calling system call. E.g.:

Handle signals

-I interruptible option is used to handle signals. The interruptible 's value can be $1 \sim 4$:

Value	Meaning
1	Don't block any signal
2	Block fatal signals while decoding syscall, and this is default behaviour.
3	Block fatal signals, and this is default behaviour when using '-o FILE PROG' option.
4	Block fatal signals and SIGTSTP (^Z), and this is useful when not want '-o FILE PROG' option to stop on ^Z.

The fatal signals include SIGHUP, SIGINT, SIGQUIT, SIGPIPE and SIGTERM. Check following example:

```
# strace -I 1 ./dead_loop
.....
nanosleep({tv_sec=1, tv_nsec=0}, 0x7fff0a0d90f0) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7fff0a0d90f0) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7fff0a0d90f0) = 0
.....
```

Open another terminal and input following command:

```
# kill -s INT `pidof strace`
```

You will find strace process is killed. If you run strace using " -I 3 ", you will find the SIGINT will not take effect when using above command:

```
# kill -s INT `pidof strace`
```

Show file descriptor related information

- -y option can be used to print file path associated with each file descriptor. Compare the following outputs:
- a) Without -y option:

```
# strace ls
.....
openat(AT_FDCWD, "/etc/ld.so.cache", 0_RDONLY|0_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=98309, ...}) = 0
.....
```

b) With -y option:

```
# strace -y ls
.....
openat(AT_FDCWD, "/etc/ld.so.cache", O_RDONLY|O_CLOEXEC) = 3</et
c/ld.so.cache>
fstat(3</etc/ld.so.cache>, {st_mode=S_IFREG|0644, st_size=98309,
...}) = 0
.....
```

Furthermore, -yy option can be used to print protocol specific information associated with socket file descriptors, and block/character device number associated with device file descriptors. Compare following outputs:

a) Without -yy option:

```
# strace ip
.....
socket(AF_NETLINK, SOCK_RAW|SOCK_CLOEXEC, NETLINK_ROUTE) = 3
setsockopt(3, SOL_SOCKET, SO_SNDBUF, [32768], 4) = 0
.....

# strace ls
.....
fstat(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(0x88, 0x1), ...}
) = 0
.....
```

b) With -yy option:

```
# strace -yy ip
......
socket(AF_NETLINK, SOCK_RAW|SOCK_CLOEXEC, NETLINK_ROUTE) = 3<NET
LINK:[29833]>
setsockopt(3<NETLINK:[29833]>, SOL_SOCKET, SO_SNDBUF, [32768], 4
) = 0
.....

# strace -yy ls
.....
fstat(1</dev/pts/1<char 136:1>>, {st_mode=S_IFCHR|0620, st_rdev=
makedev(0x88, 0x1), ...}) = 0
.....
```

Show timestamp of system call

-t option shows the wall clock time of every system call:

```
# strace -t ls
13:20:19 execve("/usr/bin/ls", ["ls"], 0x7fff489a7c98 /* 21 vars
  */) = 0
13:20:19 brk(NULL) = 0x55cd60264000
......
```

-tt option will append microseconds:

```
# strace -tt ls
13:21:07.553038 execve("/usr/bin/ls", ["ls"], 0x7ffc5238f338 /*
21 vars */) = 0
13:21:07.553713 brk(NULL) = 0x559753feb000
......
```

-ttt option prints seconds since epoch time:

```
# strace -ttt ls
1552540937.975302 execve("/usr/bin/ls", ["ls"], 0x7ffdef5c3918 /
* 21 vars */) = 0
1552540937.976413 brk(NULL) = 0x55fe713d8000
......
```

-r option prints a relative timestamp upon entry to each system call. This records the time difference between the beginning of successive system calls:

```
# strace -r ls
0.000000 execve("/usr/bin/ls", ["ls"], 0x7ffc3ad8a5e8 /* 21 vars
  */) = 0
0.000623 brk(NULL) = 0x55cce063d000
0.000172 arch_prctl(0x3001 /* ARCH_??? */, 0x7ffd8e8867d0) = -1
EINVAL (Invalid argument)
......
```

Show time spent in each system call

-T option is used to print time spent in each system call. E.g.:

Print stack trace of every system call

-k option is used to print stack trace of every system call. To enable this option,

ENABLE_STACKTRACE is needed to build strace (code is here). E.g.:

Trace only system calls accessing path

-P path option is used to set only tracing system calls which access the specified path . E.g.:

```
# strace -P /etc/ld.so.preload ls
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such fil
e or directory)
+++ exited with 0 +++
```

Only access system call is tracked.

Suppress attach/detach/exit status messages

- -q option is used to suppress attach/detach process message. Compare following outputs:
- a) Without -q option:

b) With -q option:

```
# strace -q -p 444
restart_syscall(<... resuming interrupted nanosleep ...>) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7ffc026d31c0) = 0
nanosleep({tv_sec=1, tv_nsec=0}, 0x7ffc026d31c0) = 0
nanosleep({tv_sec=1, tv_nsec=0}, ^C <detached ...>
```

- -qq option will also suppress process exit status message. Compare following outputs:
- a) Without -qq option:

```
# strace ls
.....
exit_group(0) = ?
+++ exited with 0 +++
```

b) With -qq option:

```
# strace -qq ls
.....
exit_group(0) = ?
```

Display strace's debug information

-d option can be used to show strace 's own debug information. Check following simple program:

```
# cat fork.c
#include <sys/types.h>
#include <unistd.h>

int main(void)
{
    int pid = fork();
    while (1)
    {
        sleep(1);
    }
    return 0;
}
```

Build and use strace 's -d option to track it:

```
# qcc fork.c -o fork
# strace -d ./fork
strace: ptrace_setoptions = 0x51
strace: PTRACE_GET_SYSCALL_INFO: Input/output error
strace: PTRACE_GET_SYSCALL_INFO does not work
strace: new tcb for pid 583, active tcbs:1
strace: [wait(0x80137f) = 583] WIFSTOPPED, sig=SIGSTOP, EVENT_STOP
 (128)
strace: pid 583 has TCB_STARTUP, initializing it
strace: [wait(0x80057f) = 583] WIFSTOPPED, sig=SIGTRAP, EVENT_STOP
 (128)
strace: [wait(0x00127f) = 583] WIFSTOPPED, sig=SIGCONT
strace: [wait(0x00857f) = 583] WIFSTOPPED, sig=133
execve("./fork", ["./fork"], 0x7ffcc9f68b48 /* 21 vars */strace:
 [wait(0x04057f) = 583] WIFSTOPPED, sig=SIGTRAP, EVENT_EXEC (4)
. . . . . .
strace: [wait(0x00857f) = 583] WIFSTOPPED, sig=133
clone(strace: [wait(0x00857f) = 583] WIFSTOPPED, sig=133
. . . . . .
```

The debug information is interleaved with normal output. Open another terminal to check the process relationship, and this can help knowing debug information better:

```
# pstree -p `pidof strace`
strace(580)---fork(583)---fork(584)
```

Besides child processes' exit status, strace cares about events such as forking process, exit process, etc (please refer related code).

Set the overhead for tracing system calls

option is used to set the overhead for tracing system calls, and the unit is microseconds (us). The following is excerpted from manual:

This is useful for overriding the default heuristic for guessing how much time is spent in mere measuring when timing system calls using the -c option. The accuracy of the heuristic can be gauged by timing a given program run without tracing (using time(1)) and comparing the accumulated system call time to the total produced using -c.

Check the source code:

```
ts_mul(&dtv, &overhead, counts[i].calls);
ts_sub(&counts[i].time, &counts[i].time, &dtv);
.....
```

The overhead time is subtracted from the total consuming time, and this option just makes sure the measure of time spent on system calls to be more accurate.

Align return value column

By default, the alignment column for results is 40:

-a option can be used to adjust the alignment:

```
# strace -a 80 ls
execve("/usr/bin/ls", ["ls"], 0x7fffe93ef0d0 /* 21 vars */)
                = 0
brk(NULL)
                = 0x562a6bfa1000
arch_prctl(0x3001 /* ARCH_??? */, 0x7ffd332954c0)
                = -1 EINVAL (Invalid argument)
access("/etc/ld.so.preload", R_OK)
                = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/etc/ld.so.cache", O_RDONLY|O_CLOEXEC)
                = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=98317, ...})
mmap(NULL, 98317, PROT_READ, MAP_PRIVATE, 3, 0)
                = 0x7f2f8fd22000
close(3)
                = 0
. . . . . .
```

Tune this parameter according to your screen or your habit.

The end

This manual refers strace 's manual and code. If it helps you, please give it a star in github. :-)