

Difference between REST Connector and HTTP Connector

Last updated by | Anil K B | Mar 10, 2023 at 2:28 AM PST

Contents

- [HTTP Connector vs REST Connector](#)
- [Some important status codes are given below to verify the...](#)
- [What is Rest API calls??](#)
- [Preview GET Request in both Http Connector and Rest Con...](#)
 - [Postman echo GET response](#)
 - [HttpConnector GET response](#)
 - [RESTConnector GET Response](#)
- [HTTP Connector error message for data not found\(404\)](#)
- [RESTConnector error message for data not found\(404\)](#)

HTTP Connector vs REST Connector

	REST Connector	HTTP Connector
Purpose	The REST Connector is specifically designed for working with RESTful web services and provides built-in support for pagination, error handling, and retries.	The HTTP Connector is a more general-purpose connector that allows us to send basic HTTP requests and retrieve the response, but it does not have built-in support for these advanced features.
Configuration	The REST connector has built-in support for common RESTful operations such as GET, POST, PUT, DELETE, etc. and allows us to specify the URI and headers of the request.	HTTP connector requires us to specify the full URL's and the request method, as well as any headers and body that we want to include in the request.
Input/Output	The REST connector returns the response from the web service as a JSON object	HTTP connector returns the raw response as a string
Pagination	REST Connector does support pagination, it allows us to retrieve a specific page of data from a web service that supports pagination using REST API calls.	HTTP connector does not support pagination, but you we use various methods to achieve the pagination functionality in ADF such as using custom script, For Each activity or Web Activity.
Scalability	The REST Connector is designed to handle large volumes of data.	The HTTP Connector is not designed to handle large volumes of data. If we need to retrieve or process large amounts of data, we may need to implement our own solution using custom scripts or other activities (For Each activity or Web Activity).

Some important status codes are given below to verify the response.

200	For successful request.
201	For successful request and data was created
204	For Empty Response
400	For Bad Request
401	For Unauthorized access. Authentication failed or the user does not have permission for the requested operation
403	For Forbidden, Access Denied
404	For data not found
405	For method not allowed or requested method is not supported
500	Internal server error
503	For Service unavailable

What is Rest API calls??

RESTful API calls are web-based requests made to a server using the REST (Representational State Transfer) architectural style. RESTful APIs use the standard HTTP methods (**GET, POST, PUT, DELETE, etc.**) to perform operations on resources. Here's a brief explanation of the most common RESTful API calls:

- **GET:** Used to retrieve a resource from the server. It is the most common method used to retrieve data.
- **POST:** Used to create a new resource on the server. It is used to submit data to be processed by the server, such as uploading a file or creating a new database record.
- **PUT:** Used to update an existing resource on the server. It is used to submit updates to a resource, such as modifying a database record or updating a file.
- **DELETE:** Used to delete a resource on the server. It is used to remove a resource, such as deleting a database record or removing a file.

RESTful APIs use URIs (Uniform Resource Identifiers) to identify resources, and they return data in a format such as JSON or XML. They are lightweight, easy to use, and they don't require any special software to be installed on the client side. They are platform-independent, meaning that they can be consumed by any client that can understand HTTP protocol.

Additionally, RESTful APIs are typically stateless, which means that the server does not store any information about the client session. This allows for scalability, as the server does not need to maintain state for multiple clients.

Preview GET Request in both Http Connector and Rest Connector

Postman echo GET response

https://postman-echo.com/get

Save

</>

GET

https://postman-echo.com/get

Send

Params

Authorization

Headers (8)

Body

Pre-request Script

Tests

Settings

Cookies

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
--	-----	-------	-------------	-----	-----------

Body

Cookies (1)

Headers (7)

Test Results

200 OK

842 ms

712 B

Save Response

Pretty

Raw

Preview

Visualize

JSON

```
1 {
2   "args": {},
3   "headers": {
4     "x-forwarded-proto": "https",
5     "x-forwarded-port": "443",
6     "host": "postman-echo.com",
7     "x-amzn-trace-id": "Root=1-63c64aad-14637cb2556ad2c21c3a07db",
8     "user-agent": "PostmanRuntime/7.30.0",
9     "accept": "*/*",
10    "cache-control": "no-cache",
11    "postman-token": "89bd1b24-b0f6-4f67-b6d2-4e26c34173ed",
12    "accept-encoding": "gzip, deflate, br"
13  },
14  "url": "https://postman-echo.com/get"
15 }
```

Cookies

Capture requests

Runner

Trash

HttpConnector GET response

Preview data

Linked service: HttpConnector

Object:

```
[
  {
    "args": {
    },
    "headers": {
      "x-forwarded-proto": "https",
      "x-forwarded-port": "443",
      "host": "postman-echo.com",
      "x-amzn-trace-id": "Root=1-63c65363-521955a63eb2b11b185b6ea2",
      "user-agent": "azure-data-factory/2.0"
    },
    "url": "https://postman-echo.com/get"
  }
]
```

RESTConnector GET Response

Preview data

Linked service: RESTConnector

Object:

```
{
  "args": {
  },
  "headers": {
    "x-forwarded-proto": "https",
    "x-forwarded-port": "443",
    "host": "postman-echo.com",
    "x-amzn-trace-id": "Root=1-63c652ff-2ad4b84a369c70750b16352c",
    "user-agent": "azure-data-factory/2.0",
    "accept": "application/json",
    "accept-encoding": "gzip, deflate"
  },
  "url": "https://postman-echo.com/get"
}
```

By default, the REST connector in Azure Data Factory (ADF) uses the "application/json" value for the "Accept" header in its HTTP requests. This tells the endpoint that the client (ADF) expects a response in JSON format. However, it is possible to configure the connector to use a different value for the "Accept" header if the endpoint requires it.

HTTP Connector error message for data not found(404)

Error details



Error code 22755

Details

Http request failed with client error, status code 404 NotFound, please check your activity settings. If you configured a baseUrl that includes path, please make sure it ends with '/'.
Request URL: https://reqres.in//api/unknown/23.
The remote server returned an error: (404) Not Found.
Activity ID: 30da18ca-2488-4058-83dc-b1f667b60631



How helpful or unhelpful was this error message?



RESTConnector error message for data not found(404)

Error details



Error code **23353** 

Details Rest call failed with client error, status code 404 NotFound, please check your activity settings.
Request URL: https://reqres.in//api/unknown/23.
Response: Not found
Activity ID: 4a255def-650e-4742-96dd-07e57cc501aa

Additional Information

- Icm References:
- cases: 2211250050000248
- Author: **kbanil**
- Reviewer: **kbanil**

How good have you found this content?

