Creating a pipeline run via REST API

Last updated by | Jackie Huang | Jan 4, 2022 at 12:24 AM PST

This is already covered by the following docs, but not in a manner that's concise and easy to follow:

https://docs.microsoft.com/en-us/rest/api/datafactory/pipelines/create-run

12

https://docs.microsoft.com/en-us/azure/data-factory/concepts-pipeline-execution-triggers#rest-api

https://docs.microsoft.com/en-us/azure/data-factory/quickstart-create-data-factory-rest-api


https://docs.microsoft.com/en-us/azure/active-directory/develop/howto-create-service-principal-portal#assign-a-role-to-the-application

- 1. Create an App registration for the Data Factory https://docs.microsoft.com/en-us/azure/active-directory/develop/quickstart-register-app □
- Add a certificate or secret




- You will need App registration's tenant ID, client ID and the secret
- 2. Assign the Contributor role to the App registration on your Data Factory Access control (IAM)

Home > testDFrabalabaWE



Add role assignment



Search for the app registration and select it, then assign the role.

3. The configuration for the call to generate the token:

Content-Type: application/x-www-form-urlencoded

Body:


grant_type: client_credentials

resource: https://management.azure.com/ https://management.azure.com/ https://management.azure.com/ D


client_id: [App registration client ID]
client_secret: [App registration secret]

Add the App registration tenant ID to the request URL and the client ID and secret to its body. This is how it should look in Postman:

Headers:



Body:



You should get a response with a Bearer token:

```
Pretty Raw Preview Visualize JSON 

"token_type": "Bearer",
"expires_in": "86399",
"ext_expires_in": "86399",
"expires_on": "1635428597",
"not_before": "1635341897",
"resource": "https://management.azure.com/",
"access_token": "eyJ0eXAiOiJKV1QiLCJhbGci0iJSUzIII
```


4. Running the pipeline request

POST


https://management.azure.com/subscriptions/[subscriptionID]/resourceGroups/[RG_name]/providers/Microsoft. DataFactory/factories/[ADF_name]/pipelines/[pipeline_name]/createRun?api-version=2018-06-01 🗹

Authorisation Type: Bearer token

Token value: the "access_token" value from the previous call's response



And the response should be the pipeline runID:



Additional Information:

• Icm References:

• Author: rabalaba

Reviewer: grorcai

Keywords:

How good have you found this content?

