# Connection from PowerBI to PostgreSQL fails

Last updated by | Lisa Liu | Nov 6, 2020 at 10:33 AM PST

## Error: "The remote certificate is invalid according to the validation procedure"

This error will occur when the Cx tries to connect using a private IP, a custom domain name or <a href="mailto:privatelink.postgres.database.azure.com">privatelink.postgres.database.azure.com</a> <a href="mailto:postgres.database.azure.com">privatelink.postgres.database.azure.com</a> <a href="mailto:postgres.database.database.azure.com">privatelink.postgres.database.databas

#### **Solution:**

To connect using private link Cx should use the following string:

#### servername.database.windows.net Z

Additionally, the following line will need to be added to the hosts table if the connection still fails:

Private IP <servername>.database.windows.net

### Example:

#

#

#

```
*hosts - Notepad

File Edit Format View Help

# Copyright (c) 1993-2009 Microsoft Corp.

#

# This is a sample HOSTS file used by Microsoft TCP/IP for Windows.
```

# This file contains the mappings of IP addresses to host names. Each # entry should be kept on an individual line. The IP address should # be placed in the first column followed by the corresponding host name. # The IP address and the host name should be separated by at least one

# The IP address and the host name should be separated by at least one # space.
#

# Additionally, comments (such as these) may be inserted on individual # lines or following the machine name denoted by a '#' symbol.

# For example:

```
# 102.54.94.97 rhino.acme.com # source server
# 38.25.63.10 x.acme.com # x client host
```

# localhost name resolution is handled within DNS itself.

```
# 127.0.0.1 localhost
# ::1 localhost
```

# 10.1.0.4 pa-pgserver.database.windows.net

For more information review this Tech Blog post: <a href="https://techcommunity.microsoft.com/t5/azure-database-support-blog/lesson-learned-127-using-azure-sql-database-private-link-and/ba-p/1254208">https://techcommunity.microsoft.com/t5/azure-database-support-blog/lesson-learned-127-using-azure-sql-database-private-link-and/ba-p/1254208</a>

Error: "No connection could be made because the target machine actively refused it"

This error could be due to port 5432 being blocked on the user's network.

Solution: Ask Cx to allow port 5432 to accept traffic in their organization

# How good have you found this content?

