




Last updated by | Ruoyu Li | Feb 16, 2023 at 1:02 AM PST

201029- [SFTP] Basic Auth not work and Error Message contains "keyboard-interactive"		ASC Onboard
--	--	-------------

[https://supportability.visualstudio.com/AzureDataFactory/\\_wiki/wikis/AzureDataFactory/286800/-SFTP-Basic-Auth-not-work-and-Error-Message-contai...](https://supportability.visualstudio.com/AzureDataFactory/_wiki/wikis/AzureDataFactory/286800/-SFTP-Basic-Auth-not-work-and-Error-Message-contai...) 1/2

SME	
Symptoms	<p>Error message saying Basic auth fail and contains "keyboard-interactive" keyword (like below sample)</p> <p><i>Meet authentication failure when connect to Sftp server 'xxxx' using 'Basic' authentication type. No suitable authentication method found to complete authentication (publickey, keyboard-interactive)</i></p> <p>Also customer may have able to connect to the SFTP server by using other tool like WinSCP.</p>
Cause	SFTP keyboard-interactive auth is supported in ADF but not by default open to customers for security concern.
Resolution	<div><div><div>1. CSS make sure customer is really facing the keyboard-interactive auth not supported issue from error message</div><div>2. Notify customer that we need his confirmation to open keyboard-interactive feature for his subscription. A sample could be like:</div></div><div><div>From Gateway log, the error message is</div><div>Meet authentication failure when connect to Sftp server 'xxx' using 'Basic' authentication. No suitable authentication method found to complete authentication (publickey, keyboard-interactive)</div><div>This means customer's SFTP server only allow keyboard-interactive auth (RFC4256) but not basic auth (aka password auth, RFC4252 Sec.8.). These 2 authentication types are actually different although some SFTP tool hide this detail (e.g. WinSCP).</div><div>Keyboard-interactive is design to be used in interactive scenario that user need to input password manually each time when establish a SSH session. It is somehow not suitable in ADF, which is a schedule scenario.</div><div>But technically, it is possible to login through keyboard-interactive auth automatically in backend, without customer manual input.</div><div>In ADF, keyboard-interactive is supported for Copy, but from security concern, <b>we need customer to explicitly confirm to grant ADF</b> to use keyboard-interactive auth to establish SSH session in the schedule Copy.</div><div>Once we receive the ack from customer, we will open that feature for this customer.</div></div><div><div>3. After customer confirm to open keyboard-interactive auth feature, then tell customer to follow below steps to enable keyboard-interactive auth</div><div><div>On UX, click on Connections-&gt;Linked Services</div><div>Find the SFTP linked service you created</div><div>Click on the button heighted as right snapshot</div></div><div><div><div><div></div><div></div><div></div></div></div></div><div><div>Remove encryptedCredential property, Add property allowKeyboardInteractiveAuth with value true, below is an example</div><div><pre>"name": "XXXXXXXXXX", "type": "Microsoft.DataFactory/factories/linkedservices", "properties": {   "type": "Sftp",   "typeProperties": {     "host": "XXXXXXXXXX",     "port": 22,     "skipHostKeyValidation": true,     "authenticationType": "Basic",     "userName": "{your user name}",     "password": "{your password}",     "allowKeyboardInteractiveAuth": true   } }</pre></div><div>Save the changes and rerun the copy</div></div></div></div>
More Information	
Tags	SFTP

How good have you found this content?

