# SAP ODC Connector: ODC name loading failed for BW (BW 4HANA) ODC context type

Last updated by | Anil K B | Feb 21, 2023 at 3:55 AM PST

# Contents • Issue • RCA: • Resolution:


### Issue


Customer is trying to create dataset for SAP ODC connector where Context name is BW/(BW/4HANA)

While trying to fetch ODC name out of the context, it is unable to fetch the ODC name and failed with below error.

Error code: 27153

**Details**: Sap Odp operation 'ListOdpSourcesFromSap' failed. Error Number: '519', error message: 'BW/ is not a valid context' Activity ID: 894d3282-604c-4bae-b273-bc403aa7ce28





# RCA:


In the Dataset for the section for ODP context, even if we choose the context name as BW/(BW/4HANA) from the drop down. In the payload the value added as BW/, an extra / is coming with BW name for which it is not able to resolve the context name and fails with the invalid context error.

Sample Json-


## **Resolution:**

We need to remove the extra / from the context section and try refresh the ODP file name, it will work as expected and shows tables name.

1. Click on Edit and manually give the ODP context name as BW in the dataset.



2. Try refresh the ODP name, you will be able to see the ODP names on the drop down.



### **Additional Information**

• Icm References:

• cases: 2302170030000437

• Author: priyankapr

• Reviewer: sveldurthi

### How good have you found this content?

