

# [MongoDB|MongoAPI] The GuidRepresentation for the reader is CSharpLegacy

Last updated by | Jackie Huang | Jan 4, 2022 at 12:24 AM PST

	201055- [MongoDB/MongoAPI] The		
	GuidRepresentation for the reader is CSharpLegacy		
			ASC Onboard
	Thursday, July 18, 2019		
	10:35 AM		

SME	
Symptoms	Error thrown when reading UUID from Cosmos DB MongoAPI/MongoDB
Cause	There are two ways to represent UUID in Bson - UuidStardard and UuidLegacy, by default UuidLegacy is used to read data. And it will throw error like this when customer's uuid data in Db is UuidStandard.
Resolution	To fix this, customer should add below option in MongoAPI connection string <a href="https://docs.microsoft.com/en-us/azure/data-factory/connector-mongodb#linked-service-properties">https://docs.microsoft.com/en-us/azure/data-factory/connector-mongodb#linked-service-properties</a> uuidRepresentation= <b>standard</b>
More Information	Full error message is like this:  Failed to read data via MongoDB client.,Source=Microsoft.DataTransfer.Runtime.MongoDbV2Connector,"Type=System.FormatException,Message=GuidRepresentation for the reader is CSharpLegacy&#44; which requires the binary sub type to be UuidLegacy not UuidStandard.,Source=MongoDB.Bson,"
Tags	Mongo DB;Mongo API;UuidLegacy; GuidRepresentation

Created with Microsoft OneNote 2016.

How good have you found this content?

