

[SFTP] Invalid Sftp credential provided for 'SshPublicKey' authentication type

Last updated by | Jackie Huang | Jan 4, 2022 at 12:24 AM PST

	201030- [SFTP] Invalid Sftp credential provided for 'SshPublicKey' authentication type		
		ASC Onboard	

Monday, December 18, 2017
11:22 AM

SME	
Symptoms	Customer is using SshPublicKey auth but hit Invalid Sftp credential provided for 'SshPublicKey' authentication type.
Cause	<p>There are three possible root causes could lead this error</p> <ol style="list-style-type: none">1. Private key content is set from AKV/SDK but they are not encoded correctly2. Wrong key content format3. Invalid credential or private key content
Resolution	<p>Please follow below steps to figure out the right solution</p> <p>1. If private key content is from AKV and original key file can work if customer upload it directly to SFTP linked service</p> <p>As described in https://docs.microsoft.com/en-us/azure/data-factory/connector-sftp#using-ssh-public-key-authentication , the privateKeyContent is a Base64 encoded SSH private key content.</p> <p>You should encode the whole content of original private key file with base64 encoding and store the encoded string to AKV. We have some customers decode their key content and then encode the key content again, that is wrong, don't do anything to the original private key file, treat it as a black box and encode all content of this file. Original private key file means the one that can work on SFTP linked service if you click on upload from file.</p> <p>To generate such string, customer can use below 2 ways:</p> <ul style="list-style-type: none">• Using C# code<pre>byte[] keyContentBytes = File.ReadAllBytes(privateKeyPath); string keyContent = Convert.ToBase64String(keyContentBytes, Base64FormattingOptions.None);</pre>• Using Python code<pre>import base64 rfd = open(r'{Your private key file}', 'rb') keyContent = rfd.read() rfd.close() print base64.b64encode(keyContent)</pre>• Using 3rd party base64 convert tool Paste the whole private key content to such tool (like https://www.base64encode.org/) and encode to a base64 format string. Paste this string to key vault <p>2. If customer's key is using PKCS#8 format ssh private key</p> <p>Customer is using PKCS#8 format SSH private key to access SFTP server, but this format is not supported in ADF. ADF supports the traditional SSH Key format. In detail, the difference between PKCS#8 format and traditional Key format is PKCS#8 key content starts with "-----BEGIN ENCRYPTED PRIVATE KEY-----" while traditional key format starts with "-----BEGIN RSA PRIVATE KEY-----".</p> <p>please let customer run below commands to convert the key to traditional key format:</p> <pre>openssl pkcs8 -in pkcs8_format_key_file -out traditional_format_key_file // decrypt the pkcs8 key and convert the format to traditional key format chmod 600 traditional_format_key_file ssh-keygen -f traditional_format_key_file -p // re-encrypt the key file using passphrase</pre> <p>(Above commands should be composed in one line)</p> <p>3. Elsewise</p> <p>Suggest customer to double check if their key file or password is correct using other tools (like winscp) and get back to us if other tool can succeed</p>
More Information	
Tags	SFTP

Created with Microsoft OneNote 2016.

How good have you found this content?

