How to check dataflow Debug session status

Last updated by | Nelson Gomes | Mar 9, 2023 at 11:49 PM PST

How to check dataflow Debug session status


Contents

- Steps
 - Step 1: Get pipeline run id
 - Step 2: Use pipeline run id to find debug session ID
 - Step 3: Search for debug guid in ApiOperationEvent

Steps

Step 1: Get pipeline run id

ActivityRuns| where activityRunId == "f80ae58f-1c4b-48ab-9d0a-3a95ac1314a6" |project TIMESTAMP, status, activityType, activityRunId, pipelineName, pipelineRunId, activityName, subscripti



For our example, let's assume pipeline Runld is 442e79cf-47e1-44a0-af56-5e675e305121

Step 2: Use pipeline run id to find debug session ID

Use pipeline run id to find debug session ID. (Search for debug keyword, and see if any guid found)


AdfTraceEvent|where TraceCorrelationId == "442e79cf-47e1-44a0-af56-5e675e305121"

DataFactoryMonitoringServiceClient.CreateOrUpdateDataflowDebugSessionRunAdminAsync - starting for dataFactoryId 73b747d4-a99e-4584-bd67-ce922afb9792, run Partition , id: 46609bca-79ff-445c-9c16-8b67a17801b5, DataFactoryVersion: 2018-06-01, Resourceid: /SUBSCRIPTIONS/128987e1-e400-40c2-be1c-da5d9f54e967/RESOURCEGRDUPS/rlm-dev-dpl-uks-rg-adf/PROVMDERS/MICROSOFF-DATAFACTORY/FACTORIES/rlm-dev-dpl-uks-adf-data-platform, Timestamp: 06/21/2022 08:53:16-00000.

For our example, let's assume sessionld is 46609bca-79ff-445c-9c16-8b67a17801b5

Step 3: Search for debug guid in ApiOperationEvent

ApiOperationEvent| where RequestUri contains "46609bca-79ff-445c-9c16-8b67a17801b5" | project TIMESTAMP, PreciseTimeStamp, env_cloud_deploymentUnit, operationName, ApiName, ClientRequestId



Conclusions:

- Debug session stopped at 2022-06-21 12:57:16.9950010.
- Activity run started at 2022-06-21 08:57:00.000000. Cluster was running at that time.

Additional information

• IcM reference:

Ava: 2206030050000749

Author: vetcaci

• Reviewer: negome

Keywords:

How good have you found this content?



