10.1.3 KHF_DRBG

10.1.3.1 Discussion

KHF_DRBG (...) specifies multiple uses of a hash function. The same Approved hash function **shall** be used throughout. The hash function used **shall** meet or exceed the security requirements of the consuming application. Table 1 in Section 10.1.1 specifies the entropy and seed length requirements that **shall** be used for each hash function in order to meet a specified security level.

KHF_DRBG (...) is specified using two internal functions: **KHF (...)** and **Update (...)**. Both are called during the instantiation, pseudorandom bit generation and reseeding processes to adjust the state.

10.1.3.2 Interaction with KHF_DRBG

10.1.3.2.1 Instantiating KHF_DRBG (...)

Prior to the first request for pseudorandom bits, the **KHF_DRBG (...) shall** be instantiated using the following call:

(*status*, *usage_class*) = **Instantiate_KHF_DRBG** (*requested_strength*, *prediction_resistance_flag*, *personalization_string*, *mode*)

as described in Sections 9.6.1 and 10.1.3.3.3.

10.1.3.2.2 Reseeding a KHF_DRBG (...) Instantiation

When a **KHF_DRBG (...)** instantiation requires reseeding, the DRBG **shall** be reseeded using the following call:

status = **Reseed_KHF_DRBG_Instantiation** (*usage_class*, *mode*)

as described in Sections 9.7.2 and 10.1.3.3.4.

10.1.3.2.3 Generating Pseudorandom Bits Using KHF_DRBG (...)

An application may request the generation of pseudorandom bits by **KHF_DRBG (...)** using the following call:

(*status*, *pseudorandom_bits*) = **KHF_DRBG** (*usage_class*, *requested_no_of_bits*, *requested_strength*, *additional_input*, *prediction_resistance_requested*, *mode*)

as discussed in Sections 9.8.2 10.1.3.3.5.

10.1.3.2.4 Removing a KHF_DRBG (...) Instantiation

An application may request the removal of a **KHF_DRBG (...)** instantiation using the following call:

status = **Uninstantiate_KHF_DRBG** (*usage_class*)

as described in Sections 9.X.X and 10.1.3.3.6.

10.1.3.2.5 Self Testing of the KHF_DRBG (...) Process

A **KHF_DRBG (...)** implementation is tested at power-up and on demand using the following call:

status = **Self_Test_KHF_DRBG** ( )

as described in Sections 9.9 and 10.1.3.3.7.

10.1.3.3 Specifications

10.1.3.3.1 General

The instantiation and reseeding of **KHF_DRBG (...)** consists of obtaining a *seed* with the appropriate amount of entropy. The entropy input is used to derive a *seed,* which is then used to derive elements of the initial *state*. The *state* consists of:

1. The value *V*, which is updated each time another *outlen* bits of output are produced (where *outlen* is the number of output bits from the underlying hash function).
2. The values K_0 and K_1, which are updated at least once each time the DRBG generates pseudorandom bits.
3. The security *strength* of the DRBG instantiation.
4. A counter (*ctr*) that indicates the number of times that pseudorandom bits were generated since the DRBG instantiation was seeded, reseeded or prediction resistance was obtained.
5. A *prediction_resistance_flag* that indicates whether or not a prediction resistance capability is required for the DRBG.
6. (Optional) A transformation of the *entropy_input* using a one-way function for later comparison with new *entropy_input* when the DRBG is reseeded or prediction resistance is requested; this value **shall** be present if the DRBG will potentially be reseeded or a prediction resistance capability is required for the instantiation.

The variables used in the description of **KHF_DRBG (...)** are:

additional_input	Optional additional input.
ctr	A counter that records the number of times that pseudorandom bits were generated since the DRBG instantiation was seeded, reseeded or prediction resistance was obtained.
entropy_input	The bits containing entropy that are used to determine the *seed_material*.
Find_state_space (*mode*)	A function that returns a *usage_class* indicating an available state space. The *mode* indicates whether the request is made during normal operation or during testing.

Get_entropy (*min_entropy*, *outlen*, 2^{35}, *mode*)

	A function that acquires a string of bits from an entropy input source. *min_entropy* indicates the minimum amount of entropy to be provided in the returned bits; *outlen* indicates the minimum number of bits to return; 2^{35} indicates the maximum number of bits that may be returned; *mode* is used to indicate whether the bits are to be obtained during normal operation or during testing. See Section 9.6.2.
K_0, K_1	Values in the state that are updated when the DRBG generates pseudorandom bits.
len(string)	A function returning the number of bits in a string.
M	The number of bytes in the hash function input block.
max_no_of_states	The maximum number of states and instantiations that an implementation can handle.
max_updates	The maximum number of *state* updates allowed for the DRBG instantiation from one seeding, reseeding or prediction resistance operation.
min_entropy	The minimum amount of entropy to be provided in the *entropy_input*.
mode	An indication of whether a process is to be conducted for normal operations or for testing. *mode* = 1 = *Normal_operation* indicates that normal operation is required; *mode* = 2 = *Fixed_1* indicates that a predetermined value is to be used during instantiation, *mode* = 3 = *Fixed_2* indicates that a predetermined value is to be used during reseeding, mode = 4 = *Failure* indicates that a failure indication is to be returned. Note that the *mode* = 2 fixed values **shall** be different than the *mode* = 3 fixed values.
N	The number of bytes in the hash function output block.
old_transformed_entropy_input	The *transformed_entropy_input* from the previous acquisition of *entropy_input* (e.g., used during reseeding).
outlen	The number of bits in the hash function output block.
Pad_0, *Pad_1*	Zero padding used by the **KHF (...)** function.
*Padded_*K_0	K_0 padded with zeros to create *M* bytes.
Padded_V	*V* padded with zeros to create $M - 9$ bytes.
personalization_string	A string that may be used to personalize a DRBG instantiation.
prediction_resistance_flag	Indicates whether or not prediction resistance is to be

	provided upon request during an instantiation. 1 = *Allow_prediction_resistance*: requests for prediction resistance will be handled; 0 = *No_prediction_resistance*: requests for prediction resistance will return an error indication.
prediction_resistance_requested	Indicates whether or not prediction resistance is required during the actual generation of pseudorandom bits. 1 = *Provide_prediction_resistance*: prediction resistance required; 0 = *No_prediction_resistance*: prediction resistance not required.
pseudorandom_bits	The string of *pseudorandom_bits* that are generated during a single "call" to the **KHF_DRBG (...)** process.
requested_no_of_bits	The number of pseudorandom bits to be generated.
requested_strength	The security strength to be provided for the pseudorandom bits to be obtained from the DRBG.
seed_material	The data used as the *seed.*
state(*usage_class*)	An array of *states* for different DRBG instantiations. A *state* is carried between calls to the DRBG. In the following specifications, the state for a *usage_class* is defined as *state*(*usage_class*) = {*V*, K_0, K_1, *strength*, *ctr*, *prediction_resistance_flag*, *transformed_entropy_input*}. A particular element of the *state* is specified as *state*(*usage_class*).*element*; e.g., *state*(*usage_class*).*V*.
status	The status returned from a function call, where *status* = "Success" or an indication of failure. Failure messages are: 1. Invalid *requested_strength.* 2. Cannot support prediction resistance. 3. *personalization_string* too long. 4. No available *state* space. 5. Failure indication returned by the *entropy_input* source. 6. State not available for the indicated *usage_class.* 7. *Entropy_input* source failure. 8. HMAC_DRBG can no longer be used. Please re-instantiate or reseed. 9. *additional_input* too long 10. Too many bits requested.

	11. Prediction resistance capability not instantiated.
strength	The security strength provided by the DRBG instantiation.
temp	A temporary value.
transformed_entropy_input	A one-way transformation of the *entropy_input* for the DRBG.
usage_class	The usage class of a DRBG instantiation. Used as a pointer to an instantiation's *state* values.
V	A value in the *state* that is updated whenever pseudorandom bits are generated.

10.1.3.3.2 Internal Functions

10.1.3.3.2.1 The KHF Function

The KHF (...) function is used as a compression function and to distribute the effect of the bits in the input values across the entire output string. Let N be the number of bytes of output from the hash function, and M be the number of bytes of the hash function input block.

KHF(...):

Input: string (K_0, K_1, V).

Output: string V.

Process:

1. Pad_0 = 0x00 00...00. Comment: M - N bytes of zeros.
2. Pad_1 = 0x00 00...00. Comment: M - N - 9 bytes of zeros.
3. $Padded\_K_0 = K_0 \| Pad\_0$. Comment: Since K_0 is N bytes in length, $Padded\_K_0$ is M bytes long.
4. $Padded\_V = V \| Pad\_1$. Comment: Since V is N bytes in length, $Padded\_V$ is M-9 bytes long.
5. $temp = Padded\_V \oplus K_1$.
6. V = **Hash** ($Padded\_K_0 \| temp$).
7. **Return** (V).

10.1.3.3.2.2 The Update Function

The **Update (...)** function updates the internal *state* of the **KHF_DRBG (...)** using the *seed_material*. The *seed_material* can be any input string of 2^{35} bits or less, including the Null string. **Update (...)** makes extensive use of both the **KHF (...)** and the **hash_df (...)** functions described in Sections 10.1.3.3.2.1 and 9.6.4.2, respectively. Let N be the output length of the hash function in bytes, and let M be the hash function input block size in bytes.

Update (...):

Input: string (*seed_material*, K_0, K_1, V).

Output: string (K_0, K_1, V).

Process:

1. *temp* = the Null string.
2. While ((8 ×**len** (*temp*)) < $N + M - 9$) do:
   2.1 V = **KHF** (K_0, K_1, V).
   2.2 *temp* = *temp* || V.
3. *temp* = The rightmost (least significant) $N+M-9$ bytes of *temp*.
4. *temp* = *temp* ⊕ **hash_df** (*seed_material*, $8 \times (N + M - 9)$).
5. K_0 = The rightmost N bytes of *temp*.
6. K_1 = The leftmost $M-9$ bytes of *temp*.
7. V = **KHF** (K_0, K_1, V).
8. **Return** (K_0, K_1, V).

10.1.3.3.3 Instantiation of KHF_DRBG(...)

The following process or its equivalent **shall** be used to initially instantiate the **KHF_DRBG (...)** process. Let **Hash (...)** be the Approved hash function to be used. Let *outlen* be the output length of that hash function in bits, and let N be the output length of the hash function in bytes. Let M be the hash function input block size in bytes.

Instantiate_KHF_DRBG (...):

Input: integer (*requested_strength*, *prediction_resistance_flag*, *personalization_string*, *mode*).

Output: string *status*, integer *usage_class*.

Process:

1. If (*requested_strength* > the maximum security *strength* that can be provided by the hash function (see Table 1)), then **Return** ("Invalid *requested_strength*", 0).
2. If (*prediction_resistance_flag* = *Allow_prediction_resistance*) and prediction resistance cannot be supported, then **Return** ("Cannot support prediction resistance", 0).
3. If (**len**(*personalization_string*)>2^{35}), then **Return**("*personalization_string* too long.")

   Comment: Find state space.
4. (*status*, *usage_class*) = **Find_state_space** (*mode*).
5. If (*status* = "Failure"), then **Return** ("No available state space", 0).

   Comment: Set the *strength* to one of the five security strengths.
6. If (*requested_strength* ≤ 80), then *strength* = 80

Else if (*requested_strength* ≤ 112), then *strength* = 112

Else (*requested_strength* ≤ 128), then *strength* = 128

Else (*requested_strength* ≤ 192), then *strength* = 192

Else *strength* = 256.

Comment: Get the *entropy_input*.

7. *min_entropy* = **max** (128, *strength*).
8. (*status*, *entropy_input*) = **Get_entropy** (*min_entropy*, *outlen*, 2^{35}, *mode*).
9. If (*status* = "Failure"), then **Return** ("Failure indication returned by the entropy source", 0).

   Comment: Perform a one-way function on the *entropy_input* for later comparison during reseeding.
10. *transformed_entropy_input* = **Hash** (*entropy_input*).

    Comment: Set up the working values.
11. K_0 = 0x00 00...00. Comment: *N* bytes of zeroes.
12. K_1 = 0x01 01...01. Comment: *M* - 9 bytes of ones.
13. *V* = 0x02 02...02. Comment: *N* bytes of twos.
14. *seed_material* = *entropy_input* || *personalization_string*.
15. *ctr* = 0.
16. (K_0, K_1, *V*) = **Update** (*seed_material*, K_0, K_1, *V*).

    Comment: Set up the state.
17. *state* (*usage_class*) = {*V*, K_0, K_1, *strength*, *ctr*, *prediction_resistance_flag*, *transformed_entropy_input*}.
18. **Return** ("Success", *usage_class*).

If an implementation does not handle all five security strengths, then step 6 must be modified accordingly.

If no *personalization_string* will ever be provided, then the *personalization_string* parameter in the input may be omitted, and step 13 becomes *seed_material* = *entropy_input*.

If an implementation will never be reseeded using the process specified in Section 10.1.3.3.4, then step 10 may be omitted, as well as the *transformed_entropy_input* in the *state* (see step 17).

If an implementation does not need the *prediction_resistance_flag* as a calling parameter (i.e., the **KHF_DRBG (....)** routine in Section 10.1.3.3.5 either always or never acquires new entropy in step 7), then the *prediction_resistance_flag* in the calling parameters and in the *state* (see step 17) may be omitted, as well as omitting step 2.

10.1.3.3.4 Reseeding a KHF_DRBG(...) Instantiation

The following or an equivalent process **shall** be used to explicitly reseed the **KHF_DRBG (...)** process. Let **Hash (...)** be the Approved hash function to be used; let *outlen* be the output length of that hash function in bits, and let *N* be the output length of the hash function in bytes. Let *M* be the hash function input block size in bytes.

Reseed_KHF_DRBG_Instantiation (...):

Input: integer *mode* (*usage_class*,).

Output: string *status*.

Process:

1. If ((*usage_class* > *max_no_of_states*) or (*state*(*usage_class*) = {Null, Null, Null, 0, 0, 0, Null}), then **Return** ("State not available for the indicated *usage_class*").

   Comment: Get the appropriate *state* values for the indicated *usage_class.*

2. V = *state*(*usage_class*).V, K_0 = *state*(*usage_class*).K_0, K_1 = *state*(*usage_class*).K_1, *strength* = *state*(*usage_class*).*strength*, *prediction_resistance_flag* = *state(usage_class).prediction_resistance_flag*, *old_transformed_entropy_input* = *state*(*usage_class*).*transformed_entropy_input*.

   Comment: Get the new *entropy_input*.

3. *min_entropy* = **max** (128, *strength*).

4. (*status*, *entropy input*) = **Get_entropy** (*min_entropy*, *outlen*, 2^{35}, *mode*).

5. If (*status* = "Failure"), then **Return** ("Failure indication returned by the *entropy_input* source").

   Comment: Compare the old *entropy_input* with the new *entropy_input*.

6. *transformed_entropy_input* = **Hash** (*entropy_input*).

7. If (*transformed_entropy_input* = *old_transformed_entropy_input*), then **Return** ("*Entropy_input* source failure").

   Comment: Set up the new working values.

8. *ctr* = 0.

9. (K_0, K_1, V) = **Update** (*entropy_input*, K_0, K_1, V).

   Comment: Set the state values.

10. *state*(*usage_class*) = {V, K_0, K_1, *strength*, *ctr*, *prediction_resistance_flag*, *transformed_entropy_input*}.

10. **Return** ("Success").

10.1.3.3.5 Generating Pseudorandom Bits Using KHF_DRBG (...)

The following process or an equivalent **shall** be used to generate pseudorandom bits:

KHF_DRBG(...):

Input: integer (*usage_class*, *requested_no_of_bits*, *requested_strength*, *additional_input*, *prediction_resistance_requested*, *mode*).

Output: string (*status*, *pseudorandom_bits*).

Process:

1. If ((*usage_class* > *max_no_of_states*) or (*state*(*usage_class*) = {Null, Null, Null, 0, 0, 0, Null}), then **Return** ("State not available for the indicated *usage_class*", Null).

   Comment: Get the appropriate *state* values for the indicated *usage_class*.

2. V = *state*(*usage_class*).V, K_0 = *state*(*usage_class*).K_0, K_1 = *state*(*usage_class*).K_1, *strength* = *state*(*usage_class*).*strength*, *ctr* = *state*(*usage_class*).*ctr*, *prediction_resistance_flag* = *state*(*usage_class*).*prediction_resistance_flag*, *old_transformed_entropy_bits* = *state*(*usage_class*).*transformed_entropy_bits*.

   Comment: If *ctr* ≥ *max_updates*, then reseeding could not be done in step 14 (below) during the previous call because of no available entropy source.

3. If (*requested_strength* > *strength*), then **Return** ("Invalid *requested_strength*", Null).
4. If (*requested_no_of_bits* > 2^{35}), then **Return** ("Too many bits requested", Null).
5. If(**len**(*additional_input*)>2^{35}), then **Return**("*additional_input* too long.")
6. If ((*prediction_resistance_requested* = *Provide_prediction_resistance*) and (*prediction_resistance_flag* = *No_prediction_resistance*)), then **Return** ("Prediction resistance capability not instantiated", Null).
7. If (*prediction_resistance_requested* = *Provide_prediction_resistance*), then
   - 7.1 *min_entropy* = **max** (128, *strength*).
   - 7.2 (*status*, *entropy_bits*) = **Get_entropy** (*min_entropy*, *outlen*, 2^{35}, *mode*).
   - 7.3 If (*status* = "Failure"), then **Return** ("Failure indication returned by the *entropy_input* source", Null).
   - 7.4 *transformed_entropy_input* = **Hash** (*entropy_input*).

7.5 If (*transformed_entropy_input* = *old_transformed_entropy_input*), then **Return** ("Entropy_input source failure", Null).

7.6 *ctr* = 0.

Else

7.7 *entropy_input* = Null.

8. *seed_material* = *entropy_input* || *additional_input*.
9. If (*seed_material* ≠ Null), then (K_0, K_1, *V*) = **Update** (*seed_material*, K_0, K_1, *V*).
10. If (*ctr* ≥ *max_updates*), then

    10.1 *status* = **Reseed_KHF_DRBG** (*usage_class*, *mode*).

    10.2 If (*status* ≠ "Success"), then **Return** (*status*, Null).
11. *temp* = Null.
12. While (**len** (*temp*) < *requested_no_of_bits*) do:

    12.1 *V* = **KHF** (K_0, K_1, *V*).

    12.2 *temp* = *temp* || *V*.
13. *pseudorandom_bits* = Leftmost (*requested_no_of_bits*) of *temp*.
14. (K_0, K_1, *V*) = **Update** (*seed_material*, K_0, K_1, *V*).
15. *ctr* = *ctr* + 1
16. *state*(*usage_class*) = {*V*, K_0, K_1, *strength*, *ctr*, *prediction_resistance_flag*, *transformed_entropy_bits*).
17. **Return** ("Success", *pseudorandom_bits*).

If an implementation will never provide *additional_input*, then the *additional_input* input parameter may be omitted, and step 8 becomes *seed_material* = *entropy_input*.

If an implementation does not need the *prediction_resistance_flag*, then the *prediction_resistance_flag* may be omitted as an input parameter, and step 6 may be omitted. If prediction resistance is never used, then step 7 becomes *entropy_input* = Null.

If an implementation does not have a reseeding capability, then step 10 **shall** be replaced by the following:

If (*ctr* ≥ *max_updates*), then **Return** ("HMAC_DRBG can no longer be used. Please re-instantiate or reseed", Null).

10.1.3.3.6 Removing a KHF_DRBG (...) Instantiation

The following or an equivalent process **shall** be used to remove a **KHF_DRBG (...)** instantiation:

Uninstantiate_KHF_DRBG (...):

Input: integer *usage_class*.

Output: string *status*.

Process:

1. If (*usage_class* > *max_no_of_states*), then **Return** ("Invalid *usage_class*").
2. *state*(*usage_class*) = {Null, Null, Null, 0, 0, 0, Null}.
3. **Return** ("Success").

10.1.3.3.7 Self Testing of the KHF_DRBG (...)

[To be added later]

10.1.3.4 Generator Strength and Attributes

10.1.3.5 Reseeding and Optional Input