

Resources. Any entropy input source may be used with **Dual_EC_DRBG**, provided that it is capable of generating at least *seedlen* bits. This DRBG also requires an appropriate hash function (see Table 4) that is used exclusively for producing an appropriately-sized initial state from the entropy input at instantiation or reseeding. An implementation of this DRBG must also have enough storage for the internal state (see 10.3.1.1). Some optimizations require additional storage for moderate to large tables of pre-computed values.

Algorithm Choices. The choice of appropriate elliptic curves and points used by **Dual_EC_DRBG** is discussed in Appendix A.1.

Below are Table 4 from Section 10.3.1, and the example in Appendix F.5. I have some questions,

1. In the table, which entries are required for the curve to work properly, and which entries are really dependent on the requested security strength during instantiation? For example, if a consuming application requests instantiation at the 112-bit security level, theoretically, any curve could be used. If it is determined that the P-256 curve will be used in this case, do all the values in the P-256 column need to be used, or can lesser values be used in some cases.
 - a. Can the *min_length*, for example, be reduced to 224? Why is the *min_length* about twice the minimum entropy anyway? To give a big security cushion?
 - b. Can the *seedlen* be 224, as it was for the P-224 curve, or must it be 256?
 - c. Can the *max_outlen* be 208, or must it be 240?

These same questions apply if any curve is used to support a security strength < the max. that it can support?

2. Please check the blue text that is highlighted in gray. Does it make sense?

Table 4: Definitions for the Dual_EC_DRBG

	P-224	P-384	P-521
	P-256		
Supported security strengths	See SP 800-57		
highest_supported_security_strength	See SP 800-57		
Output block length (<i>max_outlen</i> = largest multiple of 8 less than <i>seedlen</i> - (13 + log ₂ (the cofactor)))	208 240	368	504
Required minimum entropy for instantiate and reseed	<i>security_strength</i>		
Minimum entropy input length (<i>min_length</i> = $8 \times \lceil \text{seedlen}/8 \rceil$)	224 256	384	528
Maximum entropy input length (<i>max_length</i>)	$\leq 2^{13}$ bits		
Maximum personalization string length (<i>max_personalization_string_length</i>)	$\leq 2^{13}$ bits		
Supported security strengths	See SP 800-57		
Seed length (<i>seedlen</i> = <i>m</i>)	224 256	384	521

	P-224 P-256	P-384	P-521
Appropriate hash functions	SHA-1, SHA-224, SHA-256, SHA-384, SHA-512	SHA-224, SHA-256, SHA-384, SHA-512	SHA-256, SHA-384, SHA-512
<i>max_number_of_bits_per_request</i>	<i>max_outlen</i> × <i>reseed_interval</i>		
Number of blocks between reseeding (<i>reseed_interval</i>)	$\leq 2^{32}$ blocks		

The generate function is the same as that provided in Annex E.3.5.

F.5 Dual_EC_DRBG Example

This example of **Dual_EC_DRBG** allows a consuming application to instantiate using any of the three prime curves. The elliptic curve to be used is selected during instantiation in accordance with the following:

<i>requested instantiation security strength</i>	Elliptic Curve
112	P-256
128	P-256
192	P-384
256	P-521

A reseed capability is available, but prediction resistance is not available. Both a *personalization_string* and an *additional_input* are allowed. A total of 10 internal states are provided. For this implementation, the algorithms are provided as inline code within the functions.

The nonce for instantiation (*instantiation_nonce*) consists of a random value with *security_strength*/2 bits of entropy; the nonce is obtained by a separate call to the **Get_entropy_input** routine than that used to obtain the entropy input itself.

The internal state contains values for *s*, *seedlen*, *p*, *a*, *b*, *n*, *P*, *Q*, *r_old*, *block_counter* and *security_strength*. In accordance with Table 4 in Section 10.3.1, security strengths of 112, 128, 192 and 256 may be supported. SHA-256 has been selected as the hash function. The following definitions are applicable for the instantiate, reseed and generate functions:

1. *highest_supported_security_strength* = 256.
2. Output block length (*outlen*): See Table 4.
3. Required minimum entropy for the entropy input at instantiation and reseed = *security_strength*.

4. Minimum entropy input length (*min_length*): See Table 4.
5. Maximum entropy input length (*max_length*) = 1000 bits.
6. Maximum personalization string length (*max_personalization_string_length*) = 800 bits.
7. Maximum additional input length (*max_additional_input_length*) = 800 bits.
8. Seed length (*seedlen*): See Table 4.
9. Maximum number of bits per request (*max_number_of_bits_per_request*) = 1000 bits.
10. Reseed interval (*reseed_interval*) = $10,000 \cdot 2^{32}$ blocks.

F.5.1 Instantiation of Dual_EC_DRBG

This implementation will return a text message and an invalid state handle (-1) when an **ERROR** is encountered. **Hash_df** is specified in Section 10.4.1.

Instantiate_Dual_EC_DRBG (...):

Input: integer (*requested_instantiation_security_strength*), bitstring *personalization_string*.

Output: string *status*, integer *state_handle*.

Process:

Comment : Check the validity of the input parameters.

1. If (*requested_instantiation_security_strength* > 256) then **Return** ("Invalid *requested_instantiation_security_strength*", -1).
2. If (**len** (*personalization_string*) > 800), then **Return** ("*personalization_string* too long", -1).

Comment : Select the prime field curve in accordance with the *requested_instantiation_security_strength*

3. If *requested_instantiation_security_strength* ≤ 112, then
~~{*security_strength* = 112; *seedlen* = 256; *outlen* = 240;
min_entropy_input_len = 256}~~

Else if (*requested_instantiation_security_strength* ≤ 128), then

{*security_strength* = 128; *seedlen* = 256; *outlen* = 240;
min_entropy_input_len = 256}

Else if (*requested_instantiation_security_strength* ≤ 192), then

{*security_strength* = 192; *seedlen* = 384; *outlen* = 368;
min_entropy_input_len = 384}

Else {*security_strength* = 256; *seedlen* = 521; *outlen* = 504;
min_entropy_input_len = 528}.

4. ~~Select the appropriate elliptic curve from Appendix A using the Table in Appendix F.5 to obtain the domain parameters p, a, b, n, P , and Q .~~

Comment: Request *entropy_input*.

5. (*status*, *entropy_input*) = **Get_entropy_input** (*security_strength*, *min_entropy_input_length*, 1000).
6. If (*status* ≠ "Success"), then **Return** ("Failure indication returned byCatastrophic failure of the *entropy_input* source:" || *status*, -1).
7. (*status*, *instantiation_nonce*) = **Get_entropy_input** (*security_strength*/2, *security_strength*/2, 1000).
8. If (*status* ≠ "Success"), then **Return** ("Catastrophic failure of Failure indication returned by the random nonce source:" || *status*, -1).

Comment: Perform the instantiate algorithm.

9. *seed_material* = *entropy_input* || *instantiation_nonce* || *personalization_string*.

10. *s* = **Hash_df** (*seed_material*, *seedlen*).

11. ~~*r_old* = $\phi(x(s * Q))$.~~

12. ~~*block_counter* = 0.~~

Comment: Find an unused internal state and save the initial values.

12. (*status*, *state_handle*) = **Find_state_space** ().

13. If (*status* ≠ "Success"), then **Return** (*status*, -1).

14. ~~*internal_state* (*state_handle*) = {*s*, *seedlen*, *p*, *a*, *b*, *n*, *P*, *Q*, *r_old*, *block_counter*, *security_strength*}.~~

15. **Return** ("Success", *state_handle*).

F.5.2 Reseeding a Dual_EC_DRBG Instantiation

The implementation is designed to return a text message as the status when an error is encountered.

Reseed_Dual_EC_DRBG_Instantiation (...):

Input: integer *state_handle*, string *additional_input_string*.

Output: string *status*.

Process:

Comment: Check the input parameters.

1. If $((state_handle < 0) \text{ or } (state_handle > 9) \text{ or } (internal_state(state_handle).security_strength = 0))$, then **Return** ("State not available for the *state_handle*").
2. If $(len(additional_input) > 800)$, then **Return** ("Additional_input too long").

Comment: Get the appropriate *state* values for the indicated *state_handle*.

3. $s = internal_state(state_handle).s$, $seedlen = internal_state(state_handle).seedlen$, $security_strength = internal_state(state_handle).security_strength$.

Comment: Request new *entropy_input* with the appropriate entropy and bit length.

3. $(status, entropy_input) = \text{Get_entropy_input}(security_strength, min_entropy_input_length, 1000)$.
4. If $(status \neq \text{"Success"})$, then **Return** ("Catastrophic failure of Failure indication returned by the entropy source:" || *status*).

Comment: Perform the reseed algorithm.

-
5. $seed_material = pad8(s) || entropy_input || additional_input$.

6. $s = \text{Hash_df}(seed_material, seedlen)$.

Comment: Update the changed values in the *state*.

7. $internal_state(state_handle).s = s$.
8. $internal_state.block_counter = 0$.
9. **Return** ("Success").

F.5.3 Generating Pseudorandom Bits Using Dual_EC_DRBG

The implementation returns a *Null* string as the pseudorandom bits if an error is encountered.

Dual_EC_DRBG (...):

Input: integer (*state_handle*, *requested_security_strength*, *requested_no_of_bits*),
bitstring *additional_input*.

Output: string *status*, bitstring *pseudorandom_bits*.

Process:

Comment: Check for an invalid *state_handle*.

1. If $((state_handle < 0) \text{ or } (state_handle > 9) \text{ or } (internal_state(state_handle) = 0))$, then **Return** ("State not available for the *state_handle*", *Null*).

Comment: Get the appropriate *state* values for the indicated *state_handle*.

2. $s = \text{internal_state}(\text{state_handle}).s$, $\text{seedlen} = \text{internal_state}(\text{state_handle}).\text{seedlen}$, $P = \text{internal_state}(\text{state_handle}).P$, $Q = \text{internal_state}(\text{state_handle}).Q$, $r_old = \text{internal_state}(\text{state_handle}).r_old$, $\text{block_counter} = \text{internal_state}(\text{state_handle}).\text{block_counter}$.

Comment: Check the rest of the input parameters.

3. If ($\text{requested_number_of_bits} > 1000$), then **Return** ("Too many bits requested", *Null*).
4. If ($\text{requested_security_strength} > \text{security_strength}$), then **Return** ("Invalid requested_strength", *Null*).
5. If ($\text{len}(\text{additional_input}) > 800$), then **Return** ("Additional_input too long", *Null*).

Comment: Check whether a reseed is required.

6. If ($\text{block_counter} + \left\lceil \frac{\text{requested_number_of_bits}}{\text{outlen}} \right\rceil > 10,0002^{32}$), then

6.1 **Reseed_Dual_EC_DRBG_Instantiation** (*state_handle*, *additional_input*).

6.2 If ($\text{status} \neq \text{"Success"}$), then **Return** (*status*).

6.3 $s = \text{internal_state}(\text{state_handle}).s$, $\text{block_counter} = \text{internal_state}(\text{state_handle}).\text{block_counter}$.

6.4 $\text{additional_input} = \text{Null}$.

Comment: Execute the generate algorithm.

7. If ($\text{additional_input} = \text{Null}$) then $\text{additional_input} = 0$

Comment: *additional_input* set to *m* zeroes.

Else $\text{additional_input} = \text{Hash_df}(\text{pad8}(\text{additional_input}), \text{seedlen})$.

Comment: Produce *requested_no_of_bits*, *outlen* bits at a time:

8. $\text{temp} = \text{the Null string}$.
9. $i = 0$.
10. $t = s \oplus \text{additional_input}$.
11. $s = \phi(x(t * P))$.

12. $r = \varphi(x(s * Q))$.

13. If $(r = r_old)$, then **Return** ("ERROR: outputs match", *Null*).

~~14. $r_old = r$.~~

~~15. $temp = temp \parallel$ (rightmost $outlen$ bits of r).~~

~~16. $additional_input = 0^{seedlen}$.~~ Comment: *seedlen* zeroes; *additional_input* is added only on the first iteration.

~~17. $block_counter = block_counter + 1$.~~

~~18. $i = i + 1$.~~

~~19. If $(len(temp) < requested_no_of_bits)$, then go to step 10.~~

~~20. $pseudorandom_bits = Truncate(temp, i \times outlen, requested_no_of_bits)$.~~

Comment: Update the changed values in the *state*.

~~21. $internal_state.s = s$.~~

~~22. $internal_state.r_old = r_old$.~~

~~23. $internal_state.block_counter = block_counter$.~~

~~24. **Return** ("Success", *pseudorandom_bits*).~~