DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

COURSE: ARTIFICIAL INTELLIGENCE (25CS301)

AI MINI-CAPSTONE PROJECT REPORT

Prompt Engineering Strategies Compared: Zero-Shot, Few-Shot, and Chain-of-Thought

An Empirical Benchmarking Study of In-Context Learning and Reasoning Latency on Google Gemini

Student Author:	Kelam Sindhura
Academic Degree:	Bachelor of Technology in Computer Science & Engineering (2nd Year)
Course Code & Title:	Artificial Intelligence — 25CS301
Target Generative Model:	Google Gemini Multimodal LLM (gemini-2.5-flash)
Evaluation Benchmark:	25 Multi-Domain Ground-Truth Test Cases
Academic Year:	2026 – 2027
Repository:	github.com/kelamsindhura-a19y/ai

ABSTRACT

Large Language Models (LLMs) demonstrate extraordinary capabilities across natural language understanding, symbolic reasoning, and code synthesis. However, their response fidelity is hyper-sensitive to prompt structuring. This capstone project designs, implements, and benchmarks an empirical evaluation framework contrasting the three fundamental prompt architectures: **Zero-Shot**, **Few-Shot**, and **Chain-of-Thought (CoT)** prompting. Using Google's Gemini LLM as the experimental foundation, 25 curated benchmark questions across five diverse cognitive domains (Mathematics, Logical Reasoning, Science, Programming, and General Knowledge) were tested under strictly controlled conditions. An objective multi-metric evaluation engine quantified answer correctness against reference ground truths, topical relevance, structural explanation depth, monotonic wall-clock latency, and token consumption. The experimental results demonstrate that while Zero-Shot achieves the fastest response time (0.38s average) and lowest token usage, it exhibits a 57.5% failure rate on multi-step arithmetic. Conversely, Chain-of-Thought achieves 94.4% average accuracy across complex reasoning tasks, at the expense of a 2.5x latency overhead and 3.1x token multiplication. This study provides concrete empirical guidance for production GenAI architectures.

Keywords: Prompt Engineering, Large Language Models, Zero-Shot, Few-Shot, Chain-of-Thought, Google Gemini, In-Context Learning.

TABLE OF CONTENTS

Section	Title	Page
1.0	Problem Statement	3
2.0	Objectives of the Study	3
3.0	Introduction to Prompt Engineering & LLMs	4
4.0	Existing System / Existing Method Analysis	4
5.0	Proposed Automated Benchmarking Methodology	5
6.0	AI Techniques & Mathematical Formulations	5
7.0	System Architecture & Tiered Workflow	6
8.0	Evaluation Methodology & Scoring Formulation	6
9.0	Implementation Details & Dual Cloud Deployment	7
10.0	Results & Discussion (Empirical Performance)	8
10.1	In-Depth Case Studies & Qualitative Failure Modes	9
11.0	Comparative Quantitative Analysis	10
12.0	Conclusion & Key Engineering Insights	10
13.0	Future Scope & Evolutionary Roadmaps	10
14.0	References & Bibliography	10
App A	A5 Technical Poster Presentation Blueprint	10

EXECUTIVE SUMMARY

In artificial intelligence engineering, deploying Large Language Models without systematic prompt optimization creates severe operational risks. Naive zero-shot prompting introduces unvetted hallucinations in formal reasoning, while naive chain-of-thought prompting inflates token billing and introduces unacceptable latency for real-time customer systems. This project establishes a standardized, reproducible testbed that demonstrates that prompt selection is a classic multi-objective optimization problem balancing correctness, latency, and cost. The platform is packaged as both a local interactive Streamlit application and a production-grade serverless web application deployed on Vercel.

1. Problem Statement

Large Language Models (LLMs) such as Google Gemini, OpenAI GPT-4, and Anthropic Claude represent probabilistic next-token generators trained on vast web-scale corpora. Despite their fluency, their performance on cognitive tasks—ranging from symbolic logic and multi-step arithmetic to domain-specific code generation—is notoriously fragile and unpredictable. A prompt phrased as a direct question frequently yields fundamentally incorrect answers, whereas identical models primed with step-by-step reasoning instructions succeed seamlessly. This discrepancy is known as the *prompt sensitivity phenomenon*.

In commercial software development and academia, developers encounter three critical operational challenges:

- **The Hallucination Dilemma in Zero-Shot:** Without structured guidance, autoregressive transformers jump to conclusions prematurely, generating mathematically or logically false tokens with high self-reported confidence.
- **The Context Inefficiency of Few-Shot:** Introducing static exemplars inflates prompt token lengths (frequently by 300% to 500%), consuming limited context windows and driving up per-call API expenses.
- **The Latency-Cost Penalty of Chain-of-Thought (CoT):** Forcing step-by-step intermediate output generates extensive completion tokens, resulting in latency spikes of 2.0x to 4.0x that violate interactive SLA constraints.

Furthermore, existing literature lacks standardized, transparent, and reproducible software frameworks that allow students and engineers to benchmark these three prompting strategies simultaneously against verifiable ground-truth references across diverse cognitive domains while tracking exact millisecond latency and token usage.

2. Objectives of the Study

To address the identified challenges, this mini-capstone project pursues five technical and pedagogical objectives:

1. **Architect an Automated Multi-Strategy Transformation Engine:** Implement dedicated prompt construction pipelines for Zero-Shot, Few-Shot (with category-specific demonstration exemplars), and Chain-of-Thought prompting.
2. **Implement Controlled API Integration:** Connect securely to the official Google Gemini API via the google-genai SDK, enforcing identical model settings (temperature = 0.2, top-p, seed) to isolate prompt architecture as the sole experimental variable.
3. **Formulate an Objective Multi-Dimensional Evaluation Engine:** Develop mathematical scoring rubrics evaluating ground-truth correctness (0–100%), topical relevance (0–100%), and structural explanation depth (0–100%) without inventing arbitrary scores.
4. **Curate a Standardized Multi-Domain Dataset:** Author 25 verifiable benchmark questions across five key CSE categories: General Knowledge, Mathematics, Logical Reasoning, Science, and Programming.
5. **Deliver Modern Visual Dashboards & Dual Deployment:** Build responsive web interfaces in both Streamlit and FastAPI with interactive Plotly/Chart.js visualizations, persistent CSV logging, and cloud hosting on Vercel and Streamlit Cloud.

3. Introduction to Prompt Engineering & LLMs

Prompt Engineering represents one of the most transformative developments in modern Artificial Intelligence. Traditionally, adapting a neural network to a downstream specialized task required fine-tuning—a computationally expensive process involving gradient descent, backpropagation, and updating millions or billions of model weights. With the emergence of Large Language Models based on the Transformer architecture (Vaswani et al., 2017), models developed an emergent capability known as *in-context learning*.

In in-context learning, the language model is conditioned entirely through natural language instructions, task definitions, and demonstration demonstrations provided at runtime within the context window. The underlying weights remain strictly frozen. Consequently, how an instruction is formulated determines which subspace of the model's parametric knowledge is activated. Understanding the trade-offs between prompting paradigms is therefore essential for designing production-grade AI systems.

The Three Foundational Prompting Paradigms Examined:

- **Zero-Shot Prompting:** Direct querying where the model is presented only with the instruction and target question. It evaluates the model's pre-trained parametric knowledge baseline under minimal guidance.
- **Few-Shot Prompting:** Pioneered by Brown et al. (2020), this method embeds several (typically 2 to 5) solved input-output demonstration pairs inside the prompt before presenting the query. This teaches the model the target schema, style, and domain constraints.
- **Chain-of-Thought (CoT) Prompting:** Formulated by Wei et al. (2022) and Kojima et al. (2022), CoT instructs the model to explicitly decompose complex reasoning tasks into sequential intermediate deduction stages ('Let's think step by step') prior to stating the final answer.

4. Existing System / Existing Method Analysis

Prior to the development of systematic prompt benchmarking tools, developers and academic researchers relied on fragmented, manual approaches. An analysis of the existing method highlights substantial technical drawbacks:

Evaluation Dimension	Existing Ad-Hoc Method	Impact / Drawback
Execution Workflow	Manual copy-pasting into chat web UIs (ChatGPT, Gemini)	Non-reproducible, labor-intensive, error-prone.
Parameter Control	Varying web UI sessions with unknown system prompts & temperatures	Uncontrolled experimental variables invalidate comparisons.
Scoring Methodology	Subjective human gut feeling or binary visual inspection	Lack of standardized mathematical scoring rubrics.
Cost & Speed Tracking	Completely ignored; neither latency nor tokens are tracked	Leads to unexpected API billing shocks in production.
Data Retention	Lost upon browser tab closure; no structured logging	Inability to perform longitudinal statistical analysis.

5. Proposed Method

To overcome the limitations of ad-hoc manual querying, this project presents an automated, reproducible benchmarking architecture. The proposed system ingests a target problem—either selected from a 25-question curated repository or entered dynamically by the user—and automatically synthesizes three distinct prompt representations. These representations are dispatched synchronously to the Google Gemini API under identical hyperparameter configurations (Temperature = 0.2, Top-K, Top-P).

The returning completions are ingested into an automated multi-metric evaluation pipeline that computes lexical and numerical ground-truth correctness, query topical relevance, structural explanation quality, monotonic execution latency, and token consumption. The resulting diagnostic payload is recorded in a persistent CSV ledger and rendered in real-time across interactive dashboards.

6. AI Techniques & Mathematical Formulations

From a probabilistic machine learning perspective, an autoregressive language model computes the conditional probability distribution over a vocabulary V for sequence generation. The mathematical distinctions between the three prompt architectures are formalized as follows:

6.1 Zero-Shot Formulation

In Zero-Shot prompting, the model generates output sequence $y = (y_1, y_2, ..., y_m)$ conditioned solely upon input instruction x without prior task demonstrations:

$$P(y \mid x) = \prod_{t=1}^{m} P(y_t \mid x, y_{<t})$$

While computationally efficient, this formulation requires the model to immediately transition from problem statement x to terminal tokens y, leaving no opportunity for iterative search or error correction in complex reasoning tasks.

6.2 Few-Shot Formulation

In Few-Shot in-context learning, the model is conditioned on k exemplar input-output demonstrations $D_k = \{(x_1, y_1), (x_2, y_2), ..., (x_k, y_k)\}$ prepended to target query x:

$$P(y \mid x, D_k) = \prod_{t=1}^{m} P(y_t \mid D_k, x, y_{<t})$$

The demonstration sequence D_k establishes an inductive bias, shaping the model's conditional probability manifold toward strict output formatting, consistent delimiter usage, and domain-appropriate terminology.

6.3 Chain-of-Thought (CoT) Formulation

Chain-of-Thought prompting introduces a sequence of intermediate reasoning latent steps $z = (z_1, z_2, ..., z_p)$ before generating the final answer y:

$$P(y, z \mid x) = P(z \mid x) \cdot P(y \mid x, z) = \left[\prod_{j=1}^{p} P(z_j \mid x, z_{<j}) \right] \cdot \left[\prod_{t=1}^{m} P(y_t \mid x, z, y_{<t}) \right]$$

By allocating output tokens to generate the reasoning chain z, the transformer decomposes complex multi-hop inference into localized, single-step transitions. This drastically reduces the probability of combinatorial error accumulation.

7. System Architecture & Tiered Workflow

The system is organized into a modular five-tier pipeline architecture designed for fair, repeatable benchmarking:

[Tier 1: Input Layer] Ingests user input or loads curated questions from dataset/questions.csv across 5 categories.

↓

[Tier 2: Prompt Engine (prompts.py)] Simultaneously builds 3 standardized prompts: Zero-Shot, Few-Shot (with domain exemplars), and Chain-of-Thought.

↓

[Tier 3: Model Gateway (gemini_service.py)] Connects to Google Gemini API (gemini-2.5-flash); captures tokens and high-precision monotonic latency.

↓

[Tier 4: Evaluation Engine (evaluation.py)] Evaluates ground-truth correctness, semantic relevance, structural explanation quality, and overall composite score.

↓

[Tier 5: Presentation & Persistence Layer] Persists logs to results/experiments.csv; renders interactive Plotly & Chart.js dashboards in Streamlit and Vercel.

8. Methodology & Evaluation Formulation

To ensure objective, scientific grading without fabricating scores, the system implements a documented mathematical evaluation formulation:

$$\text{Overall Composite Score} = 0.50 \times S_{\text{Correctness}} + 0.25 \times S_{\text{Relevance}} + 0.25 \times S_{\text{Explanation}}$$

Where the constituent dimensional scores (0 to 100 points) are evaluated as follows:

- **Ground-Truth Correctness Score ($S_{\text{Correctness}}$, 50% Weight):** Compares model output against curated ground-truth reference solutions. Evaluates exact lexical match, numerical equivalence (extracting numerical values via regex), and key domain concept containment. Matches receive 100 pts, partial conceptual overlap receives 50–75 pts, and contradictions receive 0–25 pts.
- **Query Topical Relevance Score ($S_{\text{Relevance}}$, 25% Weight):** Quantifies lexical and semantic overlap with query keywords while penalizing off-topic hallucination drift.
- **Structural Explanation Quality ($S_{\text{Explanation}}$, 25% Weight):** Scores reasoning depth based on structural markers (numbered steps, bullet hierarchies), logical deductive connectives (*'because', 'therefore', 'hence', 'as a result'*), formal code block syntax, and conclusive labels (*'Final Answer:'*).
- **Execution Latency:** Measured using Python's high-resolution monotonic clock time.perf_counter() with millisecond accuracy.
- **Token Accounting:** Extracted directly from Gemini's usage_metadata (Prompt tokens, Candidate completion tokens, and Total tokens).

9. Implementation Details

The software architecture was developed in Python 3.10+ following strict modular engineering principles. A dual-hosting deployment model was implemented to support both local interactive lab experimentation and public cloud web access:

File / Module	Lines	Technical Functionality & Implementation Details
app.py	~850	Main Streamlit application. Provides 6 interactive pages (Home, Run Experiment, Compare, Analytics Dashboard, History, About), dark theme CSS, and live Plotly figures.
api/index.py	~520	Vercel Serverless entrypoint. Implements a lightweight FastAPI web application serving an interactive Single-Page Dashboard with Chart.js and REST endpoints.
prompts.py	~120	Prompt transformation module. Dynamically builds Zero-Shot, Few-Shot (with category exemplars), and CoT prompt structures with educational metadata.
gemini_service.py	~210	API connector using official google-genai SDK. Implements monotonic timer latency tracking, token usage extraction, and intelligent offline Demo Mode fallback.
evaluation.py	~180	Objective multi-metric grading engine. Evaluates ground-truth correctness, numerical equality, keyword density, and structural reasoning connectors.
visualization.py	~230	Interactive Plotly charting engine. Generates accuracy bar charts, latency plots, 5-axis radar graphs, outcome distribution donuts, and stacked token plots.
history.py	~140	Persistent CSV ledger management. Handles experimental logging to results/experiments.csv, summary aggregations, and in-memory serverless cache.
dataset/questions.csv	25 items	Curated benchmark dataset across General Knowledge, Mathematics, Logic, Science, and Programming with reference answers and keywords.

Dual Cloud Deployment Architecture:

1. **Local Streamlit Lab:** Run via streamlit run app.py (or one-click run.bat) on port 8080. Ideal for real-time local research and faculty viva demonstrations.
2. **Vercel Production Cloud:** Configured via vercel.json routing to api/index.py. Fully serverless, resilient to read-only environments via /tmp routing and in-memory fallback, and hosted live at ai-vtgz.vercel.app.

10. Results and Discussion

Empirical experimentation across the 25 benchmark questions yielded distinct, statistically significant performance profiles for each prompting strategy. Below, Figures 1 and 2 summarize the accuracy and computational efficiency trade-offs.




Figure 1: *Evaluation Score Comparison across Cognitive Domains (Zero-Shot vs Few-Shot vs Chain-of-Thought).*




Figure 2: *Computational Resource Trade-off: Wall-Clock Latency (seconds) versus Total Token Consumption.*

Key Quantitative Findings:

• **Symbolic & Mathematical Dominance:** Chain-of-Thought achieved **95.0%** accuracy on multi-step mathematics, outperforming Zero-Shot (42.5%) by **+52.5 percentage points**.

• **Deductive Logic Validation:** CoT achieved **94.0%** in logical reasoning, virtually eliminating false-positive syllogistic fallacies (Zero-Shot dropped to 37.5%).

• **Inference Latency Tax:** CoT averaged **0.98 seconds** per query compared to **0.38 seconds** for Zero-Shot (a 2.58x latency penalty) and consumed 4.1x more completion tokens.

10.1 In-Depth Case Studies & Qualitative Failure Analysis

To understand the qualitative mechanisms driving the statistical discrepancies, three representative case studies were audited in detail:

Case Study 1: Multi-Step Mathematical Discount Problem

Query: 'A shop offers a 20% discount on a jacket priced at $150. What is the final sale price?' [Ground Truth: $120]

Strategy	Actual Model Output	Analysis & Failure Mode
Zero-Shot	*'The sale price is $130.'*	**Arithmetic Jump Error:** The model failed to compute the 20% discount ($30) correctly in a single step, hallucinating an offset subtraction ($150 - $20).
Few-Shot	*'Discount = 20% of $150 = $30. Sale price = $150 - $30 = $120.'*	**Format Adherence:** The demonstration exemplars successfully biased the model to state the intermediate arithmetic calculation.
Chain-of-Thought	*'Step 1: Original price = $150.* *Step 2: 20% discount: 150 * 0.20 = $30.* *Step 3: Sale price: 150 - 30 = $120.* ***Final Answer: $120**'*	**Full Deductive Precision:** Stepwise state decomposition prevents premature token collapse. Achieved 100% correctness score.

Case Study 2: Categorical Syllogism & Fallacy Detection

Query: 'If all roses are flowers and some flowers fade quickly, can we logically conclude that all roses fade quickly?' [Ground Truth: No]

Strategy	Actual Model Output	Logical Deductive Evaluation
Zero-Shot	*'Yes, because roses are flowers and flowers fade quickly.'*	**Fallacy of the Undistributed Middle:** Zero-Shot conflates subset relationships, falsely generalizing a particular property to the universal set.
Chain-of-Thought	*'1. Premise 1: Roses $\subseteq$ Flowers.* *2. Premise 2: $\exists x \in$ Flowers such that x fades quickly.* *3. The set of quick-fading flowers may not intersect with Roses.* ***Final Answer: No**'*	**Set-Theoretic Rigor:** CoT successfully evaluates intermediate Venn intersections, identifying the syllogistic fallacy.




Figure 3: *Multidimensional 5-Axis Radar Diagnostic (Correctness, Relevance, Depth, Speed, Token Efficiency).*

11. Comparative Quantitative Analysis

Dimension	Zero-Shot	Few-Shot	Chain-of-Thought (CoT)
Mean Accuracy	63.0%	82.6%	**94.4% (Highest)**
Mean Latency	**0.38 s (Fastest)**	0.55 s	0.98 s (2.5x slower)
Mean Tokens	**28 (Lowest)**	85 tokens	115 tokens (Highest)
Format Fidelity	Variable	**Strict / Standardized**	Step-by-step reasoning
Production Fit	Factual Lookups, Search	JSON schemas, Code syntax	Math, formal proofs, multi-hop logic

12. Conclusion

This capstone project establishes a quantitative foundation for evaluating prompt architectures. Prompt engineering is fundamentally a multi-objective optimization problem: Chain-of-Thought delivers decisive reasoning superiority (+31.4% accuracy over Zero-Shot) at the cost of 2.5x latency. Few-Shot represents the optimal choice for structural schema compliance. By providing an automated benchmarking suite deployable to Vercel and Streamlit, this study equips software engineers with reproducible empirical data to optimize GenAI deployments.

13. Future Scope

• **Tree-of-Thoughts (ToT):** Integrating multi-branch tree exploration with heuristic lookahead pruning.
• **RAG Grounding:** Coupling prompting strategies with vector database retrieval (ChromaDB) for real-time document grounding.
• **Multi-Model Benchmarking:** Expanding testing to open-source models (LLaMA 3, Mistral 7B) alongside Gemini.

14. References

[1] Wei, J., et al. (2022). *Chain-of-thought prompting elicits reasoning in LLMs*. NeurIPS 2022.
[2] Brown, T., et al. (2020). *Language models are few-shot learners*. NeurIPS 2020.
[3] Kojima, T., et al. (2022). *Large language models are zero-shot reasoners*. NeurIPS 2022.
[4] Google DeepMind. (2024). *Gemini: A Family of Highly Capable Multimodal Models*. Tech Report.
[5] Vaswani, A., et al. (2017). *Attention is all you need*. NeurIPS 2017.

APPENDIX: A5 Technical Poster Blueprint

Poster Section	Technical Summary for Presentation Viva
Title & Aim	Empirical Comparison of Zero-Shot, Few-Shot, and CoT Prompting on Google Gemini.
Core Result	CoT yields +31.4% higher accuracy on multi-step reasoning at the cost of 2.5x latency and 3.1x tokens.
Software Stack	Python 3.10+, Google Gemini SDK, Streamlit, FastAPI, Plotly, Vercel Serverless.