Spatial

Tian Zhao

November 2018

1 Introduction

This document provides a guideline on implementing the Fringe module for Intel Arria10 boards. However, this guideline can be generalized to other FPGA platforms as well.

2 Environment Variables

This section includes specifications for environment variables being used in this documentation.

- *Spatial*: The spatial language.
- $SPATIAL\_HOME$: The home directory of your installed Spatial.
- $JAVA\_HOME$: The home directory of your installed Java.
- IP_SRC_HOME: The directory for storing source files of the *Accel* IP block.
- $FRINGE\_MEM\_BASEADDR$: The base address for shared DRAM between $Host$ and *Accel*.
- $FRINGE\_SCALAR\_BASEADDR$: The base address for shared registerfile between $Host$ and *Accel*.
- *Accel*: The accelerator hardware. In this document, the accelerator is the targeted Intel Arria 10 board.
- $Host$: The host CPU.
- $ArgIn$: The Spatial argument registers. This type of registers transfers scalars from $Host$ to *Accel*.
- *ArgOut*: The Spatial argument registers. This type of registers transfers scalars from *Accel* to $Host$.
- $DRAM$: The Spatial DRAMs. DRAMs can transfer data bidirectionally between $Host$ and *Accel*.

3 Spatial App Setup

We use *Lab*1*Part*1*RegExampleExample* as the driving application in this document. The *Spatial* implementation can be found in Figure **??**. The code block between line 11 to 17 creates two *ArgIn* registers and write two scalar values into them. The code block between line 19 to 23 executes *Accel* and writes the result to an *ArgOut*. Line 25 fetches the result at *Host*.

4 Interface between *Host* and *Accel*

Accel and *Host* share a memory-mapped register file and a DRAM. The register file is used for storing *ArgIn* and *ArgOut* registers. *Accel* can access this register file using the Avalon-MM lite interface. *Host* can access this register file by memory-mapping it into *Host*'s Virtual Memory Space. The DRAM is used for transferring data stored in *DRAM* objects. *Accel* can access this DRAM using the AXI4-MM interface. *Host* can access this DRAM by memory-mapping it into *Host*'s Virtual Memory Space.

4.1 Generating *Accel* Code from *Spatial*

A *Spatial* design can be translated into a *Verilog* design. The Top level of this design is exposed in the form of an AXI4 master interface and an Avalon lite slave interface. The following commands will generate the *Verilog* design for *Lab*1*Part*1*RegExample*.

```
cd $SPATIAL_HOME
sbt -batch "apps/run-main Lab1Part1RegExample --synth"
cd gen/Lab1Part1RegExample
sbt "runMain top.Instantiator --verilog --testArgs arria10"
```

We can find the generated *Verilog* design by going to:

```
cd $SPATIAL_HOME/gen/Lab1Part1RegExample/verilog-arria10
```

The *Top.v* file includes the generated design. Notice that *SRFF* is a reserved keyword in Intel's toolchain. To avoid naming conflicts, we need to change the name to *SRFF_sp*:

```
sed -i 's/SRFF/SRFF_sp/g' Top.v
```

Now we have the generated design of *Lab*1*Part*1*RegExample* in *Top.v*. Next, we need to integrate it into the rest of the system. We wrap the design file, *Top.v*, as an IP in Intel's Platform Designer. The Platform Designer will handle the process of creating interconnects. The next session gives an example on how to create such IP.

```
import spatial.dsl._
import org.virtualized._


// Register
object Lab1Part1RegExample extends SpatialApp {
  type T = Int

  @virtualize
  def main() {
    val N = args(0).to[T]
    val M = args(1).to[T]
    val argRegIn0 = ArgIn[T]
    val argRegIn1 = ArgIn[T]
    setArg(argRegIn0, N)
    setArg(argRegIn1, M)
    val argRegOut = ArgOut[T]

    Accel {
      val argRegIn0Value = argRegIn0.value
      val argRegIn1Value = argRegIn1.value
      argRegOut := argRegIn0Value + argRegIn1Value
    }

    val argRegOutResult = getArg(argRegOut)
    println("Result = " + argRegOutResult)

    val gold = M + N
    println("Gold = " + gold)
    val cksum = gold == argRegOutResult
    println("PASS = " + cksum + "(Lab1Part1RegExample)")
  }
}
```

Figure 1: Lab1Part1RegExample. This application performs reading and writing $ArgIn, ArgOut$ registers

4.2 Creating an IP for *Accel*

In this section, we demonstrate the process of wrapping the generated *Verilog* design in an IP and export it to Intel's Platform Designer. In the starter project, we provide a folder called *ip_src* and a *tcl* script called *Top_hw.tcl*. *ip_src* contains source files for building this IP. *Top_hw.tcl* specifies the interfaces to communicate with this IP. Specifically, the exposed interfaces are Avalon-MM slave and AXI4-MM master. You can find more information about these interfaces in the *tcl* script.

After generating *Top.v*, you can copy it into *ip_src*. Now you can import *Accel* as an IP in your *Quartus* project.

```
cp Top.v $IP_SRC_HOME/ip_src/
```

A little more information is needed for the *Host* software. When instantiating the *Accel* IP in your design, the Platform Designer will ask for the base addresses of the Avalon-MM and the AX44-MM interfaces. These base addresses will be used by the *Host* code for reading and writing the register files and the memory-mapped DRAM. For convenience, we assume that the base address of Avalon-MM is at $FRINGE\_SCALAR\_BASEADDR$, and the base address of AXI4-MM is at $FRINGE\_MEM\_BASEADDR$.

5 Supporting *Host* Code of *Spatial*

In this tutorial, we assume that the *Host* uses *ARM* compilers. If you are using a different compiler for *cpp*, you can change the compiler options in $\$SPATIAL\_HOME/gen/Lab1Part1RegExample/scripts/arria10.mk$.

5.1 *Host* API Specifications

First, move into the *Host* code directory by running:

```
cd $SPATIAL_HOME/gen/Lab1Part1RegExample/cpp/
```

The logic for running *Accel* is autogenerated by *Spatial* and is stored in *TopHost.cpp*. *TopHost.cpp* first loads the bitstream to *Accel* using *load* function. Then, it sets the *ArgIn*, *ArgOut* registers using *setArg* functions. If your design contains *DRAM*, *TopHost* will also set addresses for the *DRAM* using *setArg* functions. To move data from *Host* to *Accel*, *TopHost* will call *memcpy*. After the setup is done, *TopHost* calls *run* to start *Accel*. Once *Accel* finishes, *TopHost* will call *getArg* to collect the final results. If your design contains *DRAM*, *TopHost* will call *memcpy* to copy data from *Accel* to *Host*. *setArg* and *getArg* functions are implemented using *readReg* and *writeReg* functions. *run* function is implemented using *setArg*, *getArg*.

We can see that *load*, *readReg*, *writeReg*, *memcpy* are the key functions for *TopHost* to control *Accel*. To support *Spatial*'s *Host* code on your platform, you will need to implement these functions as shown in Table **??**. These *API*s are defined in as shown in $fringeArria10/FringeContextBase.h$ You will also

void load()	Loads a bitstream to *Accel*.
uint64_t malloc(*size_t* bytes)	Allocates *bytes* memory.
void free(*uint64_t* buf)	Free the memory pointer *buf*.
void memcpy(*uint64_t* devmem, *void* hostmem, *size_t* size)	*Accel* side memcpy. Memcpy data of *size* from *devmem* to a virtual address at *host*.
void memcpy(*void* hostmem, *uint64_t* devmem, *size_t* size)	*Host* side memcpy. Memcpy data of *size* from *hostmem* to a physcial address at *devmem*.
void writeReg(*uint32_t* reg, *uint64_t* data)	Write *data* to the register located at *reg* starting from the scalar offset.
uint64_t readReg(*uint32_t* reg)	Read data stored at the register located at *reg* starting from the scalar offset.

Table 1: Specifications for *Host* Functions

need to change $FRINGE\_SCALAR\_BASEADDR$, $FRINGE\_MEM\_BASEADDR$ in $fringeArria10/Arria10AddressMap.h$.

Table **??** provides a specifications on what each function does. For a detailed example, check $fringeArria10/FringeContextArria10.h$. Figure **??** shows the complete API.

After implementing these functions, you can generate an executable for the *Host* code and try to use it to control the execution of *Accel*. If the flow works, you will need to update the templates for *Host* and *Accel* generation. The *Host* templates are stored at:

```
$SPATIAL_HOME/spatial/core/resources/cppgen/fringeArria10/
```

The *Accel* templates are stored at:

```
$SPATIAL_HOME/spatial/core/resources/chiselgen/ \
    template-level/fringeArria10/build/
```

Then, you will need to update the project resources by running:

```
cd $SPATIAL_HOME
bash bin/update_resources.sh
```

You will also need to update the $Makefile$ with your build flow. The $Makefile$ is at

```
$SPATIAL_HOME/spatial/core/resources/chiselgen/app-level/Makefile
```

6 OPAE Implementation

6.1 *Host*

The OPAE flow on the *Host* side can be decoupled into the following stage. Each stage can be implemented in a *FringeContext* function as specified in Table **??**.

- Discover / Search AFU. This stage should be implemented in the constructor of $FringeContextArria10$ class.

```
#ifndef __FRINGE_CONTEXT_BASE_H__
#define __FRINGE_CONTEXT_BASE_H__

template <class T>
class FringeContextBase {
public:
  T *dut = NULL;
  std::string path = "";

  FringeContextBase(std::string p) {
    path = p;
  }
  virtual void load() = 0;
  virtual uint64_t malloc(size_t bytes) = 0;
  virtual void free(uint64_t buf) = 0;
  virtual void memcpy(uint64_t devmem, void* hostmem, size_t size) = 0;
  virtual void memcpy(void* hostmem, uint64_t devmem, size_t size) = 0;
  virtual void run() = 0;
  virtual void writeReg(uint32_t reg, uint64_t data) = 0;
  virtual uint64_t readReg(uint32_t reg) = 0;
  virtual uint64_t getArg(uint32_t arg, bool isIO) = 0;
  virtual void setArg(uint32_t reg, uint64_t data, bool isIO) = 0;
  virtual void setNumArgIns(uint32_t number) = 0;
  virtual void setNumArgIOs(uint32_t number) = 0;
  virtual void setNumArgOutInstrs(uint32_t number) = 0;
  virtual void setNumArgOuts(uint32_t number) = 0;
  virtual void flushCache(uint32_t kb) = 0;

  ~FringeContextBase() {
//    delete dut;
  }
};

// Fringe error codes


// Fringe APIs - implemented only for simulation
void fringeInit(int argc, char **argv);

#endif
```

Figure 2: FringeContextBase.h



Figure 3: Example System Diagram in Platform Designer

- Acquire ownership of an AFU. This stage should be implemented in the constructor of $FringeContextArria10$ class.
- Map AFU registers to user space. This stage should be implemented in the constructor of $FringeContextArria10$ class.
- Allocate / Define shared memory Space. This stage should be implemented in the constructor of $FringeContextArria10$ class.
- Start / Stop computation on AFU and wait for results. Implement $writeReg$, $readReg$ and $memcpy$ functions in $FringeContextArria10$. Spatial $Host$ will automatically start and stop the communication on AFU. More details can be found in the run function defined in $FringeContextArria10$ class.
- Deallocated shared memory. This stage should be implemented in the $free$ function.
- Relinquish ownership of an AFU. This stage should be implemented in the deconstructor of $FringeContextArria10$.

6.2 *Accel*

The OPAE AFU side can communicate with the $Host$ through Avalon-MM (for scalar communication) and AXI4-MM (for DRAM communication). The system diagram is shown in Figure **??**. The *Accel* IP is instantiated as Top_1. You can connect $io\_M\_AXI\_0$ to $EMIF$ via Avalon-MM and $io\_S\_AVALON\_0$ to the CCI-P bus. The Platform Designer will translate the protocol automatically once you make the connection.