

Documentation of Python Files

Kelsey O'Donnell

July 20, 2024

Contents

1	Introduction	2
2	Python Script Overview	2
3	Detailed Script Documentation	3
3.1	gen_smf_1d.py	3
3.2	calc_area_of_ft_data.py	3
3.3	calc_legett_at_t.py	4
3.4	calc_oscill_period_at_t.py	4
3.5	fourier_utils.py	4
3.6	gen_smf_2d.py	5
3.7	plot_density_evolution_at_t.py	5
3.8	plot_density_evolution_at_x.py	5
3.9	plot_ft_at_t.py	5
3.10	plot_ft_at_x.py	6
3.11	plot_intensity.py	6
3.12	plot_spatial_analysis_graphs_changing_p0.py	6
3.13	plot_spatial_ft_graphs_changing_p0.py	6
3.14	plot_temporal_analysis_graphs_changing_p0_at_x.py	7
3.15	plot_temporal_ft_graphs_changing_p0_at_x.py	7
3.16	snapshots1d_bec_intens.py	7
3.17	standard_data_utils.py	7

1 Introduction

This document provides detailed documentation for a collection of Python scripts. It includes information on how to run each script, the arguments they accept, and the purpose of each argument.

2 Python Script Overview

- `gen_smf_1d.py`
- `calc_area_of_ft_data.py`
- `calc_legett_at_t.py`
- `calc_oscill_period_at_t.py`
- `fourier_utils.py`
- `gen_smf_2d.py`
- `plot_density_evolution_at_t.py`
- `plot_density_evolution_at_x.py`
- `plot_ft_at_t.py`
- `plot_ft_at_x.py`
- `plot_intensity_2d.py`
- `plot_intensity.py`
- `plot_spatial_analysis_graphs_changing_p0.py`
- `plot_spatial_ft_graphs_changing_p0.py`
- `plot_temporal_analysis_graphs_changing_p0_at_x.py`
- `plot_temporal_ft_graphs_changing_p0_at_x.py`
- `snapshots1d_bec_intens.py`
- `standard_data_utils.py`

3 Detailed Script Documentation

3.1 `gen_smf_1d.py`

- **Description:** Generates a new $|\psi|^2$ dataset with one spatial dimension and one time dimension given some input parameters and arguments.
- **Prerequisites:**
 - Create a folder in `/patt1d_inputs` titled with the name of the dataset (can be named whatever you choose).
 - In this folder, you must have a file named `seed.in` which contains all of the initial values used to generate the dataset.
- **Usage:** `python gen_smf_1d.py -f <file name> -n <number of frames> -s <start p0> -e <end p0>`
- **Arguments:**
 - `-f` (required): The name of the file, which is the same name as the folder in `patt1d_inputs`.
 - `-n` (required): The number of frames/generated data with different p_0 values. If more than 1 is input, then you will have to specify the start and end p_0 values.
 - `-s` (required): The starting p_0 value to generate data for.
 - `-e` (required): The ending p_0 value to generate data for.
- **Output:**
 - A new folder with the inputted filename in `/patt1d_outputs`.
 - In this folder will be n `psi*.out` and `s*.out` files where n is the inputted `-n` argument.
 - If n is greater than 1, then the `psi` and `s` filenames will be formatted to have an index followed by the p_0 value at that index.
- **Next Steps:** Once this data is obtained, all of the other Python scripts can be used to analyze this data.

3.2 `calc_area_of_ft_data.py`

- **Description:** Calculates the area of FT data.
- **Usage:** `python calc_area_of_ft_data.py -f <filename> -x <x_position> -s <starting frequency position> -e <ending frequency position> [-i <frame_index>]`
- **Arguments:**

- `-f, --filename` (required): The name of the file to save to.
- `-x, --xpos` (required): The x coordinate to inspect the Fourier transform at.
- `-s, --start_f` (required): The starting frequency limit of integration.
- `-e, --end_f` (required): The ending frequency limit of integration.
- `-i, --frame_index` (optional): The index of the frame to plot.

3.3 `calc_legett_at_t.py`

- **Description:** Calculates Leggett at time t .
- **Usage:** `python calc_legett_at_t.py -f <filename> -t <time> [-i <frame_index>]`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-t, --time` (required): The time to inspect the amplitude evolution at.
 - `-i, --frame_index` (optional): The index of the frame to plot.

3.4 `calc_oscill_period_at_t.py`

- **Description:** Calculates the oscillation period at time t .
- **Usage:** `python calc_oscill_period_at_t.py -f <filename> -t <time> [-i <frame_index>]`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-t, --time` (required): The time to inspect the amplitude evolution at.
 - `-i, --frame_index` (optional): The index of the frame to plot.

3.5 `fourier_utils.py`

- **Description:** Utility functions for Fourier transforms.
- **Usage:** This file is not intended to be run directly. It contains functions used by other scripts.

3.6 `gen_smf_2d.py`

- **Description:** Generates 2D SMF data.
- **Usage:**
- **Arguments:**

–

3.7 `plot_density_evolution_at_t.py`

- **Description:** Plots density evolution over time.
- **Usage:** `python plot_density_evolution_at_t.py -f <filename> -t <time> [-i <index>]`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-t, --time` (required): The time to inspect the amplitude evolution at.
 - `-i, --index` (optional): The index of the frame to plot.

3.8 `plot_density_evolution_at_x.py`

- **Description:** Plots density evolution at a specific x position.
- **Usage:** `python plot_density_evolution_at_x.py -f <filename> -x <xpos> [-i <frame_index>] -t <trail_x_max>`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-x, --xpos` (required): The x-position coordinate to inspect the amplitude evolution at.
 - `-i, --frame_index` (optional): The index of the frame to plot.
 - `-t, --trail_x_max` (required): Specifies whether to follow the peaks that start at the required x position (`True` or `False`).

3.9 `plot_ft_at_t.py`

- **Description:** Analyzes PATT1D output data at a specific time.
- **Usage:** `python plot_ft_at_t.py -f <filename> -t <time> [-i <frame_index>]`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.

- `-t, --time` (required): The time to inspect the amplitude evolution at.
- `-i, --frame_index` (optional): The index of the frame to plot.

3.10 `plot_ft_at_x.py`

- **Description:** Analyzes PATT1D output data at a specific x position.
- **Usage:** `python plot_ft_at_x.py -f <filename> -x <xpos> [-i <frame_index>]`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-x, --xpos` (required): The x coordinate to inspect the Fourier transform at.
 - `-i, --frame_index` (optional): The index of the frame to plot.

3.11 `plot_intensity.py`

- **Description:** Plots PSI and S data from simulation outputs.
- **Usage:** `python plot_intensity.py -f <filename> [-i <frame_index>]`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-i, --frame_index` (optional): The index of the frame to plot.

3.12 `plot_spatial_analysis_graphs_changing_p0.py`

- **Description:** Analyzes and plots data from PATT1D outputs.
- **Usage:** `python plot_spatial_analysis_graphs_changing_p0.py -f <filename>`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.

3.13 `plot_spatial_ft_graphs_changing_p0.py`

- **Description:** Data analysis for 1D pattern formation.
- **Usage:** `python plot_spatial_ft_graphs_changing_p0.py -f <filename>`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.

3.14 `plot_temporal_analysis_graphs_changing_p0_at_x.py`

- **Description:** Analyzes temporal statistics of PATT1D outputs.
- **Usage:** `python plot_temporal_analysis_graphs_changing_p0_at_x.py -f <filename> -x <xpos>`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-x, --xpos` (required): The x coordinate to inspect the temporal statistics at.

3.15 `plot_temporal_ft_graphs_changing_p0_at_x.py`

- **Description:** Analyzes Fourier transforms of PATT1D outputs.
- **Usage:** `python plot_temporal_ft_graphs_changing_p0_at_x.py -f <filename> -x <xpos>`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.
 - `-x, --xpos` (required): The x coordinate to inspect the Fourier transform at.

3.16 `snapshots1d_bec_intens.py`

- **Description:** Generates snapshots of 1D BEC intensity.
- **Usage:** `python snapshots1d_bec_intens.py -f <filename>`
- **Arguments:**
 - `-f, --filename` (required): The name of the file to save to.

3.17 `standard_data_utils.py`

- **Description:** Standard utility functions for data manipulation.
- **Usage:** This file is not intended to be run directly. It contains functions used by other scripts.