



COLLEGE OF ENGINEERING, DESIGN AND PHYSICAL SCIENCES,
ELECTRONIC AND COMPUTER ENGINEERING

DISTRIBUTED COMPUTING SYSTEMS ENGINEERING

INTERIM REPORT

Conception and realization of a distributed and
automated computer vision pipeline

Michael Watzko

1841795

Supervisor:

Dr. Paul Kyberd

Date of Submission: September 15, 2019

Contents

1	Introduction	1
1.1	MEC-View?	2
1.2	The Tool	2
1.3	Defining the Problem Space	2
1.4	Analyzing the Problem Space	3
2	State of the art	5
2.1	Existing software solutions	5
2.1.1	Hadoop MapReduce	5
2.1.2	Quartz	5
2.1.3	Pipeline examples: Jenkins / GitLab	6
2.1.4	Camunda	6
2.1.5	Cubernetes	6
2.1.6	Luigi	6
2.1.7	Celery	6
2.1.8	Nomad	6
2.2	Docker	6
3	Things to solve / decide upon	7
3.1	Programming language	7
3.1.1	Java	7
3.1.2	Rust	7
3.1.3	Scala?	7
3.1.4	Go?	7
3.2	Docker image packaging?	7
3.3	REST interface	7
3.4	WebInterface	7
3.5	CLI?	7
3.6	Authentication / Encryption / SSL	7
3.7	Data Model	7
3.8	Distributed File System	7

3.8.1	HDFS	7
3.8.2	dCache	8
3.8.3	zsync	8
3.8.4	OpenIO	8
3.8.5	seaweed	8
3.8.6	Alluxio	9
3.8.7	GlusterFS	9
3.9	Winslow	9
4	Implementation	10
4.1	Orientation	10
4.2	No unexpected behavior	10
4.3	EventSystem	10
4.3.1	Via already distributed filesystem	10
4.4	Failure recovery	11
4.4.1	paradigm: let it crash	11
	Bibliography	12
A	Extra data	12

Chapter 1

Introduction

Since the industrial revolution, humans strive for more automation in the industry as well as in the every days life. What was at first a cost saving measurement in factories, now also is a differentiation methods for products. A new product must prove a higher level comfort to the customer than the previous generation as well as all the competitors to be accepted by the customer. As such, the ambitions of the industry are focused on increasing the ** value of their products to improve comfort in the every day life.

The automotive industry is one of the prime examples for this. Never was traveling from one place to another as comfortable as nowadays. Aspect like an elegant interior design, comfortable seats, air conditioning, entertainment systems and safety measurements need to be considered by car manufacturers to be competitive these days. As such, the next step onward in this battle for the most luxurious driving experience, is the autonomous driving vehicle. No longer shall the owner of a car steer it, but instead the car becomes his or hers personal chauffeur, driving the optimal route, the most comfortable way and being more reliable and safer than any human ever could.

While this sounds like the next logical step, the technology required from controlling the air conditioner, the engine or a entertainment system to the level that is required to drive a car autonomously is **TODO: gigantic**. The industry has no choice than to divide into many small steps to be able to conquer it **TODO: dude....**

The MEC-View research project is such a small step. It discusses whether and how to include external, steady mounted sensors in the decision **TODO: finding** of partly autonomous vehicles. **TODO: Finding** the right decision also includes understanding the traffic flow. What might seem to be the right decision for a single car, might disastrous for the traffic flow, such as being the cause for a **TODO: Phantomstau**. It is important to understand and therefore watch traffic flow, before trying implementing steering strategies.

This thesis will try to conceptualize and realize a distributed and automated computer vision pipeline which analyzes traffic flow within video footage captured by drones for the above described scenario.

1.1 MEC-View?

1.2 The Tool

describe the tool, what it is for, what it does, current workflow

The current workflow consists of the following steps:

- define reference points in one single frame through a user input
- track stationary reference points on all other frames
- estimate the camera position for each frame
- detect vehicles in all frames
- track detections and assign them to trajectories
- perform lane detection
- record a result video
- export trajectories to a csv-file
- create charts

As listed above, at least one stage must be able to process user-input. The current progress must be observed and errors must be reported in an way, that

allows one to understand the circumstances for the cause of the error.

For easy and fast scalability, docker images shall be used to distribute the binaries onto the nodes.

1.3 Defining the Problem Space

what is required / what shall the implementation be capable of from the view of the "user"

user interaction

1.4 Analyzing the Problem Space

describe scenarios the implementations must be able to handle in order to archive the requirements?

resource tracking - global (read-only) input resources ("big" data files) - per stage evolving project files - might have some kind of version control? - dynami-

cally detect within a stage whether user input is required - be able to continue / redo latest stage - error / warning detection / tracking! ([!a-zA-z]err[!a-zA-z])|([!a-zA-z]error[!a-zA-z]) - web technology

- retrieve required binaries - retrieve required resource files - archive output files and logs

- persistence stage/state tracking of projects/pipelines/states

Problems to solve

- stages might have individual hardware requirements

- multiple stages might require the same hardware at the same time

- stages can depend on the result of another stage

- for scalability, it shall be easy to add and remove hardware-nodes

- the video files are large (4k footage), sending decoded frames (25MB)

through the network might be unreasonable

- the definition of a pipeline shall be easy to understand for good

maintainability

- the hardware shall be used efficiently to achieve a high throughput

- docker images need to contain and provide all required libraries

- prevent stages from leaving other stages far behind?

- storage and distribution of intermediate results

- log collection

adding a new host - instantiate docker image and mount config and docker socket? - encrypt communication between control and worker? - possibility for decentralization - makes archiving logs and results hard

scenarios

define pipeline - define gpu stage - define cpu stage - define required input assets - define assets for each stage to be accessible in the next stage - stages depend on other stages - do it the other way around? set next stage? - next stage + "parameters" (assets to keep/transfer) - allows branching

upload resource file (video) - ... upload <path> <name-at-remote> - maybe to one common pool of resources? - free disk space?

start pipeline - select resources required by the pipeline - start

go through stages until finished - take care of cpu/gpu env requirements - if no common pool of resources: concurrently copy assets to target machines - archive

maybe: halt at stage because of error / required user interaction - allow continuation - allow download / upload of assets into this stage - free disk space?

easy installation and binary distribution - docker image per pipeline stage? - map management binary into docker -> exec - requires standalone binary - implicitly requires compatible libc env/unix system - requires administrative (docker) privileges

outputs of a stage are immutable after it has finished, stages using that data are working on a copy

nice to have: display progress captured from log (regex filter with multiple subjects/progresses per stage)

show time a stage is running

show estimated remaining time (based on captured progress)

todo list per project

project can run through multiple pipelines multiple times

nomad -> .deb archive?

deployment - web - controller - third party / nomad

start start from a certain stage pause after a stage redo a stage change variables at a stage

Chapter 2

State of the art

2.1 Existing software solutions

IBM InfoSphere https://www.ibm.com/support/knowledgecenter/en/SSZJPZ_9.1.0/com.ibm.swg.im.iis.ds.design.doc/topics/c_ddesref_Server_Job_Stages_.html

GitLab <https://docs.gitlab.com/ee/ci/yaml/>

Jenkins <https://jenkins.io/doc/book/pipeline/jenkinsfile/>

Quartz?? <http://www.quartz-scheduler.org/documentation/quartz-2.3.0/quick-start.html>

CSCS High Throughput Scheduler?? https://user.cscs.ch/tools/high_throughput/

qsub job submission <https://wiki.uiowa.edu/display/hpcdocs/Basic+Job+Submission>

2.1.1 Hadoop MapReduce

focus transforming a big dataset by splitting it into many jobs, distributing it onto many workers, doing a transformation on each dataset, and merging it back together (only map -> reduce) Distributed filesystem

2.1.2 Quartz

<http://www.quartz-scheduler.org/> <http://www.quartz-scheduler.org/overview/>

- + Java
- - requires integration
- - aimed towards running a job at a given time or in certain intervals

2.1.3 Pipeline examples: Jenkins / GitLab

Pipeline file with multiple stages a stage can be executed on a host focused on doing a job with different inputs again and again and again CI -> usually no user interaction

2.1.4 Camunda

<https://camunda.com/> <https://docs.camunda.org/manual/7.6/user-guide/process-engine/process-engine-api/> <https://docs.camunda.org/manual/7.8/reference/rest/>

Rich Business Process Management tool, many types of tasks, steps, transitions, triggers and endpoints. Focused upon moving a dataset along the matching path of the process. Out of the box graphical user interface for process definition and interaction. Allows custom external worker through queues. Misses capability to control which task to process on which worker through fine grained filters and how to allocate and distribute resources(?). Requires custom plugins for more advanced user forms, not designed for that. Not designed provide an overview on the docker machines, cluster state nor logs, file up and download

2.1.5 Cubernetes

too heavy?

2.1.6 Luigi

Similar, but locked-down on python (+machine learning)? <https://www.datarevenue.com/en/blog/to-scale-your-machine-learning-pipeline>

2.1.7 Celery

<http://www.celeryproject.org/>

2.1.8 Nomad

Deployment and management of containers rich REST API can handle resource requirements device plugins / GPU support

vs kubernetes <https://www.nomadproject.io/intro/vs/kubernetes.html>
++ available through debian / ubuntu std-repositories

2.2 Docker

Chapter 3

Things to solve / decide upon

3.1 Programming language

3.1.1 Java

3.1.2 Rust

3.1.3 Scala?

3.1.4 Go?

3.2 Docker image packaging?

3.3 REST interface

3.4 WebInterface

3.5 CLI?

3.6 Authentication / Encryption / SSL

3.7 Data Model

3.8 Distributed File System

3.8.1 HDFS

secondary nameserver only through common centralized filesystem
federation does not provide unified root

3.8.2 dCache

used by 10 of 13 top research facilities <https://www.dcache.org/manuals/dcache-whitepaper-light.pdf>

- can replicate data-pools, access through NFS (and many more) is possible

- used in grid computing facilities, integration with LDAP and Kerberos possible, supports tertiary storage, supports GssFtp, GsiFtp/GridFtp, HPSS, CERNs GridFileAccessLayer GFAL

- complex installation many dependencies: postgresql, configuration of inter-dependent internal service: pool, poolmanager, glzma?, zookeeper

- documentation is lückenhaft, outside of dcache.org only veraltet versions are found

- too much overhead for just having a distributed file system

- zookeeper admin poolmanager spacemanager pnfsmanager cleaner gpazma pinmanager billing httpd topo info nfs pool

3.8.3 zsync

<http://zsync.moria.org.uk/>

3.8.4 OpenIO

limited to distributed file system

- provides docker image

- simple CLI, focused on managing storage containers and replicas

- Java SDK?

- Supports NFS (for Linux workers), and Samba/SMB for Windows/Linux clients

- NFS only through paid plan

3.8.5 seaweed

datacenter and rack aware in volume replication scenarios

- easy to setup

- single binary

- mount through FUSE

- [volumes] <-> [master] <-> [filer] <-> [clients] bzw filer mit master und volumes

- master halten die zuweisung file -> adresse filer machen nur ein lookup und zuweisen oder sowas aber der client fragt filer an und der muss dann zu irgendeinem master die verbindung aufbauen und nachschlagen dh wollte pro physi-

calischen server 1 volume, 1 master, 1 filer haben damit einfach dezentral kommen und gehen kann aber problem 1: anzahl der master soll immer ungerade sein problem 2: du kannst nicht einfach master on-the-fly hinzufügen und musst stattdessen teilweise die neu starten mitm parameter: hey da drüben ist noch ein master problem 3: es läuft nicht zuverlässig

3.8.6 Alluxio

requires centralized filesystem for masters

<https://en.wikipedia.org/wiki/Alluxio>

3.8.7 GlusterFS

Bought by IBM very minimalistic included in ubuntu and debian repositories setup easy, without a lot of configuration (none to be precise) node information is spread on all nodes, no master/slave but replication requires that a multiple of it are assigned to the volume - can be circumvented by adding peers to a volume only every second peer (if replica is 2) geo-replication is interesting

3.9 Winslow

https://de.wikipedia.org/wiki/Frederick_Winslow_Taylor

coordination withing a container - start nomad and join existing nomad instances - start weed and join existing weed masters

requires winslow to winslow communication

might need to restart services, must ensure that happens not everywhere at the same time

using distributed filesystem as configuration storage? - hard for initial start / problematic if down -but automatically distributes configurations + allows replications

Chapter 4

Implementation

log strategy?

how to handle changes in configuration on a restart - how to sync with nomad
- how to handle still running jobs on an now invalid configuration? - keep copy
of old configuration?

4.1 Orientation

bash -> variable substitution

4.2 No unexpected behavior

no null, instead use Optional

lists are never null nor Optional but empty or filled instead

see `de.itd.tracking.winslow.config.*`

called defensive programming? - good to be error-resilient - bad in performance critical scenarios

4.3 EventSystem

4.3.1 Via already distributed filesystem

<https://docs.oracle.com/javase/tutorial/essential/io/move.html>

events/ directory with files being named after a integer, being the unique next event id write event to tmp/, then atomically move to events/ without replacing existing ids (which would indicate an collision)

4.4 Failure recovery

what if an instance suddenly crashes/disconnects/fails

- heartbeats to detect, with max number of allowed skips (so no "timeout")

- assign pipeline to a node? (supervising node) on failure, try to recover what has already been processed by re-assigning pipeline and then trying to load prev-state

4.4.1 paradigm: let it crash

Appendix A

Extra data