

```

-- =====
-- CRIAÇÃO DO BANCO
-- =====

CREATE DATABASE fraude_analytics
CHARACTER SET utf8mb4
COLLATE utf8mb4_unicode_ci;

USE fraude_analytics;

-- =====
-- CRIAÇÃO DAS TABELAS
-- =====

-- USERS

CREATE TABLE users (
  id INT PRIMARY KEY,
  current_age INT,
  retirement_age INT,
  birth_year INT,
  birth_month INT,
  gender VARCHAR(20),
  address VARCHAR(255),
  latitude DECIMAL(10,6),
  longitude DECIMAL(10,6),
  per_capita_income VARCHAR(50),
  yearly_income VARCHAR(50),
  total_debt VARCHAR(50),
  credit_score INT,
  num_credit_cards INT
);

-- CARDS

CREATE TABLE cards (
  id INT PRIMARY KEY,
  client_id INT,
  card_brand VARCHAR(50),
  card_type VARCHAR(50),
  card_number VARCHAR(30),
  expires VARCHAR(20),
  cvv INT,
  has_chip VARCHAR(10),
  num_cards_issued INT,
  credit_limit VARCHAR(50),
  acct_open_date VARCHAR(20),
  year_pin_last_changed INT,
  card_on_dark_web VARCHAR(10),

  FOREIGN KEY (client_id)
  REFERENCES users(id)
);

```

-- TRANSACTIONS

```
CREATE TABLE transactions (  
  amount VARCHAR(50),  
  card_id INT,  
  client_id INT,  
  date DATETIME,  
  errors VARCHAR(255),  
  id BIGINT PRIMARY KEY,  
  mcc INT,  
  merchant_city VARCHAR(100),  
  merchant_id BIGINT,  
  merchant_state VARCHAR(50),  
  use_chip VARCHAR(50),  
  zip VARCHAR(20),  
  
  FOREIGN KEY (client_id)  
  REFERENCES users(id)  
);
```

```
-- =====  
-- POPULANDO TABELAS - **users**  
-- =====
```

USE fraude_analytics;

```
LOAD DATA INFILE 'C:/ProgramData/MySQL/MySQL Server 8.0/Uploads/users_data.csv'  
INTO TABLE users  
FIELDS TERMINATED BY ','  
ENCLOSED BY ''"  
LINES TERMINATED BY '\n'  
IGNORE 1 ROWS;
```

```
-- =====  
-- CONFERINDO DADOS IMPORTADOS  
-- =====
```

USE fraude_analytics;

```
-- verificando amostra de dados  
SELECT * FROM users LIMIT 10;
```

```
-- contagem de linhas  
SELECT COUNT(*) AS total_users FROM users;
```

```
-- =====  
-- POPULANDO TABELAS - **cards**  
-- =====
```

USE fraude_analytics;

```
LOAD DATA INFILE 'C:/ProgramData/MySQL/MySQL Server 8.0/Uploads/cards_data.csv'
INTO TABLE cards
FIELDS TERMINATED BY ','
ENCLOSED BY '"'
LINES TERMINATED BY '\n'
IGNORE 1 ROWS;
```

```
-- =====
-- CONFERINDO DADOS IMPORTADOS
-- =====
```

```
USE fraude_analytics;
```

```
-- verificando amostra de dados
SELECT * FROM cards LIMIT 10;
```

```
-- contagem de linhas
SELECT COUNT(*) AS total_cards FROM cards;
```

```
-- =====
-- POPULANDO TABELAS - **transactions**
-- =====
```

```
USE fraude_analytics;
```

```
LOAD DATA INFILE 'C:/ProgramData/MySQL/MySQL Server 8.0/Uploads/transactions_data.csv'
INTO TABLE transactions
FIELDS TERMINATED BY ','
ENCLOSED BY '"'
LINES TERMINATED BY '\n'
IGNORE 1 ROWS;
```

Apresentou erro devido espaços no csv original, então utilizei o código

```
USE fraude_analytics;
```

```
SET GLOBAL net_read_timeout = 6000;
SET GLOBAL net_write_timeout = 6000;
SET GLOBAL wait_timeout = 6000;
SET GLOBAL interactive_timeout = 6000;
SET GLOBAL max_allowed_packet = 1073741824;
```

```
TRUNCATE TABLE transactions;
```

```
LOAD DATA INFILE 'C:/ProgramData/MySQL/MySQL Server 8.0/Uploads/transactions_data.csv'
IGNORE
INTO TABLE transactions
FIELDS TERMINATED BY ','
ENCLOSED BY '"'
LINES TERMINATED BY '\n'
IGNORE 1 ROWS
(
```

```
amount,
@card_id,
@client_id,
@date,
errors,
id,
mcc,
merchant_city,
merchant_id,
merchant_state,
use_chip,
zip
)
SET
card_id = TRIM(@card_id),
client_id = TRIM(@client_id),
date = STR_TO_DATE(TRIM(@date), '%m/%d/%Y %H:%i:%s');
```

```
-- =====
-- CONFERINDO DADOS IMPORTADOS
-- =====
```

```
USE fraude_analytics;
```

```
-- verificando amostra de dados
SELECT * FROM transactions LIMIT 10;
```

```
-- contagem de linhas
SELECT COUNT(*) AS total_transactions FROM transactions;
```