

SAFETY DATA SHEET

Version 6.13
Revision Date 05/05/2025
Print Date 05/06/2025

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Ethylenediamine

Product Number : E26266
Brand : Sigma-Aldrich
Index-No. : 612-006-00-6
CAS-No. : 107-15-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Sigma-Aldrich - E26266

Page 1 of 17

Acute toxicity (Inhalation)	: Category 4
Acute toxicity (Dermal)	: Category 3
Skin corrosion	: Category 1B
Serious eye damage	: Category 1
Respiratory sensitization	: Sub-category 1B
Skin sensitization	: Sub-category 1B
Short-term (acute) aquatic hazard	: Category 3
Long-term (chronic) aquatic hazard	: Category 3

Other hazards

None known.

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H302 + H332 Harmful if swallowed or if inhaled.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing mist or vapors.

P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P285 In case of inadequate ventilation wear respiratory protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
ethylenediamine	107-15-3*	>= 90 - <= 100	-

* Indicates that the identifier is a CAS No.
Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aiders need to protect themselves.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : After inhalation: fresh air. Immediately call in physician.
If breathing stops: immediately apply artificial respiration, if necessary also oxygen.
- In case of skin contact : In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.
Call a physician immediately.
- In case of eye contact : After eye contact: rinse out with plenty of water.
Immediately call in ophthalmologist.
Remove contact lenses.
- If swallowed : After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation).
Call a physician immediately.
Do not attempt to neutralise.
- Most important symptoms and effects, both acute and delayed : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- Protection of first-aiders : For personal protection see section 8.
- Notes to physician : No data available

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water
Foam
Carbon dioxide (CO₂)
Dry powder
- Unsuitable extinguishing media : For this substance/mixture no limitations of extinguishing agents are given.

Specific hazards during fire fighting	: Flash back possible over considerable distance. Container explosion may occur under fire conditions. Vapors may form explosive mixture with air. Combustible. Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NOx)
Specific extinguishing methods	: No data available
Further information	: Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.
---	---

Advice for emergency responders:
For personal protection see section 8.

- Environmental precautions : Do not let product enter drains.
Risk of explosion.
- Methods and materials for containment and cleaning up : Cover drains. Collect, bind, and pump off spills.
Observe possible material restrictions (see sections 7 and 10).
Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take precautionary measures against static discharge.
- Advice on safe handling : Work under hood. Do not inhale substance/mixture.
Avoid generation of vapours/aerosols.
- Further information on storage conditions : Keep container tightly closed in a dry and well-ventilated place.
Keep away from heat and sources of ignition.
Keep locked up or in an area accessible only to qualified or authorized persons.
- Storage class : 3, Flammable liquids
- Recommended storage temperature : Recommended storage temperature see product label.
- Further information on storage stability : Air and moisture sensitive.
Handle and store under inert gas.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylenediamine	107-15-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 25 mg/m ³	OSHA Z-1
		TWA	10 ppm 25 mg/m ³	NIOSH REL

Sigma-Aldrich - E26266

Page 6 of 17

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.
Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0.7 mm
Protective index : Full contact
Manufacturer : Butoject® (KCL 898)

Material : Chloroprene
Break through time : 240 min
Glove thickness : 0.65 mm
Protective index : Splash contact
Manufacturer : KCL 720 Camapren®

Remarks : This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Tightly fitting safety goggles

Skin and body protection : Flame retardant antistatic protective clothing.

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face

after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: colorless
Odor	: amine-like
Odor Threshold	: No data available
pH	: 12.2 (68 °F / 20 °C) Concentration: 100 g/l
Melting point/ range	: 47.3 °F / 8.5 °C
Boiling point/boiling range	: 244 °F / 118 °C
Flash point	: 100 °F / 38 °C (1,013 hPa) Method: DIN 51755 Part 1, closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Self-ignition	: 761 °F / 405 °C Method: DIN 51794
Upper explosion limit / Upper flammability limit	: Upper explosion limit 17 %(V)
Lower explosion limit / Lower flammability limit	: Lower explosion limit 2 %(V)
Vapor pressure	: 12 hPa (68 °F / 20 °C)
Relative vapor density	: 2.07 (Air = 1.0)
Relative density	: 0.897 (68 °F / 20 °C)

Density	: 0.899 g/mL (77 °F / 25 °C)
Solubility(ies)	
Water solubility	: 1,000 g/l miscible
Partition coefficient: n-octanol/water	: log Pow: -2.04 Method: (experimental) Bioaccumulation is not expected. (Lit.)
Autoignition temperature	: 761 °F / 405 °C Method: DIN 51794
Decomposition temperature	: > 248 °F / > 120 °C
Viscosity	
Viscosity, dynamic	: 1.265 - 1.725 mPa.s (77 °F / 25 °C)
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Molecular weight	: 60.10 g/mol
Particle characteristics	
Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapor/air-mixtures are explosive at intense warming.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: Absorbs carbon dioxide (CO ₂) from air.
Conditions to avoid	: Air Exposure to moisture. Heating.
Incompatible materials	: No data available
Hazardous decomposition products	: In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 866 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male - 4 h - 14.7 mg/l - vapor

Remarks: (ECHA)

LD50 Dermal - Rabbit - male - 560 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: Corrosive - 15 min

Remarks: (ECHA)

Remarks: Causes poorly healing wounds.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Corrosive

Remarks: (ECHA)

Remarks: Causes serious eye damage.

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: positive

(OECD Test Guideline 429)

(Regulation (EC) No 1272/2008, Annex VI)

(Regulation (EC) No 1272/2008, Annex VI)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: (ECHA)

Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: (ECHA)

Test Type: unscheduled DNA synthesis assay

Test system: rat hepatocytes

Metabolic activation: without metabolic activation

Result: negative

Remarks: (ECHA)

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
Remarks: (ECHA)

Test Type: dominant lethal test
Species: Rat

Application Route: Oral

Result: negative
Remarks: (ECHA)

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 3 Months - NOAEL (No observed adverse effect level) - 22 mg/kg - LOAEL (Lowest observed adverse effect level) - 114 mg/kg

RTECS: KH8575000

Vomiting, Diarrhea, Abdominal pain

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

ethylenediamine:

Toxicity to fish	: LC50 (<i>Poecilia reticulata</i> (guppy)): 640 mg/l End point: mortality Exposure time: 96 h Test Type: semi-static test Method: Directive 67/548/EEC, Annex V, C.1. GLP: yes Remarks: (ECHA) NOEC (<i>Gasterosteus aculeatus</i> (threespine stickleback)): > 10 mg/l Exposure time: 28 d Test Type: semi-static test Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): 16.7 mg/l End point: Immobilization Exposure time: 48 h Test Type: static test Method: Directive 67/548/EEC, Annex V, C.2. GLP: yes Remarks: (ECHA)
Toxicity to algae/aquatic plants	: ErC50 (<i>Pseudokirchneriella subcapitata</i> (algae)): 645 mg/l Exposure time: 72 h Test Type: static test Method: Directive 67/548/EEC, Annex V, C.3. GLP: yes
Toxicity to fish (Chronic toxicity)	: NOEC (<i>Gasterosteus aculeatus</i>): > 10 mg/l Exposure time: 28 d Test Type: semi-static test Method: OECD Test Guideline 210 GLP: yes
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (<i>Daphnia magna</i> (Water flea)): 0.16 mg/l End point: reproduction rate Exposure time: 21 d Test Type: semi-static test Analytical monitoring: yes Method: US-EPA
Toxicity to microorganisms	: EC50 (Bacteria): 3.2 mg/l Exposure time: 2 h Test Type: static test

GLP: yes
Remarks: (ECHA)

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

Components:

ethylenediamine:

Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 2 mg/l
Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

Bioaccumulative potential

Components:

ethylenediamine:

Partition coefficient: n-octanol/water : log Pow: -2.04
Method: (experimental)
Remarks: Bioaccumulation is not expected.
(Lit.)

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

ethylenediamine:

Additional ecological information : Avoid release to the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1604
Proper shipping name : Ethylenediamine
Class : 8
Subsidiary risk : 3
Packing group : II
Labels : Class 8 - Corrosive substances, Class 3 - Flammable liquids
Packing instruction (cargo aircraft) : 855
Packing instruction (passenger aircraft) : 851

IMDG-Code

UN number : UN 1604
Proper shipping name : ETHYLENEDIAMINE

Class : 8
Subsidiary risk : 3
Packing group : II
Labels : 8 (3)
EmS Code : F-E, S-C
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National regulation

49 CFR Road

UN/ID/NA number : UN 1604
Proper shipping name : Ethylenediamine

Class : 8
Subsidiary risk : 3
Packing group : II
Labels : Class 8 - Corrosive substances, Class 3 - Flammable liquids
ERG Code : 132

Marine pollutant : no

Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylenediamine	107-15-3	5000	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylenediamine	107-15-3	5000	5000

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

Components	CAS-No.	Component TPQ (lbs)
ethylenediamine	107-15-3	10000

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

ethylenediamine 107-15-3 >= 90 - <= 100 %

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

ethylenediamine 107-15-3 >= 90 - <= 100 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

ethylenediamine 107-15-3 >= 90 - <= 100 %

Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 05/05/2025

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

US / EN