

# SAFETY DATA SHEET

Version 8.7 Revision Date 09/07/2024 Print Date 09/08/2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Diisopropylamine for synthesis

Product Number : 8.03646
Catalogue No. : 803646
Brand : Millipore
Index-No. : 612-129-00-5
CAS-No. : 108-18-9

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Chemical for synthesis

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

## 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331

Millipore - 8.03646

Page 1 of 13



Skin corrosion (Category 1B), H314

Serious eye damage (Category 1), H318

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Short-term (acute) aquatic hazard (Category 3), H402 Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram	
Signal Word	Danger
Hazard Statements H225 H302 H314 H331 H335 H412	Highly flammable liquid and vapor. Harmful if swallowed. Causes severe skin burns and eye damage. Toxic if inhaled. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.
Precautionary Statements P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No
P233 P240 P241 P242 P243 P261	smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.
P201 P264 P270 P271	Avoid breathing mist or vapors.  Wash skin thoroughly after handling.  Do not eat, drink or smoke when using this product.  Use only outdoors or in a well-ventilated area.
P273 P280	Avoid release to the environment.  Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 P303 + P361 + P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P363 P370 + P378	Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233 P403 + P235 P405	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Millipore - 8.03646



plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Formula : C6H15N Molecular weight : 101.19 g/mol CAS-No. : 108-18-9 EC-No. : 203-558-5 Index-No. : 612-129-00-5

Component	Classification	Concentration
diisopropylamine		
	Flam. Liq. 2; Acute Tox. 4; Acute Tox. 3; Skin Corr. 1B; Eye Dam. 1; STOT SE 3; Aquatic Acute 3; Aquatic Chronic 3; H225, H302, H331, H314, H318, H335, H402, H412	<= 100 %
	Concentration limits: >= 5 %: STOT SE 3, H335;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

## 4.1 Description of first-aid measures

## **General advice**

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

## If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

## In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

## In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

Millipore - 8.03646



Page 3 of 13

#### If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed

No data available

# **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

## 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NOx)

Combustible.

Fire may cause evolution of:

nitrogen oxides

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

## **5.3** Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

#### 5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

# 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

Millipore - 8.03646

Page 4 of 13



### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

#### 6.4 Reference to other sections

For disposal see section 13.

# **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

#### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

# **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

**Ingredients with workplace control parameters** 

Component	CAS-No.	Value	Control parameters	Basis	
diisopropylamine	108-18-9	TWA	5 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Danger of cutaneous absorption			
		TWA	5 ppm 20 mg/m3	USA. NIOSH Recommended Exposure Limits	
		Potential for dermal absorption			

Millipore - 8.03646 Page 5 of 13



TWA	5 ppm 20 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
Skin designation		
PEL	5 ppm 20 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		

## 8.2 Exposure controls

## **Appropriate engineering controls**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

## **Personal protective equipment**

### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

# **Skin protection**

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 30 min

Material tested:Butoject® (KCL 898)

#### **Body Protection**

Flame retardant antistatic protective clothing.

### **Respiratory protection**

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented. required when vapours/aerosols are generated.

Millipore - 8.03646

Page 6 of 13



Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

#### **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

## **SECTION 9: Physical and chemical properties**

## .1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor amine-like

c) Odor Threshold No data available

d) pH 11.8 at 6 g/l at 20 °C (68 °F)

e) Melting Melting point: -61 °C (-78 °F) point/freezing point

f) Initial boiling point and boiling range

83 - 84 °C 181 - 183 °F at 1,013 hPa

g) Flash point -13.45 °C (7.79 °F) - closed cup - ISO 3679

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 7.1 %(V) flammability or Explosive limits Upper explosion limit: 1.1 %(V)

k) Vapor pressure 93.33 hPa at 20 °C (68 °F)

I) Vapor density 3.5

m) Density 0.72 g/cm3 at 20 °C (68 °F)

Relative density No data available

n) Water solubility miscible

o) Partition coefficient: log Pow: 0.4 at 20 °C (68 °F) - Bioaccumulation is not expected. n-octanol/water

p) Autoignition 295 °C (563 °F) at 1,007 hPa temperature

q) Decomposition No data available temperature

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties none

Millipore - 8.03646

Millipore Sigma

#### 9.2 Other safety information

Relative vapor 3.5 density

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Vapors may form explosive mixture with air.

## 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

# 10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Strong oxidizing agents

nitrates

perchlorates

Aluminum

Peroxides

Exothermic reaction with:

halogens

acids

Caution! In contact with nitrites, nitrates, nitrous acid possible liberation of nitrosamines!

#### 10.4 Conditions to avoid

Warming.

#### 10.5 Incompatible materials

Aluminum

#### 10.6 Hazardous decomposition products

In the event of fire: see section 5

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

LD50 Oral - Rat - male and female - 420 mg/kg

(US-EPA)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

LC50 Inhalation - Rat - male and female - 4 h - 5.35 mg/l - vapor

(OECD Test Guideline 403)

Symptoms: mucosal irritations, Cough, Shortness of breath, Lung edema, Possible

damages:, damage of respiratory tract Inhalation: Corrosive to respiratory system.

Millipore - 8.03646

Page 8 of 13

LD50 Dermal - Rat - male and female - > 2,000 - 5,000 mg/kg (OECD Test Guideline 402)

No data available

## Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 3 min (OECD Test Guideline 404)

### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes burns. (OECD Test Guideline 405)

Remarks: Causes serious eye damage.

Remarks: conjunctivitis

# Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

## Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

### Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is OSHA:

on OSHA's list of regulated carcinogens.

# **Reproductive toxicity**

No data available

### Specific target organ toxicity - single exposure

May cause respiratory irritation.

#### Specific target organ toxicity - repeated exposure

No data available

Millipore - 8.03646

**1**illiPDRE

## Aspiration hazard

No data available

#### 11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 33 Days - NOAEL (No observed adverse effect level) - 15 mg/kg

Remarks: (ECHA)

Repeated dose toxicity - Rat - male and female - Dermal - 28 d - NOAEL (No observed adverse effect level) - >= 150 mg/kg

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

After absorption:

Headache Convulsions CNS disorders

Under given conditions, contact with nitrites or nitric acid can lead to the formation of nitrosamines, which have shown themselves to be carcinogenic in animal experiments.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Irregularities - Based on Human Evidence

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Toxicity to fish static test LC50 - Leuciscus idus (Golden orfe) - 26 mg/l - 96 h

(DIN 38412 part 15)

Toxicity to daphnia

and other aquatic invertebrates

static test LC50 - Daphnia magna (Water flea) - 110 mg/l - 48 h

Remarks: (ECHA)

Toxicity to algae static test EC50 - SELENASTRUM - 20 mg/l - 96 h

(US-EPA)

Toxicity to bacteria static test EC50 - activated sludge - > 100 mg/l - 3 h

(OECD Test Guideline 209)

Millipore - 8.03646

4illiPORE

Page 10 of 13

Toxicity to semi-static test EC50 - Gasterosteus aculeatus - 250 mg/l - 35 d

fish(Chronic toxicity) (OECD Test Guideline 210)

### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 11 % - Not readily biodegradable.

(OECD Test Guideline 301D)

## 12.3 Bioaccumulative potential

No data available

# 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

### **SECTION 14: Transport information**

DOT (US)

UN number: 1158 Class: 3 (8) Packing group: II

Proper shipping name: Diisopropylamine

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

**IMDG** 

UN number: 1158 Class: 3 (8) Packing group: II EMS-No: F-E, S-C

Proper shipping name: DIISOPROPYLAMINE

**IATA** 

UN number: 1158 Class: 3 (8) Packing group: II

Proper shipping name: Diisopropylamine

Millipore - 8.03646 Page 11 of 13



#### **SECTION 15: Regulatory information**

## **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

## **US State Regulations**

# **Massachusetts Right To Know**

diisopropylamine 108-18-9

## **Pennsylvania Right To Know**

diisopropylamine 108-18-9

#### **Maine Chemicals of High Concern**

Product does not contain any listed chemicals

# **Vermont Chemicals of High Concern**

Product does not contain any listed chemicals

## **Washington Chemicals of High Concern**

Product does not contain any listed chemicals

#### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

#### **TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **SECTION 16: Other information**

#### **Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact

Millipore - 8.03646



with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.7 Revision Date: 09/07/2024 Print Date: 09/08/2024

Millipore - 8.03646

