

SAFETY DATA SHEET

Version 6.21 Revision Date 09/06/2024 Print Date 09/07/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Tetrahydrofuran

Product Number : 34865 Brand : SIGALD

Index-No. : 603-025-00-0 CAS-No. : 109-99-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 4), H302 Eye irritation (Category 2A), H319

SIGALD - 34865

Page 1 of 14



Carcinogenicity (Category 2), H351

Pictogram

Specific target organ toxicity - single exposure (Category 3), Respiratory system, Central nervous system, H335, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS Label elements, including precautionary statements 2.2

| Signal Word | Danger | |
|-------------------|--------|--|
| Hazard Statements | | |

| Hazara Statements | |
|-------------------|------------------------------------|
| H225 | Highly flammable liquid and vapor. |
| H302 | Harmful if swallowed. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| 11054 | |

| 11330 | May cause urowsiness or urzz |
|-------|------------------------------|
| H351 | Suspected of causing cancer. |
| D | |

| H335 H336 H351 | May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. |
|--------------------------|---|
| Precautionary Statements | |
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing mist or vapors. |
| P264 | Wash skin thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |

| F Z U I | Avoid breatining mist of vapors. |
|---------|---|
| P264 | Wash skin thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/ protective clothing/ eye protection |
| | |

| PZ/1 | ose only outdoors of in a well-ventilated area. |
|--------------------|---|
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face |
| | protection. |
| P301 + P312 + P330 | IF SWALLOWED: Call a POISON CENTER/ doctor if you feel |

| F301 T F312 T F330 | II SWALLOWED. Call a POISON CLIVILRY doctor if you reel |
|--------------------|---|
| | unwell. Rinse mouth. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated |
| | clothing. Rinse skin with water/ shower. |
| P304 + P340 + P312 | IF INHALED: Remove person to fresh air and keep comfortable |
| | for breathing. Call a POISON CENTER/ doctor if you feel unwell. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. |
| L202 + L221 + L220 | If the Lies. Kinse cautiously with water for several minutes. |

| | Remove contact lenses, if present and easy to do. Continue |
|-------------|--|
| | rinsing. |
| D200 + D212 | TE assessed as assessed. Oak and disable defined attacking |

| P308 + P313 | If exposed or concerned: Get medical advice/ attention. |
|-------------|--|
| P337 + P313 | If eye irritation persists: Get medical advice/ attention. |
| D270 - D270 | To see of five the down and down beautiful an elected wester |

| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant |
|-------------|--|
| | foam to extinguish. |

| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
|-------------|--|
| D/U3 T D332 | Store in a well-ventilated place Keen cool |

Store in a well-ventilated place. Keep cool. P403 + P235

P405 Store locked up.

SIGALD - 34865 Page 2 of 14



plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides. May form explosive peroxides.

SECTION 3: Composition/information on ingredients

3.1 Substances

Index-No. : 603-025-00-0

| Component | Classification | Concentration |
|-----------------|---|---------------|
| Tetrahydrofuran | | |
| | Flam. Liq. 2; Acute Tox. 4; Eye Irrit. 2A; Carc. 2; STOT SE 3; H225, H302, H319, H351, H335, H336 Concentration limits: >= 25 %: Eye Irrit. 2, H319; >= 25 %: STOT SE 3, H335; | <= 100 % |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

SIGALD - 34865

Page 3 of 14



4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SIGALD - 34865

Page 4 of 14

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Test for peroxide formation periodically and before distillation.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

| 2.19 Calcillo With Workplace Control parameters | | | | | |
|---|----------|---|--------------------|---|--|
| Component | CAS-No. | Value | Control parameters | Basis | |
| Tetrahydrofuran | 109-99-9 | TWA | 50 ppm | USA. ACGIH Threshold Limit Values (TLV) | |
| | Remarks | Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption | | | |
| | | STEL | 100 ppm | USA. ACGIH Threshold Limit Values (TLV) | |
| | | Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption | | | |

SIGALD - 34865



| ST | 250 ppm 735 mg/m3 | USA. NIOSH Recommended Exposure Limits |
|------|----------------------|---|
| TWA | 200 ppm 590 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| TWA | 200 ppm 590 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| PEL | 200 ppm 590 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| STEL | 250 ppm 735 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |

Biological occupational exposure limits

| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
|-----------------|----------|--|--------|---------------------|--|
| Tetrahydrofuran | 109-99-9 | Tetrahydrof uran | 2 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | End of shift (As soon as possible after exposure ceases) | | | |

Derived No Effect Level (DNEL)

| Derived No Lifect Level (DNLL) | | | | |
|--------------------------------|--------------|----------------------------|--------------|--|
| Application Area | Routes of | Health effect | Value | |
| | exposure | | | |
| Workers | Skin contact | Long-term systemic effects | 25mg/kg BW/d | |
| Consumers | Skin contact | Long-term systemic effects | 15mg/kg BW/d | |
| Workers | Inhalation | Long-term local effects | 150 mg/m3 | |
| Workers | Inhalation | Long-term systemic effects | 150 mg/m3 | |
| Consumers | Inhalation | Long-term systemic effects | 62 mg/m3 | |
| Consumers | Inhalation | Acute local effects | 150 mg/m3 | |
| Consumers | Inhalation | Acute systemic effects | 150 mg/m3 | |

Predicted No Effect Concentration (PNEC)

| Fredicted No Lifect Concentration (FNEC) | | | |
|--|------------|--|--|
| Compartment | Value | | |
| Soil | 2.13 mg/kg | | |
| Sea water | 0.432 mg/l | | |
| Fresh water | 4.32 mg/l | | |
| Sea sediment | 2.33 mg/kg | | |
| Fresh water sediment | 23.3 mg/kg | | |
| Onsite sewage treatment plant | 4.6 mg/l | | |

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SIGALD - 34865

Millipore SigMa

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 10 min

Material tested:Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

b) Odorc) Odor Thresholddata available

d) pH ca.7 - 8

e) Melting point: -108.44 °C (-163.19 °F) - (ECHA)

point/freezing point

f) Initial boiling point 65 °C 149 °F at 1,013.25 hPa - (ECHA) and boiling range

g) Flash point -21.2 °C (-6.2 °F) - closed cup - DIN 51755 Part 1

h) Evaporation rate No data availablei) Flammability (solid, No data available

SIGALD - 34865

Millipore Sigma gas)

j) Upper/lower Upper explosion limit: 12.4 %(V) - (THF)

flammability or Lower explosion limit: 1.5 %(V)

explosive limits

k) Vapor pressure 170 hPa at 20 °C (68 °F) - (THF)

I) Vapor density No data available

m) Density 0.89 g/cm3 at 20 °C (68 °F)

Relative density No data available

n) Water solubility miscible

o) Partition coefficient: log Pow: 0.45 at 25 °C (77 °F) - Bioaccumulation is not

n-octanol/water expected.

p) Autoignition 215 °C (419 °F) at 1,013 hPa - DIN 51794

temperature

q) Decomposition No data available

temperature

r) Viscosity No data available

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Formation of peroxides possible.

Vapors may form explosive mixture with air.

10.2 Chemical stability

Sensitivity to light

Sensitive to air.

The product is chemically stable under standard ambient conditions (room temperature) . Stable under recommended storage conditions.

Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Distillation (Risk of explosion).

Warming.

Moisture.

SIGALD - 34865

Millipore SiGMa

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Peroxides

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 1,650 mg/kg

Remarks: (ECHA)

Symptoms: Irritation of mucous membranes

LC50 Inhalation - Rat - male and female - 6 h - > 14.7 mg/l - vapor

(US-EPA)

LD50 Dermal - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 72 h

(Draize Test)

Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to

degreasing properties of the product.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

Remarks: (IUCLID)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

SIGALD - 34865

4illiPORE

Page 9 of 14

Method: OECD Test Guideline 473

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Red blood cells (erythrocytes) Application Route: inhalation (vapor) Method: OECD Test Guideline 474

Result: negative **Carcinogenicity**

Suspected of causing cancer.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Tetrahydrofuran)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Central nervous system Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 4 Weeks

RTECS: LU5950000

irritant effects, Cough, Shortness of breath, narcosis, somnolence

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

In high doses:

somnolence narcosis

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

SIGALD - 34865

<u>JilliPDRe</u>

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

2,160 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - 3,485 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to flow-through test NOEC - Pimephales promelas (fathead minnow) -

fish(Chronic toxicity) 216 mg/l - 33 d

Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability aerobic Biochemical oxygen demand - Exposure time 28 d

Result: 39 % - Not readily biodegradable.

(OECD Test Guideline 301D)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SIGALD - 34865

SECTION 14: Transport information

DOT (US)

UN number: 2056 Class: 3 Packing group: II

Proper shipping name: Tetrahydrofuran Reportable Quantity (RQ): 1000 lbs Poison Inhalation Hazard: No

IMDG

UN number: 2056 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: TETRAHYDROFURAN

IATA

UN number: 2056 Class: 3 Packing group: II

Proper shipping name: Tetrahydrofuran

SECTION 15: Regulatory information

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|-----------------|----------|-----------------------|--------------------------------|
| Tetrahydrofuran | 109-99-9 | 1000 | 1000 |

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 : Fire Hazard

Hazards Acute Health Hazard

Chronic Health Hazard

SARA 313 : This material does not contain any chemical

> components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). This product does not contain any hazardous air pollutants (HAP), as defined by the U.S.

Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

SIGALD - 34865

Page 12 of 14



This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Tetrahydrofuran 109-99-9

Pennsylvania Right To Know

Tetrahydrofuran 109-99-9

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including Tetrahydrofuran, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

SIGALD - 34865

Page 13 of 14



Version: 6.21 Revision Date: 09/06/2024 Print Date: 09/07/2024

SIGALD - 34865

