

SAFETY DATA SHEET

Version 6.14 Revision Date 05/05/2025 Print Date 05/06/2025

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Isopropyl acetate

Product Number : 537462

Brand : SIGALD

Index-No. : 607-024-00-6

CAS-No. : 108-21-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose

product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Eye irritation : Category 2A

SIGALD - 537462

Page 1 of 15



Specific target organ toxicity - single exposure

: Category 3 (Central nervous system)

Other hazards

Repeated exposure may cause skin dryness or cracking. Repeated exposure may cause skin dryness or cracking.

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot

surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/

lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static

discharge.

P261 Avoid breathing mist or vapors.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical

advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Storage:

SIGALD - 537462



P403 + P233 Store in a well-ventilated place. Keep

container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
isopropyl acetate	108-21-4*	>= 90 - <= 100	-

^{*} Indicates that the identifier is a CAS No.

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : After inhalation: fresh air. Call in physician.

In case of skin contact : In case of skin contact: Take off immediately all

contaminated clothing. Rinse skin with water/ shower.

In case of eye contact : After eye contact: rinse out with plenty of water.

Call in ophthalmologist. Remove contact lenses.

If swallowed : After swallowing: caution if victim vomits. Risk of

aspiration! Keep airways free.

Pulmonary failure possible after aspiration of vomit.

Call a physician immediately.

Most important symptoms and effects,

symptoms and effects, both acute and delayed : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in

section 11

Protection of first-aiders : For personal protection see section 8.

Notes to physician : No data available

SECTION 5. FIRE-FIGHTING MEASURES

SIGALD - 537462

4illiPDRE

Page 3 of 15

Suitable extinguishing

media

: Carbon dioxide (CO2)

Foam Dry powder

Unsuitable extinguishing

media

: For this substance/mixture no limitations of

extinguishing agents are given.

Specific hazards during

fire fighting

: Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

Hazardous combustion

products

: Carbon oxides

Specific extinguishing

methods

: No data available

Further information

Remove container from danger zone and cool with

water.

Prevent fire extinguishing water from contaminating

surface water or the ground water system.

Special protective equipment for fire-

fighters

: In the event of fire, wear self-contained breathing


apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact.

SIGALD - 537462

Page 4 of 15





Ensure adequate ventilation.

Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency

procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.

Environmental precautions

: Do not let product enter drains.

Risk of explosion.

Methods and materials for containment and cleaning up

: Cover drains. Collect, bind, and pump off spills.
Observe possible material restrictions (see sections 7

and 10).

Take up with liquid-absorbent material (e.g.

Chemizorb®). Dispose of properly. Clean up affected

area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

Advice on protection against fire and explosion

: Keep away from open flames, hot surfaces and

sources of ignition.

Take precautionary measures against static discharge.

Advice on safe handling

: Work under hood. Do not inhale substance/mixture.

Avoid generation of vapours/aerosols.

Further information on storage conditions

: Keep container tightly closed in a dry and well-

ventilated place.

Keep away from heat and sources of ignition.

Storage class : 3, Flammable liquids

Recommended storage

temperature

: Recommended storage temperature see product label.

Further information on

storage stability

: Moisture sensitive.

Packaging material : Suitable material: Mild Steel Drum

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

•	-			
Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
isopropyl acetate	108-21-4	TWA	250 ppm	OSHA Z-1

SIGALD - 537462



Page 5 of 15



	950 mg/m3	
TWA	100 ppm	ACGIH
STEL	150 ppm	ACGIH

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.

> Our recommendations on filtering respiratory protection are based on the following standards: DIN

EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection

system.

Recommended Filter

type:

: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Material : butyl-rubber : 60 min Break through time Glove thickness : 0.7 mm

Protective index : Splash contact

Manufacturer : Butoject® (KCL 898)

: This recommendation applies only to the product Remarks

stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-

36124 Eichenzell, Internet: www.kcl.de).

Eye protection : Use equipment for eye protection tested and

approved under appropriate government standards

such as NIOSH (US) or EN 166(EU).

Safety glasses

Skin and body protection : Flame retardant antistatic protective clothing.

Hygiene measures : Change contaminated clothing. Preventive skin

protection recommended. Wash hands after working

with substance.

SIGALD - 537462



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid (68 °F / 20 °C, 1,013 hPa)

Color : colorless

Odor : pleasant, aromatic

Odor Threshold : No data available pH : No data available

Melting point/ range : -99 °F / -73 °C

Method: lit.

Boiling point/boiling range : 185 - 196 °F / 85 - 91 °C

Method: lit.

Flash point : $41 \, ^{\circ}\text{F} / 5 \, ^{\circ}\text{C}$

(1,013.25 hPa)

Method: closed cup, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : No data available

Burning rate : No data available

Self-ignition : 860 °F / 460 °C

1,013 hPa

Upper explosion limit / : Upper explosion limit

Upper flammability limit

8 %(V)

Lower explosion limit / : Lower explosion limit

Lower flammability limit

1.8 %(V)

(99 °F / 37 °C)

Vapor pressure : 92.27 hPa (82.62 °F / 28.12 °C)

Relative vapor density : 3.53

operates as MilliporeSigma in the US and Canada

(Air = 1.0)

Relative density : No data available

Density : 0.872 g/cm3

Water solubility : No data available

SIGALD - 537462

Millipore SigMa

Page 7 of 15

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : 860 °F / 460 °C (1,013 hPa)

Decomposition temperature

: No data available

Viscosity

Viscosity, dynamic : 0.602 mPa.s (68 °F / 20 °C)

Viscosity, kinematic : 0.6 mm2/s (68 °F / 20 °C)

0.475 mm2/s (104 °F / 40 °C)

Flow time : No data available

Explosive properties : Not classified as explosive.

Oxidizing properties : none

Molecular weight : 102.13 g/mol

Particle characteristics

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Vapors may form explosive mixture with air.

Chemical stability : The product is chemically stable under standard

ambient conditions (room temperature) .

Possibility of hazardous

reactions

: Violent reactions possible with:

Strong oxidizing agents

alkalines **Bases**

Conditions to avoid : Avoid moisture.

Heat.

Warming.

Incompatible materials : various plastics

products

Hazardous decomposition : In the event of fire: see section 5

SIGALD - 537462

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 6,750 mg/kg

Remarks: (ECHA)

Symptoms: Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration of

omit.

LC50 Inhalation - Rat - female - 4 h - 63.75 mg/l - vapor

Remarks: (ECHA)

Symptoms: Possible damages:, mucosal irritations LD50 Dermal - Rabbit - male - > 20,000 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation Remarks: No data available

Serious eve damage/eve irritation

Eyes - Rabbit

Result: Eye irritation Remarks: (IUCLID)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative Remarks: (IUCLID)

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: US-EPA Result: negative

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

SIGALD - 537462

4illiPORe

Page 9 of 15

May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: AI4930000

prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Systemic effects:

lack of appetite Headache somnolence Drowsiness Dizziness narcosis

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

isopropyl acetate:

Toxicity to daphnia and

other aquatic

invertebrates

: EC50 (Artemia salina (Brine shrimp)): 110 mg/l

End point: Immobilization Exposure time: 48 h

Test Type: static test Remarks: (ECHA)

Persistence and degradability

Components:

isopropyl acetate:

Biodegradability : aerobic

Inoculum: activated sludge Result: Readily biodegradable.

Biodegradation: 76 % Exposure time: 20 d

Method: OECD Test Guideline 301D

SIGALD - 537462 Page 10 of 15



BOD/ThOD : 61 %

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential: Regulation: 40 CFR Protection of Environment; Part

82 Protection of Stratospheric Ozone - CAA Section

602 Class I Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

Components:

isopropyl acetate:

Results of PBT and vPvB

assessment

: Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex

XIII.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Waste material must be disposed of in accordance

with the national and local regulations. Leave

chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product

itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1220

Proper shipping name : Isopropyl acetate

Class : 3 Packing group : II

Labels : Class 3 - Flammable liquids

Packing instruction (cargo: 364

aircraft)

Packing instruction : 353

(passenger aircraft)

SIGALD - 537462

Page 11 of 15



IMDG-Code

UN number : UN 1220

Proper shipping name : ISOPROPYL ACETATE

Class : 3 Packing group : II Labels : 3

EmS Code : F-E, S-D

Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National regulation

49 CFR Road

UN/ID/NA number : UN 1220

Proper shipping name : Isopropyl acetate

Class : 3 Packing group : II

Labels : Class 3 - Flammable liquids

ERG Code : 129 Marine pollutant : no

Poison Inhalation Hazard : No

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 : Fire Hazard

Hazards Acute Health Hazard

SARA 313 : This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

SIGALD - 537462

1illiPDRE

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

isopropyl acetate 108-21-4 >= 90 - <= 100 %

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

isopropyl acetate 108-21-4

Pennsylvania Right To Know

isopropyl acetate 108-21-4

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-

1 Limits for Air Contaminants

SIGALD - 537462

Page 13 of 15



ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Decomposition Temperature; SARA Superfund Amendments Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 05/05/2025

SIGALD - 537462

Page 14 of 15



The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

US / EN

SIGALD - 537462



Page 15 of 15