

SAFETY DATA SHEET

Version 7.0 Revision Date 10/01/2024 Print Date 10/02/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Cumene hydroperoxide

Product Number : 247502 Brand : Aldrich

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 4), H227 Organic peroxides (Type F), H242 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 4), H312

Aldrich - 247502

Page 1 of 17



Skin corrosion (Category 1B), H314 Serious eye damage (Category 1), H318 Carcinogenicity (Category 1B), H350

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Lungs, H373

Aspiration hazard (Category 1), H304

Short-term (acute) aquatic hazard (Category 2), H401 Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram	
Signal Word	Danger
Hazard Statements	
H227	Combustible liquid.
H242	Heating may cause a fire.
H302 + H312	Harmful if swallowed or in contact with skin.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H373	May cause damage to organs (Lungs) through prolonged or
H411	repeated exposure if inhaled. Toxic to aquatic life with long lasting effects.
11411	Toxic to aquatic life with long lasting effects.
Precautionary Statements	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and
D210	understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No
P220	smoking. Keep/Store away from clothing/ combustible materials.
P234	Keep only in original container.
P260	Do not breathe mist or vapors.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 +	IF IN EYES: Rinse cautiously with water for several minutes.
P310	Remove contact lenses, if present and easy to do. Continue
1 310	Remove contact ichoes, if present and easy to do. Continue



	rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant
	foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P410	Protect from sunlight.
P420	Store away from other materials.
P501	Dispose of contents/ container to an approved waste disposal
	plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration
Cumol hydroperoxide	9		
CAS-No. EC-No. Index-No.	80-15-9 201-254-7 617-002-00-8	Flam. Liq. 4; Org. Perox. E; Acute Tox. 4; Acute Tox. 3; Acute Tox. 4; Skin Corr. 1B; Eye Dam. 1; STOT RE 2; Aquatic Acute 2; Aquatic Chronic 2; H227, H242, H302, H331, H312, H314, H318, H373, H401, H411 Concentration limits: 3 - < 10 %: Skin Irrit. 2, H315; 1 - < 3 %: Eye Irrit. 2, H319; >= 10 %: Skin Corr. 1B, H314; 3 - < 10 %: Eye Dam. 1, H318; >= 1 %: STOT SE 3, H335;	>= 70 - < 90 %
cumene			
CAS-No. EC-No. Index-No.	98-82-8 202-704-5 601-024-00-X	Flam. Liq. 3; Carc. 1B; STOT SE 3; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 2; H226, H350, H335, H304, H401, H411	>= 10 - < 20 %
2-Phenylpropan-2-ol			
CAS-No. EC-No.	617-94-7 210-539-5	Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; H302, H315, H319	>= 10 - < 20 %

Aldrich - 247502 Page 3 of 17



For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Pulmonary failure possible after aspiration of vomit. Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

Explosive decomposition possible on heating.

Aldrich - 247502

....

Page 4 of 17

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep locked up or in an area accessible only to qualified or authorized persons. Separately or together with other organic peroxides only and away from sources of ignition and heat.

Storage stabilityRecommended storage temperature 2 - 8 °C

Storage class

Storage class (TRGS 510): 5.2: Organic peroxides and self-reacting hazardous materials

Aldrich - 247502

Page 5 of 17



7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Ingredients with workplace control parameters				
Component	CAS-No.	Value	Control parameters	Basis
Cumol hydroperoxide	80-15-9	TWA	1 ppm	USA. Workplace Environmental Exposure Levels (WEEL)
	Remarks	Skin		
cumene	98-82-8	TWA	5 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed animal carcinogen with unknown relevance to humans		en with unknown relevance to
		TWA	50 ppm 245 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		
		TWA	50 ppm 245 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Skin designation		
		PEL	50 ppm 245 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Aldrich - 247502

Page 6 of 17



Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 240 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

protective clothing

Respiratory protection

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented. required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless, to, light yellow

b) Odor
c) Odor Threshold
d) pH
e) Melting
No data available
No data available
No data available

point/freezing point

and boiling range

f) Initial boiling point 100 - 101 °C 212 - 214 °F at 10 hPa - lit.

g) Flash point
h) Evaporation rate
i) Flammability (solid, No data available

gas)

Aldrich - 247502

Millipore SigMa j) Upper/lower No data available flammability or

explosive limits

k) Vapor pressure 0.5 hPa at 55 °C (131 °F) < 0.04 hPa at 20 °C(68 °F)

I) Vapor density 5.25 - (Air = 1.0)

m) Density 1.03 g/mL at 25 °C (77 °F)

Relative density No data available

n) Water solubility soluble

o) Partition coefficient: No data available

n-octanol/water

p) Autoignition No data available temperature

q) Decomposition 70 °C (158 °F) - Self-Accelerating decomposition temperature

temperature (SADT)

r) Viscosity No data available

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

9.2 Other safety information

Relative vapor 5.25 - (Air = 1.0)

density

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

10.2 Chemical stability

Self-Accelerating decomposition temperature (SADT) 70°C

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

alkalines

Lead

Cobalt

Copper

Bases

carbon/soot

Risk of explosion with:

Amines

combustible substances

hydrides

Aldrich - 247502

Millipore SigMa mineral acids
iodides
nitrides
Organic Substances
oxidisable substances
Reducing agents
Rust
acids
Sulfides
Heavy metal salts

10.4 Conditions to avoid

Do not expose to temperatures above: 40°C Strong heating.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - 477.87 mg/kg

(Calculation method)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Acute toxicity estimate Inhalation - 4 h - 4.03 mg/l - vapor(Calculation method)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Acute toxicity estimate Dermal - 1,429 mg/kg

(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes burns.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye damage.

Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Possible carcinogen.



IARC: 2B - Group 2B: Possibly carcinogenic to humans (cumene)

NTP: RAHC - Reasonably anticipated to be a human carcinogen (cumene)

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture may cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Mixture may cause damage to organs through prolonged or repeated exposure.

- Lungs

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

RTECS: MX2450000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Components

Cumol hydroperoxide

Acute toxicity

LD50 Oral - Rat - 382 mg/kg

Remarks: Kidney, Ureter, Bladder: Hematuria.

(RTECS)

LC50 Inhalation - Rat - male - 4 h - 1.37 mg/l

Remarks: (ECHA)

LD50 Dermal - Rat - male and female - 1,200 - 1,520 mg/kg

Remarks: (ECHA) No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns.

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2) (ECHA)

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available



Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Result: positive

Species: Mouse - male and female

Result: negative Remarks: (ECHA) Carcinogenicity No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Lungs

Aspiration hazard

No data available

cumene

Acute toxicity

Symptoms: gastric pain, Vomiting

Inhalation: Irritating to respiratory system.

Symptoms: mucosal irritations, Cough, Shortness of breath, Headache, Nausea,

Vomiting, Possible damages:, damage of respiratory tract

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation (OECD Test Guideline 404)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 72 h (OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig



Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Result: negative Test Type: Ames test

Test system: S. typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Result: negative

Test Type: unscheduled DNA synthesis assay

Test system: rat hepatocytes

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Red blood cells (erythrocytes)

Result: negative

Method: OECD Test Guideline 474 Species: Rat - male - Bone marrow

Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

Presumed to have carcinogenic potential for humans

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory Tract

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute oral toxicity - gastric pain, Vomiting

Acute inhalation toxicity - mucosal irritations, Cough, Shortness of breath, Headache, Nausea, Vomiting, Possible damages:, damage of respiratory tract

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

2-Phenylpropan-2-ol

Acute toxicity

LD50 Oral - Rat - 1,300 mg/kg

Remarks: (RTECS)

Inhalation: No data available Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Severe skin irritation



Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

Components

Cumol hydroperoxide

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) -

3.9 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia static test EC50 - Daphnia magna (Water flea) - 18.84 mg/l -

and other aquatic 48 h

Aldrich - 247502 Page 13 of 17

invertebrates (OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) -

3.1 mg/l - 72 h

(OECD Test Guideline 201)

cumene

flow-through test LC50 - Cyprinodon variegatus (sheepshead Toxicity to fish

minnow) - 4.7 mg/l - 96 h

(US-EPA)

Toxicity to daphnia and other aquatic

static test EC50 - Daphnia magna (Water flea) - 2.14 mg/l - 48

invertebrates (OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) -

2.01 mg/l - 72 h

(OECD Test Guideline 201)

static test EC50 - activated sludge - > 2,000 mg/l - 3 h Toxicity to bacteria

(OECD Test Guideline 209)

Toxicity to daphnia and other aquatic

semi-static test NOEC - Daphnia magna (Water flea) - 0.35

mg/l - 21 d

invertebrates(Chronic (OECD Test Guideline 211)

toxicity)

2-Phenylpropan-2-ol

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 3109 Class: 5.2

Proper shipping name: Organic peroxide type F, liquid (Cumyl hydroperoxide, <=90%)

(Cumyl hydroperoxide)

Aldrich - 247502

Page 14 of 17



Reportable Quantity (RQ): 12 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 3109 Class: 5.2 EMS-No: F-J, S-R Proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID (CUMYL HYDROPEROXIDE)

(Cumyl hydroperoxide) Marine pollutant : yes

IATA

UN number: 3109 Class: 5.2 (HEAT)

Proper shipping name: Organic peroxide type F, liquid (Cumyl hydroperoxide) (Cumyl

hydroperoxide)

Special Provisions: "Keep away from heat" label required.

SECTION 15: Regulatory information

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Cumol hydroperoxide	80-15-9	10	12

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting

levels established by SARA Title III, Section 313:

Cumol 80-15-9 >= 70 - < 90 %

hydroperoxide

cumene 98-82-8 >= 10 - < 20 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

cumene 98-82-8 >= 10 - < 20 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Cumol hydroperoxide 80-15-9 >= 70 - < 90 % cumene 98-82-8 >= 10 - < 20 %

Aldrich - 247502

Page 15 of 17

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Cumol hydroperoxide	80-15-9
cumene	98-82-8

Pennsylvania Right To Know

Cumol hydroperoxide	80-15-9
cumene	98-82-8

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including cumene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16: Other information

Relevant changes since previous version

- 5. Fire-fighting measures
- 10. Stability and reactivity
- 14. Transport information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its

Aldrich - 247502 Page 16 of 17



Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 7.0 Revision Date: 10/01/2024 Print Date: 10/02/2024

