

SAFETY DATA SHEET

Version 6.9 Revision Date 09/07/2024 Print Date 09/08/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Octane

Product Number : 412236 Brand : SIGALD

Index-No. : 601-009-00-8 CAS-No. : 111-65-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

SIGALD - 412236

Page 1 of 12



Aspiration hazard (Category 1), H304 Short-term (acute) aquatic hazard (Category 1), H400 Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram Signal Word Danger Hazard Statements H225 Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. H304 Causes skin irritation. H315 H336 May cause drowsiness or dizziness. H410 Very toxic to aquatic life with long lasting effects. **Precautionary Statements** Keep away from heat/ sparks/ open flames/ hot surfaces. No P210 smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. P271 P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301 + P310 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P331 Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. P332 + P313 P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage. Store in a well-ventilated place. Keep container tightly closed. P403 + P233 P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

plant.

SIGALD - 412236



Page 2 of 12

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : n-Octane

Formula : C8H18

Molecular weight : 114.23 g/mol : 111-65-9 CAS-No. EC-No. : 203-892-1 Index-No. : 601-009-00-8

Component	Classification	Concentration
n-octane		
	Flam. Liq. 2; Skin Irrit. 2;	<= 100 %
	STOT SE 3; Asp. Tox. 1;	
	Aquatic Acute 1; Aquatic	
	Chronic 1; H225, H315,	
	H336, H304, H400, H410	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 **Description of first-aid measures**

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eve contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed No data available

SIGALD - 412236

Page 3 of 12

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

SIGALD - 412236

Page 4 of 12



Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

hygroscopic

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
n-octane	111-65-9	TWA	75 ppm 350 mg/m3	USA. NIOSH Recommended Exposure Limits
		С	385 ppm 1,800 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	500 ppm 2,350 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	300 ppm 1,450 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	375 ppm 1,800 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		TWA	300 ppm	USA. ACGIH Threshold Limit Values (TLV)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SIGALD - 412236



Page 5 of 12

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 480 min

Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 30 min

Material tested: KCL 741 Dermatril® L

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor characteristic

SIGALD - 412236

Page 6 of 12



c) Odor Threshold No data availabled) pH No data available

e) Melting point/ range: -57 °C (-71 °F) - lit. point/freezing point

f) Initial boiling point 125 - 127 °C 257 - 261 °F - lit. and boiling range

g) Flash point 13 °C (55 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, No data available gas)

j) Upper/lower Upper explosion limit: 6.5 %(V) flammability or explosive limits Upper explosion limit: 0.96 %(V)

k) Vapor pressure 14.7 hPa at 20.0 °C (68.0 °F)

I) Vapor density No data available

m) Density 0.703 g/cm3 at 25 °C (77 °F) - lit.

Relative density No data available

n) Water solubility ca.0.007 g/l at 20 °C (68 °F)

o) Partition coefficient: log Pow: 5.15 n-octanol/water

p) Autoignition 220 °C (428 °F) temperature

q) Decomposition No data available temperature

r) Viscosity 0.8 mm2/s at 20 °C (68 °F) -

s) Explosive properties No data available

t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with: Strong oxidizing agents

SIGALD - 412236

Millipore Sigma

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - > 5,000 mg/kg

(OECD Test Guideline 401)

Remarks: The value is given in analogy to the following substances: isooctane

LC50 Inhalation - Rat - male and female - 4 h - > 24.88 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Remarks: The value is given in analogy to the following substances: isooctane

Skin corrosion/irritation

Skin - Rabbit

Result: Irritating to skin. - 24 h (OECD Test Guideline 404)

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: isooctane

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: isooctane

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

SIGALD - 412236

Page 8 of 12

Result: negative

Remarks: The value is given in analogy to the following substances: n-heptaneTest Type:

Chromosome aberration test in vitro Test system: rat hepatocytes Method: OECD Test Guideline 473

Result: negative

Remarks: The value is given in analogy to the following substances: n-heptaneTest Type:

In vitro mammalian cell gene mutation test Test system: human lymphoblastoid cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Remarks: The value is given in analogy to the following substances:

isooctane Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

RTECS: RG8400000

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Vomiting, Central nervous system depression, narcosis

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

After uptake of large quantities:

Headache

Dizziness

Nausea

Vomiting

agitation

somnolence

Drowsiness

Unconsciousness

SIGALD - 412236

MilliPORE

respiratory arrest

It generally applies for aliphatic hydrocarbons with 6 - 18 carbon atoms that they may cause pneumonia, in some cases also pulmonary oedema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar). After absorption of very large quantities: narcosis.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - Oryzias latipes - 0.42 mg/l - 96.0 h

Remarks: (Lit.)

Toxicity to daphnia and other aquatic

static test EC50 - Daphnia magna (Water flea) - 0.38 mg/l - 48 h

Remarks: (ECOTOX Database)

Toxicity to algae

invertebrates

NOEC - Pseudokirchneriella subcapitata (microalgae) - 5.8 mg/l - 72

Remarks: (Lit.)

Toxicity to daphnia and other aquatic

static test NOEC - Daphnia magna (Water flea) - 0.17 mg/l - 21 d

(OECD Test Guideline 211)

invertebrates(Chronic Remarks: (in analogy to similar products)

toxicity)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 10 d

Result: 70.3 % - Readily biodegradable.

Remarks: (ECHA)

Theoretical oxygen 3,500 mg/gdemand Remarks: (Lit.)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SIGALD - 412236

Page 10 of 12



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 1262 Class: 3 Packing group: II

Proper shipping name: Octanes Reportable Quantity (RQ):

Marine pollutant: yes Poison Inhalation Hazard: No

IMDG

UN number: 1262 Class: 3 Packing group: II EMS-No: F-E, S-E

Proper shipping name: OCTANES

Marine pollutant : yes Marine pollutant : yes

IATA

UN number: 1262 Class: 3 Packing group: II

Proper shipping name: Octanes

SECTION 15: Regulatory information

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 : Fire Hazard

Hazards Acute Health Hazard

SIGALD - 412236

Millipore SigMa

Page 11 of 12

SARA 313 : This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

US State Regulations

Massachusetts Right To Know

n-octane 111-65-9

Pennsylvania Right To Know

n-octane 111-65-9

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.9 Revision Date: 09/07/2024 Print Date: 09/08/2024

SIGALD - 412236

Page 12 of 12

