

Agglomerative clustering_unsupervised Euclidean with complete linkage

complete or maximum linkage uses the maximum distances between all observations of the two sets.

```
In [1]: from sklearn import datasets
from sklearn import preprocessing
from sklearn.model_selection import train_test_split
from sklearn import cluster
from sklearn.cluster import KMeans
from sklearn.ensemble import IsolationForest
from sklearn.neighbors import LocalOutlierFactor
from sklearn import svm, neighbors
from sklearn.neighbors import NearestNeighbors
from sklearn.cluster import AgglomerativeClustering
from sklearn.metrics import classification_report
from sklearn.metrics import confusion_matrix
from sklearn.metrics import recall_score
from sklearn.metrics import roc_auc_score
from sklearn.model_selection import GridSearchCV
from sklearn.metrics import make_scorer
from sklearn.metrics import accuracy_score

import pandas as pd
import numpy as np
import itertools
import matplotlib.pyplot as plt
import datetime

%matplotlib inline
```

```
In [2]: train_split = 0.80
nrows = 250_000
path = 'c:/users/ugy1/abs/'
df=pd.read_csv(path+'datasets/processed_abs_loan_'+str(nrows)+'.csv',
               #usecols=use_list,
               #sep='\t',
               #compression=bz2,
               nrows=nrows,
               low_memory=False,
               index_col=0,
               parse_dates=True
               )

df.shape
```

```
Out[2]: (237024, 58)
```


```
In [3]: column_list=df.columns.tolist()
```

In [4]: `df.head()`

Out[4]:

	originalloanamount	originalloanterm	originalinterestratepercentage	graceperiodnuml
0	66711.84	60	3.29	1
1	16258.45	60	0.90	0
2	31930.41	72	2.90	1
3	26065.02	65	0.90	0
4	42091.00	72	3.90	0

5 rows × 58 columns



In [5]: `# prepare label for scikit-learn`
`Y=df.label.values`
`Y.shape`

Out[5]: (237024,)

In [6]: `# prepare input data for scikit-learn`
`input=df.values`
`input.shape`

Out[6]: (237024, 58)

In [7]: `# calculate train/test split`
`len_train = int(len(input)*train_split)`
`print(len_train)`

189619

In [8]: `# apply train/test split to labels`
`y_train = Y[0:len_train]`
`y_test = Y[len_train:]`
`x_train = input[0:len_train]`
`x_test = input[len_train:]`
`x_train.shape`

Out[8]: (189619, 58)


In [9]: `export_x_test = pd.DataFrame(data=x_test)`

```
In [10]: export_x_test.columns=column_list
export_x_test.rename(columns={'label':'True Label'}, inplace=True)
export_x_test.head()
```

Out[10]:

	originalloanamount	originalloanterm	originalinterestratepercentage	graceperiodnuml
0	36863.24	72.0	1.00	1.0
1	23811.32	60.0	1.90	0.0
2	30669.00	48.0	1.00	1.0
3	54083.21	72.0	1.00	0.0
4	31557.75	72.0	3.89	1.0

5 rows × 58 columns



```
In [11]: #from sklearn.preprocessing import MinMaxScaler
# from sklearn.preprocessing import minmax_scale
# from sklearn.preprocessing import MaxAbsScaler
from sklearn.preprocessing import StandardScaler
# from sklearn.preprocessing import RobustScaler
# from sklearn.preprocessing import Normalizer
# from sklearn.preprocessing import QuantileTransformer
# from sklearn.preprocessing import PowerTransformer
```

```
In [12]: x_scaler=StandardScaler()
x_train = x_scaler.fit_transform(x_train)
x_test = x_scaler.fit_transform(x_test)
```

```
In [13]: #Linkage=["complete", "single", "average", 'ward']

agg=AgglomerativeClustering(affinity='euclidean', compute_full_tree='auto',
                             connectivity=None, linkage="complete", memory=None, n_clusters=2,
                             pooling_func='deprecated').fit(x_test)
# agg = AgglomerativeClustering(n_clusters=2,
#                               linkage="average", affinity="cityblock").fit(x_test)
```

```
In [14]: #x_pred = x_test
```

```
In [15]: prediction_agg = agg.labels_
```

```
In [16]: np.unique(prediction_agg)
```

```
Out[16]: array([0, 1], dtype=int64)
```

```
In [17]: np.bincount(np.array(prediction_agg).reshape(1,prediction_agg.size)[0])
```

```
Out[17]: array([47400,      5], dtype=int64)
```


```
In [18]: export_x_test['Predicted Label']=prediction_agg
```

```
In [19]: export_x_test.head()
```

```
Out[19]:
```

	originalloanamount	originalloanterm	originalinterestratepercentage	graceperiodnuml
0	36863.24	72.0	1.00	1.0
1	23811.32	60.0	1.90	0.0
2	30669.00	48.0	1.00	1.0
3	54083.21	72.0	1.00	0.0
4	31557.75	72.0	3.89	1.0

5 rows × 59 columns



```
In [20]: export_x_test.shape
```

```
Out[20]: (47405, 59)
```

```
In [21]: export_x_test.to_csv(path+"prediction/agg/predicated_agg_euc_complete_abs_loan  
s_"+str(nrows)+".csv", chunksize=10000)
```

```
In [22]: def plot_confusion_matrix(cm, title, classes=['Current', 'Non_Current'],
                                     cmap=plt.cm.Blues, save=False, saveas="MyFigure.png"
                                     ):

    # print Confusion matrix with blue gradient colours

    cm = cm.astype('float') / cm.sum(axis=1)[:, np.newaxis]

    plt.imshow(cm, interpolation='nearest', cmap=cmap)
    plt.title(title)
    plt.colorbar()
    tick_marks = np.arange(len(classes))
    plt.xticks(tick_marks, classes, rotation=90)
    plt.yticks(tick_marks, classes)

    fmt = '.1%'
    thresh = cm.max() / 2.
    for i, j in itertools.product(range(cm.shape[0]), range(cm.shape[1])):
        plt.text(j, i, format(cm[i, j], fmt),
                 horizontalalignment="center",
                 color="white" if cm[i, j] > thresh else "black")

    plt.tight_layout()
    plt.ylabel('True label')
    plt.xlabel('Predicted label')

    if save:
        plt.savefig(saveas, dpi=100)
```

```

In [23]: def plot_gridsearch_cv(results, estimator, x_min, x_max, y_min, y_max, save=False, saveas="MyFigure.png"):

    # print GridSearch cross-validation for parameters

    plt.figure(figsize=(10,8))
    plt.title("GridSearchCV for "+estimator, fontsize=24)

    plt.xlabel(estimator)
    plt.ylabel("Score")
    plt.grid()

    ax = plt.axes()
    ax.set_xlim(x_min, x_max)
    ax.set_ylim(y_min, y_max)

    pad = 0.005
    X_axis = np.array(results["param_"+estimator].data, dtype=float)

    for scorer, color in zip(sorted(scoring), ['b', 'k']):
        for sample, style in (('train', '--'), ('test', '-')):
            sample_score_mean = results['mean_%s_%s' % (sample, scorer)]
            sample_score_std = results['std_%s_%s' % (sample, scorer)]
            ax.fill_between(X_axis, sample_score_mean - sample_score_std,
                           sample_score_mean + sample_score_std,
                           alpha=0.1 if sample == 'test' else 0, color=color)
            ax.plot(X_axis, sample_score_mean, style, color=color,
                    alpha=1 if sample == 'test' else 0.7,
                    label="%s (%s)" % (scorer, sample))

        best_index = np.nonzero(results['rank_test_%s' % scorer] == 1)[0][0]
        best_score = results['mean_test_%s' % scorer][best_index]

        # Plot a dotted vertical line at the best score for that scorer marked by x
        ax.plot([X_axis[best_index], ] * 2, [0, best_score],
                linestyle='-.', color=color, marker='x', markeredgewidth=3, ms=8
        )

        # Annotate the best score for that scorer
        ax.annotate("%0.2f" % best_score,
                    (X_axis[best_index], best_score+pad))

    plt.legend(loc="best")
    plt.grid('off')
    plt.tight_layout()
    if save:
        plt.savefig(saveas, dpi=100)


    plt.show()

```

```
In [24]: print(classification_report(y_test, prediction_agg, target_names=['Current',  
    'Non_Current']))  
print ("AUC: ", "{:.1%}".format(roc_auc_score(y_test, prediction_agg)))  
cm = confusion_matrix(y_test, prediction_agg)  
plot_confusion_matrix(cm, title="Agg Euc Complete Confusion Matrix",save=True,  
    saveas='prediction/agg/cm'+str(' Agg Euc Complete Accura  
cy-')+str(nrows)+' .jpg')
```

	precision	recall	f1-score	support
Current	0.97	1.00	0.98	45938
Non_Current	0.20	0.00	0.00	1467
avg / total	0.95	0.97	0.95	47405

AUC: 50.0%



```

In [25]: class_names = ['Current', 'Non-Current']

def plot_confusion_matrix(cm, classes,
                          normalize=False,
                          title='Confusion matrix',
                          cmap=plt.cm.Blues):
    """
    This function prints and plots the confusion matrix.
    Normalization can be applied by setting `normalize=True`.
    """
    if normalize:
        cm = cm.astype('float') / cm.sum(axis=1)[:, np.newaxis]
        print("Normalized confusion matrix")
    else:
        print('Confusion matrix, without normalization')

    print(cm)

    plt.imshow(cm, interpolation='nearest', cmap=cmap)
    plt.title(title)
    plt.colorbar()
    tick_marks = np.arange(len(classes))
    plt.xticks(tick_marks, classes, rotation=45)
    plt.yticks(tick_marks, classes)

    fmt = '.2f' if normalize else 'd'
    thresh = cm.max() / 2.
    for i, j in itertools.product(range(cm.shape[0]), range(cm.shape[1])):
        plt.text(j, i, format(cm[i, j], fmt),
                 horizontalalignment="center",
                 color="white" if cm[i, j] > thresh else "black")

    plt.ylabel('True label')
    plt.xlabel('Predicted label')
    plt.tight_layout()

print('ROC_AUC_SCORE ; ', roc_auc_score(y_test, prediction_agg))
# Compute confusion matrix
cnf_matrix = confusion_matrix(y_test, prediction_agg)
np.set_printoptions(precision=2)


# Plot non-normalized confusion matrix
plt.figure()
plot_confusion_matrix(cnf_matrix, classes=class_names, title= 'Confusion matrix, Agg Euc Complete')
plt.savefig('prediction/agg/cm'+str(' Agg Euc Complete-')+str(nrows)+'.jpg')
plt.show()

```


ROC_AUC_SCORE ; 0.500297294688

Confusion matrix, without normalization

```
[[45934    4]
 [ 1466    1]]
```



In []: