



# Package math

```
import "math"
```

[Overview](#)[Index](#)[Examples](#)[Subdirectories](#)

## Overview ▾

Package math provides basic constants and mathematical functions.

This package does not guarantee bit-identical results across architectures.

## Index ▾

### Constants

[func Abs\(x float64\) float64](#)[func Acos\(x float64\) float64](#)[func Acosh\(x float64\) float64](#)[func Asin\(x float64\) float64](#)[func Asinh\(x float64\) float64](#)[func Atan\(x float64\) float64](#)[func Atan2\(y, x float64\) float64](#)[func Atanh\(x float64\) float64](#)[func Cbrt\(x float64\) float64](#)[func Ceil\(x float64\) float64](#)[func Copysign\(x, y float64\) float64](#)[func Cos\(x float64\) float64](#)[func Cosh\(x float64\) float64](#)[func Dim\(x, y float64\) float64](#)[func Erf\(x float64\) float64](#)[func Erfc\(x float64\) float64](#)[func Erfcinv\(x float64\) float64](#)[func Erfinv\(x float64\) float64](#)[func Exp\(x float64\) float64](#)[func Exp2\(x float64\) float64](#)[func Expm1\(x float64\) float64](#)[func FMA\(x, y, z float64\) float64](#)[func Float32bits\(f float32\) uint32](#)[func Float32frombits\(b uint32\) float32](#)[func Float64bits\(f float64\) uint64](#)

```
func Float64frombits(b uint64) float64
func Floor(x float64) float64
func Frexp(f float64) (frac float64, exp int)
func Gamma(x float64) float64
func Hypot(p, q float64) float64
func Llogb(x float64) int
func Inf(sign int) float64
func IsInf(f float64, sign int) bool
func IsNaN(f float64) (is bool)
func J0(x float64) float64
func J1(x float64) float64
func Jn(n int, x float64) float64
func Ldexp(frac float64, exp int) float64
func Lgamma(x float64) (lgamma float64, sign int)
func Log(x float64) float64
func Log10(x float64) float64
func Log1p(x float64) float64
func Log2(x float64) float64
func Logb(x float64) float64
func Max(x, y float64) float64
func Min(x, y float64) float64
func Mod(x, y float64) float64
func Modf(f float64) (int float64, frac float64)
func NaN() float64
func Nextafter(x, y float64) (r float64)
func Nextafter32(x, y float32) (r float32)
func Pow(x, y float64) float64
func Pow10(n int) float64
func Remainder(x, y float64) float64
func Round(x float64) float64
func RoundToEven(x float64) float64
func Signbit(x float64) bool
func Sin(x float64) float64
func Sincos(x float64) (sin, cos float64)
func Sinh(x float64) float64
func Sqrt(x float64) float64
func Tan(x float64) float64
func Tanh(x float64) float64
func Trunc(x float64) float64
func Y0(x float64) float64
func Y1(x float64) float64
func Yn(n int, x float64) float64
```

## Examples (Collapse All)

```
Abs
Acos
Acosh
Asin
Asinh
Atan
```

Atan2  
Atanh  
Cbrt  
Ceil  
Copysign  
Cos  
Cosh  
Dim  
Exp  
Exp2  
Expm1  
Floor  
Log  
Log10  
Log2  
Mod  
Modf  
Pow  
Pow10  
Round  
RoundToEven  
Sin  
Sincos  
Sinh  
Sqrt  
Tan  
Tanh  
Trunc

## Package files

[abs.go](#) [acosh.go](#) [asin.go](#) [asinh.go](#) [atan.go](#) [atan2.go](#) [atanh.go](#) [bits.go](#) [cbrt.go](#) [const.go](#) [copysign.go](#)  
[dim.go](#) [erf.go](#) [erfinv.go](#) [exp.go](#) [exp\\_asm.go](#) [expm1.go](#) [floor.go](#) [fma.go](#) [frexp.go](#) [gamma.go](#) [hypot.go](#)  
[j0.go](#) [j1.go](#) [jn.go](#) [ldexp.go](#) [lgamma.go](#) [log.go](#) [log10.go](#) [log1p.go](#) [logb.go](#) [mod.go](#) [modf.go](#)  
[nextafter.go](#) [pow.go](#) [pow10.go](#) [remainder.go](#) [signbit.go](#) [sin.go](#) [sincos.go](#) [sinh.go](#) [sqrt.go](#) [tan.go](#)  
[tanh.go](#) [trig\\_reduce.go](#) [unsafe.go](#)

## Constants

Mathematical constants.

```
const (  
    E      =  
    2.71828182845904523536028747135266249775724709369995957496696763 //  
    https://oeis.org/A001113  
    Pi     =  
    3.14159265358979323846264338327950288419716939937510582097494459 //  
    https://oeis.org/A000796  
    Phi    =  
    1.61803398874989484820458683436563811772030917980576286213544862 //  
    https://oeis.org/A001622  
  
    Sqrt2   =  
    1.41421356237309504880168872420969807856967187537694807317667974 //  
    https://oeis.org/A002193  
    SqrtE   =  
    1.64872127070012814684865078781416357165377610071014801157507931 //  
    https://oeis.org/A019774  
    SqrtPi  =  
    1.77245385090551602729816748334114518279754945612238712821380779 //  
    https://oeis.org/A002161  
    SqrtPhi =  
    1.27201964951406896425242246173749149171560804184009624861664038 //  
    https://oeis.org/A139339  
  
    Ln2     =  
    0.693147180559945309417232121458176568075500134360255254120680009 //  
    https://oeis.org/A002162  
    Log2E   = 1 / Ln2  
    Ln10    =  
    2.30258509299404568401799145468436420760110148862877297603332790 //  
    https://oeis.org/A002392  
    Log10E  = 1 / Ln10  
)
```

Floating-point limit values. Max is the largest finite value representable by the type. SmallestNonzero is the smallest positive, non-zero value representable by the type.

```
const (
    MaxFloat32          = 3.40282346638528859811704183484516925440e+38
    // 2**127 * (2**24 - 1) / 2**23
    SmallestNonzeroFloat32 =
    1.401298464324817070923729583289916131280e-45 // 1 / 2**(127 - 1 + 23)

    MaxFloat64          =
    1.797693134862315708145274237317043567981e+308 // 2**1023 * (2**53 - 1) /
    2**52
    SmallestNonzeroFloat64 =
    4.940656458412465441765687928682213723651e-324 // 1 / 2**(1023 - 1 + 52)
)
```

Integer limit values.

```
const (
    MaxInt8   = 1<<7 - 1
    MinInt8   = -1 << 7
    MaxInt16  = 1<<15 - 1
    MinInt16  = -1 << 15
    MaxInt32  = 1<<31 - 1
    MinInt32  = -1 << 31
    MaxInt64  = 1<<63 - 1
    MinInt64  = -1 << 63
    MaxUint8  = 1<<8 - 1
    MaxUint16 = 1<<16 - 1
    MaxUint32 = 1<<32 - 1
    MaxUint64 = 1<<64 - 1
)
```

## func Abs

```
func Abs(x float64) float64
```

Abs returns the absolute value of x.

Special cases are:

```
Abs(±Inf) = ±Inf
Abs(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    x := math.Abs(-2)
    fmt.Printf("%.1f\n", x)

    y := math.Abs(2)
    fmt.Printf("%.1f\n", y)
}
```

[Run](#)[Format](#)[Share](#)

## func Acos

```
func Acos(x float64) float64
```

Acos returns the arccosine, in radians, of x.

Special case is:

```
Acos(x) = NaN if x < -1 or x > 1
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Acos(1))
}
```

[Run](#)[Format](#)[Share](#)

## func Acosh

```
func Acosh(x float64) float64
```

Acosh returns the inverse hyperbolic cosine of x.

Special cases are:

```
Acosh(+Inf) = +Inf
Acosh(x) = NaN if x < 1
Acosh(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Acosh(1))
}
```

[Run](#)[Format](#)[Share](#)

## func Asin

```
func Asin(x float64) float64
```

Asin returns the arcsine, in radians, of x.

Special cases are:

```
Asin(±0) = ±0
Asin(x) = NaN if x < -1 or x > 1
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Asin(0))
}
```

[Run](#)[Format](#)[Share](#)

## func Asinh

```
func Asinh(x float64) float64
```

Asinh returns the inverse hyperbolic sine of x.

Special cases are:

```
Asinh(±0) = ±0
Asinh(±Inf) = ±Inf
Asinh(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Asinh(0))
}
```

[Run](#)[Format](#)[Share](#)

## func Atan



```
func Atan(x float64) float64
```

Atan returns the arctangent, in radians, of x.

Special cases are:

```
Atan( $\pm 0$ ) =  $\pm 0$   
Atan( $\pm \text{Inf}$ ) =  $\pm \text{Pi}/2$ 
```

### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    fmt.Printf("%.2f", math.Atan(0))  
}
```

[Run](#)[Format](#)[Share](#)

## func Atan2

```
func Atan2(y, x float64) float64
```

Atan2 returns the arc tangent of y/x, using the signs of the two to determine the quadrant of the return value.

Special cases are (in order):

```
Atan2(y, NaN) = NaN
Atan2(NaN, x) = NaN
Atan2(+0, x>=0) = +0
Atan2(-0, x>=0) = -0
Atan2(+0, x<=-0) = +Pi
Atan2(-0, x<=-0) = -Pi
Atan2(y>0, 0) = +Pi/2
Atan2(y<0, 0) = -Pi/2
Atan2(+Inf, +Inf) = +Pi/4
Atan2(-Inf, +Inf) = -Pi/4
Atan2(+Inf, -Inf) = 3Pi/4
Atan2(-Inf, -Inf) = -3Pi/4
Atan2(y, +Inf) = 0
Atan2(y>0, -Inf) = +Pi
Atan2(y<0, -Inf) = -Pi
Atan2(+Inf, x) = +Pi/2
Atan2(-Inf, x) = -Pi/2
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Atan2(0, 0))
}
```

[Run](#)[Format](#)[Share](#)

## func Atanh

```
func Atanh(x float64) float64
```

Atanh returns the inverse hyperbolic tangent of x.

Special cases are:

```
Atanh(1) = +Inf
Atanh( $\pm 0$ ) =  $\pm 0$ 
Atanh(-1) = -Inf
Atanh(x) = NaN if  $x < -1$  or  $x > 1$ 
Atanh(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Atanh(0))
}
```

[Run](#)[Format](#)[Share](#)

## func Cbrt

```
func Cbrt(x float64) float64
```

Cbrt returns the cube root of x.

Special cases are:

```
Cbrt( $\pm 0$ ) =  $\pm 0$ 
Cbrt( $\pm \text{Inf}$ ) =  $\pm \text{Inf}$ 
Cbrt(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f\n", math.Cbrt(8))
    fmt.Printf("%.2f\n", math.Cbrt(27))
}
```

[Run](#)[Format](#)[Share](#)

## func Ceil

```
func Ceil(x float64) float64
```

Ceil returns the least integer value greater than or equal to x.

Special cases are:

```
Ceil(±0) = ±0
Ceil(±Inf) = ±Inf
Ceil(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    c := math.Ceil(1.49)
    fmt.Printf("%.1f", c)
}
```

[Run](#)[Format](#)[Share](#)

## func Copysign

```
func Copysign(x, y float64) float64
```

Copysign returns a value with the magnitude of x and the sign of y.

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Copysign(3.2, -1))
}
```

[Run](#)[Format](#)[Share](#)

## func Cos

```
func Cos(x float64) float64
```

Cos returns the cosine of the radian argument x.

Special cases are:

```
Cos(±Inf) = NaN
Cos(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Cos(math.Pi/2))
}
```

[Run](#)[Format](#)[Share](#)

## func Cosh

```
func Cosh(x float64) float64
```

Cosh returns the hyperbolic cosine of x.

Special cases are:

```
Cosh(±0) = 1
Cosh(±Inf) = +Inf
Cosh(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Cosh(0))
}
```

[Run](#)[Format](#)[Share](#)

## func Dim

```
func Dim(x, y float64) float64
```

Dim returns the maximum of x-y or 0.

Special cases are:

```
Dim(+Inf, +Inf) = NaN
Dim(-Inf, -Inf) = NaN
Dim(x, NaN) = Dim(NaN, x) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f\n", math.Dim(4, -2))
    fmt.Printf("%.2f\n", math.Dim(-4, 2))
}
```

[Run](#)[Format](#)[Share](#)

## func Erf

```
func Erf(x float64) float64
```

Erf returns the error function of x.

Special cases are:

```
Erf(+Inf) = 1
Erf(-Inf) = -1
Erf(NaN) = NaN
```

## func Erfc

```
func Erfc(x float64) float64
```

Erfc returns the complementary error function of x.

Special cases are:

```
Erfc(+Inf) = 0  
Erfc(-Inf) = 2  
Erfc(NaN) = NaN
```

## func Erfcinv

**1.10**

```
func Erfcinv(x float64) float64
```

Erfcinv returns the inverse of Erfc(x).

Special cases are:

```
Erfcinv(0) = +Inf  
Erfcinv(2) = -Inf  
Erfcinv(x) = NaN if x < 0 or x > 2  
Erfcinv(NaN) = NaN
```

## func Erfinv

**1.10**

```
func Erfinv(x float64) float64
```

Erfinv returns the inverse error function of x.

Special cases are:

```
Erfinv(1) = +Inf  
Erfinv(-1) = -Inf  
Erfinv(x) = NaN if x < -1 or x > 1  
Erfinv(NaN) = NaN
```

## func Exp



```
func Exp(x float64) float64
```

Exp returns  $e^x$ , the base-e exponential of x.

Special cases are:

```
Exp(+Inf) = +Inf  
Exp(NaN) = NaN
```

Very large values overflow to 0 or +Inf. Very small values underflow to 1.

#### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    fmt.Printf("%.2f\n", math.Exp(1))  
    fmt.Printf("%.2f\n", math.Exp(2))  
    fmt.Printf("%.2f\n", math.Exp(-1))  
}
```

[Run](#)[Format](#)[Share](#)

## func Exp2

```
func Exp2(x float64) float64
```

Exp2 returns  $2^x$ , the base-2 exponential of x.

Special cases are the same as Exp.

#### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f\n", math.Exp2(1))
    fmt.Printf("%.2f\n", math.Exp2(-3))
}
```

[Run](#)[Format](#)[Share](#)

## func Exp<sub>m</sub>1

```
func Expm1(x float64) float64
```

Exp<sub>m</sub>1 returns  $e^x - 1$ , the base-e exponential of  $x$  minus 1. It is more accurate than  $\text{Exp}(x) - 1$  when  $x$  is near zero.

Special cases are:

```
Expm1(+Inf) = +Inf
Expm1(-Inf) = -1
Expm1(NaN) = NaN
```

Very large values overflow to -1 or +Inf.

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.6f\n", math.Expml(0.01))
    fmt.Printf("%.6f\n", math.Expml(-1))
}
```

[Run](#)[Format](#)[Share](#)

## func FMA

1.14

```
func FMA(x, y, z float64) float64
```

FMA returns  $x * y + z$ , computed with only one rounding. (That is, FMA returns the fused multiply-add of  $x$ ,  $y$ , and  $z$ .)

## func Float32bits

```
func Float32bits(f float32) uint32
```

Float32bits returns the IEEE 754 binary representation of  $f$ , with the sign bit of  $f$  and the result in the same bit position. `Float32bits(Float32frombits(x)) == x`.

## func Float32frombits

```
func Float32frombits(b uint32) float32
```

Float32frombits returns the floating-point number corresponding to the IEEE 754 binary representation  $b$ , with the sign bit of  $b$  and the result in the same bit position. `Float32frombits(Float32bits(x)) == x`.

## func Float64bits

```
func Float64bits(f float64) uint64
```

Float64bits returns the IEEE 754 binary representation of *f*, with the sign bit of *f* and the result in the same bit position, and `Float64bits(Float64frombits(x)) == x`.

## func Float64frombits

```
func Float64frombits(b uint64) float64
```

Float64frombits returns the floating-point number corresponding to the IEEE 754 binary representation *b*, with the sign bit of *b* and the result in the same bit position. `Float64frombits(Float64bits(x)) == x`.

## func Floor

```
func Floor(x float64) float64
```

Floor returns the greatest integer value less than or equal to *x*.

Special cases are:

```
Floor(±0) = ±0  
Floor(±Inf) = ±Inf  
Floor(NaN) = NaN
```

### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    c := math.Floor(1.51)  
    fmt.Printf("%.1f", c)  
}
```

## func Frexp

[Run](#)[Format](#)[Share](#)

```
func Frexp(f float64) (frac float64, exp int)
```

Frexp breaks  $f$  into a normalized fraction and an integral power of two. It returns  $\text{frac}$  and  $\text{exp}$  satisfying  $f == \text{frac} \times 2^{\text{exp}}$ , with the absolute value of  $\text{frac}$  in the interval  $[\frac{1}{2}, 1)$ .

Special cases are:

```
Frexp( $\pm 0$ ) =  $\pm 0$ , 0  
Frexp( $\pm \text{Inf}$ ) =  $\pm \text{Inf}$ , 0  
Frexp(NaN) = NaN, 0
```

## func Gamma

```
func Gamma(x float64) float64
```

Gamma returns the Gamma function of  $x$ .

Special cases are:

```
Gamma(+Inf) = +Inf  
Gamma(+0) = +Inf  
Gamma(-0) = -Inf  
Gamma(x) = NaN for integer  $x < 0$   
Gamma(-Inf) = NaN  
Gamma(NaN) = NaN
```

## func Hypot

```
func Hypot(p, q float64) float64
```

Hypot returns  $\text{Sqrt}(p^2 + q^2)$ , taking care to avoid unnecessary overflow and underflow.

Special cases are:

```
Hypot(±Inf, q) = ±Inf  
Hypot(p, ±Inf) = ±Inf  
Hypot(NaN, q) = NaN  
Hypot(p, NaN) = NaN
```

## func Ilogb

```
func Ilogb(x float64) int
```

Ilogb returns the binary exponent of x as an integer.

Special cases are:

```
Ilogb(±Inf) = MaxInt32  
Ilogb(0) = MinInt32  
Ilogb(NaN) = MaxInt32
```

## func Inf

```
func Inf(sign int) float64
```

Inf returns positive infinity if sign >= 0, negative infinity if sign < 0.

## func IsInf

```
func IsInf(f float64, sign int) bool
```

IsInf reports whether f is an infinity, according to sign. If sign > 0, IsInf reports whether f is positive infinity. If sign < 0, IsInf reports whether f is negative infinity. If sign == 0, IsInf reports whether f is either infinity.

## func IsNaN

```
func IsNaN(f float64) (is bool)
```

IsNaN reports whether f is an IEEE 754 “not-a-number” value.

## func J0

```
func J0(x float64) float64
```

J0 returns the order-zero Bessel function of the first kind.

Special cases are:

```
J0(±Inf) = 0  
J0(0) = 1  
J0(NaN) = NaN
```

## func J1

```
func J1(x float64) float64
```

J1 returns the order-one Bessel function of the first kind.

Special cases are:

```
J1(±Inf) = 0  
J1(NaN) = NaN
```

## func Jn

```
func Jn(n int, x float64) float64
```

Jn returns the order-n Bessel function of the first kind.

Special cases are:

```
Jn(n, ±Inf) = 0  
Jn(n, NaN) = NaN
```

## func Ldexp

```
func Ldexp(frac float64, exp int) float64
```

Ldexp is the inverse of Frexp. It returns  $\text{frac} \times 2^{\text{exp}}$ .

Special cases are:

```
Ldexp(±0, exp) = ±0  
Ldexp(±Inf, exp) = ±Inf  
Ldexp(NaN, exp) = NaN
```

## func Lgamma

```
func Lgamma(x float64) (lgamma float64, sign int)
```

Lgamma returns the natural logarithm and sign (-1 or +1) of Gamma(x).

Special cases are:

```
Lgamma(+Inf) = +Inf  
Lgamma(0) = +Inf  
Lgamma(-integer) = +Inf  
Lgamma(-Inf) = -Inf  
Lgamma(NaN) = NaN
```

## func Log

```
func Log(x float64) float64
```

Log returns the natural logarithm of x.

Special cases are:

```
Log(+Inf) = +Inf  
Log(0) = -Inf  
Log(x < 0) = NaN  
Log(NaN) = NaN
```

### ▼ Example



```
package main

import (
    "fmt"
    "math"
)

func main() {
    x := math.Log(1)
    fmt.Printf("%.1f\n", x)

    y := math.Log(2.7183)
    fmt.Printf("%.1f\n", y)
}
```

[Run](#)[Format](#)[Share](#)

## func Log10

```
func Log10(x float64) float64
```

Log10 returns the decimal logarithm of x. The special cases are the same as for Log.

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.1f", math.Log10(100))
}
```

[Run](#)[Format](#)[Share](#)

## func Log1p

```
func Log1p(x float64) float64
```

Log1p returns the natural logarithm of 1 plus its argument x. It is more accurate than Log(1 + x) when x is near zero.

Special cases are:

```
Log1p(+Inf) = +Inf
Log1p(±0) = ±0
Log1p(-1) = -Inf
Log1p(x < -1) = NaN
Log1p(NaN) = NaN
```

## func Log2

```
func Log2(x float64) float64
```

Log2 returns the binary logarithm of x. The special cases are the same as for Log.

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.1f", math.Log2(256))
}
```

[Run](#)[Format](#)[Share](#)

## func Logb

```
func Logb(x float64) float64
```

Logb returns the binary exponent of x.

Special cases are:

```
Logb( $\pm$ Inf) =  $\pm$ Inf  
Logb(0) = -Inf  
Logb(NaN) = NaN
```

## func Max

```
func Max(x, y float64) float64
```

Max returns the larger of x or y.

Special cases are:

```
Max(x, +Inf) = Max(+Inf, x) = +Inf  
Max(x, NaN) = Max(NaN, x) = NaN  
Max(+0,  $\pm$ 0) = Max( $\pm$ 0, +0) = +0  
Max(-0, -0) = -0
```

## func Min

```
func Min(x, y float64) float64
```

Min returns the smaller of x or y.

Special cases are:

```
Min(x, -Inf) = Min(-Inf, x) = -Inf  
Min(x, NaN) = Min(NaN, x) = NaN  
Min(-0,  $\pm$ 0) = Min( $\pm$ 0, -0) = -0
```

## func Mod

```
func Mod(x, y float64) float64
```

Mod returns the floating-point remainder of x/y. The magnitude of the result is less than y and its sign agrees with that of x.

Special cases are:

```
Mod( $\pm$ Inf, y) = NaN
Mod(NaN, y) = NaN
Mod(x, 0) = NaN
Mod(x,  $\pm$ Inf) = x
Mod(x, NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    c := math.Mod(7, 4)
    fmt.Printf("%.1f", c)
}
```

[Run](#)[Format](#)[Share](#)

## func Modf

```
func Modf(f float64) (int float64, frac float64)
```

Modf returns integer and fractional floating-point numbers that sum to f. Both values have the same sign as f.

Special cases are:

```
Modf( $\pm$ Inf) =  $\pm$ Inf, NaN
Modf(NaN) = NaN, NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    int, frac := math.Modf(3.14)
    fmt.Printf("%.2f, %.2f\n", int, frac)

    int, frac = math.Modf(-2.71)
    fmt.Printf("%.2f, %.2f\n", int, frac)
}
```

Run

Format

Share

## func NaN

```
func NaN() float64
```

NaN returns an IEEE 754 “not-a-number” value.

## func Nextafter

```
func Nextafter(x, y float64) (r float64)
```

Nextafter returns the next representable float64 value after x towards y.

Special cases are:

```
Nextafter(x, x)    = x
Nextafter(NaN, y)  = NaN
Nextafter(x, NaN)  = NaN
```

## func Nextafter32

1.4

```
func Nextafter32(x, y float32) (r float32)
```

Nextafter32 returns the next representable float32 value after x towards y.

Special cases are:

```
Nextafter32(x, x)    = x
Nextafter32(NaN, y)  = NaN
Nextafter32(x, NaN)  = NaN
```

## func Pow

```
func Pow(x, y float64) float64
```

Pow returns  $x^y$ , the base-x exponential of y.

Special cases are (in order):

```
Pow(x, ±0) = 1 for any x
Pow(1, y) = 1 for any y
Pow(x, 1) = x for any x
Pow(NaN, y) = NaN
Pow(x, NaN) = NaN
Pow(±0, y) = ±Inf for y an odd integer < 0
Pow(±0, -Inf) = +Inf
Pow(±0, +Inf) = +0
Pow(±0, y) = +Inf for finite y < 0 and not an odd integer
Pow(±0, y) = ±0 for y an odd integer > 0
Pow(±0, y) = +0 for finite y > 0 and not an odd integer
Pow(-1, ±Inf) = 1
Pow(x, +Inf) = +Inf for |x| > 1
Pow(x, -Inf) = +0 for |x| > 1
Pow(x, +Inf) = +0 for |x| < 1
Pow(x, -Inf) = +Inf for |x| < 1
Pow(+Inf, y) = +Inf for y > 0
Pow(+Inf, y) = +0 for y < 0
Pow(-Inf, y) = Pow(-0, -y)
Pow(x, y) = NaN for finite x < 0 and finite non-integer y
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    c := math.Pow(2, 3)
    fmt.Printf("%.1f", c)
}
```

[Run](#)[Format](#)[Share](#)

## func Pow10

```
func Pow10(n int) float64
```

Pow10 returns  $10^{**}n$ , the base-10 exponential of n.

Special cases are:

```
Pow10(n) = 0 for n < -323
Pow10(n) = +Inf for n > 308
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    c := math.Pow10(2)
    fmt.Printf("%.1f", c)
}
```

[Run](#)[Format](#)[Share](#)

## func Remainder

```
func Remainder(x, y float64) float64
```

Remainder returns the IEEE 754 floating-point remainder of  $x/y$ .

Special cases are:

```
Remainder( $\pm$ Inf, y) = NaN  
Remainder(NaN, y) = NaN  
Remainder(x, 0) = NaN  
Remainder(x,  $\pm$ Inf) = x  
Remainder(x, NaN) = NaN
```

## func Round

**1.10**

```
func Round(x float64) float64
```

Round returns the nearest integer, rounding half away from zero.

Special cases are:

```
Round( $\pm$ 0) =  $\pm$ 0  
Round( $\pm$ Inf) =  $\pm$ Inf  
Round(NaN) = NaN
```

### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    p := math.Round(10.5)  
    fmt.Printf("%.1f\n", p)  
  
    n := math.Round(-10.5)  
    fmt.Printf("%.1f\n", n)  
}
```



Run

Format

Share

**func RoundToEven**

1.10

```
func RoundToEven(x float64) float64
```

RoundToEven returns the nearest integer, rounding ties to even.

Special cases are:

```
RoundToEven( $\pm 0$ ) =  $\pm 0$   
RoundToEven( $\pm \text{Inf}$ ) =  $\pm \text{Inf}$   
RoundToEven(NaN) = NaN
```

## ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    u := math.RoundToEven(11.5)  
    fmt.Printf("%.1f\n", u)  
  
    d := math.RoundToEven(12.5)  
    fmt.Printf("%.1f\n", d)  
}
```

Run

Format

Share

**func Signbit**

```
func Signbit(x float64) bool
```

Signbit reports whether x is negative or negative zero.

**func Sin**

```
func Sin(x float64) float64
```

Sin returns the sine of the radian argument x.

Special cases are:

```
Sin(±0) = ±0  
Sin(±Inf) = NaN  
Sin(NaN) = NaN
```

#### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    fmt.Printf("%.2f", math.Sin(math.Pi))  
}
```

[Run](#)[Format](#)[Share](#)

## func Sincos

```
func Sincos(x float64) (sin, cos float64)
```

Sincos returns Sin(x), Cos(x).

Special cases are:

```
Sincos(±0) = ±0, 1  
Sincos(±Inf) = NaN, NaN  
Sincos(NaN) = NaN, NaN
```

#### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    sin, cos := math.Sincos(0)
    fmt.Printf("%.2f, %.2f", sin, cos)
}
```

[Run](#)[Format](#)[Share](#)

## func Sinh

```
func Sinh(x float64) float64
```

Sinh returns the hyperbolic sine of x.

Special cases are:

```
Sinh(±0) = ±0
Sinh(±Inf) = ±Inf
Sinh(NaN) = NaN
```

### ▼ Example

```
package main

import (
    "fmt"
    "math"
)

func main() {
    fmt.Printf("%.2f", math.Sinh(0))
}
```

[Run](#)[Format](#)[Share](#)

## func Sqrt

```
func Sqrt(x float64) float64
```

Sqrt returns the square root of x.

Special cases are:

```
Sqrt(+Inf) = +Inf  
Sqrt(±0) = ±0  
Sqrt(x < 0) = NaN  
Sqrt(NaN) = NaN
```

### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    const (  
        a = 3  
        b = 4  
    )  
    c := math.Sqrt(a*a + b*b)  
    fmt.Printf("%.1f", c)  
}
```

[Run](#)[Format](#)[Share](#)

## func Tan

```
func Tan(x float64) float64
```

Tan returns the tangent of the radian argument x.

Special cases are:

```
Tan( $\pm 0$ ) =  $\pm 0$   
Tan( $\pm \text{Inf}$ ) = NaN  
Tan(NaN) = NaN
```

### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    fmt.Printf("%.2f", math.Tan(0))  
}
```

[Run](#)[Format](#)[Share](#)

## func Tanh

```
func Tanh(x float64) float64
```

Tanh returns the hyperbolic tangent of x.

Special cases are:

```
Tanh( $\pm 0$ ) =  $\pm 0$   
Tanh( $\pm \text{Inf}$ ) =  $\pm 1$   
Tanh(NaN) = NaN
```

### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    fmt.Printf("%.2f", math.Tanh(0))  
}
```



[Terms of Service](#)[Privacy Policy](#)[Run](#)[Format](#)[Share](#)

Supported by Google

## func Trunc

```
func Trunc(x float64) float64
```

Trunc returns the integer value of x.

Special cases are:

```
Trunc(±0) = ±0  
Trunc(±Inf) = ±Inf  
Trunc(NaN) = NaN
```

### ▼ Example

```
package main  
  
import (  
    "fmt"  
    "math"  
)  
  
func main() {  
    fmt.Printf("%.2f\n", math.Trunc(math.Pi))  
    fmt.Printf("%.2f\n", math.Trunc(-1.2345))  
}
```

[Run](#)[Format](#)[Share](#)

## func Y0

```
func Y0(x float64) float64
```

Y0 returns the order-zero Bessel function of the second kind.

Special cases are:

```
Y0(+Inf) = 0
Y0(0) = -Inf
Y0(x < 0) = NaN
Y0(NaN) = NaN
```

## func Y1

```
func Y1(x float64) float64
```

Y1 returns the order-one Bessel function of the second kind.

Special cases are:

```
Y1(+Inf) = 0
Y1(0) = -Inf
Y1(x < 0) = NaN
Y1(NaN) = NaN
```

## func Yn

```
func Yn(n int, x float64) float64
```

Yn returns the order-n Bessel function of the second kind.

Special cases are:

```
Yn(n, +Inf) = 0
Yn(n ≥ 0, 0) = -Inf
Yn(n < 0, 0) = +Inf if n is odd, -Inf if n is even
Yn(n, x < 0) = NaN
Yn(n, NaN) = NaN
```

## Subdirectories

Name	Synopsis
..	
<a href="#">big</a>	Package big implements arbitrary-precision arithmetic (big numbers).
<a href="#">bits</a>	Package bits implements bit counting and manipulation functions for the predeclared unsigned integer types.

- `cmplx` Package `cmplx` provides basic constants and mathematical functions for complex numbers.
- `rand` Package `rand` implements pseudo-random number generators.