

Airtime Top Up for EVC (Organization Operator)

Interface Introduction

The Mobile Money system provides an agent with the airtime electronic recharge and management functions. A third-party system can invoke this interface to enable an agent operator to provide the airtime recharge function for end users.

Request Parameter Specification

Common field specification				
Command ID	Follow InitTrans_{ServiceCode} format			
Initiator	- Operator ID of an Organization Operator/PIN/ShortCode - User Name of an Organization Operator/Password/ShortCode			
PrimaryParty	Not required			
ReceiverParty	Organization ShortCode NOTE The receiver party must be an MNO organization.			
Requester	Not required			
Specific parameters in Request/Body/TransactionRequest/Parameters				
Parameter	Data Type	Mandatory or Optional	Description	Example
Amount	xs:string	Mandatory	Indicates the amount to purchase airtime. The precision ranges from the minimum currency unit to 10^9 * minimum currency unit. For example, for CNY, the value of this parameter ranges from 1 to 1000000000.00. This field is optional when the transaction amount is 0.	10.00
Currency	xs:string	Mandatory	Indicates the currency type. It is specified by using the Char 3 Code defined in the ISO 4217 standard.	CNY
RechargedMSISDN	xs:string	Mandatory	Indicates the MSISDN to be recharged through airtime.	861350000000

Result Parameter Specification

Specific parameters in Request/Body/TransactionResult/ResultParameters

No specific parameter for this result message.

Instance

- Request messages

```
<soapenv:Envelope
xmlns:soapenv='http://schemas.xmlsoap.org/soap/envelope/'
xmlns:api='http://cps.huawei.com/cpsinterface/api_requestmgr'
xmlns:req='http://cps.huawei.com/cpsinterface/request'
xmlns:com='http://cps.huawei.com/cpsinterface/common'>
  <soapenv:Header/>
  <soapenv:Body>
    <api:Request>
      <req:Header>
        <req:Version>1.0</req:Version>
        <req:CommandID>InitTrans_2108</req:CommandID>
        <req:Caller>
          <req:CallerType>2</req:CallerType>
          <req:ThirdPartyID>POS_Broker</req:ThirdPartyID>
          <req:Password>gMMqGGrKxsE=</req:Password>
          <req:ResultURL>http://10.64.169.132:16888/Schema
APIResult</req:ResultURL>
        </req:Caller>
        <req:KeyOwner>1</req:KeyOwner>
        <req:Timestamp>20150101010101</req:Timestamp>
      </req:Header>
      <req:Body>
        <req:Identity>
          <req:Initiator>
            <req:IdentifierType>11</req:IdentifierType>
            <req:Identifier>202001</req:Identifier>
            <req:SecurityCredential>kMhIAMNE4h8=</req:Se
curityCredential>
            <req:ShortCode>2001</req:ShortCode>
          </req:Initiator>
          <req:ReceiverParty>
            <req:IdentifierType>4</req:IdentifierType>
            <req:Identifier>10086</req:Identifier>
          </req:ReceiverParty>
        </req:Identity>
        <req:TransactionRequest>
          <req:Parameters>
            <req:Parameter>
              <com:Key>RechargedMSISDN</com:Key>
              <com:Value>861253000</com:Value>
            </req:Parameter>
            <req:Amount>10</req:Amount>
          </req:Parameters>
        </req:TransactionRequest>
      </req:Body>
    </api:Request>
  </soapenv:Body>
</soapenv:Envelope>
```

```

        <req:Currency>USD</req:Currency>
    </req:Parameters>
</req:TransactionRequest>
    <req:Remark>1212</req:Remark>
</req:Body>
</api:Request>
</soapenv:Body>
</soapenv:Envelope>

```

- **Response messages**

```

<soapenv:Envelope
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  <soapenv:Body>
    <api:Response
xmlns:api="http://cps.huawei.com/cpsinterface/api_requestmgr"
xmlns:res="http://cps.huawei.com/cpsinterface/response">
      <res:Header>
        <res:Version>1.0</res:Version>

<res:OriginatorConversationID>S_X2013012921001</res:OriginatorConver
sationID>
        <res:ConversationID>AG_20130129T102103</res:ConversationID>
      </res:Header>
      <res:Body>
        <res:ResponseCode>0</res:ResponseCode>
        <res:ResponseDesc>Accept the service request
successfully.</res:ResponseDesc>
        <res:ServiceStatus>0</res:ServiceStatus>
      </res:Body>
    </api:Response>
  </soapenv:Body>
</soapenv:Envelope>

```

- **Result messages**

```

<soapenv:Envelope
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:api="http://cps.huawei.com/cpsinterface/api_resultmgr"
xmlns:res="http://cps.huawei.com/cpsinterface/result"
xmlns:com="http://cps.huawei.com/cpsinterface/common">
  <soapenv:Header/>
  <soapenv:Body>
    <api:Result>
      <res:Header>
        <res:Version>1.0</res:Version>

<res:OriginatorConversationID>S_X2013012921001</res:OriginatorConver
sationID>
        <res:ConversationID>AG_20130129T102103</res:ConversationID>
      </res:Header>
      <res:Body>
        <res:ResultType>0</res:ResultType>
        <res:ResultCode>0</res:ResultCode>
      </res:Body>
    </api:Result>
  </soapenv:Body>
</soapenv:Envelope>

```

```

        <res:ResultDesc>Process service request
successfully.</res:ResultDesc>
        <res:TransactionResult>
            <res:TransactionID>XD2013013923689236</res:TransactionID>
        </res:TransactionResult>
    </res:Body>
</api:Result>
</soapenv:Body>
</soapenv:Envelope>

```

WS invoking (Asynchronous mode)

Please be informed that there is no login is required on our side to use the WS , only the WS username and password authentication.

The APIs are use asynchronous mode by default. That means that third party systems need to obtain the result message in asynchronous mode shown as below.

Please communicate with 3rd parties.

For example:

```

<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:req="http://cps.huawei.com/cpsinterface/request">
    <soapenv:Header/>
    <soapenv:Body>
        <req:RequestMsg><![CDATA[<?xml version="1.0" encoding="UTF-8"?>
        <Request>
            <KeyOwner>1</KeyOwner>
            <Identity>
                <Caller>
                    <CallerType>2</CallerType>
                    <ThirdPartyID>POS_Broker</ThirdPartyID>
                    <Password>B1YNY8GylVo=</Password>
                    <ResultURL>http://10.71.109.150:8888/mockResultBinding</ResultURL>
                </Caller>
            </Identity>
            <Initiator>
                <IdentifierType>1</IdentifierType>
                <Identifier>8613500000000</Identifier>
                <SecurityCredential>iUoiP9iGVwE=</SecurityCredential>
            </Initiator>
        </Request>
        </req:RequestMsg>
    </soapenv:Body>
</soapenv:Envelope>

```

