

Allocation-APIs

Request Body -

Property	Description	Type	Value	Mandatory	Constraints
transaction.payee.msisdn	MSISDN of non trust wallet	String	eg: 752604392, etc	✔	msisdn must not be null and should only contain alphanumeric characters with length not more than 15 (Mandatory if address_type is MOBILE)
transaction.payee.nickname	Nickname of non trust wallet	String	eg socgen-test	✔	Alphanumeric of max length 50 with special character allowed(-, _ etc) (Mandatory if address_type is NICKNAME)
transaction.payee.address_type		Enum	eg MOBILE	✔	Only accepts MOBILE,NICKNAME
transaction.amount	Amount of transaction	String	eg: 100, etc	✔	transaction.amount must not be null or Minimum amount should be greater than 0
transaction.id	Unique id for each transaction	String	eg: milithtest555, etc	✔	transaction.id should only contain alphanumeric characters and cannot be blank with length not more than 80
note	Remarks	String	eg Allocation Deallocation	✔	String of max length 100
additional_info	Any extra information that needs to be passed	JSON Object			NA
x-country	Opco country code	String	eg: UG, TZ, etc	✔	Country code must be between 2 and 3 characters
x-currency	Country currency code	String	eg: UGX, TZS, etc	✔	Currency code must be between 2 and 3 characters

Request:

```
curl --location --request POST 'https://openapiuat.airtel.africa/allocation' \
--header 'Content-Type: application/json' \
--header 'x-country: CD' \
--header 'Authorization: yC0ho00rxj6rQL2sP8AbJGCJtXUGYaRA' \
--header 'x-currency: CDF' \
--data-raw '{
  "transaction": {
    "id": "1701424313",
    "amount": "100.5",
    "payee": {
      "address_type": "MOBILE",
      "msisdn": "999119410"
    }
  },
  "note": "Allocation Deallocation Test1",
  "additional_info": {}
}'
```

Property	Description	Type	Value
----------	-------------	------	-------

status.message	Dev portal API message(possible values: Success, Failed) In case of Failed check status.response_code for reason	String	Eg: Success
status.code	API status code	String	Eg: 200,..
status.response_code	Dev portal response code	String	Eg: DP02050000001 ...
status.success	API status (True signifies Success, False signifies Failure)	String	Eg: true, false
transaction.id	Unique id for each transaction	String	Eg .AllocationTest1
transaction.airtel_money_id	Id generated at AIRTEL end, transaction id with suffix	String	Eg ALDL-RDCZSSG4WW-AllocationTest1
transaction.reference_id	APC id	String	APCCD122838324281664
transaction.status	Status	String	TS, TF, TA
additional_info.mq_txn_id	Mobiquity Transaction Id	String	LC231010.2056.C00041

```
{
  "data": {
    "additional_info": {
      "mq_txn_id": "LC*****7"
    },
    "transaction": {
      "reference_id": "APC*****0",
      "airtel_money_id": "ALDL-*****-****4",
      "id": "16*****4",
      "status": "TS"
    }
  },
  "status": {
    "response_code": "DP02050001001",
    "code": "200",
    "success": true,
    "message": "Success"
  }
}
```

API for testing purpose(Generating token)

```
curl --location --request POST 'https://openapiuat.airtel.africa/auth/oauth2/token' \
--header 'Content-Type: application/json' \
--header 'Accept: */*' \
--header 'Cookie: visid_incap_2967769=456uBYD8Qqm4gu+PidnzQ72GP2UAAAAAQUIPAAAAABej4wN3Bo+c6SyFDqS1uMC' \
--data-raw '{
  "client_id": "8ddea0e3740e4aa78c59245acb8d992c",
  "client_secret": "f89f006b-fd84-40b8-a264-0485702a3764",
  "grant_type": "client_credentials"
}'
```

```
{
  "token_type": "bearer",
  "access_token": "4T0FLVIGdXxSdtH2CUxRVcPNNPZGt08z",
  "expires_in": 180
}
```

Error Codes

Error Codes	Description
DP02050001000	AMBIGUOUS
DP02050001001	SUCCESS
DP02050001002	FAILED
DP02050001003	Something went wrong
DP02050001007	Transaction with given external id, channel already exists
DP02050001015	Validation Error
DP02050001016	Invalid nickname. Please try again
DP02050001017	Invalid msisdn. Please try again