



IMT API Specification Document

Moneygram Receive/ Inbound Services

v1.0.0

CONFIDENTIALITY DISCLAIMER

DEVELOPER API GUIDE DOCUMENT

THIS DOCUMENT AND THE INFORMATION IN IT ARE PROVIDED IN CONFIDENCE, FOR THE SOLE PURPOSE OF EQUITY BANK LIMITED AND MAY NOT BE DISCLOSED TO ANY THIRD PARTY OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF EQUITY BANK LIMITED.

Any form of reproduction, dissemination, copying, disclosure, modification, distribution and or publication of this material is strictly prohibited. The contents of this document have not been independently verified and they do not purport to be comprehensive, or to contain all the information that a prospective investor may need. No representation, warranty or undertaking, expressed or implied is or will be made or given and no responsibility or liability is or will be accepted by Equity Bank Limited or by any of its directors, employees or advisors in relation to the accuracy or completeness of this document or any other written or oral information made available in connection with the Company.

Revision History

Date	Version	Author	Comments
04.10.2024	v1.0.0	Kennedy N. Gatimu	Initial document creation

Table of Contents

1.0 Introduction.....	6
2.0 Overview.....	7
2.0.1 Business Purpose.....	7
2.0.2 API Flows and Processes.....	7
2.0.3 FormFree Transaction Staging Process.....	8
2.0.4 MoneyGram Receive Transaction Receipt Specification.....	8
2.0 Reference Number Request Service.....	11
2.0.1 Reference Number Request Service Description.....	11
2.0.2 Reference Number Request Headers Description.....	13
2.0.3 Reference Number Request Field Description.....	13
2.0.4 Reference Number Sample Request.....	14
2.0.5 Reference Number Response Headers Description.....	15
2.0.6 Reference Number Success Response Field Description.....	15
2.0.7 Reference Number Failure Response Field Description.....	27
2.0.8 Reference Number Sample Failure Response.....	27
3.0 Get Fields For Product Service.....	28
3.0.1 Get Fields For Product Description.....	28
3.0.2 Get Fields For Product Request Headers Description.....	29
3.0.3 Get Fields For Product Request Field Description.....	30
3.0.4 Get Fields For Product Sample Request.....	35
3.0.5 Get Fields For Product Response Headers Description.....	36
3.0.6 Get Fields For Product Success Response Field Description.....	36
3.0.7 Get Fields For Product Failure Response Field Description.....	42
3.0.8 Get Fields For Product Sample Failure Response.....	43
4.0 Receive Validation Service.....	44
4.0.1 Receive Validation Description.....	44
4.0.2 Receive Validation Request Headers Description.....	45
4.0.3 Receive Validation Request Field Description.....	46
4.0.4 Receive Validation Sample Request.....	66
4.0.5 Receive Validation Response Headers Description.....	70
4.0.6 Receive Validation Success Response Field Description.....	70
4.0.7 Receive Validation Request Response Field Description.....	71
4.0.8 Receive Validation Request Sample Failure Response.....	71
5.0 Commit Transaction Service.....	72
5.0.1 Commit Transaction Description.....	72
5.0.2 Commit Transaction Request Headers Description.....	72
5.0.4 Commit Transaction Sample Request.....	75

5.0.6 Commit Transaction Response Headers Description.....	78
5.0.7 Commit Transaction Response Field Description.....	78
5.0.8 Commit Transaction Sample Pending Response.....	78
5.0.9 Commit Transaction Sample Failure Response.....	78
6.0 Receive Reversal Service.....	78
6.0.1 Receive Reversal Description.....	79
6.0.2 Receive Reversal Request Headers Description.....	80
6.0.3 Send Reversal Request Field Description.....	80
6.0.4 Receive Reversal Sample Request.....	82
6.0.5 Receive Reversal Response Headers Description.....	82
6.0.6 Receive Reversal Success Response Field Description.....	83
6.0.7 Receive Reversal Failure Response Field Description.....	83
6.0.8 Receive Reversal Sample Failure Response.....	83
7.0 Digital Signature Generation.....	84
7.0.1 Signature Generation.....	84
7.0.2 Clear Text Values.....	84
8.0 Appendix 1: Request Field Guide.....	86
8.0.1 Request Field Guide.....	86
9.0 Appendix 1: Response Field Guide.....	88
9.0.1 Response Field Guide.....	88

1.0 Introduction

This document outlines the integration process for the inbound services offered by MoneyGram, specifically for international money transfers. It provides detailed guidance on the APIs required for seamless transaction execution, including:

- **referenceNumberRequest** service
- **getFieldsForProductRequest** service
- **receiveValidationRequest** service
- **commitTransactionRequest** service
- **receiveReversalRequest** service

To ensure secure communication, the calling channel must supply a valid digital certificate file in **.cer** format. This certificate will be used to sign requests, ensuring authenticity and integrity during transactions.

The request signing process involves using predefined fields from the clear text, which must be signed with the **SHA256withRSA** algorithm. Once signed, the resulting string is to be encoded into **Base64** format and included in the **signature** field of the respective API requests.

This integration will provide a robust and secure solution for handling outbound international money transfers through MoneyGram.

2.0 Overview

2.0.1 Business Purpose

- This document provides technical and business information required to design an application to perform MoneyGram money transfer receive transactions.

2.0.2 API Flows and Processes

Receive Transaction Process

1. The agent application sends a [referenceNumberRequest](#) containing the transaction reference number, and MoneyGram returns a [referenceNumberResponse](#) containing transaction status and other transaction details.
2. [Conditional] Choose one of the following.
 - a. The agent application sends a [referenceNumberRequest](#) containing the transaction reference number and receive PIN used to verify the receiver, and MoneyGram returns a [referenceNumberResponse](#) confirming the transaction may continue.
 - b. The agent application validates the PIN locally based on the data returned on the [referenceNumberResponse](#).
3. [Conditional] If the transaction is a currency redirect transaction, the agent must tell the consumer the new exchange rate and receive amount, and receive approval before continuing.
4. The agent verifies the receiver's name on ID against transaction details.
5. The agent application sends a [getFieldsForProductRequest](#), and MoneyGram returns a [getFieldsForProductResponse](#) containing field requirements and screen content information for the transaction.
6. A summary screen may be displayed with data collected to be confirmed by the agent or the customer. The agent application sends a [receiveValidationRequest](#) containing information collected from the customer, and MoneyGram returns a [receiveValidationResponse](#) indicating the transaction can continue, or an error indicating the issue with the receive transaction request .
7. The agent application sends a [commitTransactionRequest](#) within 60 seconds of the [receiveValidationRequest](#), and MoneyGram returns a [commitTransactionResponse](#).
8. If the [commitTransactionResponse](#) is not received due to communication error, the agent application must resend the [commitTransactionRequest](#).
9. After a successful [commitTransaction](#), the agent provides the consumer with their money and the transaction receipt.

2.0.3 FormFree Transaction Staging Process

Agents using FormFree staging develop an application used to collect receive transaction data via mobile phone, online form, or other method. The consumer completes the transaction at a later time at an agent location. At that time, the consumer provides a reference number, and photo ID if applicable, and receives funds. The advantage of transaction staging for the agent is that logic for setting up the transaction data, and the time spent with the consumer to collect all required data, is handled in a separate process from the payout process. The FormFree completion process is described in the FormFree Completion module.

1. The agent follows the transaction staging process above for receive transactions
 - a. The application must set the `formFreeStaging` field in the [receiveValidationRequest](#) to `true`
 - b. The application does not send the [commitTransactionRequest](#); the transaction is committed at a later time
2. The agent can build its own database to store transaction data until ready to receive. Current privacy agreements for handling customer and transaction data between MoneyGram and the partner apply.

2.0.4 MoneyGram Receive Transaction Receipt Specification

For detail API mapping, compliance requirements and other receipts contents, please refer to AC1512 Receipts Module. The following guidelines should be followed when designing receive transaction receipts:

1. The agent copy of the receipt must use one format; the consumer copy must use a second format
2. The MoneyGram logo must appear on receipts
3. The MoneyGram privacy statement must appear on the consumer copy of the receipt; the applicable text will be provided during development
4. The information on the receipts must not be shared with any third parties without prior approval from MoneyGram
5. The following fields are required on transactions receipts if they are returned in the [referenceNumberResponse](#)
 - o `senderFirstName`, `senderMiddleName`, `senderLastName`, `senderLastName2`
 - o `receiverFirstName`, `receiverMiddleName`, `receiverLastName`, `receiverLastName2`
 - o `receiveAmount` and `receiveCurrency`
 - o `referenceNumber`
 - o `transactionDateTime`
 - o `OriginationCountry`
 - o `Messagefield1`
 - o `Messagefield2`
6. The receipt must include the agent's name from the agent profile

7. The agent copy of the receipt must include a signature line for the consumer's signature
8. The agent copy of the receipt must include instructions to the agent to retain the signed copy
9. The receipt must include additional local regulations as required

Functionality: Redirect Functionality

10. When a receive is done in a currency not available at the location (*but is available in the country*), the receiver needs to be given an option to do a redirect to an available (base) currency.

Verbiage is as follows:

- a. This transaction is set for disbursement in a currency not currently offered by you in the MoneyGram system. You may disburse this transaction in a different currency only if directed to do so by the intended receiver. Please inform the receiver of this issue and their choice to either have this transaction disbursed in the original currency at an alternative agent location in the country or to have it disbursed in an alternative currency at this location. If the receiver desires to proceed, the transaction may be disbursed by you in the amount and form of currency described below.
 - b. El desembolso de esta transacción ha sido establecido en una moneda que actualmente usted no ofrece en el sistema de MoneyGram. Puede desembolsar esta transacción en una moneda diferente únicamente si así se lo indica el destinatario previsto. Infórmele este problema al destinatario y comuníquelo que puede elegir recibir el desembolso de esta transacción ya sea en la moneda original en una localidad de agente alternativa dentro del país, o en una moneda alternativa en esta ubicación. Si el destinatario desea continuar, usted puede desembolsar la transacción en la cantidad y el tipo de moneda que se describe a continuación.
11. Agent application should also provide the original receive amount/currency, Fx rate and new receive amount in final currency.
 12. If redirect is accepted, the Redirect Acknowledgement needs to be printed on the receive receipt

Verbiage is as follows:

- c. New receiver acknowledgement to replace current "terms and conditions" ("This transaction is subject to MoneyGram Terms and Conditions on the MoneyGram receipt holder.") line above the signature line – Agent copy only
 - i. I acknowledge that I have directed MoneyGram and [insert agent name] to disburse this transaction in a currency different than originally requested by the sender. As explained to me by [insert agent name] prior to disbursement, I understand that I had the option and ability to have this transaction disbursed in the original currency at another MoneyGram agent location within this county but have instead chosen to have this transaction disbursed in the currency available at this MoneyGram agent location

- ii. Reconozco haberle indicado a MoneyGram y a [insertar nombre del agente] que el desembolso de esta transacción se realice en una moneda diferente de la solicitada inicialmente por el remitente. Tal como me lo explicó [insertar nombre del agente] antes del desembolso, comprendo que tuve la opción y la capacidad de que el desembolso de esta transacción se realizara en la moneda original en otra localidad de agente de MoneyGram de este país; sin embargo, decidí que el desembolso de esta transacción se realice en la moneda disponible en esta localidad de agente de MoneyGram
13. Receipt also needs to include the original receive amount/currency, Fx rate and new receive amount in final currency.
 14. Receivers should sign the agent copy of the receipt and agent should retain copy with signature.
 15. For re-direct scenario to get the receipt verbiage in another language Agent receipt must use the information returned by **variable receipt info** API.

2.0 Reference Number Request Service

2.0.1 Reference Number Request Service Description

The agent application uses the [referenceNumber](#) API to obtain details about a specific MoneyGram money transfer transaction.

Business Rules to Code

1. Agent application must validate some of the fields in the response before allowing the receive transaction to continue. Fields that must be validated are:
 - a. okForAgent must be true
 - b. transactionStatus must be AVAIL
 - c. okForPickup must be true
2. The agent application must include functionality to manage transactions for which the receive currency is different than the receive currency originally intended which is referred to as currency redirect transactions.
3. For currency redirect transactions, the agent application must display the following legal text, the new amount, new currency, exchange rate, and ask whether to continue.

Tell the consumer that the original currency is not available -
Receive amount may have changed.

4. The following rules apply to agents in indicative countries - receive countries where the agent, rather than MoneyGram, manages the exchange rate from USD to local currency
 - a. The agent application can check the value of `indicativeRateAvailable` in the `countryCurrencyInfo` section of the `codeTableResponse`; indicative countries have the value set to `true`
 - The developer may also confirm with the MoneyGram whether they are in an indicative country
 - Receive applications in Brazil are not subject to this business rule
 - b. Due to regulations in California, USA, and the country of Spain, MoneyGram must guarantee the receive amount in local currency at the time of the send transaction for all transactions originating in those locations
 - At the time of the receive transaction, if the [referenceNumberResponse](#) returns `true` in the `validIndicator` field, the agent employee must pay the customer the amount and currency listed in the `indicativeReceiveAmount` and `indicativeReceiveCurrency` fields

- o The agent application must process the `receiveValidationRequest` using the rules documented in the API
 - c. If the transaction did not originate in California, USA, or Spain, `validIndicator` is false and the agent application must process the `receiveValidationRequest` using the `receiveAmount` and `receiveCurrency` according to the rules documented in the API
 - d. The receive transaction appears as if received in USD in any subsequent APIs, regardless of the value of `validIndicator`
- 4. Receive PINs are an additional method of receive transaction security; if using receive PINs, the agent application must use a PIN input device for the consumer to input a PIN and reference number in order to receive a transaction. The agent must not input the information. The input device must meet the following minimum requirements:
 - Input must be masked
 - Must allow entry of numeric characters
- 6. A receive PIN is the first four letters of the sender's last name; special characters should be skipped (e.g., "O'Hare" would result in a PIN of "OHar"); if the sender's last name is fewer than four letters the remaining letters should be zeros
- 7. If using receive PINs, the [referenceNumber](#) API may be used twice as follows:
 - a. The [referenceNumberRequest](#) is sent without the receive PIN, and MoneyGram returns the [referenceNumberResponse](#) indicating the status of the transaction and whether it is available to be received
 - b. If the transaction is available to be received, the [referenceNumberRequest](#) is sent with the receive PIN, and MoneyGram returns the [referenceNumberResponse](#) to confirm the transaction may continue
- 8. The alphabetic characters of the receive PIN must be converted to numeric characters according to the pin pad's character mapping specification below

Additional Information

1. MoneyGram may not authorize payout of transactions attempted to be received in countries, states/provinces, or via delivery options that were not originally designated by the sender at time of send.
2. The agent application may use the [referenceNumber](#) to verify the success of the `commitTransactionRequest` when completing a receive transaction; if the response returns a `transactionStatus` other than `RECVD`, the application may retry the transaction.

2.0.2 Reference Number Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/inbound/referenceNumber
Headers	content-type: application/xml
Authentication	signature

2.0.3 Reference Number Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

referenceNumber	string Maximum length: 12	Field Rules 1. If using receive PINs, the transaction reference number must be entered by the consumer 2. If using receive PINs, the value must be masked on screen	GUI	required
-----------------	------------------------------	---	-----	----------

pin	string Maximum length: 8	<i>Field Rules</i> 1. If using receive PINs, data and GUI input are required 2. If using receive PINs, the value must be entered by the consumer 3. If using receive PINs, the value must be masked on screen 4. If not using receive PINs, data and input are not allowed	GUI/conditional	optional
operatorName	string Maximum length: 7	<i>Additional Information</i> 1. Operator name or operator ID of the associate or user performing the transaction; it must be auto-populated from the agent's system and cannot be editable by the user • Agent Facing – Teller ID/User ID mapped to operatorName • Customer Facing/Self Service (kiosk, online, mobile) – User ID/User Login mapped to operatorName • ATM – unique customer ID (customer number) mapped to operatorName	application/conditional	optional

2.0.4 Reference Number Sample Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Header/>
  <soapenv:Body>
    <channelInfo>
      <rrn>1234rrn</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <referenceNumberRequest xmlns="http://www.moneygram.com/AgentConnect1512">
      <referenceNumber>123456</referenceNumber>
      <pin>001A</pin>
    </referenceNumberRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

```

    <operatorName>ATM</operatorName>
  </referenceNumberRequest>
</soapenv:Body>
</soapenv:Envelope>

```

2.0.5 Reference Number Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

2.0.6 Reference Number Success Response Field Description

Tag	Datatype	Information and Rules	Display
mgTransactionSessionID	string Maximum length: 38	An ID number that uniquely identifies the Receive transaction across APIs. <i>Additional Information</i> 1. Value must be saved and used in the receiveValidationRequest and commitTransactionRequest APIs	not allowed
senderFirstName	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
senderMiddleName	string Maximum Length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
senderLastName	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
senderLastName2	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
senderHomePhone	String Maximum length: 14	<i>Field Rules</i> 1. Display is required if required by country compliance regulations 2. Display is not allowed otherwise	conditional

senderAddress	String Maximum length: 80	<i>Field Rules</i> 1. Display is required if required by country compliance regulations 2. Only returned when required by government regulations in select countries.	conditional
---------------	------------------------------	---	-------------

senderAddress2	string Maximum length: 80	NA	NA
senderAddress3	string Maximum length: 80	NA	NA
senderAddress4	string Maximum length: 80	NA	NA
senderCity	string Maximum length: 40	<i>Field Rules</i> 1. Display is required if required by country compliance regulations 2. Only returned when required by government regulations in select countries.	conditional
senderState	string Length: 2 Must be a valid state code	<i>Field Rules</i> 1. Display is required if required by country compliance regulations 2. Only returned when required by government regulations in select countries.	conditional
senderZipCode	string Minimum length: 3 Maximum length: 10	<i>Field Rules</i> 1. If <code>senderCountry</code> is CAN, the minimum length is 6 2. If <code>senderCountry</code> is USA, the minimum length is 5 3. Display is required if required by country compliance regulations 4. Only returned when required by government regulations in select countries.	conditional

senderCountry	string Length: 3	<i>Field Rules</i> 1. Display is required if required by country compliance regulations 2. Only returned when required by government regulations in select countries.	conditional
receiverFirstName	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
receiverMiddleName	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
receiverLastName	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
receiverLastName2	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	required
receiverAddress	string Maximum length: 80	NA	not allowed
receiverAddress2	string Maximum length: 80	NA	not allowed
receiverAddress3	string Maximum length: 80	NA	not allowed
receiverAddress4	string Maximum length: 80	NA	not allowed
direction1	string Maximum length: 40	None	conditional

direction2	string Maximum length: 40	None	conditional
direction3	string Maximum length: 40	None	conditional

receiverCity	string Maximum length: 40	NA	not allowed
receiverState	string Length: 2	NA	not allowed
receiverZipCode	string Minimum length: 3 Maximum length: 10	NA	not allowed
receiverCountry	string Length: 3	NA	not allowed
receiverPhone	string Maximum length: 14	NA	Not allowed
testQuestion	string Maximum length: 30	<i>Additional Information</i> 1. Agent may use the test question and answer to authorize payout in lieu of or in addition to photo ID <i>Field Rules</i> 1. Display is required if the agent uses test questions and answers 2. Display is not required if agent does not use test questions and answers	not allowed
testAnswer	string Maximum length: 30	<i>Additional Information</i> 1. Agent may use the test question and answer to authorize payout in lieu of or in addition to photo ID <i>Field Rules</i> 1. Display is required if the agent uses test questions and answers 2. Display is not required if agent does not use test questions and answers	not allowed
messageField1	string Maximum length: 40	<i>Additional Information</i>	optional

		1. Value must be printed on consumer receipt	
messageField2	string Maximum length: 40	<i>Additional Information</i> 1. Value must be printed on consumer receipt	optional
agentCheckNumber	string Maximum length: 12	<i>Additional Information</i> 1. Field not currently used	not allowed
agentCheckAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Field not currently used	not allowed
agentCheckAuthorizationNumber	string Maximum length: 5	<i>Additional Information</i> 1. Field not currently used	not allowed
customerCheckNumber	string Maximum length: 12	<i>Additional Information</i> 1. Field not currently used	not allowed

customerCheckAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Field not currently used	not allowed
okForAgent	boolean	<i>Additional Information</i> 1. If value is <code>true</code> , the agent can receive the specified transaction option 2. If value is <code>false</code> , the agent cannot receive the specified transaction option. Agent application must display a message to the user that this transaction cannot be picked up at this location. 3. The agent application must check the <code>okForPickup</code> field to determine whether the transaction can be received at this time	optional

deliveryOption	string	None	optional
transactionStatus	string Valid values: AVAIL, CANCL, RECVD, REFND, AFR and PRCSS	<i>Additional Information</i> 1. AVAIL is available 2. CANCL is canceled 3. RECVD is received 4. REFND is refunded 5. AFR is available for refund 6. PRCSS is processing 7. Only transactions with a value of AVAIL can be received; if a transaction cannot be received, the agent application should display a message to indicate the transaction status and that the transaction cannot be received. Do not allow user to proceed to receive the transaction.	required

dateTimeSent	dateTime Format: CCYY-MM-DDThh:mm:ss.sss-hh:mm The time zone offset is required	None	optional
receiveCurrency	string Length: 3	<i>Additional Information</i> 1. If validIndicator is false, the agent must pay the receiver using this currency 2. If validIndicator is true, the agent must pay the receiver using the currency in the indicativeReceiveCurrency field 3. The agent application must use the value of this field in all subsequent APIs	required

receiveAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The amount to be paid to the receiver. <i>Additional Information</i> 1. If <code>validIndicator</code> is <code>false</code> , the agent must pay this amount to the receiver 2. If <code>validIndicator</code> is <code>true</code> , the agent must pay the amount in the <code>indicativeReceiveAmount</code> field to the receiver 3. The agent application must use the value of this field in all subsequent APIs	required
referenceNumber	string Maximum length: 12	None	optional
originatingCountry	string Length: 3	None	optional

validIndicator	boolean	Whether or not the receive amount was guaranteed at the time of the send transaction. <i>Additional Information for receiving in indicative country only</i> 1. If <code>true</code> , the receive amount was guaranteed at the time of the send and the agent must pay the consumer the amount in the <code>indicativeReceiveAmount</code> field 2. If <code>false</code> , the receive amount was estimated at the time of the send and the agent must pay the consumer the amount in the <code>receiveAmount</code> field	optional
indicativeReceiveAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The amount to pay the consumer if the receive amount was guaranteed at the time of the send transaction. <i>Additional Information for receiving in indicative country only</i> 1. This amount must be paid in the currency returned in the	conditional

		<i>indicativeReceiveCurrency</i> field 2. This amount must not be used in subsequent APIs	
<i>indicativeReceiveCurrency</i>	string Length: 3	The currency in which to pay the consumer if the receive amount was guaranteed at the time of the send transaction. <i>Additional Information for receiving in indicative country only</i> 1. This currency must not be used in subsequent APIs	conditional
<i>indicativeExchangeRate</i>	decimal Minimum inclusive value: 0 Maximum length: 14	The exchange rate between the currencies returned in the <i>receiveCurrency</i> and <i>indicativeReceiveCurrency</i> fields <i>Field Rules for receiving in indicative country only</i> 1. Value returned to four decimal places for USA and US territories 2. Value returned to six decimal places elsewhere	conditional
<i>mgCustomerReceiveNumber</i>	string Maximum length: 20	<i>Additional Information</i> 1. Field does not apply to this product	not allowed

<i>partnerCustomerReceiveNumber</i>	string Maximum length: 20	<i>Additional Information</i> 1. Field does not apply to this product	not allowed
<i>receiveAgentID</i>	string Length: 8	<i>Additional Information</i> 1. Field does not apply to this product	not allowed
<i>receiveAgentName</i>	string Maximum length: 40	None	optional
<i>receiveAgentAbbreviation</i>	string Maximum length: 10	The abbreviated form of the agent's name	optional
<i>expectedDateOfDelivery</i>	date Format: CCYY-MM-DD	The date a send transaction is expected to be delivered.	not allowed

originalSendAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	optional
originalSendCurrency	string Length: 3	None	optional
originalSendFee	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	optional

originalExchangeRate	decimal Minimum inclusive value: 0 Maximum length: 14	<i>Field Rules</i> 1. Value returned to four decimal places for USA and US territories 2. Value returned to six decimal places elsewhere	optional
redirectIndicator	boolean	<i>Additional Information</i> 1. If <code>true</code> , the transaction is a currency redirect and the application must display a message to tell the receiver the <code>newReceiveAmount</code> , <code>newReceiveCurrency</code> and <code>newExchangeRate</code> ; the receiver must accept the changes before continuing 2. If <code>false</code> , the transaction is not a currency redirect	not allowed
redirectInfo	complex Maximum number of occurrences: 1	None	N/A
originalSendAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	required

original SendCurrency	string Length: 3	None	required
original SendFee	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	required

original Exchange Rate	decimal Minimum inclusive value: 0 Maximum length: 14	<i>Field Rules</i> 1. Value returned to four decimal places for USA and US territories 2. Value returned to six decimal places elsewhere	required
original ReceiveA mount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	required
original ReceiveC urrency	string Length: 3	None	required
original ReceiveC ountry	string Length: 3	None	not allowed
newSendF ee	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Field does not apply to this product	not allowed
newExcha ngeRate	decimal Minimum inclusive value: 0 Maximum length: 14	<i>Field Rules</i> 1. Value returned to four decimal places for USA and US territories 2. Value returned to six decimal places elsewhere	required

<code>newReceiveAmount</code>	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Must be told to receiver if <code>redirectIndicator</code> is <code>true</code> ; the receiver must accept the new value to continue	required
<code>newReceiveCurrency</code>	string Length: 3 Must be a valid currency code	<i>Additional Information</i> 1. Must be told to receiver if <code>redirectIndicator</code> is <code>true</code> ; the receiver must accept the new value to continue	required
<code>feeDifference</code>	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Field does not apply to this product	not allowed
<code>redirectType</code>	string Valid values: <code>CURRENCY_REDIRECT</code>	<i>Additional Information</i> 1. <code>CURRENCY_REDIRECT</code> is currency redirect	not allowed
<code>okForPickup</code>	boolean	Whether or not the transaction can be received at this time. <i>Additional Information</i> 1. If <code>true</code> , the transaction can be received at this time 2. If <code>false</code> , the transaction cannot be received at this time 3. If <code>false</code> , the reason the transaction cannot be received is returned in the <code>notOkForPickupReasonDescription</code> and reason code is returned in the <code>notOkForPickupReasonCode</code> fields	optional
<code>notOkForPickupReasonCode</code>	integer	<i>Additional Information – some examples are</i> 1. If value is 688, the transaction cannot be picked up before 7:00 AM in the receive country's local time 2. If value is 690, the transaction cannot be picked up at this time because it was sent using 24 or 48	optional

		hour service, and the specified time has not elapsed 3. If value is 690, the number of minutes remaining until the transaction can be received is returned in the <code>minutesUntilOkForPickup</code> field	
<code>notOkForPickupReasonDescription</code>	string	The description of why the transaction cannot be received at this time to display on the agent application GUI. Refer to Error Messages document for more information	required
<code>minutesUntilOkForPickup</code>	int Maximum inclusive value: 99999	The number of minutes remaining until the transaction can be received. <i>Additional Information</i> 1. Value is returned only if <code>notOkForPickupReasonCode</code> is 690. Agent application can use this information to display the local time or x hours, x minutes until transaction can be picked up. For example, transaction will be available at 3:15 pm, or in 1 hour and 15 minutes.	optional
<code>sendPurposeOfTransaction</code>	String Length: 30	The purpose for sending the transaction	conditional
<code>sendPurposeOfTransactionOther</code>	string Length: 40	The purpose for sending the transaction	NA
<code>receiverNameSuffix</code>	String Length: 20	The suffix of the receiver name	required
<code>receiverNameSuffixOther</code>	String Length: 20	For future use	NA

2.0.7 Reference Number Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

2.0.8 Reference Number Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>
```

3.0 Get Fields For Product Service

3.0.1 Get Fields For Product Description

The agent application uses the `getFieldsForProduct(GFFP)` API to determine field requirements for the `sendValidationRequest`. The information returned in the response is also used to build screen content.

Business Rules to Code

1. This is a required backend API before doing a `sendValidation`. The response will let the application know what data fields are needed for each transaction and what fields must always be displayed on the screen during the transaction or during pre-registration.
2. For the fields with `productFieldInfo` coming back as `dynamic=true`, an Agent's application must be able to provide any additional data using fields as `keyValuePair`. For example, an Account Deposit to India may require IFSC code for the receiver's bank account
3. **The data attributes returned in GFFP can change from transaction to transaction:** visibility, fieldLabel, displayOrder, fieldMax, fieldMin, defaultValue, exampleFormat, enumeratedValues, and regular expression. The agent's application must respond to these changes in the GFFP response. The number of required fields may change depending on the country where agent is located

Examples of scenarios where GFFP attributes values will change.

- a. **Visibility** - The following values are returned in the visibility field to indicate whether a field must be included in the `sendValidationRequest`. The value indicates if data is required to complete the transaction. The value also indicates whether the agent must allow an input mechanism to populate the field.

REQ: If the value is 'REQ', then data must be provided; omission of data will result in errors. The fields required for a transaction will vary depending on business and compliance rules applied to the specific transaction. A few examples of when the visibility can change depends on agent's country, amount, destination country, delivery options, etc.

OPT: If the value is 'OPT' then the field must be available on the application screen for data entry, but data is not needed to complete the transaction. Data may be included in the request for business reasons. If the agent is collecting the data, data must be sent in the transaction; omission of data will not result in technical errors. For example, middle name and second last name fields are required to be displayed on the screen in case the consumer has a middle or second last name. If the customer does not have these, then this data is not required to complete the transaction.

NOT_ALL: Data must not be included in the request, MoneyGram does not require the field to be displayed for the specified transaction. If the agent is collecting the data, data must not be sent on the transaction; including data will be ignored or result in errors.

SUP_OPT: Data is optional on the request, and the field may optionally appear on the application screen; MoneyGram does not require data to complete the transaction.

However, if the agent is collecting the data, data must be sent in on the transaction. Some examples of SUP_OPT fields are: ID expiration, nationality, citizenship, etc.

- b. **fieldMax, fieldMin** – the application must be coded to the fieldMax and fieldMin that are returned in GFFP. These values can change from one transaction to another. The maximum/minimum lengths in schema/WSDL should be used for database design and screen layout, and the agent must follow GFFP minimum and maximum lengths during a transaction submission. These lengths will always be within the boundary of the schema/WSDL. Some maximum lengths are shorter in GFFP than the schema/WSDL because MoneyGram has plans to eventually expand these fields per the lengths defined in the WSDL.
- c. **fieldLabel** - For the accountNumber field, the application must use the fieldLabel returned in GFFP. This label can change depending on which partner the transaction is being sent.

For example, some transactions can have the label as Account Number (18 digits), Account Number (11 digits), Mobile Number or Customer's Email Address.

For the remaining field labels, agent may use the suggested fieldLabels returned by GFFP on the application screen. The fieldLabels are also translated into some additional languages including Spanish, German, French, Chinese, Italian etc. Translated labels are returned when language field in the GFFP message header is specified for a particular language as described in the Introduction to AgentConnect module.

- d. **enumeratedValue** – returns list of values for enumerated fields. This list of values depends on the agent's country and can change at any time. Application must be able to use the updated list without requiring any code changes. Examples of some the fields that are enumerated are: ID type, occupation, purpose of transaction, relationship to receiver, etc.

3.0.2 Get Fields For Product Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/inbound/getFieldsForProduct
Headers	content-type: application/xml
Authentication	signature

3.0.3 Get Fields For Product Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

receiveCountry	string Length: 3 Must be a valid country code	Additional Information 1. Use value of receiveCountry returned by feeLookupResponse for selected delivery option	application	required
deliveryOption	string Must be a valid delivery option	Additional Information 1. Use value of deliveryOption returned by feeLookupResponse for selected delivery option	application	required

thirdPartyType	string Valid values: NONE, ORG, PERSON	If the transaction is being sent on behalf of someone other than the sender, whether it is being sent for a person or an organization. Additional Information 1. If the <code>amount</code> is above the agent's third party profile limit and the agent application allows third-party transactions, the agent must ask whether the transaction is on behalf of a third party Field Rules 1. If the agent application allows third-party transactions, a field to select the type of third-party transaction must be provided on the GUI when the send amount is above the third party limit. This third party limit is returned in the <code>profileResponse</code> API documented in the Introduction to AgentConnect module. 2. For US agents only – If agent does not allow third party transactions, agent application must still ask customer if this is a third party	conditional	required
-----------------------	--	---	--------------------	-----------------

		transaction if the send amount is above the profile third party limit. If transaction is a third party and agent does not allow third party, do not allow the transaction to be completed 3. If the agent application does not allow third-party transactions, the agent must communicate this to an account representative		
receiveAgentID	string Length: 8	Additional Information 1. Use value of <code>receiveAgentID</code> returned by feeLookupResponse for selected delivery option Field Rules 1. Data is required if <code>receiveAgentID</code> is returned in the <code>feeInformation</code> section of the feeLookupResponse for the selected delivery option	application	conditional
customerReceiveNumber	string Maximum length: 20	Additional Information 1. If <code>moneyGramConsumerLookup</code> API was used to find transaction history, use the <code>customerReceiveNumber</code> returned in	GUI/application	conditional

		moneyGramConsumerLookup Response. 2. This data can also be populated from the customer's profile in the agent's database.		
billerAccountNumber	string Maximum length: 30	The receiver's card number for payout via card. Additional Information 1. Field does not apply to this product	not allowed	not allowed
cardSwiped	boolean	Additional Information 1. Field does not apply to this product	not allowed	not allowed
otherPayoutType	string	The type of payment instrument used to payout the transaction, other than cash or money order. Additional Information 1. Field does not apply to this product	not allowed	not allowed
receiveCurrency	string Maximum length: 3 Must be a valid currency code	Additional Information 1. Use value of <code>validReceiveCurrency</code> returned by <code>feeLookupResponse</code> for selected delivery option	application	required
amount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Additional Information 1. Use value of <code>sendAmount</code> from <code>feeLookupResponse</code>	application	required

sendCurrency	string Maximum length: 3 Must be a valid currency code	Additional Information 1. Use value returned in <code>feeLookupResponse</code> for the selected delivery option	Application	required
--------------	---	---	-------------	----------

productType	string Valid values: SEND	Must be SEND.	Application	required
productVariant	string	Additional Information 1. Field does not apply for this product	not allowed	not allowed
serviceOfferingID	string Maximum length: 21	Additional Information 1. Field does not apply for this product	not allowed	not allowed
consumerId	string Maximum length: 20	Additional Information 1. Use value returned by the moneyGramConsumerLookupResponse 2. If the moneyGramConsumerLookup API was not used, or no value was returned, value must be 0	not allowed	required
formFreeStaging	boolean	Whether or not the transaction is a FormFree transaction. Additional Information 1. If <code>true</code> , the transaction is staged and prepared for FormFree completion which will be committed at a later time 2. If <code>false</code> , the transaction is not a FormFree type	not allowed	required

3.0.4 Get Fields For Product Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <channelInfo>
      <rrn>1234rrn</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <getFieldsForProductRequest
      xmlns="http://www.moneygram.com/AgentConnect1512">
      <receiveCountry>KEN</receiveCountry>
      <deliveryOption>TEST</deliveryOption>
      <thirdPartyType>ORG</thirdPartyType>
      <receiveAgentID>TEST1234</receiveAgentID>
      <customerReceiveNumber>TEST</customerReceiveNumber>
      <receiveCurrency>USD</receiveCurrency>
      <amount>100</amount>
      <sendCurrency>USD</sendCurrency>
      <productType>SEND</productType>
      <consumerId>1234</consumerId>
      <formFreeStaging>true</formFreeStaging>
      <mgiTransactionSessionID>TEST</mgiTransactionSessionID>
    </getFieldsForProductRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

3.0.5 Get Fields For Product Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

3.0.6 Get Fields For Product Success Response Field Description

Tag	Datatype	Information and Rules	Display
fqdoInfo	complex Maximum number of occurrences: unbounded	None	N/A
receiveCountry	string Maximum length: 3 Must be a valid currency code	None	N/A
deliveryOption	string Must be a valid delivery option	None	N/A
receiveAgentID	string length: 8	None	not allowed
receiveCurrency	string Maximum length: 3 Must be a valid currency code	None	N/A
receiveAgentName	string Maximum length: 40	None	N/A
receiveAgentAbbreviation	string Maximum length: 10	None	N/A
deliveryOptionDisplayNam e	string Maximum length: 50	None	N/A

registrationAuthorizationText	string Maximum length: 40	Field is not currently in use. The field <code>registrationAuthorizationText</code> may contain information about additional data required to complete DS registration by a Directed Sends Partner before activating a registration number.	N/A
speedOfDeliveryText	string Maximum length: 40	None	N/A
productFieldInfo	complex Maximum number of occurrences: unbounded	None	N/A
xmlTag	string Maximum length: 80	This is the key identifying a particular field and must be mapped to <code>sendValidationRequest</code>	N/A
visibility	string Valid values: <code>OPT</code> , <code>NOT_ALL</code> , <code>REQ</code> , <code>SUP_OPT</code>	See Business Rules to Code section above regarding this API <i>Additional Information</i> <code>OPT</code> - data is optional; but if collected data must be sent to MoneyGram <code>NOT_ALL</code> - data is not allowed <code>REQ</code> - data is required <code>SUP_OPT</code> - data is not required; but if collected data must be sent to MoneyGram	N/A

fieldLabel	string Maximum length: 80	The field's suggested label. Translation is returned based on the language indicated in the request header.	N/A
displayOrder	integer	The order in which the field appears on screen relative to other fields in the same category	N/A
fieldCategory	string	Identifier used to group the fields in a category	N/A

fieldCategoryLabel	String	The category's suggested label	N/A
dynamic	boolean	<i>Additional Information</i> 1. If <code>true</code>, the field is dynamic and not included in the XML schema for the sendValidationRequest, and its name and value must be provided as a <code>keyValuePair</code> 2. If <code>false</code>, the field is not dynamic	N/A
fieldMax	long	Use the value provided for each field. In some cases such as consumer name and address, the maximum length may be less than the length indicated in the WSDL.	N/A
fieldMin	long	None	N/A

dataType	string Valid values: boolean, cntrycode, date, datetime, decimal, enum, int, string, stringbool, text, time	None	N/A
enumerated	boolean	<i>Additional Information</i> 1. If value is <code>true</code> , the field is restricted to a list of values 2. If value is <code>false</code> , the field is not restricted to a list of values	N/A
defaultValue	string Maximum length: 255	None	N/A
validationRegEx	string Maximum length: 255	A regular expression used to validate the field's value.	N/A
arrayName	string Maximum length: 255	The xml tag of the array.	N/A

arrayLength	int	The length of the array arrayName <i>Additional Information</i> 1. -1 means the field is not an array and must only contain a value 2. A value of 0 or larger indicates the number of values in the array	N/A
-------------	-----	---	-----

exampleFormat	string Maximum length: 255	None	N/A
enumeratedValues	complex Maximum number of occurrences: 1	Contains information on the field's list of possible values. <i>Additional Information</i> 1. The information in this list must be used if <code>enumerated</code> is <code>true</code>	N/A
enumeratedValueInfo	complex Maximum number of occurrences: unbounded	Contents define an individual enumerated value.	N/A
value	string Maximum length: 255	None	N/A
label	string Maximum length: 255	None	N/A
dynamicFieldInfo	complex Maximum number of occurrences: unbounded	For future use	N/A
xmlTag	string Maximum length: 80	None	N/A
visibility	string	None	N/A

fieldMax	long	None	N/A
fieldMin	long	None	N/A
scale	integer	The number of places allowed after the decimal point. <i>Additional Information</i>	N/A

		1. Only applies if <code>dataType</code> is decimal	
<code>dataType</code>	string Valid values: <code>boolean</code> , <code>cntrycode</code> , <code>date</code> , <code>datetime</code> , <code>decimal</code> , <code>enum</code> , <code>int</code> , <code>string</code> , <code>stringbool</code> , <code>text</code> , <code>time</code>	None	N/A
<code>fieldLabel</code>	string Maximum length: 80	The field's suggested label	N/A
<code>displayOrder</code>	integer	The order in which the field must appear on screen relative to other fields.	N/A
<code>enumerated</code>	boolean	<i>Additional Information</i> 1. If value is <code>true</code>, the field is restricted to a list of values 2. If value is <code>false</code>, the field is not restricted to a list of values	N/A
<code>defaultValue</code>	string Maximum length: 255	None	N/A
<code>validationRegex</code>	string Maximum length: 255	A regular expression used to validate the field's value.	N/A
<code>exampleFormat</code>	string Maximum length: 255	None	N/A

enumeratedValues	complex Maximum number of occurrences: 1	Contains information on the field's list of possible values. <i>Additional Information</i> 1. The information in this list must be used if <code>enumerated</code> is <code>true</code>	N/A
enumeratedValueInfo	complex Maximum number of occurrences: unbounded	Contents define an individual enumerated value.	N/A
value	string Maximum length: 255	None	N/A
label	string Maximum length: 255	None	N/A

3.0.7 Get Fields For Product Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

3.0.8 Get Fields For Product Sample Failure Response

```
<statusDetails>  
  <rrn>100001001010</rrn>  
  <status>ERROR|503</status>  
  <responseCode>503</responseCode>  
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing  
via chat or email.</responseDesc>  
</statusDetails>
```

4.0 Receive Validation Service

4.0.1 Receive Validation Description

The agent application uses the [receiveValidation](#) API to receive a MoneyGram money transfer transaction.

1. The agent application must use the field lengths returned in the fieldMax field of [getFieldsForProductResponse](#)
2. A summary screen may be displayed with data collected to be confirmed by the agent or the customer. The agent application sends a [receiveValidationRequest](#) containing information collected from the customer, and MoneyGram returns a [receiveValidationResponse](#) indicating the transaction can continue, or an error indicating the issue with the receive transaction request
3. If the readyForCommit field in the [receiveValidationResponse](#) is true, the agent application may proceed to commit the transaction.
4. For FormFree transactions, the agent application must send the [receiveValidationRequest](#) with formFreeStaging field set to true until the response returns a readyForCommit value of true.
5. MoneyGram will recycle the reference numbers after the transactions have been closed/received for 6 months. If you are storing reference numbers in your database, you should also store the transaction date. The combination of the reference number and transaction date will be the unique key for a transaction.
6. For all Enumerated Fields, some examples are below, agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.

Enumerated Field
receiverOccupation
relationshipToSender
receivePurposeOfTransaction
thirdPartyReceiverNameSuffix
thirdPartyOccupation

7. If phone number is provided corresponding phone country code field is required, and vice versa.

Phone Field	Phone Country Code Field
receiverPhone	receiverPhoneCountryCode

8. State fields will always be returned as Optional by the `getFieldsForProduct` (GFFP) API. If a country is selected from the list that has states available in the `codeTable` API response, then a state is required. Agent application should change the list of states available depending on the country selected. If the country selected does not have any state list in the `codeTable` API, then the field should be disabled so data is not collected. The fields impacted are: `receiverState`, `receiverPhotoIDState`, `thirdPartyState`
9. When the `receiveValidation` API is submitted, MoneyGram performs validations on the transaction and returns any and all errors that are found. The validation involves screenings for compliance, aggregation, etc. and based on the consumer details submitted, MoneyGram may require additional information that was not marked required in the GFFP response.

Additional Information

1. The agent application may only receive transactions for which the `transactionStatus` field of the [referenceNumberResponse](#) is `AVAIL`, `okForAgent` is `true` and `okForPickup` is `true`.
2. A transaction cannot be sent and received by the same agent location.
3. A transaction cannot be sent and received by locations within the same postal code.
4. MoneyGram may not authorize payout of transactions attempted to be received in countries, states/provinces, or via delivery options that were not originally designated by the sender at time of send.

4.0.2 Receive Validation Request Headers Description

Method	POST
URL	<code>http://10.11.6.110:8580/api/v1/moneygram/inbound/receiveValidation</code>
Headers	<code>content-type: application/xml</code>
Authentication	signature

4.0.3 Receive Validation Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystem Id	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

agentStagingChannel	string Maximum length: 128	The AgentStagingChannel field is required when Agents <i>do not</i> use MoneyGram’s FormFree staging and completion process and still want to do a two part transaction. The first part is the transaction <i>staging/initiation</i> portion and the second part is the <i>completion</i> portion. This is used for agent applications where the receive transaction is completed in 2 parts: 1) transaction staging/initiation and 2) transaction completion. 1) During transaction staging/initiation, the customer provides all transaction information at a kiosk, mobile application or online. All transaction information collected is saved in the agent’s database. 2) During transaction completion, the customer goes to the agent location and provides the reference number to retrieve the transaction information from the agent’s system. All data is verified by the agent including photo ID. This field identifies the type of channel for the POS application where part 1 of the transaction was staged/initiated. Valid channel type codes are listed below: <table><thead><tr><th>Channel Type Code</th><th>Description</th></tr></thead><tbody><tr><td>ATM</td><td>Transaction is done using ATM that has MoneyGram products enabled.</td></tr></tbody></table>	Channel Type Code	Description	ATM	Transaction is done using ATM that has MoneyGram products enabled.	application	optional
Channel Type Code	Description							
ATM	Transaction is done using ATM that has MoneyGram products enabled.							

		KIOSK	Transaction is done with either a MoneyGram or agent owned kiosk.			
--	--	-------	---	--	--	--

		LOCATION	Transaction is done at a physical location (Brick & Mortar)			
		MOBILE	Transaction is done using either a MoneyGram owned or agent owned web interface via a mobile device			
		SYSTEM	Transaction is done using backend processes or rules.			

		WEB	Transacti on is done using either a MoneyGr am owned or agent owned web interface . Does not include transacti ons through a mobile device.			
		TABLET	Transacti on staged using Tablet device either a MoneyGr am owned or agent owned web interface . Does not include transacti ons through a Kiosk or Mobile device.			

		OTHER	Other staging initiation and completion Channel		
operatorName	string Maximum length: 80	<i>Additional Information</i> - Operator name or operator ID of the associate or user performing the transaction; it must be auto-populated from the agent's system and cannot be editable by the user - Agent Facing – Teller ID/User ID mapped to operatorName		Application / conditional	required

		- Customer Facing/Self Service (kiosk, online, mobile) – User ID/User Login mapped to operatorName - ATM – unique customer ID (customer number) mapped to operatorName		
referenceNumber	string Length: 12	Data should be populated from reference number response.	application	required
Pin	string Maximum length: 8	None	application	GFFP
receiveCurrency	string Length: 3 Must be a valid currency code	Data should be populated from reference number response.	application	required
agentCheckNumber	string Maximum length: 12	NA	NA	NA
agentCheckType	string	NA	NA	NA

agentCheckAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The amount of the transaction paid to the receiver <i>Field Rules</i> 1. Must contain value of <code>receiveAmount</code> field returned by the referenceNumberResponse	application	required
customerCheckNumber	string Maximum length: 12	NA	NA	NA
customerCheckType	string	NA	NA	NA
customerCheckAmount	decimal	NA	NA	NA

	Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3			
receiverAddress	string Maximum length: 80	The receiver's permanent street address. <i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	required
receiverAddress2	string Maximum length: 80	The receiver's permanent street address. <i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP
receiverAddress3	string Maximum length: 80	The receiver's permanent street address. <i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP
receiverCity	string Maximum length: 40	The receiver's permanent address city.	GUI	required
receiverState	string Length: 2 Must be a valid state code	The receiver's permanent address state. <i>Field Rules</i> 1. Data and GUI input are required if <code>receiverCountry</code> is CAN, MEX, or USA	GUI/conditional	conditional

		2. Data and input are not allowed otherwise		
receiverZipCode	String Length: 10	Application should not code to a specific country postal code format. Postal code should remain a free form text field adhering to the maximum length.	GUI	GFFP

receiverCountry	string Length : 3 Must be a valid country code	Country of receiver's permanent residence. Allow for all possible countries to be entered, not just the country where agent is located.	GUI	required
receiverMailingAddress	string maximum length: 80	Mailing address for the receiver. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverMailingAddress2	string maximum length: 80	Mailing address for the receiver. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverMailingAddress3	string maximum length: 80	Mailing address for the receiver. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverMailingCity	string maximum length: 40	Mailing city for the receiver. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverMailingState	string maximum length: 2	Mailing state for the receiver. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverMailingZipCode	string maximum length: 10	Mailing zip code for the receiver. Currently only applies to agents in Puerto Rico	GUI/application	GFFP

		See Data Quality Edits Addendum for data quality rules		
receiverMailingCountry	string length: 3	Mailing country for the receiver. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverPhotoIdType	string	<u>Enumerated value - agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI	required
receiverPhotoIdNumber	string Minimum length: 4 Maximum length: 25	<i>Field Rules</i> 1. Only alphanumeric and hyphen (-) characters allowed	GUI	required
receiverPhotoIdState	string Length: 2 Must be a valid state code	<i>Field Rules</i> 1. Data and GUI input are required if receiverPhotoIdCountry is CAN, MEX, or USA 2. Data and input are not allowed if senderPhotoIdCountry is not CAN, MEX, or USA	GUI/conditional	conditional
receiverPhotoIdCountry	string Length: 3 Must be a valid country code	Country where receiver photo ID was issued. Allow for countries other than the agent's country.	GUI	required
receiverLegalIdType	string	<u>Enumerated value - agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI	GFFP

receiverLegalIdNumber	string Minimum length: 4 Maximum length: 20	<i>Field Rules</i> 1. Only alphanumeric and hyphen (-) characters allowed	GUI	GFFP
receiverDOB	date Format: CCYY-MM-DD	<i>Field Rules</i> 1. Cannot be later than the current date 2. Some countries have minimum age requirements which will be validated based on the country where the transaction is received	GUI	required
receiverOccupation	string Maximum length: 30	Must use valid values returned in GFFP. The list returned can be different based on the agent's country	GUI	GFFP
thirdPartyFirstName	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP
thirdPartyMiddleName	string Length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP
thirdPartyLastName	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP
thirdPartyLastName2	string Maximum length: 40	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP
thirdPartyAddress	string Maximum length: 80	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP

thirdPartyAddress2	string Maximum length: 80	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP
thirdPartyAddress3	string Maximum length: 80	<i>Field Rules</i> 1. See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	GFFP

thirdPartyCity	string Maximum length: 40	None	GUI	GFFP
thirdPartyState	string Length: 2 Must be a valid state code	<i>Field Rules</i> 1. Data and GUI input are required if <code>thirdPartyCountry</code> is CAN, MEX, or USA 2. Data and GUI input are not allowed if <code>thirdPartyCountry</code> is not CAN, MEX, or USA	GUI/conditional	GFFP
thirdPartyZipCode	string Minimum length: 3 Maximum length: 10		GUI	GFFP
thirdPartyCountry	string Length: 3 Must be a valid country code	None	GUI	GFFP
thirdPartyLegalIdType	string	<u>Enumerated value - agent application must use the valid enumerations returned from <code>getFieldsForProduct</code> (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI	GFFP
thirdPartyLegalIdNumber	string	<i>Field Rules</i>	GUI	GFFP

	Minimum length: 4 Maximum length: 20	1. Only alphanumeric and hyphen (-) characters allowed		
thirdPartyDOB	date Format: CCYY-MM-DD	<i>Field Rules</i> 1. Cannot be later than the current date 2. Some countries have minimum age requirements which will be validated based on the country where the transaction is received	GUI	GFFP
thirdPartyOrg	string Maximum length: 60	The name of the third party organization	GUI	GFFP

receiverBirthCity	string Maximum length: 40	None	GUI	GFFP
receiverBirthCountry	string Length: 3 Must be a valid country code	None	GUI	GFFP
receiverNationalityCountry	string length: 3 must be a valid country code	Current nationality. Legal status of the country where the customer is registered	GUI	GFFP
receiverNationalityAtBirthCountry	string length: 3 Must be a valid country code	Nationality at the time the customer was born	GUI	GFFP
pcTerminalNumber	string Maximum length: 10	The agent-assigned ID number of the point-of-sale.	application	optional

agentUseReceiveData	string Maximum length: 200	Additional data chosen by the agent for the agent's use. Stored with the transaction by MoneyGram.	GUI/application	optional
billerAccountNumber	string Length: 30	NA.	NA	NA
otherPayoutType	string	NA	NA	NA
otherPayoutAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	NA	NA	NA

cardExpirationMonth	string Length: 2 Format: MM	NA	NA	NA
cardExpirationYear	string Length: 4 Format: CCYY	NA	NA	NA
cardSwiped	boolean	NA	NA	NA
consumerId	String Maximum length: 20	<i>Additional Information</i> 1. Value must be same as in GFFP 2. If data is not known, default value is 0	not allowed	required
receiverPhone	string Maximum length: 14	1. Numeric only, do not include plus(+) or dash(-) signs or parenthesis.	GUI	GFFP

		2. If data is provided in this field, receiverPhoneCountryCode field must also be collected and sent. 3. See <i>Data Quality Edits Addendum</i> for data quality rules		
agentConsumerID	String	The agent's number used to uniquely identify a customer <i>Field Rules</i> 1. Value is stored unencrypted and must not contain PCI data	Not Allowed	GFFP
agentTransactionId	String Maximum length: 20	An ID number that uniquely identifies the receive transaction across APIs. <i>Additional Information</i> 1. The agent's externally generated transaction ID	Not allowed	GFFP

mgTransactionSessionID	String Maximum length: 38	An ID number that uniquely identifies the receive transaction across APIs. <i>Additional Information</i> 1. Value must be that returned in the referenceNumberResponse	Not allowed	required
formFreeStaging	Boolean	Whether or not the transaction is a FormFree transaction. <i>Additional Information</i> Data should be carried from <code>getFieldsForProductRequest</code>	Not allowed	required
timeToLive	Int Maximum 5 digits	For future use	NA	NA
receivePurposeOfTransaction	string	<u>Enumerated value - agent application must use the valid enumerations returned from <code>getFieldsForProduct</code></u>	GUI/Application	GFFP

	Maximum length: 30	<u>(GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country Please refer to Business Rule #9 for additional field visibility requirements		
receivePurposeOfTransactionOther	string Maximum length: 30	<u>For future use</u>	NA	NA
relationshipToSender	string Maximum length: 30	<u>Enumerated value - agent application must use the valid enumerations returned from <code>getFieldsForProduct</code> (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country Please refer to Business Rule #9 for additional field visibility requirements	GUI/Application	GFFP
relationshipToSenderOther	string Maximum length: 30	<u>For future use</u>	NA	NA

receiverOccupationOther	string Maximum length: 30	<u>For future use</u>	NA	NA
receiverGender	string Maximum length: 30	<u>Enumerated value - agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI/Application	GFFP
receiverBirthState	string Maximum length: 2	For future use	NA	NA
receiverCitizenshipCountry	string Length: 3	Current citizenship. Legal status of the country where the customer is registered	GUI/Application	GFFP

	Must be a valid country code	Please refer to Business Rule #9 for additional field visibility requirements		
receiverCitizenshipAtBirthCountry	string Length: 3 Must be a valid country code	Citizenship at the time the customer was born	GUI/Application	GFFP
receiverDualCitizenshipCountry	String Length: 3 Must be a valid country code	For future use If receiverCitizenshipCountry is required, dual citizenship will be optional and data must be provided if customer has dual citizenship	NA	NA
receiverPhotoIdIssueMonth	string Length: 2 Format: MM	If information is available, issue month must be collected, then issue year must also be collected	GUI/Application	GFFP

receiverPhotoIdIssueYear	string Length: 4 Format: CCYY	If information is available, issue year must be collected	GUI/Application	GFFP
receiverPhotoIdIssueDay	string Length: 2 Format: DD	If information is available, issue day must be collected in addition to issue month and issue year	GUI/Application	GFFP
receiverPhotoIdExpirationMonth	string Length: 2 Format: MM	If information is available, expiration month must be collected, then expiration year must also be collected	GUI/Application	GFFP
receiverPhotoIdExpirationYear	string Length: 4	If information is available, expiration year must be collected	GUI/Application	GFFP

	Format: CCYY			
receiverPhotoIdExpirationDay	string Length: 2 Format: DD	If information is available, expiration day must be collected in addition to expiration month and expiration year	GUI/Application	GFFP
receiverPhotoIdIssueAuthority	string Maximum length: 30	For future use.	NA	NA
receiverLegalIdIssueMonth	string Length: 2 Format: MM	If information is available, issue month must be collected, then issue year must also be collected	GUI/Application	GFFP
receiverLegalIdIssueYear	string Length: 4 Format: CCYY	If information is available, issue year must be collected	GUI/Application	GFFP

receiverLegalIdIssueDay	string Length: 2 Format: DD	If information is available, issue day must be collected in addition to issue month and issue year	GUI/Application	GFFP
receiverLegalIdExpirationMonth	string Length: 2 Format: MM	If information is available, expiration month must be collected, then expiration year must also be collected	GUI/Application	GFFP
receiverLegalIdExpirationYear	string Length: 4 Format: CCYY	If information is available, expiration year must be collected	GUI/Application	GFFP

receiverLegalIdExpirationDay	string Length: 2 Format: DD	If information is available, expiration day must be collected in addition to expiration month and expiration year	GUI/Application	GFFP
receiverLegalIdIssueAuthority	string Maximum length: 30	For future use	NA	NA
receiverLegalIdState	string Length: 2 Must be a valid state	For future use	NA	NA
receiverLegalIdIssueCountry	string Length: 3 Must be a valid country code		GUI/Application	GFFP
receiverPhoneNotAvailable	boolean	For future use	NA	NA

receiverPhoneCountryCode	string Length: 3	- Country dial in code (ISD). Numeric only, do not include plus(+) or dash(-) signs or parenthesis. - If data is provided in this field, receiverPhone field must also be collected and sent.	GUI/Application	required
thirdPartyFirstNameNotAvailable	boolean	For future use	NA	NA
thirdPartyReceiverNameSuffix	string Maximum length: 30	<u>Enumerated value - agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI/Application	GFFP

thirdPartyReceiverNameSuffixOther	string Maximum length: 30	<u>For future use</u>	NA	NA
thirdPartyReceiverGender	string Maximum length: 30	<u>Enumerated value - agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI/Application	GFFP
thirdPartyReceiverOccupation	string Maximum length: 30	<u>Enumerated value - agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI/Application	GFFP
thirdPartyReceiverOccupationOther	string Maximum length: 30	<u>For future use</u>	NA	NA
thirdPartyReceiverBirthCity	string Maximum Length: 40	City where customer was born	GUI/Application	GFFP

thirdPartyReceiverBirthState	receiverState string Length: 2 Must be a valid state code	For future use	NA	NA
thirdPartyReceiverBirthCountry	string Length: 3 Must be a valid country code		GUI/Application	GFFP
thirdPartyReceiverCitizenshipCountry	string Length: 3	Current citizenship. Legal status of the country where the customer is registered	GUI/Application	GFFP

	Must be a valid country code			
thirdPartyReceiverCitizenshipAtBirthCountry	string Length: 3 Must be a valid country code	Citizenship at the time the customer was born	GUI/Application	GFFP
thirdPartyReceiverDualCitizenshipCountry	string Length: 3 Must be a valid country code	For future use If thirdPartyReceiverCitizenshipCountry is required, dual citizenship will be optional and data must be provided if customer has dual citizenship	NA	NA
thirdPartyLegalIdIssueMonth	string Length: 2 Format: MM	If information is available, issue month must be collected, then issue year must also be collected	GUI/Application	GFFP
thirdPartyLegalIdIssueYear	string Length: 4 Format: CCYY	If information is available, issue year must be collected	GUI/Application	GFFP

thirdPartyLegalIdIssueDay	string Length: 2 Format: DD	If information is available, issue day must be collected in addition to issue month and issue year	GUI/Application	GFFP
thirdPartyLegalIdExpirationMonth	string Length: 2 Format: MM	If information is available, expiration month must be collected, then expiration year must also be collected	GUI/Application	GFFP
thirdPartyLegalIdExpirationYear	string Length: 4	If information is available, expiration year must be collected	GUI/Application	GFFP

	Format: CCYY			
thirdPartyLegalIdExpirationDay	string Length: 2 Format: DD	If information is available, expiration day must be collected in addition to expiration month and expiration year	GUI/Application	GFFP
thirdPartyLegalIdIssueAuthority	string Maximum length: 30	For future use	NA	NA
thirdPartyLegalIdState	string Length: 2 Must be a valid state code	For future use	NA	NA
thirdPartyLegalIdIssueCountry	string Length: 3 Must be a valid country code		GUI/Application	GFFP
primaryReceiptLanguage	string Maximum length: 3	For future use	NA	NA

secondaryReceiptLanguage	string Maximum length: 3	For future use	NA	NA
receiverIntendedUseOfMGI Services	string length: 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country Field can be labeled as: How do you plan to use MoneyGram?	GUI	GFFP

		The purpose of this question is to identify, in general why the consumer plans to use MoneyGram products/services. Please refer to Business Rule #9 for additional field visibility requirements		
receiptImages	Complex	Reserved for future use	NA	NA
fieldValues	Complex Maximum number of occurrences: unbounded	For future use	NA	NA
xmlTag	String Maximum length: 80	For future use	NA	NA
value	String	For future use	NA	NA

4.0.4 Receive Validation Sample Request

```

<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Header/>
  <soapenv:Body>
    <channelInfo>
      <rrn>87364529</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>generatedSignature123</signature>
    </channelInfo>
    <receiveValidationRequest
xmlns="http://www.moneygram.com/AgentConnect1512">
      <agentStagingChannel>MainChannel</agentStagingChannel>
      <operatorName>JohnDoe</operatorName>
      <referenceNumber>MG123456789</referenceNumber>
      <pin>876543</pin>
      <receiveCurrency>USD</receiveCurrency>
      <agentCheckNumber>CHK789123</agentCheckNumber>
      <agentCheckType>Personal</agentCheckType>
      <agentCheckAmount>500.00</agentCheckAmount>
      <customerCheckNumber>CUST987654</customerCheckNumber>
      <customerCheckType>Corporate</customerCheckType>
      <customerCheckAmount>500.00</customerCheckAmount>
      <receiverAddress>123 Main St</receiverAddress>
      <receiverAddress2>Apt 4B</receiverAddress2>
      <receiverAddress3>Downtown</receiverAddress3>
      <receiverCity>New York</receiverCity>
      <receiverState>NY</receiverState>
      <receiverZipCode>10001</receiverZipCode>
      <receiverCountry>US</receiverCountry>
      <receiverMailingAddress>123 Main St</receiverMailingAddress>
      <receiverMailingAddress2>Apt 4B</receiverMailingAddress2>
      <receiverMailingAddress3>Downtown</receiverMailingAddress3>
      <receiverMailingCity>New York</receiverMailingCity>
      <receiverMailingState>NY</receiverMailingState>
      <receiverMailingZipCode>10001</receiverMailingZipCode>
      <receiverMailingCountry>US</receiverMailingCountry>
      <receiverPhotoIdType>Passport</receiverPhotoIdType>
      <receiverPhotoIdNumber>J123456789</receiverPhotoIdNumber>
      <receiverPhotoIdCity>New York</receiverPhotoIdCity>
      <receiverPhotoIdState>NY</receiverPhotoIdState>
      <receiverPhotoIdCountry>US</receiverPhotoIdCountry>

```

```
<receiverLegalIdType>Driver's License</receiverLegalIdType>
<receiverLegalIdNumber>D789456123</receiverLegalIdNumber>
<receiverDOB>1985-05-12</receiverDOB>
<receiverOccupation>Software Engineer</receiverOccupation>
<thirdPartyFirstName>Jane</thirdPartyFirstName>
<thirdPartyMiddleName>Alice</thirdPartyMiddleName>
<thirdPartyLastName>Doe</thirdPartyLastName>
<thirdPartyLastName2>Smith</thirdPartyLastName2>
<thirdPartyAddress>456 Elm St</thirdPartyAddress>
<thirdPartyAddress2>Suite 200</thirdPartyAddress2>
<thirdPartyAddress3>Midtown</thirdPartyAddress3>
<thirdPartyCity>Los Angeles</thirdPartyCity>
<thirdPartyState>CA</thirdPartyState>
<thirdPartyZipCode>90001</thirdPartyZipCode>
<thirdPartyCountry>US</thirdPartyCountry>
<thirdPartyLegalIdType>Passport</thirdPartyLegalIdType>
<thirdPartyLegalIdNumber>K987654321</thirdPartyLegalIdNumber>
<thirdPartyDOB>1980-07-22</thirdPartyDOB>
<thirdPartyOrg>Acme Corp</thirdPartyOrg>
<receiverBirthCity>New York</receiverBirthCity>
<receiverBirthCountry>US</receiverBirthCountry>
<receiverNationalityCountry>US</receiverNationalityCountry>
<receiverNationalityAtBirthCountry>US</receiverNationalityAtBirthCountry>
<pcTerminalNumber>TERMINAL1234</pcTerminalNumber>
<agentUseReceiveData>Verified</agentUseReceiveData>
<billerAccountNumber>987654321</billerAccountNumber>
<otherPayoutType>Bank Transfer</otherPayoutType>
<otherPayoutAmount>300.00</otherPayoutAmount>
<cardExpirationMonth>12</cardExpirationMonth>
<cardExpirationYear>2026</cardExpirationYear>
<cardSwiped>No</cardSwiped>
<consumerId>CONSUMER987654</consumerId>
<receiverPhone>+15551234567</receiverPhone>
<agentConsumerID>AGT987654</agentConsumerID>
<agentTransactionId>TXN123456789</agentTransactionId>
<mgiTransactionSessionID>SESSION123456</mgiTransactionSessionID>
<formFreeStaging>No</formFreeStaging>
<timeToLive>2024-09-01T12:00:00Z</timeToLive>
<receivePurposeOfTransaction>Personal</receivePurposeOfTransaction>
<receivePurposeOfTransactionOther>Gift</receivePurposeOfTransactionOther>
<relationshipToSender>Brother</relationshipToSender>
<relationshipToSenderOther>N/A</relationshipToSenderOther>
<receiverOccupationOther>N/A</receiverOccupationOther>
<receiverGender>Male</receiverGender>
<receiverBirthState>NY</receiverBirthState>
```

```

<receiverCitizenshipCountry>US</receiverCitizenshipCountry>
<receiverCitizenshipAtBirthCountry>US</receiverCitizenshipAtBirthCountry>
<receiverDualCitizenshipCountry>Canada</receiverDualCitizenshipCountry>
<receiverPhotoIdIssueMonth>06</receiverPhotoIdIssueMonth>
<receiverPhotoIdIssueYear>2021</receiverPhotoIdIssueYear>
<receiverPhotoIdIssueDay>15</receiverPhotoIdIssueDay>
<receiverPhotoIdExpirationMonth>06</receiverPhotoIdExpirationMonth>
<receiverPhotoIdExpirationYear>2026</receiverPhotoIdExpirationYear>
<receiverPhotoIdExpirationDay>15</receiverPhotoIdExpirationDay>
<receiverPhotoIdIssueAuthority>US      State

```

Department</receiverPhotoIdIssueAuthority>

```

<receiverLegalIdIssueMonth>03</receiverLegalIdIssueMonth>
<receiverLegalIdIssueYear>2020</receiverLegalIdIssueYear>
<receiverLegalIdIssueDay>10</receiverLegalIdIssueDay>
<receiverLegalIdExpirationMonth>03</receiverLegalIdExpirationMonth>
<receiverLegalIdExpirationYear>2025</receiverLegalIdExpirationYear>
<receiverLegalIdExpirationDay>10</receiverLegalIdExpirationDay>
<receiverLegalIdIssueAuthority>DMV</receiverLegalIdIssueAuthority>
<receiverLegalIdState>NY</receiverLegalIdState>
<receiverLegalIdIssueCountry>US</receiverLegalIdIssueCountry>
<receiverPhoneNotAvailable>No</receiverPhoneNotAvailable>
<receiverPhoneCountryCode>1</receiverPhoneCountryCode>
<thirdPartyFirstNameNotAvailable>No</thirdPartyFirstNameNotAvailable>
<thirdPartyReceiverNameSuffix>Jr</thirdPartyReceiverNameSuffix>
<thirdPartyReceiverNameSuffixOther>N/A</thirdPartyReceiverNameSuffixOther>
<thirdPartyReceiverGender>Female</thirdPartyReceiverGender>
<thirdPartyReceiverOccupation>Accountant</thirdPartyReceiverOccupation>
<thirdPartyReceiverOccupationOther>N/A</thirdPartyReceiverOccupationOther>
<thirdPartyReceiverBirthCity>Los Angeles</thirdPartyReceiverBirthCity>
<thirdPartyReceiverBirthState>CA</thirdPartyReceiverBirthState>
<thirdPartyReceiverBirthCountry>US</thirdPartyReceiverBirthCountry>
<thirdPartyReceiverCitizenshipCountry>US</thirdPartyReceiverCitizenshipCountry>

```

```

<thirdPartyReceiverCitizenshipAtBirthCountry>US</thirdPartyReceiverCitizenshipAtBirthCountry>

```

```

<thirdPartyReceiverDualCitizenshipCountry>UK</thirdPartyReceiverDualCitizenshipCountry>

```

```

<thirdPartyLegalIdIssueMonth>09</thirdPartyLegalIdIssueMonth>
<thirdPartyLegalIdIssueYear>2019</thirdPartyLegalIdIssueYear>
<thirdPartyLegalIdIssueDay>20</thirdPartyLegalIdIssueDay>
<thirdPartyLegalIdExpirationMonth>09</thirdPartyLegalIdExpirationMonth>
<thirdPartyLegalIdExpirationYear>2024</thirdPartyLegalIdExpirationYear>
<thirdPartyLegalIdExpirationDay>20</thirdPartyLegalIdExpirationDay>

```

```

<thirdPartyLegalIdIssueAuthority>US      State
Department</thirdPartyLegalIdIssueAuthority>
  <thirdPartyLegalIdState>CA</thirdPartyLegalIdState>
  <thirdPartyLegalIdIssueCountry>US</thirdPartyLegalIdIssueCountry>
  <primaryReceiptLanguage>EN</primaryReceiptLanguage>
  <secondaryReceiptLanguage>ES</secondaryReceiptLanguage>
    <receiverIntendedUseOfMGIServices>Personal
Expenses</receiverIntendedUseOfMGIServices>
  <receiverMotherMaidenName>Johnson</receiverMotherMaidenName>
  <receiverFatherFirstName>Michael</receiverFatherFirstName>
  <receiptImages>
    <receiptImage>
      <identifier>RECEIPT123456</identifier>
      <mimeType>image/png</mimeType>
      <image>cid:708652510496</image>
    </receiptImage>
  </receiptImages>

  <fieldValues>
    <keyValuePair>
      <xmlTag>Field1</xmlTag>
      <fieldValue>SampleData1</fieldValue>
    </keyValuePair>
    <keyValuePair>
      <xmlTag>Field2</xmlTag>
      <fieldValue>SampleData2</fieldValue>
    </keyValuePair>
  </fieldValues>
</receiveValidationRequest>
</soapenv:Body>
</soapenv:Envelope>

```

4.0.5 Receive Validation Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

4.0.6 Receive Validation Success Response Field Description

Tag	Datatype	Information and Rules	Display
mgTransactionSessionID	string Maximum length: 38	An ID number that uniquely identifies the receive transaction across APIs.	not allowed
readyForCommit	boolean	<i>Additional Information</i> 1. When <code>true</code> , the agent application may continue the transaction.	not allowed
disclosureText	complex Maximum number of occurrences: unbounded	None	N/A
longLanguageCode	string Length: 3	The language of the disclosure message.	required
textTranslation	string Maximum length: 2000	Additional disclosure info when taxes/fees can't be determined based on included fields.	required
additionalFieldsToCollect	complex Maximum number of occurrences: unbounded	For future use.	N/A
receipts	Complex	Reserved for future use	N/A

4.0.7 Receive Validation Request Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

4.0.8 Receive Validation Request Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact
servicing via chat or email.</responseDesc>
</statusDetails>
```

5.0 Commit Transaction Service

5.0.1 Commit Transaction Description

The agent application uses the [commitTransaction](#) API to commit a MoneyGram money transfer receive transaction.

Business Rules to Code

1. The [commitTransactionRequest](#) may only be used when the readyForCommit field of the last [receiveValidationResponse](#) was true.
2. At this time, the commitTransactionRequest must be sent within 60 seconds of the receiveValidationRequest. If the commitTransactionRequest is not received by MoneyGram within 60 seconds, the transaction will not be marked as RECEIVED in MoneyGram's system.
3. If agent's application does not receive a commitTransactionResponse within 10-40 seconds, application must send the commitTransactionRequest again using the same mgiTransactionSessionID . This must be retried up to 3 times. If the retry attempt fails, check transaction status using referenceNumber API to confirm if the transaction was successful.
4. If error code 935 is returned on commit, it must be handled the same way as if the commit response is not received (see rule above).
5. Other errors may be returned on a commit thereby stopping the transaction. The application must handle scenarios where the transaction fails (an error code is returned) on commit
6. After the commit is successful, agent may proceed to print receipts and payout the transaction. Refer to AC 1512 (SP1) Receipts module for detailed information and requirements for receipts

5.0.2 Commit Transaction Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/inbound/commitTransaction
Headers	content-type: application/xml
Authentication	signature

5.0.3 Commit Transaction Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required
senderAccountNumber	String	Sender account number	not allowed	required
destinationAccountNumber	String	Receiver account number	not allowed	required
amount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Value must be the same as that used in the getFieldsForProductRequest	not allowed	required
transactionCurrency	String Length: 3 Must be a valid currency code	Transaction currency	not allowed	required

mgTransaction SessionID	string Maximum length: 38	An ID number that uniquely identifies the send transaction across APIs. <i>Additional Information</i> 1. Value must be that returned in the feeLookupResponse	not allowed	required
productType	string Valid values: SEND	None	application	required
fieldValues	complex Maximum number of occurrences: unbounded	For future use	NA	NA
xmlTag	string Maximum length: 80	For future use	NA	NA
fieldValue	String Maximum length: 255	For future use	NA	NA
stateRegulator Version	string Maximum length: 20	Version of the state regulator information used on the transaction receipt. Obtain from doddFrankStateRegulatorInfo API. <i>Field Rules</i> 1. Data is required for US agents for this product. 2. Data is not allowed for non-US agents	application	conditional

5.0.4 Commit Transaction Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <channelInfo>
      <rrn>100001001010</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <senderAccountNumber>100001001010</senderAccountNumber>
      <destinationAccountNumber>1000007363</destinationAccountNumber>
      <amount>100.10</amount>
      <transactionCurrency>USD</transactionCurrency>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <commitTransactionRequest
      xmlns="http://www.moneygram.com/AgentConnect1512">
      <mgiTransactionSessionID>16773711E172492497686521858318NN</mgiTransactionSessionID>
      <productType>SEND</productType>
      <fieldValues>
        <keyValuePair>
          <xmlTag>xmlTag</xmlTag>
          <fieldValue>fieldValue</fieldValue>
        </keyValuePair>
      </fieldValues>
      <stateRegulatorVersion>1</stateRegulatorVersion>
    </commitTransactionRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

5.0.5 Commit Transaction Response Field Description

Tag	Datatype	Information and Rules	Display
<i>referenceNumber</i>	<i>string</i> <i>Length: 12</i>	<i>Must be printed on receipt</i>	<i>required</i>
<i>partnerConfirmationNumber</i>	<i>string</i> <i>Maximum length: 11</i>	<i>When populated, must be provided on receipt</i>	<i>required</i>
<i>partnerName</i>	<i>string</i>	1. MoneyGram's Directed Sends Partner name when the delivery option is an Account Deposit, Card Deposit or Home Delivery. 2. Data is not returned for a 10 minute service delivery option. 3. Data is required to be displayed after a successfully committed transaction.	<i>required</i>
<i>freePhoneCallPIN</i>	<i>string</i> <i>Maximum length: 14</i>	<i>PIN used to call using the telephone number in tollFreePhoneNumber</i>	<i>optional</i>
<i>tollFreePhoneNumber</i>	<i>string</i> <i>Maximum length: 14</i>	<i>Additional Information</i> 1. Toll-free telephone number used by consumer with <i>freePhoneCallPIN</i> to make free phone call	<i>required</i>
<i>expectedDateOfDelivery</i>	<i>date</i> <i>Format: CCYY-MM-DD</i>	<i>The date a send transaction is expected to be delivered or deposited.</i>	<i>required</i>
<i>transactionDateTime</i>	<i>dateTime</i> <i>Format: CCYY-MM-DDThh:mm:ss.sss-hh:mm</i> <i>The time zone offset is required</i>	<i>Additional Information</i> 1. Value indicates the date and the time at which a particular transaction is successfully completed. 2. Data is always returned	<i>required</i>

<i>receiptText Info</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>None</i>	<i>N/A</i>
<i>longLanguageCode</i>	<i>string</i> <i>Length : 3</i>	<i>The language of the receipt message.</i>	<i>required</i>
<i>textTranslation</i>	<i>string</i> <i>Maximum length: 2000</i>	<i>Additional information must be printed on the receipt.</i>	<i>required</i>
<i>receipts</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>For future use. Receipt data when receipts are managed by MoneyGram</i>	<i>N/A</i>
<i>reference numberText tCode</i>	<i>string</i> <i>maximum length: 20</i>	<i>This is the code used to identify the referenceNumberText and referenceNumberConsumerText. All 3 fields will be populated when a message needs to be displayed to the sender.</i>	<i>optional</i>
<i>reference NumberText</i>	<i>string</i> <i>Maximum length: 240</i>	<i>Data may be returned due to compliance rules that requires the agent to notify the customer to call MoneyGram. This must be displayed on the screen for the agent to advise the customer</i>	<i>required</i>
<i>reference NumberCon sumer Text</i>	<i>string</i> <i>Maximum length: 240</i>	<i>Data may be returned due to compliance rules that requires the agent to notify the customer to call MoneyGram. This must be printed on the receipt, and/or displayed on the screen for customer view.</i>	<i>required</i>

5.0.6 Commit Transaction Response Headers Description

Success Http Status Code	202 - Accepted
---------------------------------	----------------

5.0.7 Commit Transaction Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	status. a. Sample pending status i. PENDING 001 , where 001 is the pending status code b. Sample failure status ii. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

5.0.8 Commit Transaction Sample Pending Response

```

<statusDetails>
  <rrn>100001001010</rrn>
  <status>PENDING|001</status>
  <responseCode>001</responseCode>
  <responseDesc>Transaction received. Processing started. Final status to be
determined.</responseDesc>
</statusDetails>

```

5.0.9 Commit Transaction Sample Failure Response

```

<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>

```

6.0 Receive Reversal Service

6.0.1 Receive Reversal Description

The agent application uses the [receiveReversal](#) API if the transaction was received in error, or if a failure in some other part of the agent's system requires the rollback of a transaction (e.g., a printer jammed during processing).

This API may also be used to reverse a receive transaction due to network communication issues occurring at the time of committing a Receive transaction. The Agent application can send a receive reversal and then retry the receive request again and then commit.

Business Rules to Code

1. Reversals must be completed before 23:59:59 US Central Time the same day the original transaction was received.
2. Reversals can only be performed by the same agent that performed the original transaction.
3. Reference number lookup should be performed to check the status of the transaction before performing a receive reversal. The status must be in RECVD before a receive reversal can be done.
4. A reversal reason is required.

Additional Information

1. For manual reversal, the agent application may use the [referenceNumber](#) API to verify the status of a transaction as RECVD before using a [receiveReversal](#) API. However for reversals due to communication issues there is no need to reverse the transaction if transaction is in RECVD status. To avoid fraudulent transactions, agents should restrict manual receive reversal for call center or requiring manager's approval.
2. Receive reversal will revert the transaction status back to AVAIL making the transaction available for receive again.

6.0.2 Receive Reversal Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/inbound/receiveReversal
Headers	content-type: application/xml
Authentication	signature

6.0.3 Send Reversal Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

receiveAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	Application	Required
referenceNumber	string Maximum length: 12	None	GUI/ Application	Required

operatorName	string Maximum length: 7	1. Operator name or operator ID of the associate or user performing the transaction; it must be auto-populated from the agent's system and cannot be editable by the user • Agent Facing – Teller ID/User ID mapped to operatorName • Customer Facing/Self Service (kiosk, online, mobile) – User ID/User Login mapped to operatorName • ATM – unique customer ID (customer number) mapped to operatorName	Application	Optional
communicationRetryIndicator	Boolean	Default value= false. If agent application has sent a receiveReversalRequest and did not receive a response, the application can retry the receiveReversalRequest again and set this indicator to true.	not allowed	Optional
receiveReversalReason	String	<i>Valid values:</i> WANTS_CASH [CUSTOMER WANTS CASH/NOT CHECK] WRONG_TX [Wrong Transaction] OUT_OF_CHECKS [Agent is out of checks] ID_PROBLEM [No ID/Wrong ID/Etc.]	GUI/ Application	Required

6.0.4 Receive Reversal Sample Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Header/>
  <soapenv:Body>
    <channelInfo>
      <rrn>87364529</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>generatedSignature123</signature>
    </channelInfo>
    <receiveReversalRequest xmlns="http://www.moneygram.com/AgentConnect1512">
      <receiveAmount>100.00</receiveAmount>
      <referenceNumber>123456</referenceNumber>
      <operatorName>ATM</operatorName>
      <communicationRetryIndicator>false</communicationRetryIndicator>
      <receiveReversalReason>WANTS_CASH</receiveReversalReason>
    </receiveReversalRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

6.0.5 Receive Reversal Response Headers Description

Success Http Status Code	200 - OK
--------------------------	----------

6.0.6 Receive Reversal Success Response Field Description

Tag	Datatype	Information and Rules	Display
transactionDateTime	dateTime Format: CCYY-MM-DDThh:mm:ss.sss-hh:mm	None	not allowed

6.0.7 Receive Reversal Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

6.0.8 Receive Reversal Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>
```

7.0 Digital Signature Generation

To ensure secure communication, the calling channel must provide a valid certificate file(**.cer**) certificate file.

The digital signature is generated using the **SHA256withRSA** algorithm and passed as a **Base64-encoded** value in the signature field of the API request.

7.0.1 Signature Generation

1. **Provide a Valid Certificate:**
 - The calling channel must supply a **.cer** certificate file.
2. **Generate the Digital Signature:**
 - **Concatenate the clear text fields** (detailed below).
 - **Format the amount** as a **BigDecimal** with two decimal places using `setScale(2, RoundingMode.CEILING)`.
 - **Hash** the concatenated string using **SHA-256**.
 - **Encrypt** the hash with **RSA** using the private key.
 - **Encode** the encrypted hash as a Base64 string.
 - **Pass** the Base64 signature in the signature field.

7.0.2 Clear Text Values

For each transaction type, the clear text values must be concatenated in the specified order. The amount field must be a **BigDecimal** with two decimal places.

1. **Reference Number Request Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + referenceNumber
2. **Get Fields For Product Request Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + amount + sendCurrency + receiveCurrency + receiveCountry + consumerId
 - Ensure the amount is a **BigDecimal** and formatted as `setScale(2, RoundingMode.CEILING)`.
3. **Receive Validation Request Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + referenceNumber + agentCheckAmount + receiveCurrency + mgiTransactionSessionID
 - Ensure the agentCheckAmount is a **BigDecimal** and formatted as `setScale(2, RoundingMode.CEILING)`.

4. **Commit Transaction Request Service**

- Concatenate the following fields in this order:
rrn + channel + sourceSystemId + sourceAccount + destinationAccount + amount + currency + mgiTransactionSessionID + productType
- Ensure the amount is a BigDecimal and formatted as `setScale(2, RoundingMode.CEILING)`.

5. **Receive Reversal Request Service**

- Concatenate the following fields in this order:
rrn + channel + sourceSystemId + referenceNumber + receiveAmount + receiveReversalReason
- Ensure the receiveAmount is a BigDecimal and formatted as `setScale(2, RoundingMode.CEILING)`.

8.0 Appendix 1: Request Field Guide

8.0.1 Request Field Guide

The following is an example of a table used to describe API request field details.

Tag	Datatype	Information and Rules	Input	Data
<code>requestExampleField1</code>	string Maximum length: 10	An example of a field containing a string.	GUI	required
<code>requestExampleField2</code>	string Length: 3 Must be a valid country code	An example of a field containing a country code	application	required
<code>requestExampleField3</code>	boolean	An example field whose data and visibility requirements depend on the <code>getFieldsForProduct</code> API. <i>Additional Information</i> 1. If <code>true</code> , then... 2. If <code>false</code> , then...	not allowed	not allowed

Definitions

- **Tag:** The field's XML tag; fields for which data is required are shown in bold red text
- **Datatype:** Describes the type and restrictions of the field's data
- **Information and Rules:** Provides additional information, business rules, and a description of the field if necessary
- **Input:** Indicates how the field's value is obtained
 - **Application:** The agent application must retrieve the data from another part of the agent application or from a previous MoneyGram API response. Data can be displayed on the application screen
 - **GUI:** The agent application must display the field on its user interface and allow user input

- **Conditional:** The agent application may or may not display the field on the user interface for user input depending on the conditions stated in the Information and Rules column
- **GFFP:** Whether or not the field is shown on the user interface for user inputs depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
- **N/A:** Input does not apply; for instance, if the field only contains other fields
- **Not Allowed:** The agent application must not allow data to be entered by the user. Data must not be displayed. The agent application must retrieve the data from another part of the agent application or from a previous MoneyGram API response
- **Optional:** The agent may choose whether to display the field on the user interface for user input
- **Data:** Indicates whether the field must contain data; only used on API requests
 - **Required:** The field must contain data
 - **Not allowed:** The field must not contain data
 - **Optional:** The agent must display the field on the user interface, but data collection is optional
 - **Conditional:** The field may or may not contain data depending on the conditions stated in the Information and Rules column
 - **GFFP:** Whether or not the field contains data depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
 - **Response:** Whether or not the field contains data depends on the information returned by a message specified in the additional information for the API

9.0 Appendix 1: Response Field Guide

9.0.1 Response Field Guide

The following is an example of a table used to describe API response field details.

Tag	Datatype	Information and Rules	Display
responseExampleField1	string Maximum length: 10	An example of a field containing a string.	required
responseExampleField2	string Length: 3 Must be a valid country code	An example of a field containing a country code	optional
responseExampleField3	boolean	An example field whose data and visibility requirements depend on the getFieldsForProduct API. <i>Additional Information</i> 1. If <code>true</code> , then... 2. If <code>false</code> , then...	required

Definitions

- **Tag:** The field's XML tag; fields for which data is required are shown in bold red text
- **Datatype:** Describes the type and restrictions of the field's data
- **Information and Rules:** Provides additional information, business rules, and a description of the field if necessary
- **Display:** Indicates whether the value of the field is shown on the agent application's user interface
 - **Conditional:** The value may or may not be shown on the user interface depending on the conditions stated in the Information and Rules column
 - **GFFP:** Whether or not the value is shown on the user interface depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)

- **N/A:** Visibility does not apply; for instance, if the field doesn't contain displayable data
- **Not allowed:** The value must not be shown on the user interface; for fields in API responses, the data in the field should not be edited unless otherwise stated
- **Optional:** The agent may choose whether to show the value on the user interface
- **Required:** The value must be shown on the user interface if data is returned in the API