



IMT API Specification Document

Moneygram Amend & Refund API

v1.0.0

CONFIDENTIALITY DISCLAIMER

DEVELOPER API GUIDE DOCUMENT

THIS DOCUMENT AND THE INFORMATION IN IT ARE PROVIDED IN CONFIDENCE, FOR THE SOLE PURPOSE OF EQUITY BANK LIMITED AND MAY NOT BE DISCLOSED TO ANY THIRD PARTY OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF EQUITY BANK LIMITED.

Any form of reproduction, dissemination, copying, disclosure, modification, distribution and or publication of this material is strictly prohibited. The contents of this document have not been independently verified and they do not purport to be comprehensive, or to contain all the information that a prospective investor may need. No representation, warranty or undertaking, expressed or implied is or will be made or given and no responsibility or liability is or will be accepted by Equity Bank Limited or by any of its directors, employees or advisors in relation to the accuracy or completeness of this document or any other written or oral information made available in connection with the Company.

Revision History

Date	Version	Author	Comments
01.10.2024	v1.0.0	Kennedy N. Gatimu	Initial document creation

Table of Contents

1.0 Introduction.....	6
2.0 Overview.....	7
2.0.1 Business Purpose.....	7
2.0.2 API Flows and Processes.....	7
2.0.2.1 Amend MoneyGram Send Transaction Process.....	7
2.0.2.2 Refund MoneyGram Send Transaction Process.....	7
3.0 Detail Lookup Service.....	8
3.0.1 Detail Lookup Description.....	8
3.0.2 Detail Lookup Request Headers Description.....	8
3.0.3 Detail Lookup Request Field Description.....	8
3.0.4 Detail Lookup Sample Request.....	9
3.0.5 Detail Lookup Response Headers Description.....	9
3.0.6 Detail Lookup Response Field Description.....	9
3.0.7 Detail Lookup Sample Success Response.....	11
3.0.8 Detail Lookup Sample Failure Response.....	11
4.0 Amend Transaction Service.....	12
4.0.1 Amend Transaction Description.....	12
4.0.2 Amend Transaction Request Headers Description.....	12
4.0.3 Amend Transaction Request Field Description.....	13
4.0.4 Amend Transaction Sample Request.....	15
4.0.5 Amend Transaction Response Headers Description.....	16
4.0.6 Amend Transaction Success Response Field Description.....	16
4.0.7 Amend Transaction Failure Response Field Description.....	16
4.0.8 Amend Transaction Sample Failure Response.....	16
5.0 Send Reversal Service.....	17
5.0.1 Send Reversal Description.....	17
5.0.2 Send Reversal Request Headers Description.....	18
5.0.3 Send Reversal Request Field Description.....	18
5.0.4 Send Reversal Sample Request.....	23
5.0.5 Send Reversal Response Headers Description.....	25
5.0.6 Send Reversal Success Response Field Description.....	25
5.0.7 Send Reversal Failure Response Field Description.....	26
5.0.8 Send Reversal Sample Failure Response.....	26
6.0 Digital Signature Generation.....	27
6.0.1 Signature Generation.....	27
6.0.2 Clear Text Values.....	27
7.0 Appendix 1: Request Field Guide.....	28

7.0.1 Request Field Guide..... 28

8.0 Appendix 1: Response Field Guide..... 30

8.0.1 Response Field Guide..... 30

1.0 Introduction

The MoneyGram Amend and Reverse API facilitates secure and efficient management of outbound international money transfers through three key services:

1. **Detail Lookup Service** – This service mirrors the functionality of the outbound API, allowing the retrieval of specific transaction details.
2. **Amend Transaction** – This service enables the modification of an existing transaction, providing flexibility for updates.
3. **Send Reversal** – This service allows for the reversal of a previously initiated transaction.

To ensure the security and integrity of all transactions, the calling channel is required to supply a valid digital certificate in **.cer** format. This certificate is used to sign the API requests, ensuring both authenticity and protection against tampering.

The request signing process involves the signing of predefined fields from the clear text using the **SHA256withRSA** algorithm. The resulting signature is then encoded in **Base64** format and included in the signature field of each API request.

This integration is designed to provide a robust and secure solution for handling international money transfers via MoneyGram, ensuring the highest standards of data security and transaction integrity.

2.0 Overview

2.0.1 Business Purpose

- This document provides technical and business information required to amend and refund pending MoneyGram send transactions in order to handle customer service issues
- All Agent applications that include sends must include functionality for amends and reversals.
- For a successful Amend or Reversal, the original send must have been performed from the same location.
- (**Amends or Refunds can only be performed by the original send location**)

2.0.2 API Flows and Processes

2.0.2.1 Amend MoneyGram Send Transaction Process

1. The agent application sends a [detailLookupRequest](#) containing the transaction reference number, and MoneyGram returns a [detailLookupResponse](#) indicating whether the transaction can be amended.
2. The agent confirms the consumer's identity matches the identity of the transaction's sender.
3. If the transaction is available, the agent application sends an [amendTransactionRequest](#) containing the transaction reference number and amended receiver name (first, middle, last, second last name), and MoneyGram returns a [amendTransactionResponse](#) indicating whether the amend succeeded.

2.0.2.2 Refund MoneyGram Send Transaction Process

1. The agent application sends a [detailLookupRequest](#) containing the transaction reference number, and MoneyGram returns a [detailLookupResponse](#) indicating whether the transaction can be refunded.
2. The agent confirms the consumer's identity matches the identity of the transaction's sender.
3. If the transaction is available, the agent application sends a [sendReversalRequest](#) containing details of the refund request, and MoneyGram returns a [sendReversalResponse](#) containing refund information.
4. The agent refunds the consumer's funds if reversal API is successful.

3.0 Detail Lookup Service

3.0.1 Detail Lookup Description

The agent application uses the detailLookup API to determine the status and other information for a MoneyGram money transfer send transaction before amending or refunding it.

Additional Information

1. Agent application can look up a transaction by **mgTransactionSessionID**. In our case, the channel will call GAG using the original **RRN from commit transaction services**. The session ID can be used to look up the transaction for up to 24 hours to check the transaction status
2. This API can only be used by the original sending location/agent ID.
3. This is an Optional API to code and not required in the actual Send transaction flow.

3.0.2 Detail Lookup Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/detailLookup
Headers	content-type: application/xml
Authentication	signature

3.0.3 Detail Lookup Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	- Retrieval reference number. - Same with the one supplied on Commit Transaction Request - Alphanumeric. - Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required

sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

3.0.4 Detail Lookup Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <detailLookupRequest>
      <rrn>100001001010</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <signature>signature</signature>
    </detailLookupRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

3.0.5 Detail Lookup Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

3.0.6 Detail Lookup Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Statuses: Sample status 1. OK 000 , where 000 is the success status code Sample pending status	String

		2. PENDING 001, where 001 is the pending status code Sample failure status 3. ERROR 409, where 409 is the error status code	
3	responseCode	Status response code	String
4	responseDesc	Status response description	String
5	imtReferenceNumber	Imt reference number. Returned when status is OK (Success)	String
6	imtSessionTranId	Imt session tran ID. Returned when status is OK (Success)	String
7	imtTransactionDate	Imt Transaction Date. Returned when status is OK (Success)	String
8	imtStatus	Valid values: 1. AVAIL is available 2. CANCL is canceled 3. RECVD is received 4. REFND is refunded 5. AFR is available for refund 6. PRCSS is for processing. With this status, the transaction can be reversed or amended, but it cannot be received	String

3.0.7 Detail Lookup Sample Success Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <imtReferenceNumber>12345</imtReferenceNumber>
  <imtSessionTranId>12345</imtSessionTranId>
  <imtTransactionDate>3455566</imtTransactionDate>
  <status>OK|000</status>
  <imtStatus>AVAIL</imtStatus>
  <responseCode>000</responseCode>
  <responseDesc>Transaction Completed Successfully.</responseDesc>
</statusDetails>
```

3.0.8 Detail Lookup Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>
```

4.0 Amend Transaction Service

4.0.1 Amend Transaction Description

The agent application uses the [amendTransaction](#) API to make minor spelling changes to the receiver name (first, middle, last, and/or second last names) of money transfer send transaction. If the transaction was sent to the wrong person/receiver, the transaction must be cancelled and a new one must be created for a different receiver. MoneyGram does not allow the receiver name to be changed to a completely different person.

Business Rules to Code

1. The agent application may only amend a transaction if the [detailLookupResponse](#) returns a `transactionStatus` of AVAIL, AFR or PRCSS. Not all transactions in the listed statuses can automatically be amended. If a transaction is in AVAIL, AFR or PRCSS status and cannot be amended, the response will return an error.
2. The agent application may only amend transactions originally sent by the agent.
(**Amends can only be performed by the original send location**)
3. If any of the name fields are not changed, the same data that was used on the original send must be sent in this request. If any of the name fields are left blank, that name field will be erased.
4. This name change is intended to correct the spelling only. It's not intended to be used to change to an entirely different name.

4.0.2 Amend Transaction Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/amendTransaction
Headers	content-type: application/xml
Authentication	signature

4.0.3 Amend Transaction Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

referenceNumber	string Maximum length: 12	None	GUI	required
operatorName	string Maximum length: 80	<i>Additional Information</i> - Operator name or operator ID of the associate or user performing the transaction; it must be auto-populated from the agent's system and cannot be editable by the user - Agent Facing – Teller ID/User ID mapped to operatorName - Customer Facing/Self Service (kiosk, online, mobile) – User ID/User Login mapped to operatorName - ATM – unique customer ID (customer number) mapped to operatorName	application	required

receiverFirstName	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	required
receiverMiddleName	string Maximum length: 40	<i>Additional Information</i> - The value of <code>receiverMiddleName</code> must be sent even if the Middle name has not changed in order prevent a blank value overwriting the existing second last name <i>Field Rules</i> - Data is required if a value was returned in the detailLookupResponse - See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	conditional
receiverLastName	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	required

receiverLastName2	string Maximum length: 40	<i>Additional Information</i> - The value of <code>receiverLastName2</code> must be sent even if the second last name has not changed in order prevent a blank value overwriting the existing second last name <i>Field Rules</i> - Data is required if a value was returned in the detailLookupResponse - See <i>Data Quality Edits Addendum</i> for data quality rules	GUI	conditional
receiverNameSuffix	string maximum length: 30	For future use	NA	NA
receiverNameSuffixOther	String Maximum length: 30	For future use	NA	NA
receiverFirstNameNotAvailable	boolean	For future use	NA	NA

4.0.4 Amend Transaction Sample Request

```
soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Header/>
  <soapenv:Body>
    <channelInfo>
      <rrn>1234rrn</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <amendTransactionRequest xmlns="http://www.moneygram.com/AgentConnect1512">
      <referenceNumber>12345678</referenceNumber>
      <operatorName>ATM</operatorName>
      <receiverFirstName>John</receiverFirstName>
      <receiverMiddleName>M</receiverMiddleName>
      <receiverLastName>Doe</receiverLastName>
      <receiverLastName2>John</receiverLastName2>
      <receiverNameSuffix>Mr</receiverNameSuffix>
      <receiverNameSuffixOther>Mr</receiverNameSuffixOther>
      <receiverFirstNameNotAvailable>>false</receiverFirstNameNotAvailable>
    </amendTransactionRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

4.0.5 Amend Transaction Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

4.0.6 Amend Transaction Success Response Field Description

Tag	Datatype	Information and Rules	Display
transactionSucceeded	Boolean Valid value: true	<i>Additional Information</i> 1. If <code>true</code> , the transaction was amended 2. If transaction is not successful, an error is returned.	required

4.0.7 Amend Transaction Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

4.0.8 Amend Transaction Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing via chat or email.</responseDesc>
</statusDetails>
```


5.0 Send Reversal Service

5.0.1 Send Reversal Description

The agent application uses the [sendReversal](#) API to refund a MoneyGram money transfer send transaction.

Business Rules to Code

1. The agent application may only reverse a transaction if the [detailLookupResponse](#) returns a transactionStatus of AVAIL, AFR or PRCSS. Not all transactions in the listed statuses can automatically be reversed. If a transaction is in AVAIL, AFR or PRCSS status and cannot be reversed, the response will return an error.
2. The agent application must issue a refund receipt
3. For a successful Refund, the original send must have been done from the same location. (**Refund can only be performed by the original send location**)

Additional Information

1. The consumer must always show identification prior to obtaining a refund
2. The values of refundFaceAmount and refundFeeAmount appear on settlement reports
3. Refunds are available to the agent application for ninety days
4. Refunds after ninety days, or reversals of transactions that can't be processed by the agent application, can only be performed by contacting MoneyGram
5. There are no restrictions on the type of transactions eligible for reversal. Transactions may only be reversed if they have a status of AVAIL. However, a reversal attempt on a directed send transaction may not always be successful in cases where MoneyGram has sent the transaction to the account deposit partner. An error will be returned when the reversal fails. Agent must wait for a successful response before refunding the money.

Refund Receipt Specification

Refund receipts must go through MoneyGram legal approval process. The following rules must be followed when designing refund receipts:

1. The agent copy of the receipt must use one format; the consumer copy must use a second format
2. The receipt must be titled REFUND RECEIPT
3. Phrase 1 shall state, "The following transfer has been canceled."
4. Phrase 2 shall state, "Agent: Please return the total amount collected. Keep signed copy."
5. Phrase 3 shall appear near the bottom of the receipt and state, "Customer signature"
6. The following fields are required on refund receipts:
 - From the agent's profile:
 - Agent's name
 - Agent's address

- Agent's telephone number
- From the [detailLookupResponse](#):
 - transactionDateTime
 - senderFirstName
 - senderMiddleName
 - senderLastName
 - senderLastName2
 - receiverFirstName
 - receiverMiddleName
 - receiverLastName
 - receiverLastName2
- From information used in the [sendReversalRequest](#):
 - referenceNumber
 - sendReversalReason
- From the [sendReversalResponse](#):
 - transactionDateTime
 - refundFaceAmount
 - refundFeeAmount
 - refundTotalAmount

5.0.2 Send Reversal Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/sendReversal
Headers	content-type: application/xml
Authentication	signature

5.0.3 Send Reversal Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required

bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

sendAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Use value from detailLookupResponse	application	required
feeAmount	decimal Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Use value from detailLookupResponse	application	required
sendCurrency	string Length: 3 Must be a valid currency code	<i>Additional Information</i> 1. Use value from detailLookupResponse	application	required
referenceNumber	string Maximum length: 8	<i>Additional Information</i> 1. Use value from detailLookupRequest	application	required
operatorName	string Maximum length: 80	<i>Additional Information</i> 1. Operator name or operator ID of the associate or user performing the transaction; it must be auto-populated from the agent's system and cannot be editable by the user • Agent Facing – Teller ID/User ID mapped to operatorName • Customer Facing/Self Service (kiosk, online, mobile) – User ID/User	application	required

		Login mapped to operatorName ATM – unique customer ID (customer number) mapped to operatorName		
--	--	--	--	--

reversalType	string Valid values: C, R	<i>Additional Information</i> - C is cancel. If reversal is done same day as the transaction based on US Central time. - R is refund. If reversal is done day after the send transaction based on US Central time. Agent application must restrict reversalType = R for same day refunds - Agent application can always start with a reversalType of 'C'. If error code 605 (subErrorCode 3401, "Send reversal/cancel must be requested same day") is encountered, then application should programmatically submit the reversal request again with reversalType = R.	application	required
sendReversalReason	string Valid values: NO_RCV_LOC, WRONG_SERVICE, NO_TQ, INCORRECT_AMT, MS_NOT_USED	<i>Additional Information</i> - NO_RCV_LOC is no receive location - WRONG_SERVICE is wrong delivery option - NO_TQ is missing test question and answer - INCORRECT_AMT is incorrect Send/ Receive amount - MS_NOT_USED is MoneyGram Plus or a card number not used	GUI	conditional

		<i>Field Rules</i> 1. Data is required if reversalType is R		
feeRefund	string Valid values: Y, N	<i>Additional Information</i> 1. If value is Y, the transaction fee is to be refunded to the consumer 2. If value is N, the transaction fee is not to be refunded to the consumer 3. Value must be Y if reversalType=C or also if reversalType=R i.e, a Refund attempted within 30 minutes of original Send. (Currently this rule applies to US & territories only).	optional	required

agentCheckType	string Valid values: MTC	<i>Additional Information</i> 1. MTC is MoneyGram checks <i>Field Rules</i> 1. Data is required if using MoneyGram checks 2. Data is not allowed if not using MoneyGram checks	not allowed	conditional
agentCheckNumber	string Maximum length: 12	<i>Field Rules</i> 1. Data and GUI input are required if using MoneyGram checks 2. Data and input are not allowed if not using MoneyGram checks	conditional	conditional

<code>agentCheckAmount</code>	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The amount of the transaction paid the receiver in cash. <i>Field Rules</i> 1. Data and GUI input are required if using MoneyGram checks 2. Data and input are not allowed if not using MoneyGram checks 3. If not using MoneyGram Money Transfer Checks (MTCs), must contain value of <code>receiveAmount</code> field returned by the <code>referenceNumberResponse</code> 4. If using MTCs, must contain the portion of the receive amount that was paid in cash and recorded against <code>agentCheckNumber</code>.	conditional	conditional
<code>customerCheckType</code>	string Valid values: MTC	The type of non-cash instrument issued to the receiver. <i>Additional Information</i> 1. MTC is MoneyGram checks	not allowed	optional

<code>customerCheckNumber</code>	string Maximum length: 12	The number of the non-cash instrument issued to the receiver. <i>Field Rules</i> 1. Data and GUI input are required if using MoneyGram checks 2. Data and input are not allowed if not using MoneyGram checks	conditional	conditional
----------------------------------	---	--	-------------	-------------

customerCheckAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The amount of the transaction paid to the receiver by money order. <i>Field Rules</i> 1. Data and GUI input are required if using MoneyGram checks 2. Data and input are not allowed if not using MoneyGram checks 3. If using MTCs, must contain the portion of the receive amount that was paid in non-cash instruments and recorded against customerCheckNumber.	conditional	Conditional
communicationRetryIndicator	Boolean	If you are sending the reversal request for the first time, send it as false. If there is a communication error and you must send the request again, send it as true after the communication error has been resolved.	application	required

5.0.4 Send Reversal Sample Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Header/>
  <soapenv:Body>
    <channelInfo>
      <rrn>1234rrn</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <sendReversalRequest xmlns="http://www.moneygram.com/AgentConnect1512">
      <sendAmount>100.00</sendAmount>
      <feeAmount>5.00</feeAmount>
      <sendCurrency>USD</sendCurrency>
      <referenceNumber>12345678</referenceNumber>
      <operatorName>ATM</operatorName>
      <reversalType>C</reversalType>
    </sendReversalRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

```
<sendReversalReason>MS_NOT_USED</sendReversalReason>
<feeRefund>Y</feeRefund>
<agentCheckType>MTC</agentCheckType>
<agentCheckNumber>123456789</agentCheckNumber>
<agentCheckAmount>100.00</agentCheckAmount>
<customerCheckType>MTC</customerCheckType>
<customerCheckNumber>123456</customerCheckNumber>
<customerCheckAmount>100.00</customerCheckAmount>
<communicationRetryIndicator>false</communicationRetryIndicator>
</sendReversalRequest>
</soapenv:Body>
</soapenv:Envelope>
```


5.0.5 Send Reversal Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

5.0.6 Send Reversal Success Response Field Description

Tag	Datatype	Information and Rules	Display
transactionDateTime	dateTime Format: CCYY-MM-DDThh:mm:ss.sss-hh:mm	None	required
refundTotalAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The amount to return to the consumer 1. Data not returned when reversal type is 'C' 2. When returned, it is the total of refundFaceAmount and RefundFeeAmount (if fee is refunded)	required
refundFaceAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None Data not returned when reversal type is 'C'	required
refundFeeAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The original transaction fee amount. <i>Additional Information</i> 1. Data not returned when reversal type is 'C' 2. A value is always returned for Refunds, even when the transaction fee is not to be returned. Application should use the value in the refundTotalAmount to determine total refund amount	required

totalCheck Amount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Field is not currently used	required
reversalType	string Valid values: C, R	<i>Additional Information</i> 1. C is cancel 2. R is refund	not allowed
agentCheck AuthorizationNum ber	string Maximum length: 5	<i>Additional Information</i> 1. Field is not currently used	required
receipts		For future use	

5.0.7 Send Reversal Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. b. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

5.0.8 Send Reversal Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>
```

6.0 Digital Signature Generation

To ensure secure communication, the calling channel must provide a valid certificate file(**.cer**) certificate file.

The digital signature is generated using the **SHA256withRSA** algorithm and passed as a **Base64-encoded** value in the signature field of the API request.

6.0.1 Signature Generation

1. **Provide a Valid Certificate:**
 - The calling channel must supply a **.cer** certificate file.
2. **Generate the Digital Signature:**
 - **Concatenate the clear text fields** (detailed below).
 - **Format the amount** as a **BigDecimal** with two decimal places using `setScale(2, RoundingMode.CEILING)`.
 - **Hash** the concatenated string using **SHA-256**.
 - **Encrypt** the hash with **RSA** using the private key.
 - **Encode** the encrypted hash as a Base64 string.
 - **Pass** the Base64 signature in the signature field.

6.0.2 Clear Text Values

For each transaction type, the clear text values must be concatenated in the specified order. The amount field must be a **BigDecimal** with two decimal places.

1. **Detail Lookup Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + bankId
2. **Amend Transaction Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + referenceNumber + receiverFirstName + receiverMiddleName + receiverLastName
3. **Send Reversal Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + amount + fee + currency + referenceNumber
 - Ensure the amount is a **BigDecimal** and formatted as `setScale(2, RoundingMode.CEILING)`.

7.0 Appendix 1: Request Field Guide

7.0.1 Request Field Guide

The following is an example of a table used to describe API request field details.

Tag	Datatype	Information and Rules	Input	Data
requestExampleField1	string Maximum length: 10	An example of a field containing a string.	GUI	required
requestExampleField2	string Length: 3 Must be a valid country code	An example of a field containing a country code	application	required
requestExampleField3	boolean	An example field whose data and visibility requirements depend on the getFieldsForProduct API. <i>Additional Information</i> 1. If true, then... 2. If false, then...	not allowed	not allowed

Definitions

- **Tag:** The field's XML tag; fields for which data is required are shown in bold red text
- **Datatype:** Describes the type and restrictions of the field's data
- **Information and Rules:** Provides additional information, business rules, and a description of the field if necessary
- **Input:** Indicates how the field's value is obtained
 - **Application:** The agent application must retrieve the data from another part of the agent application or from a previous MoneyGram API response. Data can be displayed on the application screen
 - **GUI:** The agent application must display the field on its user interface and allow user input

- **Conditional:** The agent application may or may not display the field on the user interface for user input depending on the conditions stated in the Information and Rules column
- **GFFP:** Whether or not the field is shown on the user interface for user inputs depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
- **N/A:** Input does not apply; for instance, if the field only contains other fields
- **Not Allowed:** The agent application must not allow data to be entered by the user. Data must not be displayed. The agent application must retrieve the data from another part of the agent application or from a previous MoneyGram API response
- **Optional:** The agent may choose whether to display the field on the user interface for user input
- **Data:** Indicates whether the field must contain data; only used on API requests
 - **Required:** The field must contain data
 - **Not allowed:** The field must not contain data
 - **Optional:** The agent must display the field on the user interface, but data collection is optional
 - **Conditional:** The field may or may not contain data depending on the conditions stated in the Information and Rules column
 - **GFFP:** Whether or not the field contains data depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
 - **Response:** Whether or not the field contains data depends on the information returned by a message specified in the additional information for the API

8.0 Appendix 1: Response Field Guide

8.0.1 Response Field Guide

The following is an example of a table used to describe API response field details.

Tag	Datatype	Information and Rules	Display
responseExampleField1	string Maximum length: 10	An example of a field containing a string.	required
responseExampleField2	string Length: 3 Must be a valid country code	An example of a field containing a country code	optional
responseExampleField3	boolean	An example field whose data and visibility requirements depend on the getFieldsForProduct API. <i>Additional Information</i> 1. If true, then... 2. If false, then...	required

Definitions

- **Tag:** The field's XML tag; fields for which data is required are shown in bold red text
- **Datatype:** Describes the type and restrictions of the field's data
- **Information and Rules:** Provides additional information, business rules, and a description of the field if necessary
- **Display:** Indicates whether the value of the field is shown on the agent application's user interface
 - **Conditional:** The value may or may not be shown on the user interface depending on the conditions stated in the Information and Rules column
 - **GFFP:** Whether or not the value is shown on the user interface depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
 - **N/A:** Visibility does not apply; for instance, if the field doesn't contain displayable data

- **Not allowed:** The value must not be shown on the user interface; for fields in API responses, the data in the field should not be edited unless otherwise stated
- **Optional:** The agent may choose whether to show the value on the user interface
- **Required:** The value must be shown on the user interface if data is returned in the API