



IMT API Specification Document

Moneygram Outbound Services

v1.0.0

CONFIDENTIALITY DISCLAIMER

DEVELOPER API GUIDE DOCUMENT

THIS DOCUMENT AND THE INFORMATION IN IT ARE PROVIDED IN CONFIDENCE, FOR THE SOLE PURPOSE OF EQUITY BANK LIMITED AND MAY NOT BE DISCLOSED TO ANY THIRD PARTY OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF EQUITY BANK LIMITED.

Any form of reproduction, dissemination, copying, disclosure, modification, distribution and or publication of this material is strictly prohibited. The contents of this document have not been independently verified and they do not purport to be comprehensive, or to contain all the information that a prospective investor may need. No representation, warranty or undertaking, expressed or implied is or will be made or given and no responsibility or liability is or will be accepted by Equity Bank Limited or by any of its directors, employees or advisors in relation to the accuracy or completeness of this document or any other written or oral information made available in connection with the Company.

Revision History

Date	Version	Author	Comments
24.09.2024	v1.0.0	Kennedy N. Gatimu	Initial document creation

Table of Contents

1.0 Introduction.....	6
2.0 Fee Lookup Service.....	7
2.0.1 Fee Lookup Service Description.....	7
2.0.2 Fee Look Up Request Headers Description.....	8
2.0.3 Fee Lookup Request Field Description.....	8
2.0.5 Fee Lookup Success Response Field Description.....	14
2.0.6 Fee Lookup Sample Success Response.....	27
2.0.4 Fee Look Up Response Headers Description.....	37
2.0.7 Fee Lookup Failure Response Field Description.....	37
2.0.8 Fee Lookup Sample Failure Response.....	37
3.0 Get Fields For Product Service.....	37
3.0.1 Get Fields For Product Description.....	38
3.0.2 Get Fields For Product Request Headers Description.....	39
3.0.3 Get Fields For Product Request Field Description.....	40
3.0.4 Get Fields For Product Success Response Field Description.....	46
3.0.5 Get Fields For Product Sample Request.....	53
3.0.6 Get Fields For Product Response Headers Description.....	54
3.0.7 Get Fields For Product Failure Response Field Description.....	54
3.0.8 Get Fields For Product Sample Failure Response.....	54
4.0 Send Validation Request Service.....	55
4.0.1 Send Validation Request Description.....	55
4.0.2 Send Validation Request Headers Description.....	56
4.0.3 Send Validation Request Field Description.....	57
4.0.4 Send Validation Success Response Field Description.....	88
4.0.5 Send Validation Request Sample Request.....	98
4.0.6 Send Validation Response Headers Description.....	103
4.0.7 Send Validation Request Failure Response Field Description.....	103
4.0.8 Send Validation Request Sample Failure Response.....	103
5.0 Commit Transaction Service.....	104
5.0.1 Commit Transaction Description.....	104
5.0.2 Commit Transaction Request Headers Description.....	105
5.0.5 Commit Transaction Sample Request.....	110
5.0.6 Commit Transaction Response Headers Description.....	111
5.0.7 Commit Transaction Response Field Description.....	111
5.0.8 Commit Transaction Sample Pending Response.....	111
5.0.9 Commit Transaction Sample Failure Response.....	111
6.0 Detail Lookup Service.....	111

6.0.1 Detail Lookup Description.....	112
6.0.2 Detail Lookup Request Headers Description.....	113
6.0.3 Detail Lookup Request Field Description.....	113
6.0.4 Detail Lookup Sample Request.....	114
6.0.5 Detail Lookup Response Headers Description.....	114
6.0.6 Detail Lookup Response Field Description.....	114
6.0.7 Detail Lookup Sample Success Response.....	115
6.0.8 Detail Lookup Sample Failure Response.....	115
7.0 Channel Callback Service.....	116
7.0.1 Channel Callback Description.....	116
7.0.2 Callback Sample Success Response.....	116
7.0.3 Callback Sample Failure Response.....	116
8.0 Code Table.....	117
8.0.1 Code Table Description.....	117
8.0.2 Code Table Request Headers Description.....	117
8.0.3 Code Table Request Field Description.....	118
8.0.4 Code Table Sample Request.....	119
8.0.5 Code Table Response Headers Description.....	119
8.0.6 Code Table Success Response Field Description.....	119
8.0.7 Code Table Request Failure Response Field Description.....	128
8.0.8 Code Table Request Sample Failure Response.....	128
9.0 Digital Signature Generation.....	129
9.0.1 Signature Generation.....	129
9.0.2 Clear Text Values.....	129
10.0 Appendix 1: Request Field Guide.....	131
10.0.1 Request Field Guide.....	131
11.0 Appendix 1: Response Field Guide.....	133
11.0.1 Response Field Guide.....	133

1.0 Introduction

This document outlines the integration process for the outbound services offered by MoneyGram, specifically for international money transfers. It provides detailed guidance on the APIs required for seamless transaction execution, including:

- **feeLookupRequest** service
- **getFieldsForProductRequest** service
- **sendValidationRequest** service
- **commitTransactionRequest** service
- **Detail Lookup** service
- **callback** service

To ensure secure communication, the calling channel must supply a valid digital certificate file in **.cer** format. This certificate will be used to sign requests, ensuring authenticity and integrity during transactions.

The request signing process involves using predefined fields from the clear text, which must be signed with the **SHA256withRSA** algorithm. Once signed, the resulting string is to be encoded into **Base64** format and included in the **signature** field of the respective API requests.

This integration will provide a robust and secure solution for handling outbound international money transfers through MoneyGram.

2.0 Fee Lookup Service

2.0.1 Fee Lookup Service Description

The agent application uses the `feeLookup` API to determine delivery options and pricing available from a particular location to any destination in MoneyGram's network. The response includes information to use in subsequent APIs to support the transaction flow for the option selected by the consumer.

Business Rules to Code

1. For the `receiveCountry` field, the agent application must check code tables API and only display countries for which `receiveActive` in the `countryInfo` section is `true`
2. The `validAmount`, `validCurrency`, and `validExchangeRate` fields are returned with data regardless of the value of the `validCurrencyIndicator` field in order to ensure MoneyGram and agents exchange the correct information
3. Depending on the regulatory and market environment, MoneyGram may provide foreign exchange rates for cross-currency transactions that will be guaranteed at the time of send, or rates that are only estimated at the time of sending. The following rules determine how to use `validAmount`, `validCurrency`, and `validExchangeRate` to advise the consumer on the expected payout amount and currency for the receiver:
 - If `validCurrencyIndicator` is `false`, the values are used only by the agent; the agent must present `estimatedReceiveAmount`, `estimatedReceiveCurrency`, and `estimatedExchangeRate` to the consumer
 - If `validCurrencyIndicator` is `false` and estimated amounts are presented to the consumer, the agent application must display the following disclaimer:

Not all currencies available at all locations.

The above exchange rate is only an approximation. The actual exchange rate will be the rate that is in effect at the time the transfer is received.

- If `validCurrencyIndicator` is `true`, the values are valid to both the agent and the consumer; the agent should present them to the consumer
4. If amounts are given to the consumer in writing prior to the `sendValidationResponse`, the agent application must display a

disclaimer stating the amounts are not guaranteed until the `sendValidationResponse` is returned

5. The amounts returned in the `feeLookupResponse` must not be used to print the Pre-Payment Disclosure.
6. Every fee lookup call would generate a session ID for each delivery option/receive currency. Each feeInfo may have a different session ID and application must use the session ID for the selected feeInfo. The same session ID must be used in the subsequent APIs during the particular transaction.
7. All information returned by feeLookup is for information only, the actual fee and exchange rates can change. The final transaction amounts will be returned on sendValidation based on the send amount.

2.0.2 Fee Look Up Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/feeLookup
Headers	content-type: application/xml
Authentication	signature

2.0.3 Fee Lookup Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required

callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required
productType	string Valid values: SEND	Use 'SEND' for send transaction	not allowed	required
productVariant	string	<i>Additional Information</i> 1. Field does not apply to this product	not allowed	not allowed
operatorName	string Maximum length: 7	<i>Additional Information</i> 1. Operator name or operator ID of the associate or user performing the transaction; it must be auto-populated from the agent's system and cannot be editable by the user - Agent Facing – Teller ID/User ID mapped to operatorName - Customer Facing/Self Service (kiosk, online, mobile) – User ID/User Login mapped to operatorName - ATM – unique customer ID (customer number) mapped to operatorName	application	optional
amountIncludingFee	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Field Rules</i> 1. Data is required in one and only one of the following: amountIncludingFee, amountExcludingFee, receiveAmount 2. The GUI must provide input for at least one of the following: amountIncludingFee, amountExcludingFee, receiveAmount	conditional	conditional

amountExcludingFee	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Field Rules</i> 1. Data is required in one and only one of the following: amountIncludingFee, amountExcludingFee, receiveAmount 2. The GUI must provide input for at least one of the following: amountIncludingFee, amountExcludingFee, receiveAmount	conditional	conditional
receiveAmount	decimalMaximum length: 9 Maximum decimal digits: 3	<i>Field Rules</i> 1. Data is required in one and only one of the following: amountIncludingFee, amountExcludingFee, receiveAmount 2. The GUI must provide input for at least one of the following: amountIncludingFee, amountExcludingFee, receiveAmount 3. Field cannot be used to determine fees to countries with indicative rates	conditional	conditional
receiveCountry	string Length: 3 Must be a valid country code	The country in which the transaction is to be received. Application must only display the list of countries from codeTableResponse where countryInfo.receiveActive = true	GUI or application	required
deliveryOption	string Must be a valid delivery option	<i>Additional Information</i> If no value is provided and allOptions is false, the value defaults to WILL_CALL	GUI/application	optional

mgRewardsNumber	string Maximum length: 20	The sender's MoneyGram Plus Rewards number.	optional	optional
receiveCode	string Maximum length: 25	<i>Additional Information</i> 1. Field does not apply to this product	not allowed	not allowed
indicativeReceiveCurrency	string Length: 3	<i>Field Rules</i> 1. Field is not currently used	not allowed	not allowed
receiveAgentID	string Length: 8	If allOptions = false, receiveAgentID must be provided if it's available, from moneyGramConsumerLookup	application	conditional
receiveCurrency	string Length: 3 Must be a valid currency code	<i>Additional Information</i> 1. If allOptions is true and deliveryOption is provided, the value of receiveCurrency is ignored 2. If allOptions is false, the feeLookupResponse returns a result for the specified delivery option (or WILL_CALL if none is specified) and receive currency	GUI/application	optional
sendCurrency	string Length: 3 Must be a valid currency code	<i>Additional Information</i> 1. If a value is provided, the feeLookupResponse returns only delivery options using the specified send currency	optional	optional

mgCustomerReceiveNumber	string Maximum length: 20	The unique MoneyGram-managed RRN (receiver registration number) that identifies the receiver of the transaction. Use the value returned from moneyGramConsumerLookupResponse <i>Additional Information</i> 1. If a value is provided, the feeLookupResponse returns only the delivery option for the specified RRN	application	optional
defaultInformationalFee	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Field does not apply to this product	not allowed	not allowed

serviceOfferingID	string Maximum length: 21	<i>Additional Information</i> 1. Field does not apply to this product	not allowed	not allowed
defaultMaxFee	boolean	<i>Additional Information</i> 1. Field does not apply to this product	not allowed	not allowed
allOptions	boolean Valid values: true	<i>Additional Information</i> 1. If true, the feeLookupResponse returns results for all delivery options and receive currencies available to the agent. This is the recommended flow 2. If false, the feeLookupResponse returns a single result for the specified deliveryOption and receiveCurrency	not allowed	required

promoCodeValues	complex	None		
promoCode	string Maximum number of occurrences: 5 Maximum length: 20	The promotional code to apply to the transaction. <i>Additional Information</i> 1. Value is provided by consumer	GUI	optional

2.0.5 Fee Lookup Success Response Field Description

Tag	Datatype	Information and Rules	Display
<i>feeInfo</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>None</i>	<i>N/A</i>
<i>validReceiveAmount</i>	<i>decimal</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Use the totalReceiveAmount field</i>	<i>not allowed</i>
<i>validReceiveCurrency</i>	<i>String</i> <i>Length: 3</i>	<i>Use the payoutCurrency field</i>	<i>not allowed</i>
<i>validExchangeRate</i>	<i>decimal</i> <i>Minimum inclusive value: 0</i> <i>Maximum length: 14</i>	<i>Additional Information</i> <i>If validCurrencyIndicator is true, the value is valid for the customer and must be displayed</i> <i>If validCurrencyIndicator is false, use the value in estimatedExchangeRate for display</i> <i>Field Rules</i> <i>Value returned to four decimal places for USA and US territories</i> <i>Value returned to six decimal places elsewhere</i>	<i>conditional</i>
<i>estimatedReceiveAmount</i>	<i>decimal</i> <i>Minimum inclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Always use the totalReceiveAmount for display.</i>	<i>not allowed</i>
<i>estimatedReceiveCurrency</i>	<i>String</i> <i>Length: 3</i>	<i>Always use the payoutCurrency for display</i>	<i>not allowed</i>

estimatedExchangeRate	<i>decimal</i> Minimum inclusive value: 0 Maximum length: 14	<i>Field Rules</i> 1. if validCurrencyIndicator = false, this must be displayed instead of the validExchangeRate. And the following text must be displayed on the application screen: Not all currencies available at all locations. The above exchange rate is only an approximation. The actual exchange rate will be the rate that is in effect at the time the transfer is received. 2. Value returned to four decimal places for USA and US territories 3. Value returned to six decimal places elsewhere	<i>conditional</i>
totalAmount	<i>decimal</i> Minimum inclusive value: 0 Maximum length: 14	Use the totalAmountToCollect field for display.	<i>not allowed</i>
receiveCountry	<i>String</i> length: 3	None	<i>optional</i>
deliveryOption	<i>string</i>	<i>Additional Information</i> 1. Value of field is used in subsequent APIs and is not displayed on screen	<i>not allowed</i>

Tag	Datatype	Information and Rules	Display
<i>receiveAmountAltered</i>	<i>boolean</i>	<i>In some circumstances it may not be possible to convert a receive amount in one currency into the exact amount in another currency. For example, 400 of one currency might be 7998 of another currency, but 401 might be 8003; therefore, no amount can match a receive amount of 8000. In such cases MoneyGram may alter the receive amount to the closest approximation.</i> <i>Additional Information</i> <i>1. Field is only returned for quotes by receive amount</i> <i>2. If <code>true</code>, the original receive amount was altered</i> <i>3. If <code>true</code>, the agent application must display a message that the receive amount was altered</i> <i>4. If <code>false</code>, the original receive amount was not altered</i>	<i>optional</i>
<i>speedOfDeliveryText</i>	<i>string</i> <i>Validation pattern: Maximum length in English: 40</i> <i>Validation pattern: Maximum length in translation language: 2000</i>	<i>None</i>	<i>optional</i>

<i>saLimitA vailale</i>	<i>decimal</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Internal Use Only</i>	<i>Not allowed</i>
<i>revisedI nformati onalFee</i>	<i>Boolean</i>	<i>Field does not apply to this product</i>	
<i>delivery OptId</i>	<i>string</i>	<i>None</i>	<i>not allowed</i>

<i>delivery OptDispl ayName</i>	<i>string</i> <i>Validation pattern: Maximum length in English: 50</i> <i>Validation pattern: Maximum length in translation language: 2000</i>	<i>Additional Information</i> <i>1. Used with <code>receiveAgentAbbreviation</code> and <code>receiveCurrency</code> to provide a description of the delivery option for the end user</i>	<i>require d</i>
<i>regAuthT ext</i>	<i>string</i>	<i>Additional Information</i> <i>1. Field is not currently used</i> <i>2. Field is not returned</i>	<i>not allowed</i>
<i>receiveA gentID</i>	<i>string</i> <i>Length: 8</i>	<i>When value is returned, it must be used in the subsequent APIs for this transaction</i> <i>Unique ID identifying the Receiving partner and receive currency for Account Deposit, Card Deposit and Home Delivery transactions. This is different than the agent ID provided in the request header</i> <i>Not applicable for WILL_CALL (10 minute service) transactions</i>	<i>not allowed</i>
<i>receiveA gentName</i>	<i>string</i> <i>Maximum length: 40</i>		<i>not allowed</i>

receiveAgentAbbreviation	<i>string</i> Maximum length: 10	<i>Additional Information</i> 1. Used with <i>deliveryOptDisplayName</i> to provide a description of the delivery option for the end user	<i>required</i>
mgmManaged	<i>string</i> Maximum length: 20 Valid values: <i>Optional, Not Allowed, Required</i>	<i>Additional Information</i> 1. If <i>optional</i> , the RRN is optional for the delivery option 2. If <i>required</i> , the transaction can be completed as a directed send intra-transaction 3. If <i>not allowed</i> , the delivery option does not use an RRN	<i>not allowed</i>

disclosureText	<i>string</i> Maximum length: 2000	Field is not currently used and is not returned	<i>not allowed</i>
mgmTransactionSessionID	<i>string</i> Maximum length: 38	A unique ID identifying the specific feeInfo. This value must be saved (for the session) and used in the subsequent APIs such as sendValidationRequest and commitTransactionRequest APIs	<i>not allowed</i>
sendAmountAltered	<i>Boolean</i>	Indicates whether the send amount was modified from the original quote	<i>optional</i>
additionalInfoText	<i>string</i> Maximum length: 400	Field is not currently used	<i>not allowed</i>
promotionInfo	<i>complex</i> Maximum number of occurrences: <i>unbounded</i>	<i>None</i>	<i>N/A</i>
promotionCode	<i>string</i> Maximum length: 20	The code used to identify the promotion.	<i>required</i>

<i>promotionDiscountId</i>	<i>string</i> <i>Length</i> <i>: 2</i> <i>Valid values: 01, 02, 03</i>	<i>The code used to identify the type of discount.</i> <i>Additional Information</i> <i>01 is flat fee. Flat Fee is a promotion that provides the services with a specified fee.</i> <i>02 is amount off. Amount Off is a promotion that provides services with a specified amount off the fee.</i> <i>03 is percent off. Percent Off is a promotion that provides services with a percent off the fee.</i>	<i>not allowed</i>
<i>promotionCategoryId</i>	<i>String</i> <i>length: 2</i>	<i>Internal Use Only</i>	<i>not allowed</i>

<i>promotionDiscount</i>	<i>decimal</i> <i>Minimum exclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>The promotion's discount value as setup in MoneyGram system based on the promotionDiscountId</i>	<i>not allowed</i>
<i>promotionDiscountAmount</i>	<i>decimal</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>The actual discount amount applied to nonDiscountedFeeExclTax.</i>	<i>required</i>
<i>promotionErrorCode</i>	<i>string</i> <i>Length</i> <i>: 4</i>	<i>The error code returned if the promotion code was invalid.</i>	<i>required</i>
<i>promotionErrorMessage</i>	<i>string</i> <i>Maximum length: 40</i>	<i>NA</i>	<i>NA</i>
	<i>string</i> <i>Length</i> <i>: 3</i>	<i>The language of the error message.</i>	<i>optional</i>

	<i>string</i> <i>Maximum length: 2000</i>	<i>The translated error message.</i>	<i>required</i>
<i>sendAmounts</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>None</i>	<i>N/A</i>
<i>sendAmount</i>	<i>decimal</i> <i>Minimum exclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>The send amount of the transaction. This value must be used to populate the 'amount' field in GFFP request</i>	<i>required</i>
<i>sendCurrency</i>	<i>string</i> <i>Length : 3</i>	<i>None</i>	<i>required</i>

<i>totalSendFees</i>	<i>decimal</i> <i>Minimum inclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Sum of discountedMGIFee and nonMGISendFee. Total of all fees charged to sender by MoneyGram, agents, etc.</i>	<i>required</i>
<i>totalDiscountAmount</i>	<i>decimal</i> <i>Minimum inclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Discount amount applied to nonDiscountedFeeExclTax.</i>	<i>required</i>
<i>totalSendTaxes</i>	<i>decimal</i> <i>Minimum inclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Total taxes charged to the sender by MoneyGram, government agents, etc.</i>	<i>required</i>
<i>totalAmountToCollect</i>	<i>decimal</i> <i>Minimum exclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Total of all fees, taxes, and the send amount.</i>	<i>required</i>
<i>detailSendAmounts</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>None</i>	<i>N/A</i>

<i>amountType</i>	<i>string</i>	<i>The type of fee or tax</i>	<i>optional</i>
	Valid values: <i>mgNonDiscountedSendFee, nonMgiSendFee, totalNonDiscountedFees, discountedMgiSendFee, mgiSendTax, nonMgiSendTax, totalMgiCollectedFeesAndTaxes, totalAmountToMgi, totalSendFeesAndTaxes, totalNonMGISendFeesAndTaxes</i>	Additional Information <i>mgNonDiscountedSendFee is the fee amount charged by MoneyGram before discounts are applied</i> <i>nonMgiSendFee is the total of non-MoneyGram fees charged to the sender by government agents, banking channels, etc.; MoneyGram does not collect this fee</i> <i>totalNonDiscountedFees is the sum of mgNonDiscountedFee and nonMGISendFee</i> <i>discountedMgiSendFee is the fee collected by MoneyGram after discounts</i> <i>mgiSendTax is taxes collected by MoneyGram</i> <i>nonMgiSendTax is taxes the agent collects and remits</i> <i>totalMgiCollectedFeesAndTaxes is the total taxes and fees charged by MoneyGram</i> <i>totalAmountToMgi is nonMGISendFee and nonMGISendTax subtracted from totalAmountToCollect; this is the amount MoneyGram collects from the sending agent at settlement</i> <i>totalSendFeesAndTaxes is the total of all fees and taxes for the transaction</i> <i>totalNonMGISendFeesAndTaxes is the total of all non- MoneyGram fees and taxes charged to the sender by government agents, banking channels, etc.</i>	

<i>amount</i>	<i>Decimal</i> <i>Minimum exclusive value: 0 Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>None</i>	<i>optional</i>
<i>amountCurrency</i>	<i>String</i> <i>Length: 3</i>	<i>None</i>	<i>optional</i>

<i>receiveAmounts</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>None</i>	<i>N/A</i>
<i>receiveAmount</i>	<i>decimal</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>If totalReceiveFees or totalReceiveTaxes is not zero, this receive amount must be displayed</i>	<i>conditional</i>
<i>receiveCurrency</i>	<i>string</i> <i>Length: 3</i>	<i>None</i>	<i>required</i>
<i>validCurrencyIndicator</i>	<i>boolean</i>	<i>Additional Information</i> <i>1. If true, validReceiveAmount, validReceiveCurrency, and validExchangeRate are used to calculate the final payout amount</i> <i>2. If false, estimated amounts may be available to calculate the final payout amount</i>	<i>not allowed</i>

<i>payoutCurrency</i>	<i>string</i> <i>Length:</i> <i>3</i>	<i>This must be displayed on the application screen as the payout currency regardless of the validCurrencyIndicator.</i>	<i>required</i>
<i>totalReceiveFees</i>	<i>decimal</i> <i>Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3</i>	<i>Must be displayed if value returned is not zero.</i> <i>Total fees charged to the receiver by MoneyGram, agents, government entity, etc.</i>	<i>required</i>
<i>totalReceiveTaxes</i>	<i>decimal</i> <i>Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3</i>	<i>Must be displayed if value returned is not zero.</i> <i>Total taxes charged to the receiver by MoneyGram, agents, government entity, etc.</i>	<i>required</i>

<i>totalReceiveAmount</i>	<i>decimal</i> <i>Minimum exclusive value: 0</i> <i>Maximum length: 14</i> <i>Maximum decimal digits: 3</i>	<i>Must always be displayed on the application screen. Receive amount minus any receive fees/taxes.</i>	<i>required</i>
<i>receiveFeesAreEstimated</i>	<i>boolean</i>	<i>Indicates whether the receive-side taxes are "estimates"</i> <i>The word "estimated" must appear before "other fees" only when true.</i>	

<i>receiveTaxesAreEstimated</i>	<i>boolean</i>	<i>Indicates whether the receive-side taxes are "estimates"</i> <i>The word "estimated" must appear before "other taxes" only when true.</i>	
<i>detailEstimatedReceiveAmounts</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>None</i>	<i>N/A</i>
<i>amountType</i>	<i>string</i> <i>Valid values:</i> <i>mgIReceiveFee,</i> <i>nonMGIReceiveFee,</i> <i>mgIReceiveTax,</i> <i>nonMgIReceiveTax</i>	<i>The type of fee or tax</i> <i>Additional Information</i> <i>1. mgIReceiveFee is the fee amount charged by MoneyGram</i> <i>2. nonMGIReceiveFee is the total of non-MoneyGram fees charged to the receiver by government agents, banking channels, etc.; MoneyGram does not collect this fee</i> <i>3. mgIReceiveTax is taxes collected by MoneyGram</i> <i>4. nonMgIReceiveTax is taxes the agent collects and remits</i>	<i>optional</i>
<i>amount</i>	<i>decimal</i>	<i>None</i>	<i>optional</i>
<i>amountCurrency</i>	<i>string</i> <i>Length: 3</i>	<i>None</i>	<i>optional</i>

2.0.6 Fee Lookup Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <channelInfo>
      <rrn>123456789012</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>ZzbRrd8Ycwg8xClrOdddkZcZzbRrd8Ycwg8xClrOdddkZc</signature>
    </channelInfo>
    <feeLookupRequest
      xmlns="http://www.moneygram.com/AgentConnect1512">
      <productType>SEND</productType>
      <operatorName>TEST</operatorName>
      <receiveAmount>100.00</receiveAmount>
      <receiveCountry>GHA</receiveCountry>
      <deliveryOption>TEST</deliveryOption>
      <mgRewardsNumber>TEST</mgRewardsNumber>
      <receiveAgentID>TEST1234</receiveAgentID>
      <receiveCurrency>USD</receiveCurrency>
      <sendCurrency>USD</sendCurrency>
      <mgCustomerReceiveNumber>TEST</mgCustomerReceiveNumber>
      <allOptions>true</allOptions>
      <promoCodeValues>
        <promoCode>1234</promoCode>
      </promoCodeValues>
    </feeLookupRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

2.0.6 Fee Lookup Sample Success Response

```

<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soapenv:Body>
    <ac:feeLookupResponse
      xmlns:ac="http://www.moneygram.com/AgentConnect1512">
      <ac:doCheckIn>false</ac:doCheckIn>
      <ac:timeStamp>2024-08-29T04:49:36.642-05:00</ac:timeStamp>
      <ac:flags>1</ac:flags>
      <ac:feeInfo>
        <ac:validReceiveAmount>100.02</ac:validReceiveAmount>
        <ac:validReceiveCurrency>GHS</ac:validReceiveCurrency>
        <ac:validExchangeRate>7.073715</ac:validExchangeRate>
        <ac:estimatedReceiveAmount>0</ac:estimatedReceiveAmount>
        <ac:estimatedExchangeRate>0.000000</ac:estimatedExchangeRate>
        <ac:totalAmount>19.95</ac:totalAmount>
        <ac:receiveCountry>GHA</ac:receiveCountry>
        <ac:deliveryOption>WILL_CALL</ac:deliveryOption>
        <ac:receiveAmountAltered>true</ac:receiveAmountAltered>
        <ac:revisedInformationalFee>false</ac:revisedInformationalFee>
        <ac:deliveryOptId>0</ac:deliveryOptId>
        <ac:deliveryOptDisplayName>10 Minute Service</ac:deliveryOptDisplayName>

      <ac:mgiTransactionSessionID>16773711E172492497686521858318NN</ac:mgiTransacti
onSessionID>
      <ac:sendAmountAltered>false</ac:sendAmountAltered>
      <ac:sendAmounts>
        <ac:sendAmount>14.14</ac:sendAmount>
        <ac:sendCurrency>USD</ac:sendCurrency>
        <ac:totalSendFees>5.00</ac:totalSendFees>
        <ac:totalDiscountAmount>0.00</ac:totalDiscountAmount>
        <ac:totalSendTaxes>0.81</ac:totalSendTaxes>
        <ac:totalAmountToCollect>19.95</ac:totalAmountToCollect>
        <ac:detailSendAmounts>
          <ac:amountType>mgiNonDiscountedSendFee</ac:amountType>
          <ac:amount>5.00</ac:amount>
          <ac:amountCurrency>USD</ac:amountCurrency>
        </ac:detailSendAmounts>
        <ac:detailSendAmounts>
          <ac:amountType>discountedMgiSendFee</ac:amountType>
          <ac:amount>5.00</ac:amount>

```

```

    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>totalMgiCollectedFeesAndTaxes</ac:amountType>
    <ac:amount>5.00</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>totalNonDiscountedFees</ac:amountType>
    <ac:amount>5.00</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>totalAmountToMgi</ac:amountType>
    <ac:amount>19.14</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>totalSendFeesAndTaxes</ac:amountType>
    <ac:amount>5.81</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>originalMgiSendFeeInclTax</ac:amountType>
    <ac:amount>5.00</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>mgiCountrySendFeeTax</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>mgiStateSendFeeTax</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>mgiCountyCitySendFeeTax</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
  <ac:detailSendAmounts>
    <ac:amountType>mgiTotalSendFeeTax</ac:amountType>
    <ac:amount>0.00</ac:amount>

```

```

    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalNonMgiSendFeesAndTaxes</ac:amountType>
  <ac:amount>0.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiSendFaceTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiSendTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>nonMgiSendTax</ac:amountType>
  <ac:amount>0.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>nonMgiSendFee</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
</ac:sendAmounts>
<ac:receiveAmounts>
  <ac:receiveAmount>100.02</ac:receiveAmount>
  <ac:receiveCurrency>GHS</ac:receiveCurrency>
  <ac:validCurrencyIndicator>true</ac:validCurrencyIndicator>
  <ac:payoutCurrency>GHS</ac:payoutCurrency>
  <ac:totalReceiveFees>0.00</ac:totalReceiveFees>
  <ac:totalReceiveTaxes>0.00</ac:totalReceiveTaxes>
  <ac:totalReceiveAmount>100.02</ac:totalReceiveAmount>
  <ac:receiveFeesAreEstimated>false</ac:receiveFeesAreEstimated>
  <ac:receiveTaxesAreEstimated>false</ac:receiveTaxesAreEstimated>
  <ac:detailEstimatedReceiveAmounts>
    <ac:amountType>mgiReceiveFee</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>GHS</ac:amountCurrency>
  </ac:detailEstimatedReceiveAmounts>
  <ac:detailEstimatedReceiveAmounts>
    <ac:amountType>nonMgiReceiveFee</ac:amountType>

```

```

    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>GHS</ac:amountCurrency>
  </ac:detailEstimatedReceiveAmounts>
<ac:detailEstimatedReceiveAmounts>
  <ac:amountType>mgiReceiveTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>GHS</ac:amountCurrency>
</ac:detailEstimatedReceiveAmounts>
<ac:detailEstimatedReceiveAmounts>
  <ac:amountType>nonMgiReceiveTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>GHS</ac:amountCurrency>
</ac:detailEstimatedReceiveAmounts>
</ac:receiveAmounts>
</ac:feeInfo>
<ac:feeInfo>
  <ac:validReceiveAmount>100.02</ac:validReceiveAmount>
  <ac:validReceiveCurrency>GHS</ac:validReceiveCurrency>
  <ac:validExchangeRate>7.073715</ac:validExchangeRate>
  <ac:estimatedReceiveAmount>0</ac:estimatedReceiveAmount>
  <ac:estimatedExchangeRate>0.000000</ac:estimatedExchangeRate>
  <ac:totalAmount>19.95</ac:totalAmount>
  <ac:receiveCountry>GHA</ac:receiveCountry>
  <ac:deliveryOption>DIRECT_TO_ACCT</ac:deliveryOption>
  <ac:receiveAmountAltered>true</ac:receiveAmountAltered>
  <ac:revisedInformationalFee>false</ac:revisedInformationalFee>
  <ac:deliveryOptId>19</ac:deliveryOptId>
  <ac:deliveryOptDisplayName>Send to Wallet</ac:deliveryOptDisplayName>
  <ac:receiveAgentID>71615181</ac:receiveAgentID>
  <ac:receiveAgentName>ZEEPAY</ac:receiveAgentName>
  <ac:receiveAgentAbbreviation>MG2Mobile</ac:receiveAgentAbbreviation>
  <ac:mgManaged>required</ac:mgManaged>

<ac:mgiTransactionSessionID>16773711E172492497686880386174NN</ac:mgiTransactionSessionID>
  <ac:sendAmountAltered>false</ac:sendAmountAltered>
  <ac:sendAmounts>
    <ac:sendAmount>14.14</ac:sendAmount>
    <ac:sendCurrency>USD</ac:sendCurrency>
    <ac:totalSendFees>5.00</ac:totalSendFees>
    <ac:totalDiscountAmount>0.00</ac:totalDiscountAmount>
    <ac:totalSendTaxes>0.81</ac:totalSendTaxes>
    <ac:totalAmountToCollect>19.95</ac:totalAmountToCollect>
  <ac:detailSendAmounts>
    <ac:amountType>mgiNonDiscountedSendFee</ac:amountType>

```

```
<ac:amount>5.00</ac:amount>
<ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>discountedMgiSendFee</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalMgiCollectedFeesAndTaxes</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalNonDiscountedFees</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalAmountToMgi</ac:amountType>
  <ac:amount>19.14</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalSendFeesAndTaxes</ac:amountType>
  <ac:amount>5.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>originalMgiSendFeeInclTax</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiCountrySendFeeTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiStateSendFeeTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiCountyCitySendFeeTax</ac:amountType>
```

```

    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>USD</ac:amountCurrency>
  </ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiTotalSendFeeTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalNonMgiSendFeesAndTaxes</ac:amountType>
  <ac:amount>0.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiSendFaceTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiSendTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>nonMgiSendTax</ac:amountType>
  <ac:amount>0.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>nonMgiSendFee</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
</ac:sendAmounts>
<ac:receiveAmounts>
  <ac:receiveAmount>100.02</ac:receiveAmount>
  <ac:receiveCurrency>GHS</ac:receiveCurrency>
  <ac:validCurrencyIndicator>true</ac:validCurrencyIndicator>
  <ac:payoutCurrency>GHS</ac:payoutCurrency>
  <ac:totalReceiveFees>0.00</ac:totalReceiveFees>
  <ac:totalReceiveTaxes>0.00</ac:totalReceiveTaxes>
  <ac:totalReceiveAmount>100.02</ac:totalReceiveAmount>
  <ac:receiveFeesAreEstimated>false</ac:receiveFeesAreEstimated>
  <ac:receiveTaxesAreEstimated>false</ac:receiveTaxesAreEstimated>
  <ac:detailEstimatedReceiveAmounts>

```



```

    <ac:amountType>mgiReceiveFee</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>GHS</ac:amountCurrency>
  </ac:detailEstimatedReceiveAmounts>
  <ac:detailEstimatedReceiveAmounts>
    <ac:amountType>nonMgiReceiveFee</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>GHS</ac:amountCurrency>
  </ac:detailEstimatedReceiveAmounts>
  <ac:detailEstimatedReceiveAmounts>
    <ac:amountType>mgiReceiveTax</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>GHS</ac:amountCurrency>
  </ac:detailEstimatedReceiveAmounts>
  <ac:detailEstimatedReceiveAmounts>
    <ac:amountType>nonMgiReceiveTax</ac:amountType>
    <ac:amount>0.00</ac:amount>
    <ac:amountCurrency>GHS</ac:amountCurrency>
  </ac:detailEstimatedReceiveAmounts>
</ac:receiveAmounts>
</ac:feeInfo>
<ac:feeInfo>
  <ac:validReceiveAmount>100.02</ac:validReceiveAmount>
  <ac:validReceiveCurrency>GHS</ac:validReceiveCurrency>
  <ac:validExchangeRate>7.073715</ac:validExchangeRate>
  <ac:estimatedReceiveAmount>0</ac:estimatedReceiveAmount>
  <ac:estimatedExchangeRate>0.000000</ac:estimatedExchangeRate>
  <ac:totalAmount>19.95</ac:totalAmount>
  <ac:receiveCountry>GHA</ac:receiveCountry>
  <ac:deliveryOption>BANK_DEPOSIT</ac:deliveryOption>
  <ac:receiveAmountAltered>true</ac:receiveAmountAltered>
  <ac:revisedInformationalFee>false</ac:revisedInformationalFee>
  <ac:deliveryOptId>10</ac:deliveryOptId>
  <ac:deliveryOptDisplayName>Account Deposit</ac:deliveryOptDisplayName>
  <ac:receiveAgentID>70811805</ac:receiveAgentID>
  <ac:receiveAgentName>ADB</ac:receiveAgentName>
  <ac:receiveAgentAbbreviation>ALL BANKS</ac:receiveAgentAbbreviation>
  <ac:mgManaged>required</ac:mgManaged>

<ac:mgiTransactionSessionID>16773711E172492497686822785518NN</ac:mgiTransactionSessionID>
  <ac:sendAmountAltered>false</ac:sendAmountAltered>
  <ac:sendAmounts>
    <ac:sendAmount>14.14</ac:sendAmount>
    <ac:sendCurrency>USD</ac:sendCurrency>

```

```
<ac:totalSendFees>5.00</ac:totalSendFees>
<ac:totalDiscountAmount>0.00</ac:totalDiscountAmount>
<ac:totalSendTaxes>0.81</ac:totalSendTaxes>
<ac:totalAmountToCollect>19.95</ac:totalAmountToCollect>
<ac:detailSendAmounts>
  <ac:amountType>mgiNonDiscountedSendFee</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>discountedMgiSendFee</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalMgiCollectedFeesAndTaxes</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalNonDiscountedFees</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalAmountToMgi</ac:amountType>
  <ac:amount>19.14</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalSendFeesAndTaxes</ac:amountType>
  <ac:amount>5.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>originalMgiSendFeeInclTax</ac:amountType>
  <ac:amount>5.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiCountrySendFeeTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
```

```
<ac:amountType>mgiStateSendFeeTax</ac:amountType>
<ac:amount>0.00</ac:amount>
<ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiCountyCitySendFeeTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiTotalSendFeeTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>totalNonMgiSendFeesAndTaxes</ac:amountType>
  <ac:amount>0.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiSendFaceTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>mgiSendTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>nonMgiSendTax</ac:amountType>
  <ac:amount>0.81</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
<ac:detailSendAmounts>
  <ac:amountType>nonMgiSendFee</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>USD</ac:amountCurrency>
</ac:detailSendAmounts>
</ac:sendAmounts>
<ac:receiveAmounts>
  <ac:receiveAmount>100.02</ac:receiveAmount>
  <ac:receiveCurrency>GHS</ac:receiveCurrency>
  <ac:validCurrencyIndicator>true</ac:validCurrencyIndicator>
  <ac:payoutCurrency>GHS</ac:payoutCurrency>
```

```
<ac:totalReceiveFees>0.00</ac:totalReceiveFees>
<ac:totalReceiveTaxes>0.00</ac:totalReceiveTaxes>
<ac:totalReceiveAmount>100.02</ac:totalReceiveAmount>
<ac:receiveFeesAreEstimated>>false</ac:receiveFeesAreEstimated>
<ac:receiveTaxesAreEstimated>>false</ac:receiveTaxesAreEstimated>
<ac:detailEstimatedReceiveAmounts>
  <ac:amountType>mgiReceiveFee</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>GHS</ac:amountCurrency>
</ac:detailEstimatedReceiveAmounts>
<ac:detailEstimatedReceiveAmounts>
  <ac:amountType>nonMgiReceiveFee</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>GHS</ac:amountCurrency>
</ac:detailEstimatedReceiveAmounts>
<ac:detailEstimatedReceiveAmounts>
  <ac:amountType>mgiReceiveTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>GHS</ac:amountCurrency>
</ac:detailEstimatedReceiveAmounts>
<ac:detailEstimatedReceiveAmounts>
  <ac:amountType>nonMgiReceiveTax</ac:amountType>
  <ac:amount>0.00</ac:amount>
  <ac:amountCurrency>GHS</ac:amountCurrency>
</ac:detailEstimatedReceiveAmounts>
</ac:receiveAmounts>
</ac:feeInfo>
</ac:feeLookupResponse>
</soapenv:Body>
</soapenv:Envelope>
```

2.0.4 Fee Look Up Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

2.0.7 Fee Lookup Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

2.0.8 Fee Lookup Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>
```

3.0 Get Fields For Product Service

3.0.1 Get Fields For Product Description

The agent application uses the [getFieldsForProduct\(GFFP\)](#) API to determine field requirements for the [sendValidationRequest](#). The information returned in the response is also used to build screen content.

Business Rules to Code

1. This is a required backend API before doing a [sendValidation](#). The response will let the application know what data fields are needed for each transaction and what fields must always be displayed on the screen during the transaction or during pre-registration.
2. For the fields with `productFieldInfo` coming back as `dynamic=true`, an Agent's application must be able to provide any additional data using fields as `keyValuePair`. For example, an Account Deposit to India may require IFSC code for the receiver's bank account
3. **The data attributes returned in GFFP can change from transaction to transaction:** visibility, fieldLabel, displayOrder, fieldMax, fieldMin, defaultValue, exampleFormat, enumeratedValues, and regular expression. The agent's application must respond to these changes in the GFFP response. The number of required fields may change depending on the country where agent is located

Examples of scenarios where GFFP attributes values will change.

- a. **Visibility** - The following values are returned in the visibility field to indicate whether a field must be included in the [sendValidationRequest](#). The value indicates if data is required to complete the transaction. The value also indicates whether the agent must allow an input mechanism to populate the field.

REQ: If the value is 'REQ', then data must be provided; omission of data will result in errors. The fields required for a transaction will vary depending on business and compliance rules applied to the specific transaction. A few examples of when the visibility can change depends on agent's country, amount, destination country, delivery options, etc.

OPT: If the value is 'OPT' then the field must be available on the application screen for data entry, but data is not needed to complete the transaction. Data may be included in the request for business reasons. If the agent is collecting the data, data must be sent in the transaction; omission of data will not result in technical errors. For example, middle name and second last name fields are required to be displayed on the screen in case the consumer has a middle or second last name. If the customer does not have these, then this data is not required to complete the transaction.

NOT_ALL: Data must not be included in the request, MoneyGram does not require the field to be displayed for the specified transaction. If the agent is collecting the data, data must not be sent on the transaction; including data will be ignored or result in errors.

SUP_OPT: Data is optional on the request, and the field may optionally appear on the application screen; MoneyGram does not require data to complete the transaction.

However, if the agent is collecting the data, data must be sent in on the transaction. Some examples of SUP_OPT fields are: ID expiration, nationality, citizenship, etc.

- b. **fieldMax, fieldMin** – the application must be coded to the fieldMax and fieldMin that are returned in GFFP. These values can change from one transaction to another. The maximum/minimum lengths in schema/WSDL should be used for database design and screen layout, and the agent must follow GFFP minimum and maximum lengths during a transaction submission. These lengths will always be within the boundary of the schema/WSDL. Some maximum lengths are shorter in GFFP than the schema/WSDL because MoneyGram has plans to eventually expand these fields per the lengths defined in the WSDL.
- c. **fieldLabel** - For the accountNumber field, the application must use the fieldLabel returned in GFFP. This label can change depending on which partner the transaction is being sent.

For example, some transactions can have the label as Account Number (18 digits), Account Number (11 digits), Mobile Number or Customer's Email Address.

For the remaining field labels, agent may use the suggested fieldLabels returned by GFFP on the application screen. The fieldLabels are also translated into some additional languages including Spanish, German, French, Chinese, Italian etc. Translated labels are returned when language field in the GFFP message header is specified for a particular language as described in the Introduction to AgentConnect module.

- d. **enumeratedValue** – returns list of values for enumerated fields. This list of values depends on the agent's country and can change at any time. Application must be able to use the updated list without requiring any code changes. Examples of some the fields that are enumerated are: ID type, occupation, purpose of transaction, relationship to receiver, etc.
- e. **dynamic** – application must code to all fields where dynamic = 'true', which is returned where deliveryOption = BANK_DEPOSIT, CARD_DEPOSIT or HOME_DELIVERY. The list of fields returned as true can vary depending on the destination country. When dynamic=true, the field should be sent in the keyValuePair of the sendValidationRequest.

Example:

```
<fieldValues>
  <keyValuePair>
    <xmlTag>RECEIVERPURPOSEOFFUNDS</xmlTag>
    <fieldValue>P130101</fieldValue>
  </keyValuePair>
</fieldValues>
</sendValidationRequest>
```

3.0.2 Get Fields For Product Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/getFieldsForProduct
Headers	content-type: application/xml
Authentication	signature

3.0.3 Get Fields For Product Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required
receiveCountry	string Length: 3 Must be a valid country code	Additional Information 1. Use value of <code>receiveCountry</code> returned by feeLookupResponse for selected delivery option	application	required

deliveryOption	string Must be a valid delivery option	Additional Information 1. Use value of <code>deliveryOption</code> returned by <code>feeLookupResponse</code> for selected delivery option	application	required
----------------	---	---	-------------	----------

thirdPartyType	string Valid values: NONE, ORG, PERSON	If the transaction is being sent on behalf of someone other than the sender, whether it is being sent for a person or an organization. Additional Information 1. If the <code>amount</code> is above the agent's third party profile limit and the agent application allows third-party transactions, the agent must ask whether the transaction is on behalf of a third party Field Rules 1. If the agent application allows third-party transactions, a field to select the type of third-party transaction must be provided on the GUI when the <code>send amount</code> is above the third party limit. This third party limit is returned in the <code>profileResponse</code> API documented in the Introduction to AgentConnect module. 2. For US agents only – If agent does not allow third party transactions, agent application must still ask customer if this is a third party	conditional	required
-----------------------	--	--	--------------------	-----------------

		transaction if the send amount is above the profile third party limit. If transaction is a third party and agent does not allow third party, do not allow the transaction to be completed 3. If the agent application does not allow third-party transactions, the agent must communicate this to an account representative		
receiveAgentID	string Length: 8	Additional Information - Use value of <code>receiveAgentID</code> returned by feeLookupResponse for selected delivery option Field Rules - Data is required if <code>receiveAgentID</code> is returned in the <code>feeInformation</code> section of the feeLookupResponse for the selected delivery option	application	conditional
customerReceiveNumber	string Maximum length: 20	Additional Information If <code>moneyGramConsumerLookup</code> API was used to find transaction history, use the <code>customerReceiveNumber</code> returned in	GUI/application	conditional

		moneyGramConsumerLookup Response. 2. This data can also be populated from the customer's profile in the agent's database.		
billerAccountNumber	string Maximum length: 30	The receiver's card number for payout via card. Additional Information 1. Field does not apply to this product	not allowed	not allowed
cardSwiped	boolean	Additional Information 1. Field does not apply to this product	not allowed	not allowed
otherPayoutType	string	The type of payment instrument used to payout the transaction, other than cash or money order. Additional Information 1. Field does not apply to this product	not allowed	not allowed
receiveCurrency	string Maximum length: 3 Must be a valid currency code	Additional Information 1. Use value of <code>validReceiveCurrency</code> returned by <code>feeLookupResponse</code> for selected delivery option	application	required
amount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Additional Information 1. Use value of <code>sendAmount</code> from <code>feeLookupResponse</code>	application	required

sendCurrency	string Maximum length: 3 Must be a valid currency code	Additional Information 1. Use value returned in <code>feeLookupResponse</code> for the selected delivery option	Application	required
--------------	---	---	-------------	----------

productType	string Valid values: SEND	Must be SEND.	Application	required
productVariant	string	Additional Information 1. Field does not apply for this product	not allowed	not allowed
serviceOfferingID	string Maximum length: 21	Additional Information 1. Field does not apply for this product	not allowed	not allowed
consumerId	string Maximum length: 20	Additional Information 1. Use value returned by the moneyGramConsumerLookupResponse 2. If the moneyGramConsumerLookup API was not used, or no value was returned, value must be 0	not allowed	required
formFreeStaging	boolean	Whether or not the transaction is a FormFree transaction. Additional Information 1. If <code>true</code> , the transaction is staged and prepared for FormFree completion which will be committed at a later time 2. If <code>false</code> , the transaction is not a FormFree type	not allowed	required

3.0.4 Get Fields For Product Success Response Field Description

Tag	Datatype	Information and Rules	Display
fqdoInfo	complex Maximum number of occurrences: unbounded	None	N/A
receiveCountry	string Maximum length: 3 Must be a valid currency code	None	N/A
deliveryOption	string Must be a valid delivery option	None	N/A
receiveAgentID	string length: 8	None	not allowed
receiveCurrency	string Maximum length: 3 Must be a valid currency code	None	N/A
receiveAgentName	string Maximum length: 40	None	N/A
receiveAgentAbbreviation	string Maximum length: 10	None	N/A
deliveryOptionDisplayNam e	string Maximum length: 50	None	N/A

registrationAuthorizationText	string Maximum length: 40	Field is not currently in use. The field <code>registrationAuthorizationText</code> may contain information about additional data required to complete DS registration by a Directed Sends Partner before activating a registration number.	N/A
speedOfDeliveryText	string Maximum length: 40	None	N/A
productFieldInfo	complex Maximum number of occurrences: unbounded	None	N/A
xmlTag	string Maximum length: 80	This is the key identifying a particular field and must be mapped to <code>sendValidationRequest</code>	N/A
visibility	string Valid values: <code>OPT</code> , <code>NOT_ALL</code> , <code>REQ</code> , <code>SUP_OPT</code>	See Business Rules to Code section above regarding this API <i>Additional Information</i> <code>OPT</code> - data is optional; but if collected data must be sent to MoneyGram <code>NOT_ALL</code> - data is not allowed <code>REQ</code> - data is required <code>SUP_OPT</code> - data is not required; but if collected data must be sent to MoneyGram	N/A

fieldLabel	string Maximum length: 80	The field's suggested label. Translation is returned based on the language indicated in the request header.	N/A
displayOrder	integer	The order in which the field appears on screen relative to other fields in the same category	N/A
fieldCategory	string	Identifier used to group the fields in a category	N/A

fieldCategoryLabel	String	The category's suggested label	N/A
dynamic	boolean	<i>Additional Information</i> 1. If <code>true</code>, the field is dynamic and not included in the XML schema for the sendValidationRequest, and its name and value must be provided as a <code>keyValuePair</code> 2. If <code>false</code>, the field is not dynamic	N/A
fieldMax	long	Use the value provided for each field. In some cases such as consumer name and address, the maximum length may be less than the length indicated in the WSDL.	N/A
fieldMin	long	None	N/A

dataType	string Valid values: boolean, cntrycode, date, datetime, decimal, enum, int, string, stringbool, text, time	None	N/A
enumerated	boolean	<i>Additional Information</i> 1. If value is <code>true</code> , the field is restricted to a list of values 2. If value is <code>false</code> , the field is not restricted to a list of values	N/A
defaultValue	string Maximum length: 255	None	N/A
validationRegEx	string Maximum length: 255	A regular expression used to validate the field's value.	N/A
arrayName	string Maximum length: 255	The xml tag of the array.	N/A

arrayLength	int	The length of the array arrayName <i>Additional Information</i> 1. -1 means the field is not an array and must only contain a value 2. A value of 0 or larger indicates the number of values in the array	N/A
-------------	-----	---	-----

exampleFormat	string Maximum length: 255	None	N/A
enumeratedValues	complex Maximum number of occurrences: 1	Contains information on the field's list of possible values. <i>Additional Information</i> 1. The information in this list must be used if <code>enumerated</code> is <code>true</code>	N/A
enumeratedValueInfo	complex Maximum number of occurrences: unbounded	Contents define an individual enumerated value.	N/A
value	string Maximum length: 255	None	N/A
label	string Maximum length: 255	None	N/A
dynamicFieldInfo	complex Maximum number of occurrences: unbounded	For future use	N/A
xmlTag	string Maximum length: 80	None	N/A
visibility	string	None	N/A

fieldMax	long	None	N/A
fieldMin	long	None	N/A
scale	integer	The number of places allowed after the decimal point. <i>Additional Information</i>	N/A

		1. Only applies if <code>dataType</code> is decimal	
<code>dataType</code>	string Valid values: <code>boolean</code> , <code>cntrycode</code> , <code>date</code> , <code>datetime</code> , <code>decimal</code> , <code>enum</code> , <code>int</code> , <code>string</code> , <code>stringbool</code> , <code>text</code> , <code>time</code>	None	N/A
<code>fieldLabel</code>	string Maximum length: 80	The field's suggested label	N/A
<code>displayOrder</code>	integer	The order in which the field must appear on screen relative to other fields.	N/A
<code>enumerated</code>	boolean	<i>Additional Information</i> 1. If value is <code>true</code>, the field is restricted to a list of values 2. If value is <code>false</code>, the field is not restricted to a list of values	N/A
<code>defaultValue</code>	string Maximum length: 255	None	N/A
<code>validationRegex</code>	string Maximum length: 255	A regular expression used to validate the field's value.	N/A
<code>exampleFormat</code>	string Maximum length: 255	None	N/A

enumeratedValues	complex Maximum number of occurrences: 1	Contains information on the field's list of possible values. <i>Additional Information</i> 1. The information in this list must be used if <code>enumerated</code> is <code>true</code>	N/A
enumeratedValueInfo	complex Maximum number of occurrences: unbounded	Contents define an individual enumerated value.	N/A
value	string Maximum length: 255	None	N/A
label	string Maximum length: 255	None	N/A

3.0.5 Get Fields For Product Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <channelInfo>
      <rrn>1234rrn</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <getFieldsForProductRequest
      xmlns="http://www.moneygram.com/AgentConnect1512">
      <receiveCountry>KEN</receiveCountry>
      <deliveryOption>TEST</deliveryOption>
      <thirdPartyType>ORG</thirdPartyType>
      <receiveAgentID>TEST1234</receiveAgentID>
      <customerReceiveNumber>TEST</customerReceiveNumber>
      <receiveCurrency>USD</receiveCurrency>
      <amount>100</amount>
      <sendCurrency>USD</sendCurrency>
      <productType>SEND</productType>
      <consumerId>1234</consumerId>
      <formFreeStaging>true</formFreeStaging>
      <mgiTransactionSessionID>TEST</mgiTransactionSessionID>
    </getFieldsForProductRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

3.0.6 Get Fields For Product Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

3.0.7 Get Fields For Product Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status ii. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

3.0.8 Get Fields For Product Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact
servicing via chat or email.</responseDesc>
</statusDetails>
```

4.0 Send Validation Request Service

4.0.1 Send Validation Request Description

The agent application uses the `sendValidation` API to send a MoneyGram money transfer transaction.

Business Rules to Code

1. The agent application must use the field lengths returned in the `getFieldsForProductResponse`. The maximum length for the consumer name and address fields may be shorter than the length defined in the AgentConnect WSDL since the AgentConnect WSDL reflects the target lengths of our future further expansion of the consumer name and address fields. While the agent application must use the field lengths returned in the `getFieldsForProductResponse`, it must also be developed to accommodate the future field lengths as indicated in the AgentConnect WSDL.
2. When the `readyForCommit` field in the `sendValidationResponse` is `true`, the agent application may continue the transaction. If there is an error or a problem with the transaction, an error message will be returned. Please refer to the Error Message document for list of errors.
3. For FormFree transactions, the agent application must send the `sendValidationRequest` until the response returns a `readyForCommit` value of `true`.
4. After the `sendValidationResponse` is received, if there are any changes needed for customer data, agent application should allow the customer data to be updated and resend the `sendValidationRequest` using the same `mgTransactionSessionID`.
5. MoneyGram will recycle the reference numbers after the transactions have been closed/received for 6 months. If you are storing reference numbers in your database, you should also store the transaction date. The combination of the reference number and transaction date will be the unique key for a transaction.

4.0.2 Send Validation Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/sendValidation
Headers	content-type: application/xml
Authentication	signature

4.0.3 Send Validation Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystem Id	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

agentStagingChannel	string Maximum length: 128	The AgentStagingChannel field is required when Agents <i>do not</i> use MoneyGram's FormFree staging and completion process and still want to do a two part transaction. The first part is the transaction <i>staging/initiation</i> portion and the second part is the <i>completion</i> portion. This is used for agent applications where the send transaction is completed in 2 parts: 1) transaction staging/initiation and 2) transaction completion. 1) During transaction staging/initiation, the customer provides all transaction information at a kiosk, mobile application or online. All transaction information collected is saved in the agent's database. 2) During transaction completion, the customer goes to the agent location and provides phone number or other information to retrieve the transaction information from the agent's system. All data is verified by the agent including photo ID. This field identifies the type of channel for the POS application where part 1 of the transaction was staged/initiated. Valid channel type codes are listed below:	application	optional
		Channel Type Code		
		ATM		

		KIOSK		
--	--	-------	--	--

		LOCATION	Transaction is done at a physical location (Brick & Mortar)			
		MOBILE	Transaction is done using either a MoneyGram owned or agent owned web interface via a mobile device			
		SYSTEM	Transaction is done using backend processes or rules.			
		WEB	Transaction is done using either a MoneyGram owned or agent owned web interface. Does not include transactions through a			

			mobile device.			
		TABLET	Transaction staged using Tablet device either a MoneyGram owned or agent owned web interface. Does not include transactions through a Kiosk or Mobile device.			
		OTHER	Other staging initiation and completion Channel			
operatorName	string Maximum length: 80	<i>Additional Information</i> Operator name or operator ID of the associate or user performing the transaction; it must be auto- populated from the agent's system and cannot be editable by the user Agent Facing – Teller ID/User ID mapped to operatorName			application	required

		- Customer Facing/Self Service (kiosk, online, mobile) – User ID/User Login mapped to operatorName - ATM – unique customer ID (customer number) mapped to operatorName		
--	--	---	--	--

amount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Value must be the same as that used in the getFieldsForProductRequest	application	required
feeAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	<i>Additional Information</i> 1. Recommended flow: should not use this value. Funds should be collected after sendValidation is sent based on the fee returned in the sendValidationResponse 2. Value must be the same as the totalSendFees returned in the feeLookupResponse for the selected delivery option 3. If the feeAmount is provided from the feeLookup response and if the fee has changed from the time of fee quote was done, an error will be returned.	Application	GFFP
mgReward sNumber	string Maximum length: 20	The sender's MoneyGram Plus Rewards number. <i>Additional Information</i> 1. Value must be the same as the mgRewardsNumber used in the feeLookupRequest or freqCustCardNumber from moneyGramConsumerLookupRequest/Response 2. This value must be provided in order for the customer to receive rewards benefits such as accrual and discounts	application	optional
agentCust omerNumbe r	string	<i>Field Rules</i>	not allowed	optional

	Maximum length: 25	1. This is agent's number used to uniquely identify a customer. Value is stored unencrypted and must not contain PCI data. 2. If this is used on the transaction, customer transaction history can be retrieved using the moneyGramConsumerLookup API		
destinationCountry	string Length : 3 Must be a valid country code	. Value must be the same as <code>receiveCountry</code> that was used in the getFieldsForProductRequest	application	required
destinationState	string Length : 2 Must be a valid state code	<i>Field Rules</i> 1. Data and GUI input are required if transaction originates from USA or Jamaica and <code>destinationCountry</code> is <code>CAN</code> or <code>USA</code> 2. Data and GUI input are not allowed if <code>destinationCountry</code> is not <code>CAN</code> or <code>USA</code>	GUI	GFFP
deliveryOption	string Length: 50 Must be a valid delivery option	<i>Additional Information</i> 1. Value must be the same as that used in the getFieldsForProductRequest	application	required
receiveCurrency	string Length : 3 Must be a valid currency code	Value must be the same as that used in the getFieldsForProductRequest	application	required
receiveAgentID	string Length : 8	Value must be the same as that used in the getFieldsForProductRequest	application	GFFP

accountNumber	string Maximum length: 255	The account identifier where funds should be deposited into for directed send/account deposit transactions	GUI	GFFP
customerReceiveNumber	string Maximum length: 40	1. If available, must use the same value from getFieldsForProductRequest 2. This field must not be displayed on the application screen.	Application	GFFP
senderFirstName	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	required
senderMiddleName	string Length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
senderLastName	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	required
senderLastName2	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
senderAddress	string Maximum length: 80	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	required
senderAddress2	string Maximum length: 80	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
senderAddress3	string Maximum length: 80	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
senderCity	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	required
senderState	string Length : 2 Must be a valid state code	See Business Rules to Code section above regarding this API	GUI/application	GFFP

senderZipCode	string Minimum length: 3 Maximum length: 14	Application should not code to a specific country postal code format. Postal code should remain a free form text field adhering to the maximum length. Postal code format is validated based on the country of the senderCountry	GUI/application	GFFP
senderCountry	string Length : 3 Must be a valid country code	None	GUI/application	required
senderHomePhone	string Maximum length: 14	This is the primary phone number. This can contain the home phone or the mobile phone. The field label should be Sender Phone. Numeric only, do not include plus(+) or dash(-) signs or parenthesis. If data is provided in this field, senderHomePhoneCountryCode field must also be collected and sent.	GUI/application	required
senderMailingAddress	string maximum length: 80	Mailing address for the sender. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
senderMailingAddress2	string maximum length: 80	Mailing address for the sender. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP

senderMailingAddress3	string maximum length: 80	Mailing address for the sender. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
senderMailingCity	string maximum length: 40	Mailing city for the sender. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
senderMailingState	string maximum length: 2	Mailing state for the sender. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
senderMailingZipCode	string maximum length: 10	Mailing zip code for the sender. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
senderMailingCountry	string length : 3	Mailing country for the sender. Currently only applies to agents in Puerto Rico See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverFirstName	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI/application	required
receiverMiddleName	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI/application	GFFP
receiverLastName	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI/application	required

receiverLastName2	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
receiverAddress	string Maximum length: 80	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
receiverAddress2	string Maximum length: 80	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
receiverAddress3	string Maximum length: 80	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
direction1	string Maximum length: 40	None	GUI/application	GFFP
direction2	string Maximum length: 40	None	GUI/application	GFFP
direction3	string Maximum length: 40	None	GUI/application	GFFP
receiverCity	string Maximum length: 40	See <i>Data Quality Edits Addendum</i> for data quality rules	GUI/application	GFFP
receiverState	string Length : 2 Must be a valid state code	See Business Rules to Code section above regarding this API	GUI/application	GFFP
receiverZipCode	string Minimum length: 3 Maximum length: 14	Application should not code to a specific country postal code format. Postal code should remain a free form text field adhering to the maximum length.	GUI/application	GFFP

		Postal code format is validated based on the country of the receiverCountry		
--	--	---	--	--

receiverCountry	string Length : 3 Must be a valid country code	None	GUI/application	
receiverPhone	string Maximum length: 14	1. Numeric only, do not include plus(+) or dash(-) signs or parenthesis. 2. If data is provided in this field, receiverPhoneCountryCode field must also be collected and sent.	GUI/application	GFFP
receiverPhoneCountryCode	string Length : 3	1. Country dial in code (ISD). Numeric only, do not include plus(+) or dash(-) signs or parenthesis. 2. If data is provided in this field, receiverPhone field must also be collected and sent.	GUI/application	GFFP
receiverEmail	string Maximum length: 128		GUI/application	GFFP
testQuestion	string Maximum length: 30	<i>Field Rules</i> 1. Data is required if a value is provided for testAnswer	GUI	GFFP
testAnswer	string Maximum length: 30	<i>Field Rules</i> 1. Data is required if a value is provided for testQuestion	GUI	GFFP
messageField1	string Maximum length: 40	Any message or note the sender wants the receiver to receive	GUI	GFFP
messageField2	string Maximum length: 40	Any message or note the sender wants the receiver to receive	GUI	GFFP

senderPhotoIdType	string	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI	required
senderPhotoIdNumber	string Minimum length: 4 Maximum length: 25	<i>Field Rules</i> 1. Only alphanumeric and hyphen (-) characters allowed	GUI	required
senderPhotoIdState	string Length : 2 Must be a valid state code	See Business Rules to Code section above regarding this API	GUI	GFFP
senderPhotoIdCountry	string Length : 3 Must be a valid country code	None	GUI	required
senderLegalIdType	string	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI	GFFP
senderLegalIdNumber	string Minimum length: 4 Maximum length: 20	<i>Field Rules</i> 1. Only alphanumeric and hyphen (-) characters allowed	GUI	GFFP
senderDOB	date	<i>Field Rules</i>	GUI	required

	Format: CCYY-MM-DD	1. Cannot be later than the current date 2. Some countries have minimum age requirements which will be validated based on the country where the transaction is sent from		
senderOccupation	string Maximum length: 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI	GFFP
thirdPartyFirstName	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI	GFFP
thirdPartyMiddleName	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI	GFFP
thirdPartyLastName	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI	GFFP
thirdPartyLastName2	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI	GFFP
thirdPartyAddress	string Maximum length: 80	See Data Quality Edits Addendum for data quality rules	GUI	GFFP
thirdPartyAddress2	string Maximum length: 80	See Data Quality Edits Addendum for data quality rules	GUI	GFFP
thirdPartyAddress3	string Maximum length: 80	See Data Quality Edits Addendum for data quality rules	GUI	GFFP
thirdPartyCity	string Maximum length: 40	See Data Quality Edits Addendum for data quality rules	GUI	GFFP

thirdPartyState	string Length : 2 Must be a valid state code	See Business Rules to Code section above regarding this API	GUI	GFFP
thirdPartyZipCode	string Minimum length: 3 Maximum length: 14	Application should not code to a specific country postal code format. Postal code should remain a free form text field adhering to the maximum length. Postal code format is validated based on the country of the thirdPartyCountry	GUI	GFFP
thirdPartyCountry	string Length : 3 Must be a valid country code	None	GUI	GFFP
thirdPartyLegalIdType	string	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI	GFFP
thirdPartyLegalIdNumber	string Minimum length: 4 Maximum length: 20	<i>Field Rules</i> 1. Only alphanumeric and hyphen (-) characters allowed	GUI	GFFP

thirdPartyDOB	date Format: CCYY-MM-DD	<i>Field Rules</i> 1. Cannot be later than the current date 2. Some countries have minimum age requirements which will be validated based on the country where the transaction is sent from	GUI	GFFP
thirdPartyOrg	string	The name of the third party organization	GUI	GFFP

	Maximum length: 60			
senderBirthCity	string Maximum length: 40	City where customer was born. If city is collected, senderBirthCountry must be collected	GUI	GFFP
senderBirthCountry	string Length : 3 Must be a valid country code	Country where customer was born	GUI	GFFP
senderLegalIdIssueCountry	string Length : 3 Must be a valid country code	None	GUI	GFFP

senderEmailAddress	string Maximum length: 128	If moneygramConsumerLookup was used and sender was selected from there, this field must be populated from the lookup using the <code>senderEmailAddress</code> field. The field must be displayed on the application and be editable to allow the user to update the email Validation pattern: Must contain one and only one commercial at symbol (@) Validation pattern: Otherwise restricted to alphanumeric, dot (.), dash (-), and underscore (_) characters	GUI	GFFP
senderMobilePhone	string Maximum length: 14	If moneygramConsumerLookup was used and sender was selected from there, this field must be populated from the lookup using the <code>senderMobilePhone</code> field. The field must be displayed on the application and be editable to allow the user to update the mobile phone Numeric only, do not include plus(+) or dash(-) signs or parenthesis.	GUI	GFFP

		2. If data is provided in this field, <code>senderMobilePhoneCountryCode</code> field must also be collected and sent.		
senderMobilePhoneCountryCode	string Length: 3	1. Country dial in code (ISD). Numeric only, do not include plus(+) or dash(-) signs or parenthesis. 2. If data is provided in this field, <code>senderMobilePhone</code> field must also be collected and sent.	GUI	GFFP

marketingOptIn	boolean	<i>Additional Information</i> 1. If <code>true</code>, the customer agrees to allow MoneyGram to send marketing materials 2. If <code>false</code>, the customer does not agree to allow MoneyGram to send marketing materials	GUI	GFFP
pcTerminalNumber	string Maximum length: 10	The agent-assigned ID number of the point-of-sale.	Not allowed	optional
agentUseSendData	string Maximum length: 200	Additional data chosen by the agent for the agent's use. Stored with the transaction by MoneyGram. <i>Additional Information</i> 1. Data is available immediately using the detailLookup API	GUI/application	optional
sendCurrency	string Length : 3 Must be a valid currency code	Value must be the same as that used in the getFieldsForProductRequest	application	GFFP
consumerId	string Maximum length: 20	Value must be the same as that used in the getFieldsForProductRequest	not allowed	GFFP
senderPhotoIdStored	boolean	<i>Additional Information</i> 1. If <code>true</code>, the agent has photocopied and stored the sender's photo ID information 2. If <code>false</code>, the agent has not photocopied and stored the sender's photo ID information	GUI/application	GFFP

senderNationalityCountry	string Length: 3 Must be a valid country code	If applicable, refer to local country regulations	GUI	GFFP
senderNationalityAtBirthCountry	string Length: 3 Must be a valid country code	If applicable, refer to local country regulations	GUI	GFFP
agentTransactionId	string Maximum length: 20	An ID number that uniquely identifies the send transaction across APIs. <i>Additional Information</i> 1. The agent's externally generated transaction ID	not allowed	GFFP
mgTransactionSessionID	string Maximum length: 38	An ID number that uniquely identifies the send transaction across APIs. <i>Additional Information</i> 1. Value must be that returned in the feeLookupResponse for the feeInfo selected	not allowed	required
formFreeStaging	boolean	Value must be the same as that used in the getFieldsForProductRequest Whether or not the transaction is a FormFree transaction. <i>Additional Information</i> 1. If <code>true</code> , the transaction is being set up as FormFree and will be completed at a later time. The exchange	not allowed	required

		rate, receive amount, taxes (if applicable) and fees provided in this API response are no longer guaranteed and may change when the transaction is completed at a later time. 2. If <code>false</code>, the transaction is not FormFree and will be completed as a full service transaction within this session		
<code>timeToLive</code>	integer Maximum length: 5	For future use only	NA	not allowed
<code>primaryReceiptLanguage</code>	string Length: 3	Primary language to be used on prepayment disclosures and receipts. <i>Field Rules</i> Value must be <code>ENG</code> for USA and territories	application	optional
<code>secondaryReceiptLanguage</code>	string Length: 3 Valid values: <code>eng</code>, <code>spa</code>, <code>deu</code>, <code>fra</code>, <code>zho</code>	Secondary language to be used on prepayment disclosures and receipts. <i>Field Rules</i> - Data is required for US-based agents - Data is optional for non-US agents	GUI	conditional

sendPurposeOfTransaction	string Length : 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent’s country This field is intended to understand the reason the consumer is using MoneyGram product/service specific to an individual transaction. Please refer to Business Rule #9 for additional field visibility requirements	GUI	GFFP
--------------------------	--------------------------	--	-----	------

sendPurposeOfTransactionOther	string Length : 40	For future use	GUI	GFFP
sourceOfFunds	string Length : 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent’s country Please refer to Business Rule #9 for additional field visibility requirements	GUI	GFFP
sourceOfFundsOther	string Length : 30	For future use	GUI	GFFP

paymentTenderedType	string Length : 20	For future use Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI	GFFP
relationshipToReceiver	string Length : 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country Please refer to Business Rule #9 for additional field visibility requirements	GUI	GFFP
relationshipToReceiverOther	string Length : 30	For future use	GUI	GFFP
proofOfFunds	string Length : 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be	GUI	GFFP

		selected. The list returned can be different based on the agent's country Please refer to Business Rule #9 for additional field visibility requirements		
proofOfFundsOther	string Length : 30	<u>For future use</u>	GUI	GFFP

senderGender	string Length : 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI/application	GFFP
senderOccupationOther	string Length : 30	<u>For future use</u>	GUI	GFFP
senderBirthState	string Length : 20	For future use	GUI/application	GFFP
senderNameSuffix	string Length : 30	<u>Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected.</u> The list returned can be different based on the agent's country	GUI/application	GFFP
senderNameSuffixOther	string Length : 30	For future use	GUI/application	GFFP
senderCitizenshipCountry	string Length: 3 Must be a valid country code	Current citizenship. Legal status of the country where the customer is registered Please refer to Business Rule #9 for additional field visibility requirements	GUI/application	GFFP

senderCitizenshipAtBirthCountry	string Length: 3 Must be a valid country code	Citizenship at the time the customer was born	GUI/application	GFFP
---------------------------------	---	---	-----------------	------

senderDualCitizenshipCountry	string Length: 3 Must be a valid country code	For future use	GUI/application	GFFP
senderPhotoIdIssueMonth	string Length: 2 Format: MM	If information is available, issue month must be collected, then issue year must also be collected	GUI	GFFP
senderPhotoIdIssueYear	string Length: 4 Format: CCYY	If information is available, issue year must be collected	GUI	GFFP
senderPhotoIdIssueDay	string Length: 2 Format: DD	If information is available, issue day must be collected in addition to issue month and issue year	GUI	GFFP
senderPhotoIdExpirationMonth	string Length: 2 Format: MM	If information is available, expiration month must be collected, then expiration year must also be collected	GUI	GFFP
senderPhotoIdExpirationYear	string Length: 4 Format: CCYY	If information is available, expiration year must be collected	GUI	GFFP

senderPhotoIdExpirationDay	string Length: : 2 Format: DD	If information is available, expiration day must be collected in addition to expiration month and expiration year	GUI	GFFP
senderPhotoIdIssueAuthority	string Length: 30	For future use	GUI	GFFP
senderLegalIdIssueMonth	string Length: 2 Format: MM	If information is available, issue month must be collected, then issue year must also be collected	GUI	GFFP
senderLegalIdIssueYear	string Length: 4 Format: CCYY	If information is available, issue year must be collected	GUI	GFFP
senderLegalIdIssueDay	string Length: 2 Format: DD	If information is available, issue day must be collected in addition to issue month and issue year	GUI	GFFP
senderLegalIdExpirationMonth	string Length: 2 Format: MM	If information is available, expiration month must be collected, then expiration year must also be collected	GUI	GFFP
senderLegalIdExpirationYear	string Length: 4 Format: CCYY	If information is available, expiration year must be collected	GUI	GFFP
senderLegalIdExpirationDay	string Length: 2	If information is available, expiration day must be collected in addition to expiration month and expiration year	GUI	GFFP

	Format: DD			
senderLegalIdIssueAuthority	string Length: 30	For future use	GUI	GFFP
senderLegalIdState	string Length: 2	For future use	GUI	GFFP
senderTransactionEmailNotificationOptIn	boolean	1a. If moneygramConsumerLookup was used and sender was selected from there, this field must be populated from the lookup using the <code>senderTransactionEmailNotificationOptIn</code> field. This field must be displayed on the application and be editable to allow the user to change their preference. 1b. If moneygramConsumerLookup was not used, default value must always be <i>blank/null</i>. The customer must agree to opt-in for notification when this is changed to <i>true</i>. 2. If true, senderEmailAddress is required	Application/ GUI	GFFP
senderTransactionSMSNotificationOptIn	boolean	1a. If moneygramConsumerLookup was used and sender was selected from there, this field must be populated from the lookup using the <code>senderTransactionSMSNotificationOptIn</code> field. The field must be displayed on the application and be editable to allow the user to change their preference. 1b. If moneyGramConsumerLookup was not used, default value must always be <i>blank/null</i>. The customer must agree to opt-in for notification when this is changed to <i>true</i>. 2. If true, senderHomePhone and senderHomePhoneCountryCode are required	Application/ GUI	GFFP
senderMarketingEmailNotificationOptIn	boolean	1a. If moneygramConsumerLookup was used and sender was selected from there, this field must be populated from the lookup using the	application/ GUI	GFFP

		senderMarketingEmailNotificationOptIn field. The field must be displayed on the application and be editable to allow the user to change their preference. 1b. If moneygramConsumerLookup was not used, default value must always be <i>blank/null</i>. The customer must agree to opt-in for notification when this is changed to <i>true</i>. 2. If true, senderEmailAddress is required		
senderMarketingSMSNotificationOptIn	boolean	1a. If moneygramConsumerLookup was used and sender was selected from there, this field must be populated from the lookup using the senderMarketingSMSNotificationOptIn field. The field must be displayed on the application and be editable to allow the user to change their preference. 1b. If moneyGramConsumerLookup was not used, default value must always be <i>blank/null</i>. The customer must agree to opt-in for notification when this is changed to <i>true</i>. 2. If true, senderHomePhone and senderHomePhoneCountryCode are required	application/ GUI	GFFP
receiverTransactionEmailNotificationOptIn	boolean	1. Default value must always be <i>false</i>. The sender must agree to opt-in for notification for the receiver when this is changed to <i>true</i>. 2. If true, receiverEmail is required	GUI	GFFP
receiverTransactionSMSNotificationOptIn	boolean	1. Default value must always be <i>false</i>. The sender must agree to opt-in for notification for the receiver when this is changed to <i>true</i>. 2. If true, receiverPhone and receiverPhoneCountryCode are required.	GUI	GFFP
senderHomePhoneNotAvailable	boolean	For future use	GUI	GFFP

senderHomePhoneCountryCode	string Length: 3	1. Country dial in code (ISD). Numeric only, do not include plus(+) or dash(-) signs or parenthesis. 2. If data is provided in this field, senderHomePhone field must also be collected and sent.	GUI	required
receiverNameSuffix	string Maximum length: 20	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI/application	GFFP
receiverNameSuffixOther	string Maximum length: 20	For future use	GUI/application	GFFP
senderFirstNameNotAvailable	boolean	For future use	GUI	GFFP
receiverFirstNameNotAvailable	boolean	For future use	GUI/application	GFFP
thirdPartyFirstNameNotAvailable	boolean	For future use	GUI/application	GFFP
thirdPartySenderBirthCity	string Length: 40		GUI	GFFP
thirdPartySenderBirthState	string Length: 2	For future use	GUI	GFFP

thirdPartySenderBirthCountry	string Length: 3 Must be a valid country code		GUI	GFFP
thirdPartySenderGender	string		GUI	GFFP

	Length: 30			
thirdPartySenderOccupation	string Length: 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI	GFFP
thirdPartySenderOccupationOther	string Length: 30	For future use	GUI	GFFP
thirdPartySenderNameSuffix	string Length: 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country	GUI	GFFP
thirdPartySenderNameSuffixOther	string Length: 30	For future use	GUI	GFFP
thirdPartySenderCitizenshipCountry	string Length: 3 Must be a valid country code	Current citizenship. Legal status of the country where the customer is registered	GUI	GFFP

thirdPartySenderCitizenshipAtBirthCountry	string Length: 3 Must be a valid country code	Citizenship at the time the customer was born	GUI	GFFP
thirdPartySenderDualCitizenshipCountry	string Length: 3 Must be a valid country code	For future use	GUI	GFFP

thirdPartyLegalIdIssueMonth	string Length: 2 Format: MM	If information is available, issue month must be collected, then issue year must also be collected	GUI	GFFP
thirdPartyLegalIdIssueYear	string Length: 4 Format: CCYY	If information is available, issue year must be collected	GUI	GFFP
thirdPartyLegalIdIssueDay	string Length: 2 Format: DD	If information is available, issue day must be collected in addition to issue month and issue year	GUI	GFFP
thirdPartyLegalIdExpirationMonth	string Length: 2 Format: MM	If information is available, expiration month must be collected, then expiration year must also be collected	GUI	GFFP
thirdPartyLegalIdExpirationYear	string Length: 4 Format: CCYY	If information is available, expiration year must be collected	GUI	GFFP

thirdPartyLegalIdExpirationDay	string Length: 2 Format: DD	If information is available, expiration day must be collected in addition to expiration month and expiration year	GUI	GFFP
thirdPartyLegalIdIssueAuthority	string Length: 30	For future use	GUI	GFFP
thirdPartyLegalIdState	string Length: 2	For future use	GUI	GFFP

thirdPartyLegalIdIssueCountry	string Length: 3 Must be a valid country code		GUI	GFFP
senderIntendedUseOfMGIServices	string length: 30	Enumerated value – agent application must use the valid enumerations returned from getFieldsForProduct (GFFP) response and allow only valid values to be selected. The list returned can be different based on the agent's country Field can be labeled as: How do you plan to use MoneyGram? The purpose of this question is to identify, in general why the consumer plans to use MoneyGram products/services. Please refer to Business Rule #9 for additional field visibility requirements	GUI	GFFP
receiptImages	complex	For future use	NA	NA
promoCodeValues	complex	None	GUI	optional

promoCode	string Maximum number of occurrences: unbounded Maximum length: 20	The promotional code to apply to the transaction. <i>Additional Information</i> 1. Value is provided by consumer	application	optional
fieldValues	complex Maximum number of occurrences: unbounded	Contains information for fields required in the request which aren't included in the static API definition.	application	conditional
xmlTag	string Maximum length: 80	The field's XML tag from <code>getFieldsForProductResponse</code> iwhere <i>dynamic</i> is <i>true</i> and <i>visibility</i> is <i>required</i>	conditional	conditional
value	string	The field's value; data for the corresponding <code>xmlTag</code>	conditional	conditional

4.0.4 Send Validation Success Response Field Description

Tag	Datatype	Information and Rules	Display
mgTransactionSessionID	string Maximum length: 38	An ID number that uniquely identifies the send transaction across APIs. <i>Additional Information</i> 1. Value must be used in the commitTransactionRequest API	not allowed
customerReceiverNumber	string Maximum length: 20	The receiver's registration number for transactions that require receiver registration. <i>Additional Information</i> 1. Must <i>not</i> appear on consumer's receipt or application screen	not allowed
displayAccountID	string Maximum length: 255	Partial or entire account identifier which was used for the transaction which can be printed on receipts and displayed on screens. Partial account identifier is retuned for data privacy and security standards	optional
customerServiceMessage	string Maximum length: 255	<i>Additional Information</i> 1. Must appear on consumer's receipt for transactions that require receiver registration	optional
accountNickname	string Maximum length: 30	None	optional
promotionInfo	complex Maximum number of occurrences: unbounded	None	N/A

promotion Code	string Maximum length: 20	The code used to identify the promotion.	required
promotion DiscountI d	string Length: 2 Valid values: 01, 02, 03	The code used to identify the type of discount. <i>Additional Information</i> 4. 01 is flat fee. Flat Fee is a promotion that provides the services with a specified fee. 5. 02 is amount off. Amount Off is a promotion that provides services with a specified amount off the fee. 6. 03 is percent off. Percent Off is a promotion that provides services with a percent off the fee.	required
promotion CategoryI d	string Length: 2	Internal Use Only	required
promotion Discount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The promotion's discount value.	required
promotion DiscountA mount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	The discount amount applied to nonDiscountedFeeExclTax.	required
promotion ErrorCode	string Length: 4	The error code returned if the promotion code was invalid.	required

promotion ErrorMessage		The error message to display if the promotion code was invalid.	required
longLanguage Code	string Length: 3	The language of the promotional message.	required

textTranslation	string Maximum length: 2000	The translated promotional message.	required
promotionalMessage	complex Maximum number of occurrences: unbounded	None	N/A
longLanguageCode	string Length: 3	The language of the promotional message.	required
textTranslation	string Maximum length: 2000	The translated promotional message.	required
readyForCommit	boolean	<i>Additional Information</i> 1. If <code>true</code> , the agent application may continue the transaction.	not allowed
disclosureText	complex Maximum number of occurrences: unbounded		N/A
longLanguageCode	string Length: 3	The language of the disclosure message.	required
textTranslation	string Maximum length: 2000	Data must be printed on the pre-payment disclosure receipt. Additional disclosure info when taxes/fees can't be determined based on included fields. When populated, required on prepayment disclosure and post-payment receipt.	required

receiveAgent Name	string Maximum length: 40	The name of the intended receive agent.	optional
----------------------	------------------------------	---	----------

receiveAgent Address	complex Maximum number of occurrences: unbounded	None	N/A
agentAddr essLine	string Maximum length: 80	A line of the receive agent's address.	optional
additionalFi eldsToCollec t	complex Maximum number of occurrences: unbounded	For future use	N/A
sendAmounts	complex Maximum number of occurrences: unbounded	None	N/A
sendAmount	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	required
sendCurren cy	string Length: 3 Must be a valid currency code	None	required
totalSend Fees	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Sum of <code>discountedMGIFee</code> and <code>nonMGISendFee</code> . Total of all fees charged to sender by MoneyGram, agents, etc.	required

totalDi scountA mount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Discount amount applied to <code>nonDiscountedFeeExclTax</code> .	required
-----------------------------	--	--	----------

totalSendTaxes	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Total taxes charged to the sender by MoneyGram, government agents, etc.	required
totalAmountToCollect	decimal Minimum exclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Total of all fees, taxes, and the send amount.	required
detailsSendAmounts	complex Maximum number of occurrences: unbounded	None	N/A

amountType	string Valid values: <code>mgNonDiscountedSendFee</code>, <code>nonMgiSendFee</code>, <code>totalNonDiscountedFees</code>, <code>discountedMgiSendFee</code>, <code>mgSendTax</code>, <code>nonMgiSendTax</code>, <code>totalMgiCollectedFeesAndTaxes</code>, <code>totalAmountToMgi</code>, <code>totalSendFeesAndTaxes</code>, <code>totalNonMGISendFeesAndTaxes</code>	The type of fee or tax <i>Additional Information</i> <code>mgNonDiscountedSendFee</code> is the fee amount charged by MoneyGram before discounts are applied <code>nonMgiSendFee</code> is the total of non-MoneyGram fees charged to the sender by government agents, banking channels, etc.; MoneyGram does not collect this fee <code>totalNonDiscountedFees</code> is the sum of <code>mgNonDiscountedFee</code> and <code>nonMGISendFee</code> <code>discountedMgiSendFee</code> is the fee collected by MoneyGram after discounts <code>mgSendTax</code> is taxes collected by MoneyGram <code>nonMgiSendTax</code> is taxes the agent collects and remits <code>totalMgiCollectedFeesAndTaxes</code> is the total taxes and fees charged by MoneyGram <code>totalAmountToMgi</code> is <code>nonMGISendFee</code> and <code>nonMGISendTax</code> subtracted from <code>totalAmountToCollect</code>; this is the amount MoneyGram collects from the sending agent at settlement <code>totalSendFeesAndTaxes</code> is the total of all fees and taxes for the transaction <code>totalNonMGISendFeesAndTaxes</code> is the total of all non- MoneyGram fees and taxes charged to the sender by government agents, banking channels, etc.	optional
------------	---	--	----------

amount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	optional
amountCurrency	string Length: 3 Must be a valid currency code	None	optional
receiveAmounts	complex Maximum number of occurrences: unbounded	None	N/A
receiveAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	required
receiveCurrency	string Length: 3 Must be a valid currency code	Use payoutCurrency	not allowed
validCurrencyIndicator	boolean	<i>Additional Information</i> - If <code>true</code>, <code>validReceiveAmount</code>, <code>validReceiveCurrency</code>, and <code>validExchangeRate</code> are used to calculate the final payout amount - If <code>false</code>, estimated amounts may be available to calculate the final payout amount	optional

payoutCurrency	string Length: 3 Must be a valid currency code	The receiveAmount, totalReceiveFees, totalReceiveTaxes, totalReceiveAmount, and the all 4 of the amount fields in detailReceiveAmounts should be returned in the payoutCurrency for indicative situations (instead of USD). This must be displayed on the application screen as the payout currency regardless of the validCurrencyIndicator	required
totalReceiveFees	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Total fees charged to the receiver by MoneyGram, agents, government entity, etc.	required
totalReceiveTaxes	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Total taxes charged to the receiver by MoneyGram, agents, government entity, etc.	required
totalReceiveAmount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Receive amount minus any receive fees/taxes.	required
receiveFeesAreEstimated	boolean	If true, indicates whether the receive-side taxes are "estimates" The word "estimated" must appear before "other fees" only when true.	Conditional

<code>receiveTaxesAreEstimated</code>	boolean	If true, indicates whether the receive-side taxes are "estimates" The word "estimated" must appear before "other taxes" only when true.	conditional
<code>detailReceiveAmounts</code>	complex Maximum number of occurrences: unbounded	None	N/A
<code>amountType</code>	string Valid values: <code>mgReceiveFee</code> , <code>nonMGIReceiveFee</code> , <code>mgReceiveTax</code> , <code>nonMgiReceiveTax</code>	The type of fee or tax <i>Additional Information</i> 1. <code>mgReceiveFee</code> is the fee amount charged by MoneyGram 2. <code>nonMGIReceiveFee</code> is the total of non-MoneyGram fees charged to the receiver by government agents, banking channels, etc.; MoneyGram does not collect this fee 3. <code>mgReceiveTax</code> is taxes collected by MoneyGram 4. <code>nonMgiReceiveTax</code> is taxes the agent collects and remits	optional
<code>amount</code>	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	None	optional
<code>amountCurrency</code>	string Length: 3 Must be a valid currency code	None	optional

exchangeRateApplied	decimal Minimum inclusive value: 0 Maximum length: 14	The exchange rate applied between <code>sendCurrency</code> and <code>receiveCurrency</code> . <i>Field Rules</i> 1. Value returned to four decimal places for USA and US territories 2. Value returned to six decimal places elsewhere	required
receiveFeeDisclosureText	boolean	<i>Additional Information</i> 1. If <code>true</code> , the <code>disclosureText</code> field contains disclosure text for the receive transaction fee 2. If <code>false</code> , the <code>disclosureText</code> field does not contain disclosure text for the receive transaction fee	not allowed

receiveTaxDisclosureText	boolean	<i>Additional Information</i> 1. If <code>true</code> , the <code>disclosureText</code> field contains disclosure text for the receive transaction taxes 2. If <code>false</code> , the <code>disclosureText</code> field does not contain disclosure text for the receive transaction taxes	not allowed
confirmationNumber	string Length: 7	<i>Additional Information</i> 1. Only used for FormFree transactions (if <code>formFreeStaging</code> = <code>true</code>). This is returned when a transaction is successfully staged/set up for completion	optional
receipts		For future use	

4.0.5 Send Validation Request Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <channelInfo>
      <rrn>100001001010</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <sendValidationRequest
      xmlns="http://www.moneygram.com/AgentConnect1512">
      <agentStagingChannel>Channel1</agentStagingChannel>
      <operatorName>OperatorName</operatorName>
      <amount>1000.00</amount>
      <feeAmount>10.00</feeAmount>
      <mg RewardsNumber>Rewards123</mg RewardsNumber>
      <agentCustomerNumber>Cust001</agentCustomerNumber>
      <destinationCountry>USA</destinationCountry>
      <destinationState>CA</destinationState>
      <deliveryOption>Standard</deliveryOption>
      <receiveCurrency>USD</receiveCurrency>
      <receiveAgentID>Agent002</receiveAgentID>
      <accountNumber>ACC12345</accountNumber>
      <customerReceiveNumber>Recv123</customerReceiveNumber>
      <senderFirstName>John</senderFirstName>
      <senderMiddleName>Doe</senderMiddleName>
      <senderLastName>Smith</senderLastName>
      <senderLastName2>Jones</senderLastName2>
      <senderAddress>123 Main St</senderAddress>
      <senderAddress2>Apt 4B</senderAddress2>
      <senderAddress3>Building 5</senderAddress3>
      <senderCity>Los Angeles</senderCity>
      <senderState>CA</senderState>
      <senderZipCode>90001</senderZipCode>
      <senderCountry>USA</senderCountry>
      <senderHomePhone>+11234567890</senderHomePhone>
      <senderMailingAddress>123 Main St</senderMailingAddress>
      <senderMailingAddress2>Apt 4B</senderMailingAddress2>
      <senderMailingAddress3>Building 5</senderMailingAddress3>
      <senderMailingCity>Los Angeles</senderMailingCity>
```

```
<senderMailingState>CA</senderMailingState>
<senderMailingZipCode>90001</senderMailingZipCode>
<senderMailingCountry>USA</senderMailingCountry>
<receiverFirstName>Jane</receiverFirstName>
<receiverMiddleName>A</receiverMiddleName>
<receiverLastName>Doe</receiverLastName>
<receiverLastName2>Smith</receiverLastName2>
<receiverAddress>456 Oak St</receiverAddress>
<receiverAddress2>Apt 2A</receiverAddress2>
<receiverAddress3>Building 3</receiverAddress3>
<direction1>Near Park</direction1>
<direction2>Behind Mall</direction2>
<direction3>Next to School</direction3>
<receiverCity>New York</receiverCity>
<receiverState>NY</receiverState>
<receiverZipCode>10001</receiverZipCode>
<receiverCountry>US</receiverCountry>
<receiverPhone>+11239876543</receiverPhone>
<receiverPhoneCountryCode>1</receiverPhoneCountryCode>
<receiverEmail>jane.doe@example.com</receiverEmail>
<testQuestion>What is your favorite color?</testQuestion>
<testAnswer>Blue</testAnswer>
<messageField1>Happy Birthday!</messageField1>
<messageField2>Best Wishes</messageField2>
<senderPhotoIdType>Passport</senderPhotoIdType>
<senderPhotoIdNumber>P123456789</senderPhotoIdNumber>
<senderPhotoIdCity>Los Angeles</senderPhotoIdCity>
<senderPhotoIdState>CA</senderPhotoIdState>
<senderPhotoIdCountry>USA</senderPhotoIdCountry>
<senderLegalIdType>Driver's License</senderLegalIdType>
<senderLegalIdNumber>D1234567</senderLegalIdNumber>
<senderDOB>1990-01-01</senderDOB>
<senderOccupation>Engineer</senderOccupation>
<thirdPartyFirstName>Michael</thirdPartyFirstName>
<thirdPartyMiddleName>B</thirdPartyMiddleName>
<thirdPartyLastName>Johnson</thirdPartyLastName>
<thirdPartyLastName2>Brown</thirdPartyLastName2>
<thirdPartyAddress>789 Pine St</thirdPartyAddress>
<thirdPartyAddress2>Apt 3C</thirdPartyAddress2>
<thirdPartyAddress3>Building 2</thirdPartyAddress3>
<thirdPartyCity>San Francisco</thirdPartyCity>
<thirdPartyState>CA</thirdPartyState>
<thirdPartyZipCode>94103</thirdPartyZipCode>
<thirdPartyCountry>USA</thirdPartyCountry>
<thirdPartyLegalIdType>State ID</thirdPartyLegalIdType>
```

```

<thirdPartyLegalIdNumber>ID12345678</thirdPartyLegalIdNumber>
<thirdPartyDOB>1985-06-15</thirdPartyDOB>
<thirdPartyOrg>ABC Corp</thirdPartyOrg>
<senderBirthCity>Chicago</senderBirthCity>
<senderBirthCountry>USA</senderBirthCountry>
<senderLegalIdIssueCountry>USA</senderLegalIdIssueCountry>
<senderEmailAddress>john.smith@example.com</senderEmailAddress>
<senderMobilePhone>+11236789012</senderMobilePhone>
<senderMobilePhoneCountryCode>1</senderMobilePhoneCountryCode>
<marketingOptIn>true</marketingOptIn>
<pcTerminalNumber>123PC</pcTerminalNumber>
<agentUseSendData>UseData1</agentUseSendData>
<sendCurrency>USD</sendCurrency>
<consumerId>Cons123</consumerId>
<senderPhotoIdStored>>false</senderPhotoIdStored>
<senderNationalityCountry>USA</senderNationalityCountry>
<senderNationalityAtBirthCountry>USA</senderNationalityAtBirthCountry>
<agentTransactionId>12344</agentTransactionId>

<mgiTransactionSessionID>16773711E172492497686521858318NN</mgiTransactionSessionID>
  <formFreeStaging>true</formFreeStaging>
  <primaryReceiptLanguage>ENG</primaryReceiptLanguage>
  <secondaryReceiptLanguage>ENG</secondaryReceiptLanguage>
  <sendPurposeOfTransaction>Purpose</sendPurposeOfTransaction>
  <sourceOfFunds>Self</sourceOfFunds>
  <sourceOfFundsOther>Other Source</sourceOfFundsOther>
  <sendPurposeOfTransactionOther>Other Purpose</sendPurposeOfTransactionOther>
  <paymentTenderedType>Type</paymentTenderedType>
  <relationshipToReceiver>Family</relationshipToReceiver>
  <relationshipToReceiverOther>Family</relationshipToReceiverOther>
  <proofOfFunds>Other</proofOfFunds>
  <proofOfFundsOther>Other</proofOfFundsOther>
  <senderGender>Male</senderGender>
  <senderOccupationOther>Engineer</senderOccupationOther>
  <senderBirthState>State</senderBirthState>
  <senderNameSuffix>Mr</senderNameSuffix>
  <senderNameSuffixOther>Mr</senderNameSuffixOther>
  <senderCitizenshipCountry>KEN</senderCitizenshipCountry>
  <senderCitizenshipAtBirthCountry>KEN</senderCitizenshipAtBirthCountry>
  <senderDualCitizenshipCountry>US</senderDualCitizenshipCountry>
  <senderPhotoIdIssueMonth>01</senderPhotoIdIssueMonth>
  <senderPhotoIdIssueYear>2020</senderPhotoIdIssueYear>
  <senderPhotoIdIssueDay>15</senderPhotoIdIssueDay>
  <senderPhotoIdExpirationMonth>01</senderPhotoIdExpirationMonth>
  <senderPhotoIdExpirationYear>2030</senderPhotoIdExpirationYear>

```

```
<senderPhotoIdExpirationDay>15</senderPhotoIdExpirationDay>
<senderPhotoIdIssueAuthority>Authority1</senderPhotoIdIssueAuthority>
<senderLegalIdIssueMonth>01</senderLegalIdIssueMonth>
<senderLegalIdIssueYear>2018</senderLegalIdIssueYear>
<senderLegalIdIssueDay>20</senderLegalIdIssueDay>
<senderLegalIdExpirationMonth>01</senderLegalIdExpirationMonth>
<senderLegalIdExpirationYear>2028</senderLegalIdExpirationYear>
<senderLegalIdExpirationDay>20</senderLegalIdExpirationDay>
<senderLegalIdIssueAuthority>Authority2</senderLegalIdIssueAuthority>
<senderLegalIdState>CA</senderLegalIdState>

<senderTransactionEmailNotificationOptIn>true</senderTransactionEmailNotificationOptIn>
  <senderTransactionSMSNotificationOptIn>false</senderTransactionSMSNotificationOptIn>
  <senderMarketingEmailNotificationOptIn>true</senderMarketingEmailNotificationOptIn>
  <senderMarketingSMSNotificationOptIn>false</senderMarketingSMSNotificationOptIn>

<receiverTransactionEmailNotificationOptIn>false</receiverTransactionEmailNotificationOptIn>

<receiverTransactionSMSNotificationOptIn>false</receiverTransactionSMSNotificationOptIn>
  <senderHomePhoneNotAvailable>false</senderHomePhoneNotAvailable>
  <senderHomePhoneCountryCode>111</senderHomePhoneCountryCode>
  <receiverNameSuffix>Jr.</receiverNameSuffix>
  <receiverNameSuffixOther>None</receiverNameSuffixOther>
  <senderFirstNameNotAvailable>false</senderFirstNameNotAvailable>
  <receiverFirstNameNotAvailable>false</receiverFirstNameNotAvailable>
  <thirdPartyFirstNameNotAvailable>false</thirdPartyFirstNameNotAvailable>
  <thirdPartySenderBirthCity>Chicago</thirdPartySenderBirthCity>
  <thirdPartySenderBirthState>IL</thirdPartySenderBirthState>
  <thirdPartySenderBirthCountry>USA</thirdPartySenderBirthCountry>
  <thirdPartySenderGender>Male</thirdPartySenderGender>
  <thirdPartySenderOccupation>Manager</thirdPartySenderOccupation>
  <thirdPartySenderOccupationOther>Consultant</thirdPartySenderOccupationOther>
  <thirdPartySenderNameSuffix>III</thirdPartySenderNameSuffix>
  <thirdPartySenderNameSuffixOther>None</thirdPartySenderNameSuffixOther>
  <thirdPartySenderCitizenshipCountry>USA</thirdPartySenderCitizenshipCountry>

<thirdPartySenderCitizenshipAtBirthCountry>USA</thirdPartySenderCitizenshipAtBirthCountry>

<thirdPartySenderDualCitizenshipCountry>None</thirdPartySenderDualCitizenshipCountry>
  <thirdPartyLegalIdIssueMonth>01</thirdPartyLegalIdIssueMonth>
  <thirdPartyLegalIdIssueYear>2015</thirdPartyLegalIdIssueYear>
  <thirdPartyLegalIdIssueDay>05</thirdPartyLegalIdIssueDay>
  <thirdPartyLegalIdExpirationMonth>01</thirdPartyLegalIdExpirationMonth>
  <thirdPartyLegalIdExpirationYear>2025</thirdPartyLegalIdExpirationYear>
  <thirdPartyLegalIdExpirationDay>05</thirdPartyLegalIdExpirationDay>
```

```
<thirdPartyLegalIdIssueAuthority>Authority3</thirdPartyLegalIdIssueAuthority>
<thirdPartyLegalIdState>IL</thirdPartyLegalIdState>
<thirdPartyLegalIdIssueCountry>USA</thirdPartyLegalIdIssueCountry>
<senderIntendedUseOfMGIServices>Personal</senderIntendedUseOfMGIServices>
<senderMotherMaidenName>Jane Doe</senderMotherMaidenName>
<senderFatherFirstName>Robert</senderFatherFirstName>
<receiptImages>
  <receiptImage>
    <identifier>12345</identifier>
    <mimeType>image/jpeg</mimeType>
    <image>cid:1034704357412</image>
  </receiptImage>
</receiptImages>
<promoCodeValues>
  <promoCode>PROMO123</promoCode>
</promoCodeValues>
<fieldValues>
  <keyValuePair>
    <xmlTag>ExampleTag</xmlTag>
    <value>ExampleValue</value>
  </keyValuePair>
</fieldValues>
</sendValidationRequest>
</soapenv:Body>
</soapenv:Envelope>
```

4.0.6 Send Validation Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

4.0.7 Send Validation Request Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. a. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

4.0.8 Send Validation Request Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact
servicing via chat or email.</responseDesc>
</statusDetails>
```

5.0 Commit Transaction Service

5.0.1 Commit Transaction Description

The agent application uses the `commitTransaction` API to commit a send transaction.

Business Rules to Code

1. The `commitTransactionRequest` may only be used when the `readyForCommit` field of the last `sendValidationResponse` was true.
2. The `commitTransactionRequest` must be sent within the time 30 minutes of the `sendValidationRequest`.
3. If the agent's application does not receive a `commitTransactionResponse` within 10-40 seconds, application must send the `commitTransactionRequest` again. This must be retried up to 3 times. If the retry attempt fails, check transaction status using the `detailLookup` API to confirm if transaction was successful.
4. If error code 935 is returned on commit, it must be handled the same way as if the commit response is not received (see rule above).
5. Other errors can be returned on commit stopping the transaction. Application must handle scenarios where the transaction fails (an error code is returned) on commit.
6. Refer to AC1512 Receipts module for detailed information and requirements for receipts.
7. If the transaction is prepared for FormFree (`formFreeStaging=true` in `sendValidationRequest`), `commitTransaction` API is not needed.

5.0.2 Commit Transaction Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/commitTransaction
Headers	content-type: application/xml
Authentication	signature

5.0.3 Commit Transaction Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	Retrieval reference number. Unique Alphanumeric. Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
callbackUrl	String	Channel callback url	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required
senderAccountNumber	String	Sender account number	not allowed	required
destinationAccountNumber	String	Receiver account number	not allowed	required

amount	decimal Minimum inclusive value: 0 Maximum length: 14 Maximum decimal digits: 3	Value must be the same as that used in the getFieldsForProductRequest	not allowed	required
transactionCurrency	String Length: 3 Must be a valid currency code	Transaction currency	not allowed	required
mgTransactionSessionID	string Maximum length: 38	An ID number that uniquely identifies the send transaction across APIs. <i>Additional Information</i> 1. Value must be that returned in the feeLookupResponse	not allowed	required
productType	string Valid values: SEND	None	application	required
fieldValues	complex Maximum number of occurrences: unbounded	For future use	NA	NA
xmlTag	string Maximum length: 80	For future use	NA	NA
fieldValue	String Maximum length: 255	For future use	NA	NA

stateRegulator Version	string Maximum length: 20	Version of the state regulator information used on the transaction receipt. Obtain from doddFrankStateRegulatorInfo API. <i>Field Rules</i> 1. Data is required for US agents for this product. 2. Data is not allowed for non-US agents	applicati on	condition al
---------------------------	-------------------------------------	---	-----------------	-----------------

5.0.4 Commit Transaction Success Response Field Description

Tag	Datatype	Information and Rules	Display
<i>referenceNumber</i>	<i>string</i> <i>Length: 12</i>	<i>Must be printed on receipt</i>	<i>required</i>
<i>partnerConfirmationNumber</i>	<i>string</i> <i>Maximum length: 11</i>	<i>When populated, must be provided on receipt</i>	<i>required</i>
<i>partnerName</i>	<i>string</i>	1. MoneyGram's Directed Sends Partner name when the delivery option is an Account Deposit, Card Deposit or Home Delivery. 2. Data is not returned for a 10 minute service delivery option. 3. Data is required to be displayed after a successfully committed transaction.	<i>required</i>
<i>freePhoneCallPIN</i>	<i>string</i> <i>Maximum length: 14</i>	<i>PIN used to call using the telephone number in tollFreePhoneNumber</i>	<i>optional</i>
<i>tollFreePhoneNumber</i>	<i>string</i> <i>Maximum length: 14</i>	<i>Additional Information</i> 1. Toll-free telephone number used by consumer with <i>freePhoneCallPIN</i> to make free phone call	<i>required</i>
<i>expectedDateOfDelivery</i>	<i>date</i> <i>Format: CCYY-MM-DD</i>	<i>The date a send transaction is expected to be delivered or deposited.</i>	<i>required</i>
<i>transactionDateTime</i>	<i>dateTime</i> <i>Format: CCYY-MM-DDThh:mm:ss.sss-hh:mm</i> <i>The time zone offset is required</i>	<i>Additional Information</i> 1. Value indicates the date and the time at which a particular transaction is successfully completed. 2. Data is always returned	<i>required</i>

<i>receiptText Info</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>None</i>	<i>N/A</i>
<i>longLanguageCode</i>	<i>string</i> <i>Length : 3</i>	<i>The language of the receipt message.</i>	<i>required</i>
<i>textTranslation</i>	<i>string</i> <i>Maximum length: 2000</i>	<i>Additional information must be printed on the receipt.</i>	<i>required</i>
<i>receipts</i>	<i>complex</i> <i>Maximum number of occurrences: unbounded</i>	<i>For future use. Receipt data when receipts are managed by MoneyGram</i>	<i>N/A</i>
<i>reference numberText Code</i>	<i>string</i> <i>maximum length: 20</i>	<i>This is the code used to identify the referenceNumberText and referenceNumberConsumerText. All 3 fields will be populated when a message needs to be displayed to the sender.</i>	<i>optional</i>
<i>reference NumberText</i>	<i>string</i> <i>Maximum length: 240</i>	<i>Data may be returned due to compliance rules that requires the agent to notify the customer to call MoneyGram. This must be displayed on the screen for the agent to advise the customer</i>	<i>required</i>
<i>reference NumberConsumer Text</i>	<i>string</i> <i>Maximum length: 240</i>	<i>Data may be returned due to compliance rules that requires the agent to notify the customer to call MoneyGram. This must be printed on the receipt, and/or displayed on the screen for customer view.</i>	<i>required</i>

5.0.5 Commit Transaction Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <channelInfo>
      <rrn>100001001010</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <senderAccountNumber>100001001010</senderAccountNumber>
      <destinationAccountNumber>1000007363</destinationAccountNumber>
      <amount>100.10</amount>
      <transactionCurrency>USD</transactionCurrency>
      <callbackUrl>http://localhost:8080/callback</callbackUrl>
      <signature>signature</signature>
    </channelInfo>
    <commitTransactionRequest
      xmlns="http://www.moneygram.com/AgentConnect1512">
      <mgTransactionSessionID>16773711E172492497686521858318NN</mgTransactionSessionID>
      <productType>SEND</productType>
      <fieldValues>
        <keyValuePair>
          <xmlTag>xmlTag</xmlTag>
          <fieldValue>fieldValue</fieldValue>
        </keyValuePair>
      </fieldValues>
      <stateRegulatorVersion>1</stateRegulatorVersion>
    </commitTransactionRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

5.0.6 Commit Transaction Response Headers Description

Success Http Status Code	202 - Accepted
---------------------------------	----------------

5.0.7 Commit Transaction Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	status. a. Sample pending status i. PENDING 001 , where 001 is the pending status code b. Sample failure status ii. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

5.0.8 Commit Transaction Sample Pending Response

```

<statusDetails>
  <rrn>100001001010</rrn>
  <status>PENDING|001</status>
  <responseCode>001</responseCode>
  <responseDesc>Transaction received. Processing started. Final status to be
determined.</responseDesc>
</statusDetails>

```

5.0.9 Commit Transaction Sample Failure Response

```

<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>

```

6.0 Detail Lookup Service

6.0.1 Detail Lookup Description

The agent application uses the [detailLookup](#) API to lookup details including status of a particular transaction (using the reference number originally performed by the location).

Additional Information

1. Agent application can look up a transaction by mgiTransactionSessionID. In our case, the channel will call GAG using the original **RRN from commit transaction services**. The session ID can be used to look up the transaction for up to 24 hours to check the transaction status
2. This API can only be used by the original sending location/agent ID.
3. This is an Optional API to code and not required in the actual Send transaction flow.

6.0.2 Detail Lookup Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/detailLookup
Headers	content-type: application/xml
Authentication	signature

6.0.3 Detail Lookup Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	- Retrieval reference number. - Same with the one supplied on Commit Transaction Request - Alphanumeric. - Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required

6.0.4 Detail Lookup Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <detailLookupRequest>
      <rrn>100001001010</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <signature>signature</signature>
    </detailLookupRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

6.0.5 Detail Lookup Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

6.0.6 Detail Lookup Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Statuses: Sample status 1. OK 000, where 000 is the success status code Sample pending status 2. PENDING 001, where 001 is the pending status code Sample failure status 3. ERROR 409, where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

5	imtReferenceNumber	Imt reference number. Returned when status is OK (Success)	String
6	imtSessionTranId	Imt session tran ID. Returned when status is OK (Success)	String
7	imtTransactionDate	Imt Transaction Date. Returned when status is OK (Success)	String

6.0.7 Detail Lookup Sample Success Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <imtReferenceNumber>12345</imtReferenceNumber>
  <imtSessionTranId>12345</imtSessionTranId>
  <imtTransactionDate>3455566</imtTransactionDate>
  <status>OK|000</status>
  <imtStatus>AVAIL</imtStatus>
  <responseCode>000</responseCode>
  <responseDesc>Transaction Completed Successfully.</responseDesc>
</statusDetails>
```

6.0.8 Detail Lookup Sample Failure Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing
via chat or email.</responseDesc>
</statusDetails>
```

7.0 Channel Callback Service

7.0.1 Channel Callback Description

The channel can get the final status of the transaction in two ways:

1. **Detail Lookup API:**

The channel can actively retrieve the transaction status by making a request to the Detail Lookup API after the transaction has been initiated. This method provides flexibility and control, allowing the channel to check the status at their convenience based on their specific needs or business logic.

2. **Callback from GAG:**

Alternatively, the channel can receive automatic updates via a callback from GAG. By providing a valid `callbackUrl` in the `callbackUrl` field of the **Commit Transaction API**, the channel will be notified as soon as the final status of the transaction is available. This eliminates the need for the channel to continuously poll the system and allows them to receive real-time updates without manual intervention.

7.0.2 Callback Sample Success Response

```
<statusDetails>
  <rrn>100001001010</rrn>
  <status>OK|000</status>
  <responseCode>000</responseCode>
  <responseDesc>Callback processed successfully.</responseDesc>
</statusDetails>
```

7.0.3 Callback Sample Failure Response

```
statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>Callback Processing Failed.</responseDesc>
</statusDetails>
```

8.0 Code Table

8.0.1 Code Table Description

The agent application uses the `codeTable` API to obtain countries, states, currencies, delivery options, and other important information required to perform transactions.

Additional Information

1. Agents must store the information returned in the `codeTableResponse` locally
2. The agent must create an automated process to obtain updates during non-business hours; the agent must also create a manual process to obtain updates in the event system changes occur during business hours
3. The code table information only needs to be updated by one location using the model agent ID; the information may be shared among locations
4. This process should be performed on a regular basis. MoneyGram recommends a daily batch process during non-business hours.
5. In the `codeTableResponse`, the agent can keep track of MoneyGram's 'version' in the agent's local table and the agent will need to perform the API call daily, but may choose to update the information only if the version changes,
6. Code Table must be carefully analyzed as information returned is critical for successful transaction processing
7. The `stateProvinceInfo` list returned will grow as MoneyGram adds more states/provinces to countries that have states. Agent application must be able to handle new states/provinces returned for these countries. State fields will always be returned as Optional by the `getFieldsForProduct` (GFFP) API. If a country is selected from the list that has states available in the `codeTable` API response, then a state is required. Agent application should change the list of states available depending on the country selected. If the country selected does not have any state list in the `codeTable` API, then the field should be disabled so data is not collected.
 - a. the fields impacted are: `senderState`, `receiverState`, `senderPhotoIDState`, `receiverPhotoIDState`, `thirdPartyState`

8.0.2 Code Table Request Headers Description

Method	POST
URL	http://10.11.6.110:8580/api/v1/moneygram/outbound/codeTable
Headers	content-type: application/xml
Authentication	signature

8.0.3 Code Table Request Field Description

Tag	Datatype	Information and Rules	Input	Data
rrn	String	- Retrieval reference number. - Same with the one supplied on Commit Transaction Request - Alphanumeric. - Must be size 12	not allowed	required
channelId	String	Calling channel Id. Example: OMNI	not allowed	required
sourceSystemId	String	Calling system. Example: OMNI	not allowed	required
bankId	String	Originating bank. Example: 43	not allowed	required
signature	String	Encrypted signature for security and authentication See Digital Signature Section	not allowed	required
agentAllowedOnly	boolean Default value: false	<i>Additional Information</i> 1. If <code>true</code>, the <code>codeTableResponse</code> returns only delivery options available to the agent 2. If <code>false</code>, the <code>codeTableResponse</code> returns all delivery options regardless of whether they are available to the agent	application	optional

		MoneyGram recommends to set the agentAllowedOnly flag to <code>true</code> if delivery options are obtained from code tables. Flag can be set to <code>false</code> if delivery options are obtained from feeLookupResponse		
--	--	---	--	--

8.0.4 Code Table Sample Request

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <channelInfo>
      <rrn>1234rrn</rrn>
      <channelId>OMNI</channelId>
      <sourceSystemId>OMNI</sourceSystemId>
      <bankId>43</bankId>
      <signature>signature</signature>
    </channelInfo>
    <codeTableRequest
      xmlns="http://www.moneygram.com/AgentConnect1512">
      <agentAllowedOnly>true</agentAllowedOnly>
    </codeTableRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

8.0.5 Code Table Response Headers Description

Success Http Status Code	200 - OK
---------------------------------	----------

8.0.6 Code Table Success Response Field Description

Tag	Datatype	Information and Rules	Display
version	string Maximum length: 20	The code table version returned.	N/A

stateProvinceInfo	complex Maximum number of occurrences: unbounded	<i>Additional Information</i> 1. Currently, data is only returned for Canada, Mexico, and the United States Business rule to code: At present; State is required and must be submitted if Sender/ReceiverCountry & photoIDCountry is equal to Canada, Mexico, the United States, and any country from codeTable API that has state/province lists	N/A
countryCode	string Length: 3	None	N/A
stateProvinceCode	string Length: 2	<i>Additional Information</i> 1. The value is a valid state code to be used whenever a state code is required	N/A
stateProvinceName	string Maximum length: 40	None	N/A
countryInfo	complex Maximum number of occurrences: unbounded	None	N/A
countryCode	string Length: 3	<i>Additional Information</i> 1. The value is a valid country code to be used whenever a country code is required	N/A
countryName	string Maximum length: 50	None	N/A

countryLegacyCode	string Length: 2	None	N/A
sendActive	boolean	<i>Additional Information</i> 1. If <code>true</code>, agents in the country may perform send transactions 2. If <code>false</code>, agents in the country may not perform send transactions	N/A
receiveActive	boolean	1. If <code>true</code>, agents in the country may perform receive transactions 2. If <code>false</code>, agents in the country may not perform receive transactions 3. List of destination countries must be filtered at the GUI level to include only countries with flag set to <code>true</code>	N/A
directedSendCountry	boolean	<i>Additional Information</i> 1. If <code>true</code>, the country has directed send partners 2. If <code>false</code>, the country does not have directed send partners	N/A
mgDirectedSendCountry	boolean	For internal use only	N/A

baseReceiveCurrency	string Length: 3	The country's default receive currency.	N/A
isZipCodeRequired	Boolean	Indicates if zip/postal code is required for the country. If true, the zip/postal code must be provided on the transaction (in senderZipCode, receiverZipCode, or thirdPartyZipCode) for the specified country. If false, the zip code field (senderZipCode, receiverZipCode, or thirdPartyZipCode) can be left blank for the specified country.	N/A
currencyInfo	complex Maximum number of occurrences: unbounded	None	N/A
currencyCode	string Length: 3	<i>Additional Information</i> 1. The value is a valid currency code to be used whenever a currency code is required	N/A
currencyName	string Maximum length: 40	None	N/A
currencyPrecision	int	The number of digits used by the currency for fractional amounts.	N/A
countryCurrencyInfo	complex Maximum number of occurrences: unbounded	None	N/A
countryCode	string Length: 3	None	N/A

baseCurrency	string Length: 3	None	N/A
localCurrency	string Length: 3	None	N/A

receiveCurrency	string Length: 3	None	N/A
indicativeRateAvailable	boolean	<i>Additional Information</i> 1. If <code>true</code>, the country uses estimated rates if valid rates are not available in the local currency. The exchange rate is not determined at time of the Send transaction, but it's determined at the time of Receiving the transaction 2. If <code>false</code>, the country does not use estimated rates and exchange rates are guaranteed. Fee information returned during a fee quote will not return any estimated values 3. <code>feeLookup</code> cannot be called with <code>receiveAmount</code>, when the destination country has at least one delivery option with this flag set to true.	N/A

deliveryOption	string	<i>Additional Information</i> 1. If value returned, the country currency information applies only to the specific delivery option	N/A
receiveAgentID	string Length: 8	<i>Additional Information</i> 1. If value returned, the country currency information applies only to the specific agent ID 2. receiveAgentID is required to complete a Send transaction	N/A
receiveAgentAbbreviation	string Maximum length: 10	The abbreviated form of the agent's name to be displayed on application screen and receipts	N/A
mgManaged	string Maximum length: 20 Valid values: NOT ALLOWED, REQUIRED, optional	For internal use only	N/A
agentManaged	string Maximum length: 20 Valid values: NOT ALLOWED, REQUIRED, optional	For internal use only	N/A

validationExprs	string Maximum length: 20	Field not currency used	N/A
checkDigitAlg	string Maximum length: 10	<i>Additional Information</i> 1. Field not currently used	N/A
deliveryOptionInfo	complex Maximum number of occurrences: unbounded	None	N/A
dssOption	boolean	<i>Additional Information</i> 1. If <code>true</code> , the delivery option is a directed send option 2. If <code>false</code> , the delivery option is not a directed send option	N/A
deliveryOptionID	int Maximum inclusive value: 999	The delivery option's numeric ID number.	N/A
deliveryOption	string	The delivery option's alphabetic ID. <i>Additional Information</i> 1. The value is a valid delivery option to be used whenever a delivery option is required	N/A
deliveryOptionName	string Maximum length: 40	1. The delivery option's display name. 2. GUI must display the text returned on the <code>deliveryOptionName</code> if <code>deliveryOption</code> is obtained from <code>codeTable</code> API	N/A

rewardsInfo	complex Maximum number of occurrences: unbounded	Contains information on the MoneyGram Plus program available to the agent's consumers.	N/A
programType	string Maximum length: 3	The program type code of the MoneyGram Plus program available to the agent's consumers. <i>Additional Information</i> 1. Maps to the <code>programType</code> returned in <code>rewardsRegistrationInfo</code>	N/A
name	string Maximum length: 64	The name of the MoneyGram Plus program available to the agent's consumers.	N/A
description	string Maximum length: 40	The description of the MoneyGram Plus program available to the agent's consumers.	N/A
rewardsCardTypeInfo	complex Maximum number of occurrences: unbounded	Contains information on the MoneyGram Plus card available to the agent's consumers.	N/A
cardType	string Maximum length: 4	The MoneyGram Plus card type available to the agent's consumers. <i>Additional Information</i> 1. Maps to the <code>cardType</code> returned in <code>rewardsRegistrationInfo</code>	N/A
description	string Maximum length: 40	The description of the MoneyGram Plus card available to the agent's consumers.	N/A

rewardsRegistrationInfo	complex Maximum number of occurrences: unbounded	Contains information on MoneyGram Plus program and card types available to the agent's consumers. <i>Additional Information</i> 1. Each occurrence maps the <code>programType</code> to the <code>programType</code> in <code>rewardsInfo</code> 2. Each occurrence maps the <code>cardType</code> to the <code>cardType</code> in <code>rewardsCardTypeInfo</code>	N/A
country	string Length: 3 Must be a valid country code	None	N/A
programType	string Maximum length: 3	This information must be used in Plus Enrollment APIs	N/A
cardType	string Maximum length: 4	This information must be used in Plus Enrollment APIs	N/A
allowPrePrintedCards	boolean	<i>Additional Information</i> 1. If <code>true</code> , the program and card combination allows agents to use pre-printed Plus cards 2. If <code>false</code> , the program and card combination does not allow agents to use pre-printed Plus cards	N/A

allowStandardCards	boolean	<i>Additional Information</i> 1. If <code>true</code>, the program and card combination allows agents to use standard Plus enrollment 2. If <code>false</code>, the program and card combination does not allow agents to use standard Plus enrollment	N/A
--------------------	---------	---	-----

8.0.7 Code Table Request Failure Response Field Description

NO	FIELD	DESCRIPTION	TYPE
1	rrn	Request RRN value	String
2	status	Error status. b. Sample failure status i. ERROR 409 , where 409 is the error status code	String
3	responseCode	Status response code	String
4	responseDesc	Status response description	String

8.0.8 Code Table Request Sample Failure Response

```

<statusDetails>
  <rrn>100001001010</rrn>
  <status>ERROR|503</status>
  <responseCode>503</responseCode>
  <responseDesc>moneygram error: this device has been deauthorized. please contact servicing via chat or email.</responseDesc>
</statusDetails>

```


9.0 Digital Signature Generation

To ensure secure communication, the calling channel must provide a valid certificate file(**.cer**) certificate file.

The digital signature is generated using the **SHA256withRSA** algorithm and passed as a **Base64-encoded** value in the signature field of the API request.

9.0.1 Signature Generation

1. **Provide a Valid Certificate:**
 - The calling channel must supply a **.cer** certificate file.
2. **Generate the Digital Signature:**
 - **Concatenate the clear text fields** (detailed below).
 - **Format the amount** as a **BigDecimal** with two decimal places using `setScale(2, RoundingMode.CEILING)`.
 - **Hash** the concatenated string using **SHA-256**.
 - **Encrypt** the hash with **RSA** using the private key.
 - **Encode** the encrypted hash as a Base64 string.
 - **Pass** the Base64 signature in the signature field.

9.0.2 Clear Text Values

For each transaction type, the clear text values must be concatenated in the specified order. The amount field must be a **BigDecimal** with two decimal places.

1. **Fee Lookup Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + amount + sendCurrency + receiveCurrency + receiveCountry
 - Ensure the amount is a **BigDecimal** and formatted as `setScale(2, RoundingMode.CEILING)`.
2. **Get Fields For Product Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + amount + sendCurrency + receiveCurrency + receiveCountry + consumerId
3. **Send Validation Service:**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + destinationAccount + amount + sendCurrency + receiveCurrency + receiveCountry + receiverFirstName
4. **Commit Transaction Request Service**
 - Concatenate the following fields in this order:
rrn + channel + sourceSystemId + sourceAccount + destinationAccount + amount + currency + mgiTransactionSessionID + productType
 - Ensure the amount is a **BigDecimal** and formatted as `setScale(2, RoundingMode.CEILING)`.

5. Detail Lookup Service

- Concatenate the following fields in this order:
rrn + channel + sourceSystemId + bankId

6. Code Table Request Service

- Concatenate the following fields in this order:
rrn + channel + sourceSystemId + agentAllowedOnly

10.0 Appendix 1: Request Field Guide

10.0.1 Request Field Guide

The following is an example of a table used to describe API request field details.

Tag	Datatype	Information and Rules	Input	Data
requestExampleField1	string Maximum length: 10	An example of a field containing a string.	GUI	required
requestExampleField2	string Length: 3 Must be a valid country code	An example of a field containing a country code	application	required
requestExampleField3	boolean	An example field whose data and visibility requirements depend on the getFieldsForProduct API. <i>Additional Information</i> 1. If <code>true</code> , then... 2. If <code>false</code> , then...	not allowed	not allowed

Definitions

- **Tag:** The field's XML tag; fields for which data is required are shown in bold red text
- **Datatype:** Describes the type and restrictions of the field's data
- **Information and Rules:** Provides additional information, business rules, and a description of the field if necessary
- **Input:** Indicates how the field's value is obtained
 - **Application:** The agent application must retrieve the data from another part of the agent application or from a previous MoneyGram API response. Data can be displayed on the application screen
 - **GUI:** The agent application must display the field on its user interface and allow user input

- **Conditional:** The agent application may or may not display the field on the user interface for user input depending on the conditions stated in the Information and Rules column
- **GFFP:** Whether or not the field is shown on the user interface for user inputs depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
- **N/A:** Input does not apply; for instance, if the field only contains other fields
- **Not Allowed:** The agent application must not allow data to be entered by the user. Data must not be displayed. The agent application must retrieve the data from another part of the agent application or from a previous MoneyGram API response
- **Optional:** The agent may choose whether to display the field on the user interface for user input
- **Data:** Indicates whether the field must contain data; only used on API requests
 - **Required:** The field must contain data
 - **Not allowed:** The field must not contain data
 - **Optional:** The agent must display the field on the user interface, but data collection is optional
 - **Conditional:** The field may or may not contain data depending on the conditions stated in the Information and Rules column
 - **GFFP:** Whether or not the field contains data depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
 - **Response:** Whether or not the field contains data depends on the information returned by a message specified in the additional information for the API

11.0 Appendix 1: Response Field Guide

11.0.1 Response Field Guide

The following is an example of a table used to describe API response field details.

Tag	Datatype	Information and Rules	Display
responseExampleField1	string Maximum length: 10	An example of a field containing a string.	required
responseExampleField2	string Length: 3 Must be a valid country code	An example of a field containing a country code	optional
responseExampleField3	boolean	An example field whose data and visibility requirements depend on the getFieldsForProduct API. <i>Additional Information</i> 1. If <code>true</code> , then... 2. If <code>false</code> , then...	required

Definitions

- **Tag:** The field's XML tag; fields for which data is required are shown in bold red text
- **Datatype:** Describes the type and restrictions of the field's data
- **Information and Rules:** Provides additional information, business rules, and a description of the field if necessary
- **Display:** Indicates whether the value of the field is shown on the agent application's user interface
 - **Conditional:** The value may or may not be shown on the user interface depending on the conditions stated in the Information and Rules column
 - **GFFP:** Whether or not the value is shown on the user interface depends on the information returned by the [getFieldsForProductResponse](#) (GFFP)
 - **N/A:** Visibility does not apply; for instance, if the field doesn't contain displayable data

- **Not allowed:** The value must not be shown on the user interface; for fields in API responses, the data in the field should not be edited unless otherwise stated
- **Optional:** The agent may choose whether to show the value on the user interface
- **Required:** The value must be shown on the user interface if data is returned in the API