



PAPSS Outbound API Doc v1.0

Revision History

Date	Version	Author	Comments
25-08-2025	v1.0	Kennedy Gatimu	Initial document creation

Table of Contents

PAPSS Outbound Service API.....	4
1.0 Get PAPSS Participants API	4
Example 1: Get All Participants	5
Example 2: Get a Specific Participant by BIC.....	7
Example 3: Get Participants by Country Code	8
2.0 Get Foreign Exchange (FX) Rate API.....	11
Example Request	12
Success Response Body (200 OK)	13
Failure Response Body	14
3.0 Name Check API	15
Example Request Body	16
Success Response Body (200 OK)	17
Failure Response Body	17
4.0 Initiate Credit Transfer	18
Example Request Body	20
Synchronous Response (Immediate)	21
Asynchronous Response (Callback)	22
5.0 Transaction Status Check	24
Request Body.....	25
Previously Successful Transaction Response.....	26
Previously Failed/Rejected Transaction	27
Internal Errors	27
6.0 Authentication.....	28
Get Participants (/participants)	28
Get FX Rate (/FXRate)	29
Name Check (/namecheck)	29
Credit Transfer (/credit-transfer)	29
Status Check (/status-check).....	30

PAPSS Outbound Service API

This document provides details for integrating with the PAPSS Outbound Service REST API through GAG. The service exposes below endpoints:

- Retrieving PAPSS participants
- Checking FX rates
- Performing name checks
- Initiating credit transfers
- Check transaction statuses

1.0 Get PAPSS Participants API

This endpoint retrieves a list of all financial institutions that are participants in the Pan-African Payment and Settlement System (PAPSS). The list can be filtered by providing an **optional bic** or **countryCode** in the JSON request body.

Base Endpoint

POST /api/v1/outbound/participants

Request Field Description

Field	Type	Required	Description
receiver	Object	Mandatory	An object containing the filter criteria.
receiver.countryCode	String	Optional	The two-letter ISO country code to filter participants by (e.g., KE). Leave empty to get all participants.
receiver.bic	String	Optional	The Business Identifier Code (BIC) to retrieve a specific participant. If provided, this takes precedence over countryCode.
channelInfo	Object	Mandatory	Contains metadata for this request.
channelInfo.rrn	String	Mandatory	A new, unique 12-digit RRN for this request. Pattern: <code>^[a-zA-Z0-9]+\$</code>
channelInfo.bankId	String	Mandatory	Identifier for the bank originating the request. Pattern: <code>^[a-zA-Z0-9]+\$</code>
channelInfo.channelId	String	Mandatory	Identifier for the channel originating the request. Pattern: <code>^[a-zA-Z0-9]+\$</code>

channelInfo.sourceSystemId	String	Mandatory	Identifier for the source system. Pattern: ^[a-zA-Z0-9-]+\$
signature	String	Mandatory	A digital signature for message integrity. See the Authentication section for construction details.

Example 1: Get All Participants

To get all participants, send the request with countryCode and bic as **empty** strings.

```
{
  "receiver": {
    "countryCode": "",
    "bic": ""
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "HnNDt4RW8RTRGSWVJ0pwfs/
+o4j2dqUrCKqKTRmxnuOUJiSjTM8W4IY13r6Y9K15lDOVr+KLjdAwH0AFeUNhCLCuqYL5G8AmTnPW24jffFYCab
wojixdFFLuLPhIssuNi+BJnnpMJhz2nM4zBhGr8QVWmQ==" }
```

Success Response Body Structure

```
{
  "participants": {
    "participant": [
      {
        "papssId": "GH1040",
        "bic": "ABNGGHAC",
        "name": "ACCESS BANK (GHANA) PLC",
        "countryCode": "GH",
        "status": "ACTIVE",
        "paymentSchemas": [
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-All",
          "PS-GH-GHS-GH1040-GH-GHS-SSA_3-DEF-SSA3",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-LLL",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-ESS-LMT",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-NNN",
          "PS-GH-GHS-USD-SSA_3-USDP",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-SSS",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GAM",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GNN",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GGG"
        ]
      },
      {
        "papssId": "GH1001",
        "bic": "ABNGGHAC",
        "name": "ACCESS BANK (GHANA) PLC",
        "countryCode": "GH",
        "status": "ACTIVE",
        "paymentSchemas": [
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-All",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_3-DEF-SSA3",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-LLL",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-ESS-LMT",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-NNN",
          "PS-GH-GHS-USD-SSA_3-USDP",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-SSS",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GAM",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GNN",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GGG"
        ]
      }
    ],
    "currencies": [
      "USD",
      "GHS"
    ]
  }
}
```

```

        "GHS",
        "USD"
    ],
    "online": true,
    "nonInstant": false
},
{
    "papssId": "KE0008NP",
    "bic": "KCOOKENE",
    "name": "COOP BANK",
    "countryCode": "KE",
    "status": "ACTIVE",
    "paymentSchemas": [],
    "currencies": [],
    "online": true,
    "nonInstant": false
},
{
    "papssId": "ZM1005",
    "bic": "ZNCOZMLU",
    "name": "Zanaco Bank",
    "countryCode": "ZM",
    "status": "ACTIVE",
    "paymentSchemas": [
        "PS-ZM-ZMW-USD-SSA_3-USDP",
        "PS-ZM-ZMW-ZM1004-ZM-ZMW-SSA_3-DEF-All"
    ],
    "currencies": [
        "USD",
        "ZMW"
    ],
    "online": true,
    "nonInstant": false
}
]
},
"channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Participants successfully retrieved."
}
}
}

```

Failure/ Error Response

If an error occurs due, a relevant HTTP status code will be returned with a descriptive error message in the response body.

Error Response Body

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Failed to retrieve participants: HTTP call to the url was unsuccessful. Connection refused"
  }
}
```

Example 2: Get a Specific Participant by BIC

To get a single participant, provide the **bic**.

```
{
  "receiver": {
    "countryCode": "",
    "bic": "ABNGGHAC"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "HnNDt4RW8RTRGSWVJ0pwfs/
+o4j2dqUrCKqKTRmxnuOUJiSjTM8W4IY13r6Y9K15lDOVr+KLjdAwH0AFeUNhCLCuqYL5G8AmTnPW24jffFYCaa
bwojixdFFLuLPhIssuNi+BJnnpMJhz2nM4zBhGr8QVWmQ==" }
```

Success Response (200 OK)

```
{
  "participants": {
    "participant": [
      {
        "papssId": "GH1040",
        "bic": "ABNGGHAC",
        "name": "ACCESS BANK (GHANA) PLC",
        "countryCode": "GH",
        "status": "ACTIVE",
        "paymentSchemas": [
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-All",
          "PS-GH-GHS-GH1040-GH-GHS-SSA_3-DEF-SSA3",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-LLL",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-ESS-LMT",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-NNN",
          "PS-GH-GHS-USD-SSA_3-USDP",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-SSS",
          "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GAM",
        ]
      }
    ]
  }
}
```

```

        "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GNN",
        "PS-GH-GHS-GH1001-GH-GHS-SSA_1-DEF-GGG"
    ],
    "currencies": [
        "GHS",
        "USD"
    ],
    "online": true,
    "nonInstant": false
}
]
},
"channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Participants successfully retrieved."
} }

```

Example 3: Get Participants by Country Code

To get all participants in a **specific country**, provide the countryCode.

```

{
    "receiver": {
        "countryCode": "KEN",
        "bic": ""
    },
    "channelInfo": {
        "rrn": "111996657000",
        "bankId": "54",
        "channelId": "OMNI",
        "sourceSystemId": "ONMI"
    },
    "signature": "HnNDt4RW8RTRGSWVJ0pwfs/ +
+KLjdAwH0AFeUNhCLCuqYL5G8AmTnPW24jfFYCaabwojixdFFLuLPhIssuNi+BJnnpMJhz2nM4zBhGr8QVWm" }

```


Success Response (200 OK)

```
{
  "participants": {
    "participant": [
      {
        "papssId": "KE0007NP",
        "bic": "DTKEKENM",
        "name": "DTB BANK",
        "countryCode": "KE",
        "status": "ACTIVE",
        "paymentSchemas": [
          "PS-KE-KES-KE1002-KE-KES-SSA_3-DEF-All"
        ],
        "currencies": [
          "KES"
        ],
        "online": true,
        "nonInstant": false
      },
      {
        "papssId": "KE1002",
        "bic": "KCBLKENX",
        "name": "KCB BANK KENYA LTD",
        "countryCode": "KE",
        "status": "ACTIVE",
        "paymentSchemas": [
          "PS-KE-KES-KE1002-KE-KES-SSA_3-DEF-All",
          "PS-KE-KES-KE1002-KE-KES-SSA_3-DEF-SSA3",
          "PS-KE-KES-USD-SSA_3-USDP"
        ],
        "currencies": [
          "KES",
          "USD"
        ],
        "online": true,
        "nonInstant": false
      },
      {
        "papssId": "KE1006",
        "bic": "IMBLKENA",
        "name": "IandM Bank Limited",
        "countryCode": "KE",
        "status": "ACTIVE",
        "paymentSchemas": [
          "PS-KE-KES-KE1006-KE-KES-SSA_3-DEF-SSA3",
          "PS-KE-KES-KE1001-KE-KES-SSA_1-DEF-All",
          "PS-KE-KES-USD-SSA_3-USDP"
        ],
        "currencies": [
          "KES",
          "USD"
        ]
      }
    ]
  }
}
```

```
        ],
        "online": true,
        "nonInstant": false
    }
]
},
"channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Participants successfully retrieved."
} }
```

2.0 Get Foreign Exchange (FX) Rate API

This endpoint provides a real-time foreign exchange (FX) rate quote for a potential cross-border transaction. It calculates the final amount the recipient will receive based on the current rates and includes a breakdown of applicable fees.

Base Endpoint

POST /api/v1/outbound/FXRate

Request Field Description

Field	Type	Required	Description
sender	Object	Mandatory	Contains the sending party's details for the quote.
sender.countryCode	String	Mandatory	The two-letter ISO country code of the sender. Pattern: <code>^[A-Z]{2}\$</code>
sender.currency	String	Mandatory	The three-letter ISO currency code of the sender. Pattern: <code>^[A-Z]{3}\$</code>
sender.amount	String	Mandatory	Transaction amount for the quote. Constraint: Must be > 0.01, with up to 10 integer and 2 fractional digits.
receiver	Object	Mandatory	Contains the receiving party's details for the quote.
receiver.institutionId	String	Mandatory	The PAPSS ID of the receiving institution. Pattern: <code>^[a-zA-Z0-9_-]+\$</code>
receiver.countryCode	String	Mandatory	The two-letter ISO country code of the receiver. Pattern: <code>^[A-Z]{2}\$</code>
receiver.currency	String	Mandatory	The three-letter ISO currency code of the receiver. Pattern: <code>^[A-Z]{3}\$</code>
channelInfo	Object	Mandatory	Contains metadata for this request.
channelInfo.rrn	String	Mandatory	A new, unique 12-digit RRN for this request. Pattern: <code>^[a-zA-Z0-9]+\$</code>
channelInfo.bankId	String	Mandatory	Identifier for the bank originating the request. Pattern: <code>^[a-zA-Z0-9]+\$</code>
channelInfo.channelId	String	Mandatory	Identifier for the channel originating the request. Pattern: <code>^[a-zA-Z0-9-]+\$</code>
channelInfo.sourceSystemId	String	Mandatory	Identifier for the source system. Pattern: <code>^[a-zA-Z09-]+\$</code>
signature	String	Mandatory	A digital signature. See the Authentication section for construction details. Size: Max 1000 characters.

Request URL

POST	https://localhost:10443/api/v1/outbound/FXRate
------	---

Example Request

```
{
  "sender": {
    "countryCode": "KE",
    "currency": "KES",
    "amount": "100"
  },
  "receiver": {
    "institutionId": "GM1015",
    "countryCode": "NG",
    "currency": "NGN"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "OMNI"
  },
  "signature": "HnNDt4RW8RTRGSWVJ0pwfs/
+o4j2dqUrCKqKTRmxnuOUJiSjTM8W4IY13r6Y9K15lDOVr+KLjdAwH0AFeUNhCLCuqYL5G8AmTnPW24jffYCaabwojixdFFLuLPhIssuNi+BJnnpMJhz2nM4zBhGr8QVWmQ=="
}
```

Responses

A successful request returns a **200 OK** with a detailed FX quote.

An unsuccessful request will return an appropriate error code (4xx or 5xx) with a failure description

Success Response Body (200 OK)

```
{
  "paymentFXRate": {
    "request": {
      "amount": "100",
      "isInvoice": "false",
      "time": "2025-04-30T11:58:41Z",
      "receiverCurrency": "NGN",
      "lclInstrm": "SSA3",
      "receiverBank": "NG2020",
      "receiverCountry": "NG",
      "senderCountry": "KE",
      "senderCurrency": "KES"
    },
    "response": {
      "time": "2025-04-30T11:58:41Z",
      "rates": [
        {
          "type": "USD/KES",
          "updateTime": "2025-04-30T09:45:36Z",
          "value": "129.55"
        },
        {
          "type": "USD/NGN",
          "updateTime": "2023-08-28T14:06:31Z",
          "value": "750.0000"
        },
        {
          "type": "KES/NGN",
          "value": "5.775000000"
        }
      ],
      "senderAmount": {
        "value": "100.00",
        "ccy": "KES"
      },
      "exchangeAmount": {
        "value": "0.77",
        "ccy": "USD"
      },
      "receiverAmount": {
        "value": "577.50",
        "ccy": "NGN"
      },
      "nationalFeeAmount": {
        "value": "259.10",
        "ccy": "KES"
      },
      "feeAmount": {
        "value": "2.00",
```

```
        "ccy": "USD"
    }
},
"channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Get Fx Rate Successfully processed"
} }
```

Failure Response Body

```
{
    "channelStatusInfo": {
        "status": "FAILURE",
        "code": "01",
        "description": "Internal Error: HTTP call to the url was unsuccessful. Calling  
PAPSS Get Fx Rate returned a Non-200 status code"
    } }
```

3.0 Name Check API

This endpoint verifies the details of a recipient's bank account, such as the account holder's name, before initiating a payment. This helps prevent misdirected funds and reduces transaction failures.

Base Endpoint

POST /api/v1/outbound/namecheck

Request Field Description

Field	Type	Required	Description
sender	Object	Mandatory	Contains the sending institution's details.
sender.institutionId	String	Mandatory	The PAPSS ID of the sending institution. Pattern: ^[a-zA-Z0-9_-]+\$
sender.bic	String	Mandatory	The BIC of the sending institution. Pattern: ^[a-zA-Z0-9]+\$
receiver	Object	Mandatory	Contains the receiving party's details to be verified.
receiver.institutionId	String	Mandatory	The PAPSS ID of the receiving institution. Pattern: ^[a-zA-Z0-9_-]+\$
receiver.bic	String	Mandatory	The BIC of the receiving institution. Pattern: ^[a-zA-Z0-9]+\$
receiver.accountNumber	String	Mandatory	The account number to be verified. Pattern: ^[a-zA-Z0-9]+\$
channelInfo	Object	Mandatory	Contains metadata about the transaction channel.
channelInfo.rrn	String	Mandatory	Retrieval Reference Number. Size: 12 characters. Pattern: ^[a-zA-Z0-9]+\$
channelInfo.bankId	String	Mandatory	Identifier for the bank originating the request. Pattern: ^[a-zA-Z0-9]+\$
channelInfo.channelId	String	Mandatory	Identifier for the channel originating the request. Pattern: ^[a-zA-Z0-9_-]+\$
channelInfo.sourceSystemId	String	Mandatory	Identifier for the source system. Pattern: ^[a-zA-Z0-9_-]+\$
signature	String	Mandatory	A digital signature for message integrity. Size: Max 1000 characters.

Request URL

POST	https://localhost:10443/api/v1/outbound/namecheck
------	---

Example Request Body

```
{
  "sender": {
    "institutionId": "KE1005",
    "bic": "EQBLKENA"
  },
  "receiver": {
    "institutionId": "GM1015",
    "bic": "ICBGGMGS",
    "accountNumber": "435000100"
  },
  "channelInfo": {
    "rrn": "111996657001",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "OMNI"
  },
  "signature": "HnNDt4RW8RTRGSWVJ0pwfs/
+o4j2dqUrCKqKTRmxnuOUJiSjTM8W4IY13r6Y9K15lDOVr+KLjdAwH0AFeUNhCLCuqYL5G8AmTnPW24jfFYCaa
bwojixdFFLuLPhIssuNi+BJnnpMJhz2nM4zBhGr8QVWmQ=="
}
```

Responses

A successful request returns a **200 OK** with the verified account holder's details.

An unsuccessful request will return an appropriate error code (4xx or 5xx) with a failure description

Success Response Body (200 OK)

```
{
  "rrn": "111996657001",
  "ipsStatusInfo": {
    "status": {
      "type": "ACCP",
      "reason": "000",
      "code": "000",
      "description": "Success"
    }
  },
  "receiver": {
    "institutionId": "GM1001",
    "accountNumber": "SLL116030003",
    "accountName": "Michael Brown",
    "emailAddress": "agadas@gmail.com"
  },
  "channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Success."
  }
}
```

Failure Response Body

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Internal Error: HTTP call to the url was unsuccessful"
  }
}
```

4.0 Initiate Credit Transfer

This endpoint initiates a cross-border credit transfer transaction through PAPSS. The process is asynchronous:

- A synchronous immediate response is returned to indicate whether the transaction has passed validation (**PENDING**) or failed (**FAILURE**).
- The final transaction status (**SUCCESS** or **FAILURE/REJECTED**) is sent later via an HTTP POST request to the provided **channelInfo.callbackURL**.

Base Endpoint

POST /api/v1/outbound/credit-transfer
--

Request Field Description

Field	Type	Required	Description
sender.institutionId	String	Yes	PAPSS-assigned institution ID of the sender bank. Must be alphanumeric or contain underscores/hyphens.
sender.bic	String	Yes	Sender's BIC code. Must be alphanumeric only (no special characters).
sender.countryCode	String	Yes	Sender's ISO 3166-1 alpha-2 or alpha-3 country code. Must be 2–3 alphabetic characters only.
sender.currency	String	Yes	Sender's ISO 4217 currency code. Must be exactly 3 alphabetic characters (e.g., KES).
sender.accountNumber	String	Yes	Sender's account number. Must be alphanumeric (letters and digits only).
sender.accountName	String	Yes	Sender's account name. Allows letters, digits, spaces, hyphens, dots, underscores, and parentheses.
sender.address	String	Yes	Sender's address. Allows letters, digits, spaces, hyphens, dots, underscores, and parentheses.
receiver.institutionId	String	Yes	PAPSS-assigned institution ID of the receiver bank. Must be alphanumeric or contain underscores/hyphens.
receiver.bic	String	Yes	Receiver's BIC code. Must be alphanumeric only.
receiver.countryCode	String	Yes	Receiver's ISO 3166-1 alpha-2 or alpha-3 country code. Must be 2–3 alphabetic characters.

receiver.currency	String	Yes	Receiver's ISO 4217 currency code. Must be exactly 3 alphabetic characters.
receiver.accountNumber	String	Yes	Receiver's account number. Must be alphanumeric.
receiver.accountName	String	Yes	Receiver's account name. Allows letters, digits, spaces, hyphens, dots, underscores, and parentheses.
receiver.emailAddress	String	No	Optional email address of receiver. Should be a valid email if provided.
channelInfo.rrn	String	Yes	Unique 12-character transaction reference number. Must be exactly 12 alphanumeric characters.
channelInfo.bankId	String	Yes	Bank identifier mapped to Finacle/PAPSS. Must be alphanumeric.
channelInfo.channelId	String	Yes	Originating channel (e.g., OMNI, MOBILE). Must be alphanumeric or hyphenated.
channelInfo.sourceSystemId	String	Yes	Identifier of the initiating system. Must be alphanumeric or hyphenated.
channelInfo.callbackURL	String	Yes	HTTPS endpoint that will receive the asynchronous callback. Must be a valid URL.
transactionInfo.senderAmount	String	Yes	Amount in sender's currency — must match paymentFXRate.response.senderAmount.value from 2.0 Get FX Rate API . Must be a positive decimal greater than 0 with up to 10 digits and 2 decimal places.
transactionInfo.receiverAmount	String	Yes	Amount in receiver's currency — must match paymentFXRate.response.receiverAmount.value. Positive decimal >0, up to 10 integer digits and 2 decimal places.
transactionInfo.fxRate	String	Yes	Exchange rate — must match corridor rate in paymentFXRate.response.rates. Positive decimal >0 with up to 10 digits and 2 decimal places.
transactionInfo.papssFeeAmount	String	Yes	PAPSS fee — must match paymentFXRate.response.nationalFeeAmount.value. Non-negative decimal, up to 10 digits and 2 decimal places.
transactionInfo.bankFeeAmount	String	Yes	Local bank fee amount. Non-negative decimal, up to 10 digits and 2 decimal places.
transactionInfo.transactionCurrency	String	Yes	ISO 4217 currency of the transaction. Exactly 3 alphabetic characters.
transactionInfo.paymentReason	String	Yes	Reason for payment. Allows alphanumeric, spaces, hyphens, underscores, and dots.

transactionInfo.narration	String	Yes	Transaction narration (max 100 characters). Allows alphanumeric, spaces, hyphens, underscores, and dots.
signature	String	Yes	Base64-encoded digital signature verifying request integrity. Maximum 1000 characters.

Request URL

POST	https://localhost:10443/api/v1/outbound/credit-transfer
-------------	---

Example Request Body

```
{
  "sender": {
    "institutionId": "KE1011",
    "bic": "EQBLKENA",
    "countryCode": "KE",
    "currency": "KES",
    "accountNumber": "0001100104442",
    "accountName": "John Doe",
    "address": "UpperHill"
  },
  "receiver": {
    "institutionId": "SL1006",
    "bic": "SKBSRLFT",
    "countryCode": "SL",
    "currency": "SLE",
    "accountNumber": "00000133800000",
    "accountName": "Mohamed Kamara",
    "emailAddress": "user@papss.com"
  },
  "channelInfo": {
    "rrn": "162996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "OMNI",
    "callbackURL": "https://testurl.co.ke"
  },
  "transactionInfo": {
    "senderAmount": "100.00",
    "receiverAmount": "213.00",
    "fxRate": "2.13",
    "papssFeeAmount": "280.00",
  }
}
```

```

        "bankFeeAmount": "0",
        "transactionCurrency": "KES",
        "paymentReason": "Papss Payments",
        "narration": "Trade Transfer Invoice for purchase of Cassava"
    },
    "signature": "HnNDt4RW8RTRGSWVJ0pwfs/
+o4j2dqUrCKqKTRmxnu0UJiSjTM8W4IY13r6Y9K15lD0Vr+KLjdAwH0AFeUNhCLCuqYL5G8AmTnPw24jffFYCaab
wojixdFFLuLPhIssuNi+BJnnpMJhz2nM4zBhGr8QVWmQ=="
}

```

Responses

Synchronous Response (Immediate)

This is the immediate response to the POST request.

1. Initial Pending

A **PENDING** status indicates the request was successfully validated and is now being processed.

```

{
  "rrn": "162996657002",
  "ipsStatusInfo": {
    "tranId": "",
    "status": {
      "type": "ACCP",
      "reason": "ACCP",
      "code": "000",
      "description": "Transaction has been accepted and is being processed"
    }
  },
  "channelStatusInfo": {
    "status": "PENDING",
    "code": "-11",
    "description": "Transaction has been accepted and is being processed"
  }
}

```

2. Initial Failure

```
{
  "rrn": "132996657120",
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "De-Dup! The request is a duplicate and has already been processed."
  }
}
```

Asynchronous Response (Callback)

This is the **final** transaction status, sent as a POST request to the **callbackURL** you provided.

1. Success (ACSC)

Indicates the transaction was successfully completed and funds credited to the receiver. The `ipsStatusInfo.status.type` will be **ACSC** (Accepted Settlement Completed).

```
{
  "rrn": "162996657002",
  "ipsStatusInfo": {
    "tranId": "",
    "status": {
      "type": "ACSC",
      "reason": "ACSC",
      "code": "000",
      "description": "Transaction completed successfully"
    }
  },
  "originalTxnStatusInfo": {
    "originalRrn": "162996657002",
    "status": "ACSC",
    "code": "00",
    "description": "Transaction completed successfully"
  },
  "channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Success."
  }
}
```

2. Rejected (RJCT)

Indicates the transaction was rejected by PAPSS or the receiving institution. The ipsStatusInfo object will contain details about the rejection reason.

```
{
  "rrn": "162996657003",
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Payment rejected by receiver Participant"
  }
}
```

3. Internal Failure Response

Indicates the transaction internally in GAG system.

```
{
  "rrn": "132996657121",
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "HTTP call to the url was unsuccessful. Connection refused"
  } }
}
```

5.0 Transaction Status Check

This endpoint queries the final status of a previously submitted credit transfer transaction using its original Retrieval Reference Number (**originalRrn**). This is useful for reconciliation or in cases where an asynchronous callback might have been missed.

This is a synchronous endpoint that returns the final recorded state of the transaction.

Base Endpoint

POST /api/v1/outbound/status-check

Request Field Description

Field	Type	Required	Description
sender	Object	Mandatory	Contains the original sending institution's details.
sender.institutionId	String	Mandatory	The PAPSS ID of the institution that initiated the original transaction. Pattern: <code>^[a-zA-Z0-9_-]+\$</code>
receiver	Object	Mandatory	Contains the original receiving institution's details.
receiver.institutionId	String	Mandatory	The PAPSS ID of the institution that was the recipient in the original transaction. Pattern: <code>^[a-zA-Z0-9_-]+\$</code>
channelInfo	Object	Mandatory	Contains metadata for this status check request.
channelInfo.rrn	String	Mandatory	A new, unique 12-digit RRN for this status check request itself. Pattern: <code>^[a-zA-Z0-9]+\$</code>
channelInfo.bankId	String	Mandatory	Identifier for the bank originating the request. Pattern: <code>^[a-zA-Z0-9]+\$</code>
channelInfo.channelId	String	Mandatory	Identifier for the channel originating the request. Pattern: <code>^[a-zA-Z0-9]+\$</code>
channelInfo.sourceSystemId	String	Mandatory	Identifier for the source system. Pattern: <code>^[a-zA-Z0-9]+\$</code>
originalTxnInfo	Object	Mandatory	An object containing the identifier of the transaction to be checked.
originalTxnInfo.originalRrn	String	Mandatory	The 12-digit RRN of the original credit transfer transaction to query. Pattern: <code>^[a-zA-Z0-9]+\$</code>
signature	String	Mandatory	A digital signature for message integrity. Size: Max 1000 characters.

Request Body

```
{
  "sender": {
    "institutionId": "KE1005"
  },
  "receiver": {
    "institutionId": "GM1015"
  },
  "channelInfo": {
    "rrn": "132996657119",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "OMNI"
  },
  "originalTxnInfo": {
    "originalRrn": "132996657119"
  },
  "signature":
"+o4j2dqUrCKqKTRmxnuOUJiSjTM8W4IY13r6Y9K15lDOVr+KLjdAwH0AFeUNhCLCuqYL5G8AmTnPW24jfFYCa
abwojixdFFLuLPhIssuNi+BJnnpMJhz2nM4zBhGr8QVWmQ==" }
```

Responses

The response will reflect the final recorded state of the queried transaction.

Previously Successful Transaction Response

If the original transaction was completed successfully, the response will mirror the ACSC callback.

```
{
  "rrn": "162996657002",
  "ipsStatusInfo": {
    "tranId": "",
    "status": {
      "type": "ACSC",
      "reason": "ACSC",
      "code": "000",
      "description": "Transaction completed successfully"
    }
  },
  "originalTxnStatusInfo": {
    "originalRrn": "162996657002",
    "status": "ACSC",
    "code": "00",
    "description": "Transaction completed successfully"
  },
  "channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Success."
  }
}
```

Previously Failed/Rejected Transaction

If the original transaction failed or was rejected, the response will contain the final failure details.

```
{
  "rrn": "162996657001",
  "ipsStatusInfo": {
    "tranId": "",
    "status": {
      "type": "RJCT",
      "reason": "RJCT",
      "code": "1080",
      "description": "Generic Error"
    }
  },
  "originalTxnStatusInfo": {
    "originalRrn": "162996657001",
    "status": "RJCT",
    "code": "1080",
    "description": "Generic Error"
  },
  "channelStatusInfo": {
    "status": "SUCCESS",
    "code": "00",
    "description": "Success."
  }
}
```

Internal Errors

Indicates the transaction internally in GAG system.

```
{
  "rrn": "132996657121",
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Internal Error"
  }
}
```

6.0 Authentication

The PAPSS Outbound Service API exclusively utilizes a digital signature for authenticating all requests to ensure message **integrity, authenticity, and non-repudiation**.

Signature Validation

Applicable Endpoints:

- POST /api/v1/outbound/participants
- POST /api/v1/outbound/FXRate
- POST /api/v1/outbound/namecheck
- POST /api/v1/outbound/credit-transfer
- POST /api/v1/outbound/status-check

Implementation

The process involves creating a specific plain-text string (the "canonical text") from the request data, signing this text with your private key, and placing the Base64-encoded result into the signature field of the JSON body.

Canonical Text Construction

The canonical text is a simple concatenation of specific field values from the request body. These values **must be appended in the exact order specified below, with no separators or extra characters**.

Get Participants (/participants)

The canonical text is built by concatenating the following fields:

- channelInfo.rrn
- channelInfo.bankId
- channelInfo.channelId
- channelInfo.sourceSystemId

Get FX Rate (/FXRate)

The canonical text is built by concatenating the following fields:

- channelInfo.rrn
- channelInfo.bankId
- channelInfo.channelId
- channelInfo.sourceSystemId

Name Check (/namecheck)

The canonical text is built by concatenating the following fields:

- channelInfo.rrn
- channelInfo.bankId
- channelInfo.channelId
- channelInfo.sourceSystemId
- sender.institutionId
- receiver.institutionId
- receiver.accountNumber

Credit Transfer (/credit-transfer)

The canonical text is built by concatenating the following fields:

- channelInfo.rrn
- channelInfo.bankId
- channelInfo.channelId
- channelInfo.sourceSystemId
- transactionInfo.senderAmount
- transactionInfo.receiverAmount
- transactionInfo.fxRate
- transactionInfo.papssFeeAmount

- transactionInfo.bankFeeAmount
- transactionInfo.transactionCurrency
- sender.currency
- sender.institutionId
- sender.accountNumber
- sender.accountName
- receiver.institutionId
- receiver.currency
- receiver.accountName

Status Check (/status-check)

The canonical text is built by concatenating the following fields:

- channelInfo.rrn
- channelInfo.bankId
- channelInfo.channelId
- channelInfo.sourceSystemId
- originalTxnInfo.originalRrn